

DZV11

DZV11 DIAG PRT 2
CVDZBB0

AH-A939B-MC
FICHE 1 OF 1

JUL 1982
COPYRIGHT © 77-82
MADE IN USA



CVDZBB
CVDZBB.P11 10-AUG-81 10:56

::GPA MACY11 30G(1063) ^{B 1} 10-AUG-81 11:11 PAGE 1

SEQ 0001

.REM 8

IDENTIFICATION

PRODUCT CODE: AC-A938B-MC
PRODUCT NAME: CVDZBB0 DZV11 DIAG PRT2
DATE RELEASED: 17-FEB-82
MAINTAINER: DIAGNOSTIC ENGINEERING

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

THE SOFTWARE DESCRIBED IN THIS DOCUMENT IS FURNISHED UNDER A LICENSE AND MAY ONLY BE USED OR COPIED IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE.

DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL.

COPYRIGHT (C) 1977, 1982 DIGITAL EQUIPMENT CORPORATION

1. ABSTRACT

THE FUNCTION OF THE DZV11 DIAGNOSTICS IS TO VERIFY THE OPTION OPERATES ACCORDING TO SPECIFICATIONS. THE DIAGNOSTICS ALSO VERIFY THAT THE DZV11 OPERATES IN ITS ENVIRONMENT SUCH AS THE SYSTEM IN WHICH IT IS INSTALLED.

PARAMETERS MAY BE SUPPLIED TO THE PROGRAM BY EITHER 'AUTO SIZING' OR INPUT FROM THE USER ON THE CONSOLE BY HAVING SW00=1 AT START TIME. AUTO SIZING WILL BE DONE ONLY THE FIRST TIME THE PROGRAM IS STARTED AND SW07=0 AND SW00=0 AND SW03=0. THE AUTOSIZER IS DESIGNED TO DETECT DZV11 DEVICE ADDRESSES AND VECTORS ONLY. ALL REMAINING PARAMETERS WILL DEFAULT TO CERTAIN VALUES (SEE SEC.8.5). CONSOLE INPUT MAY BE CONTROLLED AT ANY START TIME THROUGH THE USE OF SW00, SW03, SW04, AND SW06 (SEE SEC. 4.1.1 FOR A DETAILED DESCRIPTION OF THESE SWITCHES).

CURRENTLY THERE ARE THREE STANDALONE DIAGNOSTICS (DVDZA, DVDZB, AND DVDZC) ONE SYSTEM MODULE FOR DEC X/11 (DZBA), AND AN OVERLAY FOR ITEX (DVDZD).

DVDZA TOGETHER WITH DVDZB WILL TEST ALL LOGICAL FUNCTIONS OF THE DZV11 INTERFACE MODULE.

DVDZC IS DESIGNED AS A NON-CHAINABLE STANDALONE DIAGNOSTIC PROVIDING THE OPERATOR WITH DIRECT CONTROL OVER THE TESTING OF ALL DZV11 EIA CABLES.

```
*****
*
* NOTE: THIS DIAGNOSTIC HAS BEEN MODIFIED TO RUN IN KXT11 (SBC 11/21)
* BASED SYSTEMS. THE PROGRAM WILL AUTOMATICALLY ADJUST ITSELF TO RUN
* IN THE APPROPRIATE ENVIRONMENT AS FOLLOWS:
*
*          LSI-11, 11/2, AND 11/23          SBC 11/21
*          -----
* CSR RANGE:      160010 TO 163770          174000 TO 177770
* VECTOR RANGE:   300 TO 770                300 TO 370
* AUTO-SIZING FOR...
* ...CSR AND VECTOR:  ENABLED                DISABLED
*
*          ::GPA
*****
```

2. REQUIREMENTS

2.1 EQUIPMENT

AN LSI11 CPU WITH MINIMUM 4K OF MEMORY.
ASR 33 (OR EQUIVALENT FOR CONSOLE)
DZV11 INTERFACE MODULE
H329 STAGGERED TURNAROUND CONNECTOR.
H325 CABLE TURNAROUND CONNECTOR.

NOTE: A STAGGERED TURNAROUND CONNECTOR IS NEEDED IN ORDER TO TEST THE PARITY LOGIC.

2.2 STORAGE

PROGRAM WILL USE ALL 4K OF MEMORY EXCEPT WHERE ABL AND BOOTSTRAP LOADER RESIDE. LOCATION 1500 THRU 1740 ARE ESPECIALLY TO BE NOTED AND TO BE UNTOUCHED BY OPERATOR AFTER PARAMETERS HAVE BEEN INPUT FROM CONSOLE (SW00=1); OR AFTER THE 'AUTO SIZING' HAS BEEN DONE. THESE LOCATIONS MAY BE CHANGED IF THE USER UNDERSTANDS THEIR MEANING AND DIFFERENT PARAMETERS ARE REQUIRED.

3. LOADING PROCEEDURE

3.1 METHOD

ALL PROGRAMS ARE IN ABSOLUTE FORMAT AND ARE LOADED USING THE ABSOLUTE LOADER. NOTE: IF THE DIAGNOSTICS ARE ON A MEDIA SUCH AS DISK, MAGTAPE, DECTAPE, OR CASSETTE; FOLLOW INSTRUCTIONS FOR THE MONITOR WHICH HAS BEEN PROVIDED ON THAT SPECIFIC MEDIA.

ABSOLUTE LOADER STARTING ADDRESS *500

MEMORY * SIZE

4K	17
8K	37
12K	57
16K	77
20K	117
24K	137
28K	157

3.1.1 STARTING THE PROCESSOR AT THE ABSOLUTE LOADER STARTING ADDRESS WILL LOAD THE DIAGNOSTIC INTO MEMORY.

4. STARTING PROCEEDURE

- A. SET SWR TO ZERO FOR 'AUTO SIZING' OR SET SW00=1 FOR USER PARAMETER INPUT FROM CONSOLE TERMINAL. NOTE: LOC. 000176 IS USED AS A SOFTWARE SWITCH REGISTER IN ALL OF THE DZV11 DIAGNOSTICS. (SEE SEC. 4.1) ON THE FIRST STARTUP OF THE DIAGNOSTIC IF SW07=1 AND SW00=0 THE PROGRAM WILL ASSUME THAT THE STATUS TABLE HAS BEEN ALREADY BUILT FROM A PREVIOUS DZV11 DIAGNOSTIC RUN. NOTE: ANY DZV11 DIAGNOSTIC WILL OVERLAY THE STATUS TABLE WHEN LOADED TO PRESERVE ITS CONTENTS AND THUS WILL NOT ALTER A PREVIOUSLY BUILT TABLE.
- B. START THE DIAGNOSTIC AT LOC. 200(8). THE PROGRAM WILL TYPE MAINDEC AND PROGRAM NAMES (IF THIS WAS THE FIRST START UP OF THE PROGRAM) AND ALSO THE FOLLOWING: (ON THE FIRST PROGRAM RUN OR IF PARAMETERS WERE CHANGED)

'MAP OF DZV11 STATUS'
1500 160100
1502 000300
1504 000017
1506 017470
1510 000000

THE ABOVE IS ONLY AN EXAMPLE! THIS WOULD INDICATE THE STATUS TABLE STARTING AT ADD. 1500 IN THE PROGRAM. THE STATUS TABLE MUST BE VERIFIED BY THE USER IF AUTO SIZING IS DONE. FOR INFORMATION OF STATUS TABLE SEE SECTION 8.4 FOR HELP.

THE PROGRAM WILL TYPE 'RUNNING' AND PROCEED TO RUN THE DIAGNOSTIC.

4.1 CONTROL SWITCH SETTINGS

NOTE: THIS PROGRAM UTILIZES A SOFTWARE SWITCH REGISTER WHICH MAY BE MODIFIED BY CHANGING LOC. 176 OR BY TYPING CONTROL 'G' (^G) ON THE CONSOLE TERMINAL WHILE THE PROGRAM IS RUNNING.

SW 15	SET:	HALT ON ERROR
SW 14	SET:	LOOP ON CURRENT TEST
SW 13	SET:	INHIBIT ERROR PRINT OUT
SW 12	SET:	INHIBIT **ALL** TYPE OUT/BELL ON ERROR.
SW 11	SET:	INHIBIT ITERATIONS. (QUICK PASS)
SW 10	SET:	ESCAPE TO NEXT TEST
SW 09	SET:	LOOP WITH CURRENT DATA
SW 08	SET:	CATCH ERROR AND LOOP ON IT
SW 07	SET:	NO AUTO SIZE. IF 1ST START OF PROGRAM AFTER LOADING AND IF SW00=0 THEN THE PROGRAM WILL ASSUME THAT THE STATUS MAP HAS BEEN BUILT FROM A PREVIOUS DZV11 DIAGNOSTIC RUN.
SW 06	SET:	RESELECT DZV11'S DESIRED ACTIVE
SW 05	SET:	RESERVED
SW 04	SET:	SELECT DELAY PARAMETER (SEE SEC. 4.1.1)
SW 03	SET:	EXTRA PARAMETER INPUT (SEE SEC. 4.1.1)
SW 02	SET:	LOCK ON SELECTED TEST
SW 01	SET:	RESTART PROGRAM AT SELECTED TEST
SW 00	SET:	GET USERS PARAMETERS FROM CONSOLE

4.1.1 SWITCH REGISTER CONTROL OF PARAMETER INPUT FROM CONSOLE

- SW 00 GET USERS PARAMETERS FROM CONSOLE. SETTING THIS SWITCH AT START UP TIME ALLOWS THE USER TO INPUT AT THE CONSOLE TERMINAL THE FOLLOWING PARAMETERS: BASE DEVICE ADDRESS, BASE VECTOR ADDRESS, MODE OF OPERATION (EXTERNAL, INTERNAL, OR STAGGERED), AND THE NUMBER OF DZV11'S THAT ARE RUNNING. USING THIS SWITCH ALONE WILL DEFAULT THE FOLLOWING PARAMETERS: ALL 4 LINES ARE SET TO BE TESTED ON EACH DZV11, THE DEFAULT BAUD RATE IS SET AT 19.2 KBAUD AND THE CHARACTER LENGTH FOR THE MAJORITY OF TESTING IS SET AT EIGHT BITS PER CHARACTER WITH TWO STOP BITS.
- SW 03 EXTRA PARAMETER INPUT. SETTING THIS SWITCH AT START UP TIME PROVIDES THE USER WITH THE ABILITY TO SET THE LINES ACTIVE FOR TESTING AND TO SET THE DEFAULT BAUD RATE USED FOR THE MAJORITY OF THE DIAGNOSTIC TESTS. THE DELAY PARAMETER IS AUTOMATICALLY ADJUSTED TO THE BAUD RATE GIVEN BY THE USER.
- SW 04 SELECT DELAY PARAMETER. THE DELAY PARAMETER THIS SWITCH CONTROLS DETERMINES THE LENGTH OF TIME THE PROGRAM STALLS WAITING FOR A CHARACTER TO BE COMPLETELY TRANSMITTED OR RECEIVED. THIS DELAY COUNT IS AUTOMATICALLY SET TO PROVIDE ENOUGH DELAY TIME FOR THE DEFAULT BAUD RATE SPECIFIED WHEN RUNNING THE PROGRAM ON AN LS111 WITH MOS MEMORY. WHEN RUNNING THIS PROGRAM ON A PROCESSOR WITH A FASTER MEMORY SPEED THIS DELAY COUNT SHOULD BE ADJUSTED PROPORTIONATELY HIGHER THAN THE FOLLOWING DEFAULTED VALUES:
- | | | |
|------|-----------|------------|
| 2450 | :TIME FOR | 50 BAUD |
| 1560 | :TIME FOR | 75 BAUD |
| 1120 | :TIME FOR | 110 BAUD |
| 0750 | :TIME FOR | 134 BAUD |
| 0660 | :TIME FOR | 150 BAUD |
| 0330 | :TIME FOR | 300 BAUD |
| 0150 | :TIME FOR | 600 BAUD |
| 0060 | :TIME FOR | 1200 BAUD |
| 0040 | :TIME FOR | 1800 BAUD |
| 0030 | :TIME FOR | 2000 BAUD |
| 0020 | :TIME FOR | 2400 BAUD |
| 0010 | :TIME FOR | 3600 BAUD |
| 0001 | :TIME FOR | 4800 BAUD |
| 0001 | :TIME FOR | 7200 BAUD |
| 0001 | :TIME FOR | 9600 BAUD |
| 0001 | :TIME FOR | 19.2 KBAUD |

4.1.2 SWITCH REGISTER RESTRICTIONS

- SW 06 RESELECT DZV11'S DESIRED ACTIVE. A MESSAGE IS TYPED OUT ON THE CONSOLE TERMINAL ASKING THE OPERATOR TO TYPE A BIT MAP OF THE DZV'S DESIRED ACTIVE. USING THIS SWITCH ALLOWS LOCATION DZVACTV TO BE ALTERED (SEE SEC. 8.3 FOR A DESCRIPTION OF THIS LOCATION).
EXAMPLE:
IF THE DEVICES CORRESPONDING TO THE DZV11'S NUMBERED ZERO, TWO, AND FOUR IN THE DZV11 STATUS MAP (LOC. 1500 THROUGH 1740) ARE TO BE TESTED, TYPE IN: 25
THIS WILL SET BITS ZERO, TWO, AND FOUR IN LOCATION DZVACTV. ALL REMAINING DEVICES IN THE STATUS MAP WILL THEN NOT BE TESTED.
- SW 01 RESTART PROGRAM AT SELECTED TEST IT IS STRONGLY SUGGESTED THAT AT LEAST ONE PASS HAS BEEN MADE BEFORE TRYING TO SELECT A TEST THAT IS NOT IN THE ORDER OF SEQUENCE THE REASON BEING IS THAT THE PROGRAM HAS TO CLEAR AREAS AND SET UP PARAMETERS.
NOTE: IF RUNNING MULTIPLE DZV11'S; THE DZV11 YOU DESIRE TO BE UNDER TEST MUST BE SELECTED BY THE USE OF SW06 BEFORE LOCKING ON THE TEST. IN OTHER WORDS; EACH TIME THE PROGRAM IS STARTED; THE FIRST DZV11 WILL BE SELECTED TO BE UNDER TEST UNLESS SW06 IS USED TO SELECT ONLY ONE.
- SW 09 LOOP ON CURRENT DATA: THIS SWITCH WILL ONLY WORK IF CALL 'SCOP1' IS IN THAT TEST. THE REASON BEING THAT MOST TESTS DEAL WITH BLOCKS OF DIFFERENT DATA TO BE SENT OR RECEIVED ALL AT ONCE THUS IN BLOCK DATA, ONE PATTERN CAN'T BE SINGLED OUT. THIS SWITCH IS DESIGNED TO PROVIDE AN AID FOR A TRAINED TROUBLE-SHOOTER TO SAMPLE VARIOUS SIGNALS ON THE MODULE AND IS NOT MEANT TO BE USED AS A GENERAL USER CONTROL SWITCH.
- SW 04 SELECT DELAY PARAMETER: THIS SWITCH SHOULD BE USED WITH CARE AS TOO SHORT A DELAY WILL CAUSE VALID TESTS TO FAIL.
(SEE SEC. 4.1.1)

4.1.3 SWITCH REGISTER PRIORITIES

ERROR SWITCHES

1. SW 12 DELETE PRINT OUT/BELL ON ERROR.
2. SW 13 DELETE ERROR PRINTOUT.
3. SW 15 HALT ON THE ERROR.
4. SW 08 GO TO BEGINNING OF THE TEST(ON ERROR).
5. SW 10 GOTO NEXT TEST(ON ERROR).

SCOPE SWITCHES

1. SW 09 (IF ENABLED BY 'SCOP1'). IF AN '*' IS PRINTED IN FRONT OF THE TEST NO. ON AN ERROR REPORT (EX. *TEST NO. 10) SW09 IS INCORPORATED IN THAT TEST AND THEREFORE SW09 IS *USUALLY* THE BEST SWITCH FOR THE SCOPE LOOP (SW14=0, SW10=0, SW09=1, SW08=0) IF THE PROGRAM USER IS TECHNICALLY TRAINED TO ELECTRONICALLY ISOLATE SIGNAL PROBLEMS ON THE DZV11 MODULE. IF SW09 IS NOT ENABLED; AND THERE IS A *HARD* ERROR (CONSTANT); SW08 IS BEST.
2. FOR INTERMITTENT ERRORS EITHER START THE PROGRAM WITH SW01 AND SW02 SET WHICH WILL ALLOW THE USER TO LOCK ON A SELECTED TEST, OR ELSE SET SW14 AS AN ERROR IS BEING TYPED OUT ON THE TERMINAL. SW14 WILL CONTINUE TO LOOP ON THAT TEST REGARDLESS OF WHETHER AN ERROR OCCURS.
3. SW 14 LOOP ON CURRENT TEST.

4.2 STARTING ADDRESS

SA 200 - THE STARTING ADDRESS FOR ANY DZV11 DIAGNOSTIC IS LOC. 200

NOTE: IF ADDRESS 000042 IS NON-ZERO THE PROGRAM ASSUMES IT IS UNDER ACT11 OR XXDP CONTROL AND WILL ACT ACCORDINGLY. AFTER *ALL* AVAILABLE DZV11S ARE TESTED THE PROGRAM WILL RETURN TO 'XXDP' OR 'ACT-11'.

5. OPERATING PROCEEDURE

WHEN THE PROGRAM IS INITIALLY STARTED, MESSAGES AS DESCRIBED IN SECTION FOUR WILL BE PRINTED AND THE DIAGNOSTIC WILL BEGIN RUNNING.

5.1 NORMAL START OF DIAGNOSTIC

ON THE FIRST START OF THE DIAGNOSTIC AT ADDRESS 200, IF SW00=1 THEN THE FOLLOWING QUESTIONS ARE ASKED AND MUST BE ANSWERED:

'1ST CSR ADDRESS (160000:163770): ""
YOU MUST TYPE IN THE FIRST DZV11 CSR IN THE SYSTEM YOU WISH TESTING TO BEGIN AT. RANGE: 160000:163770

'1ST VECTOR ADDRESS (300:770): ""
YOU MUST TYPE IN THE VECTOR OF THE FIRST DZV11 IN THE SYSTEM UNDER TEST. RANGE 300:770

'MAINTENANCE MODE
[EXTERNAL <H325> (E)]
[INTERNAL <DZCSR03=1>(I)]
[STAGGERED <H329> (S)] :
TYPE 'E' OR 'I' OR 'S' DEPENDING ON WHICH MODE YOU WISH TO RUN IN. IF RUNNING 'EXTERNAL'; ALL SELECTED LINES MUST BE TERMINATED BY AN H325 TEST CONNECTOR.

'# OF DZV11'S <IN OCTAL> (1:20): ""
TYPE TOTAL NUMBER OF DZV11'S TO BE TESTED IN THE SYSTEM. RANGE IS 1 THRU 20 IN OCTAL.

***** IF SW03=1 THEN THE FOLLOWING WILL BE PRINTED *****

'LINES ACTIVE BY BIT <IN OCTAL> (001:017): ""
EACH BIT REPRESENTS A LINE AND ANY COMBINATION OF LINES MAY BE SELECTED (HOWEVER IN STAGGERED MODE TWO ADJACENT LINES MUST BE SELECTED (0-1, 2-3).

'DEFAULT BAUD RATE <IN OCTAL> (00:17): ""
THIS GIVES THE USER A CHANCE TO CHANGE THE DEFAULT BAUD RATE USED IN APP. 90% OF THE TEST. BAUD RATE CHOICES ARE:
'00'(50 BAUD), '01'(75 BAUD), '02'(110 BAUD), '03'(134 BAUD),
'04'(150 BAUD), '05'(300 BAUD), '06'(600 BAUD), '07'(1200 BAUD),
'10'(1800 BAUD), '11'(2000 BAUD), '12'(2400 BAUD), '13'(3600 BAUD),
'14'(4800 BAUD), '15'(7200 BAUD), '16'(9600 BAUD), '17'(19.2 KBAUD)
LOW DEFAULT BAUD RATES ARE NOT SUGGESTED SINCE THEY LENGTHEN THE TIME TO COMPLETE A PROGRAM PASS DRAMATICALLY.

IT IS IMPORTANT TO NOTE THAT ALL DZV11'S IN THE SYSTEM MUST BE CONTIGIOUS FOR BOTH ADDRESS AND VECTORS. ALSO ALL THE EXTRA PARAMETERS OTHER THAN CSR AND VECTORS ARE GIVEN TO THE EXISTING DZV11'S IN THE SYSTEM.

IF THE MODE OF OPERATION IS DIFFERENT FOR EACH DZV11 THIS MUST BE PATCHED INTO THE CORRECT STATUS MAP ENTRY WHICH IS PRINTED AT START TIME. AN ALTERNATIVE IS TO PUT SW00=1 AT START TIME; ANSWER QUESTIONS ABOUT DZV11 UNDER TEST AND INDICATE ONE DZV11 IN THE SYSTEM. IF THE STATUS MAP IS TO BE 'PATCHED' IT MUST BE DONE AFTER THE QUESTIONS ARE ANSWERED OR AFTER THE AUTO SIZE.

5.2 PROGRAM AND/OR OPERATOR ACTION

THE VARIETY OF PROGRAM CONTROL SWITCHES PROVIDED IN THIS DIAGNOSTIC PACKAGE IS DESIGNED TO PROVIDE THE USER WITH A WIDE RANGE OF TROUBLE-SHOOTING TECHNIQUES. BEFORE THE USER ATTEMPTS TO RUN THIS DIAGNOSTIC HE SHOULD BECOME FAMILIAR WITH THE USE OF THESE CONTROL SWITCHES AND THEIR RESTRICTIONS. (SEE SEC. 4.1, 4.1.1, 4.1.2, 4.1.3)

WHEN THE PROGRAM DETECTS AN ERROR THE TEST NUMBER AND PC WILL BE TYPED OUT AND POSSIBLY AN ERROR MESSAGE (DEPENDING ON THE PARTICULAR ERROR). IF IT IS NECESSARY TO KNOW MORE INFORMATION CONCERNING THE ERROR REPORT THEN LOOK IN THE PROGRAM LISTING FOR THAT TEST NUMBER AND THEN NOTE THE PC OF THE ERROR REPORT. THE REASON FOR THE ERROR REPORT WILL BECOME CLEARER WHEN READING THE COMMENTS IN THE PROGRAM LISTING.

6. ERRORS

AS DESCRIBED PREVIOUSLY THERE WILL ALWAYS BE A TEST NUMBER AND PC TYPED OUT AT THE TIME OF AN ERROR (PROVIDING SW 13=0 AND SW 12=0). IN MOST CASES ADDITIONAL INFORMATION WILL BE SUPPLIED TO THE THE ERROR MESSAGE WHICH IS TO GIVE THE OPERATOR AN INDICATION OF THE ERROR.

6.1 ERROR RECOVERY

IF FOR SOME REASON THE DZV11 SHOULD 'HANG THE BUS' (GAIN CONTROL OF BUS SO THAT CONSOLE MANUAL FUNCTIONS ARE INHIBITED) AN INIT OR POWER DOWN/UP IS NECESSARY FOR OPERATOR TO REGAIN CONTROL OF CPU. IF THIS SHOULD HAPPEN; LOOK IN LOCATION 'STSTNM' (ADDRESS 1246) FOR THE NUMBER OF THE TEST THAT WAS RUNNING AT THE TIME OF THE CATASTROPHIC ERROR. IN THIS WAY THE OPERATOR WILL HAVE AN IDEA AS TO WHAT THE DZV11 WAS DOING AT THE TIME OF THE ERROR.

7. RESTRICTIONS

7.1 STARTING RESTRICTIONS

SEE SECTION 4.1.2
THE STATUS TABLE SHOULD BE VERIFIED REGARDLESS OF HOW THE PROGRAM WAS STARTED. ALSO IT IS IMPORTANT TO USE THIS LISTING ALONG WITH THE INFORMATION PRINTED ON THE TTY TO COMPLETELY ISOLATE PROBLEMS.

7.2 OPERATING RESTRICTIONS

PARAMETER MUST BE INPUT FROM USER OR APT IF "AUTO SIZING" IS NOT USED.

8. MISCELLANEOUS

8.1 EXECUTION TIME

ALL DZV11 DEVICE DIAGNOSTICS WILL GIVE AN 'END PASS' MESSAGE (PROVIDING NO ERRORS AND SW12=0) WITHIN 2 MIN. THIS IS ASSUMING SW11=1 (INHIBIT ITERATIONS) IS SET TO GIVE THE FASTEST POSSIBLE EXECUTION.

8.2 PASS COMPLETE

NOTE: *EVERY* TIME THE PROGRAM IS STARTED; THE TESTS WILL RUN AS IF SW11 (DELETE ITERATIONS) WAS UP (=1). THIS IS TO 'VERIFY NO *HARD* ERRORS' AS SOON AS POSSIBLE. THEREFORE THE FIRST PASS -EACH TIME PROGRAM IS STARTED- WILL BE A 'QUICK PASS' UNTIL ALL DZV11'S IN SYSTEM ARE TESTED. WHEN THE DIAGNOSTIC HAS COMPLETED A PASS THE FOLLOWING IS AN EXAMPLE OF THE PRINT OUT TO BE EXPECTED.

END PASS DVDZB-A CSR: 160100 VEC: 300 PASSES: 000001 ERRORS: 000000

NOTE: THE NUMBERS FOR CSR AND VEC ARE NOT NECESSARILY THE VALUES FOR THE DEVICE. THEY ARE ONLY FOR THIS EXAMPLE.

8.3 KEY LOCATIONS

SLPADR (1252)	CONTAINS THE ADDRESS WHERE PROGRAM WILL RETURN WHEN ITERATION COUNT IS REACHED OR IF LOOP ON TEST IS ASSERTED.
NEXT (1362)	CONTAINS THE ADDRESS OF THE NEXT TEST TO BE PERFORMED.
STSTNM (1246)	CONTAINS THE NUMBER OF THE TEST NOW BEING PERFORMED.
RUN (1412)	THE BIT IN 'RUN' ALWAYS POINTS ONE PAST THE DZV11 CURRENTLY BEING TESTED. EXAMPLE: (RUN) 1412/0000000001000000 MEANS THAT DZV11 NO.5 IS THE DZV11 NOW RUNNING.
STATUS MAP (1500)-(1740)	THESE LOCATIONS CONTAIN THE INFORMATION NEEDED TO TEST UP TO 16 (DECIMAL) DZV11S SEQUENTIALY. THEY CONTAIN THE CSR, VECTOR AND STATUS CONCERNING THE CONFIGURATION OF EACH DZV11.
DZVACTV(1406)	EACH BIT SET IN THIS LOCATION INDICATES THAT THE ASSOCIATED DZV11 WILL BE TESTED IN TURN. EXAMPLE: (DZVACTV) 1406/0000000000011111 MEANS THAT DZV11 NO. 00,01,02,03,04 WILL BE TESTED. EXAMPLE: (DZVACTV) 1406/0000000000010001 MEANS THAT DZ11 NO. 00,04 WILL BE TESTED.
SBASE (1174)	CONTAINS THE RECEIVER CSR OF THE CURRENT DZV11 UNDER TEST.

8.4 MORE ON THAT 'STATUS TABLE' (1500-1740)

'MAP OF DZV11 STATUS'

1500	160100
1502	000300
1504	000017
1506	017470
1510	000000

THE ABOVE INFORMATION WILL BE REPEATED FOR EACH OF UP TO 16 DZV11'S IN THE SYSTEM (THESE WILL FOLLOW UNDER THIS TABLE). EXPLANATION:

1500	160100	THIS IS THE SYSTEM CONTROL REGISTER FOR THE 1ST DZV11 IN THE SYSTEM.
1502	000300	THIS IS VECTOR 'A' FOR THE FIRST DZV11 IN THE SYSTEM.
1504	000017	THIS IS THE BINARY REPRESENTATION OF WHAT LINES ARE TO BE TESTED.
1506	017470	THIS IS THE PARAMETER LOCATION USED IN MOST OF THE TESTS. IT INDICATES PARAMETERS OF: RX ON, SPEED SELECT 17 (19.2K BAUD) EIGHT BITS PER CHAR, AND TWO STOP BITS. THE USER MAY ALTER THE STOP BITS AND THE SPEED, BUT THE REMAINING PARAMETERS SHOULD BE LEFT ALONE. THIS LOCATION IS USED TO LOAD THE DZV11 LINE PARAMETER REGISTER FOR EACH LINE. THE MEANING OF THE BITS SET IN THIS LOCATION IS THE SAME AS THE FUNCTION OF THE RELATED BITS IN THE DEVICE LINE PARAMETER REGISTER.
1510	000000	THIS LOCATION WILL CONTAIN EITHER ALL ZEROS INDICATING THAT INTERNAL LOOP WAS SELECTED AS MODE OF OPERATION OR IT WILL CONTAIN 100000 INDICATING THAT "STAGGERED MODE" WAS SELECTED OR IT WILL CONTAIN 000200 INDICATING THAT "EXTERNAL" WAS THE MODE SELECTED.

THE ABOVE IS REPEATED FOR EACH DZV11 IN THE SYSTEM. THE TABLE IS FILLED BY AUTO SIZING OR BY THE MANUAL PARAMETER INPUT PROGRAM AS DESCRIBED PREVIOUSLY. ALSO IF DESIRED BY USER: THE LOCATIONS MAY BE ALTERED BY HAND TO SUIT THE SPECIFIC CONFIGURATION.

8.5 *** METHOD OF AUTO SIZING ***

8.5.1 FINDING THE CONTROL STATUS REGISTER.

THE PROGRAM WILL START AT ADDRESS 160000 AND START 'REFERENCING' THE ADDRESS IN THE POINTER. IF A NON-EX MEMORY TRAP OCCURS, THE POINTER (HOLDING 160000) IS UPDATED BY 10 AND THE ABOVE IS REPEATED UNTIL ADDRESS 163770 IS REACHED. IF A 'BUS REPLY' RESPONSE WAS ISSUED BY THE DZV11 (OR ANY OTHER DEVICE) (NO NXM TRAP), 'MASTER SCAN ENABLE' IS ATTEMPTED TO BE SET AND THE TCR BITS FOR ALL FOUR LINES ARE SET. 'TRDY' IS THEN TESTED TO BE SET AND 'MASTER SCAN ENABLE' IS TESTED TO BE STILL SET. THE DIAGNOSTIC WILL THEN CHECK THAT AT LEAST ONE TCR BIT IS STILL SET. IF ALL OF THE ABOVE WORKED, THIS DEVICE IS ASSUMED TO BE A DZV11. IF ANY OF THE ABOVE FAILED, UPDATING OF THE POINTER IS DONE AND THE SEQUENCE IS REPEATED.

NOTE: IF THE PROGRAM DOES NOT FIND YOUR DZV11, SOMETHING IS WRONG AND AUTO SIZING SHOULD NOT BE DONE.

8.5.2 FINDING THE VECTOR

THE VECTOR AREA (ADDRESS 300-776) IS FILLED WITH THE INSTRUCTION IOT AND '+2' (NEXT ADDRESS). BIT14 AND BIT5 (TX INTERRUPT ENABLE AND MSTSCAN ENABLE) ARE SET INTO THE DZVCSR. ALL TCR BITS ARE SET, A DELAY OCCURS, AND IF NO INTERRUPT OCCURS (BECAUSE OF A BAD DZV11) THE PROGRAM ASSUMES VECTOR ADDRESS 300 AND THE PROBLEM SHOULD BE FIXED IN THE DIAGNOSTIC. ONCE THE PROBLEM IS FIXED, THE PROGRAM SHOULD BE SETUP AGAIN TO SET THE CORRECT VECTOR. IF AN INTERRUPT OCCURRED, THE ADDRESS TO WHICH THE DZV11 INTERRUPTED TO IS PICKED UP AND REPORTED AS THE VECTOR. NOTE: IF THE VECTOR REPORTED IS NOT THE VECTOR SET UP BY YOU, THERE IS A PROBLEM AND AUTO SIZING SHOULD NOT BE DONE.

8.5.3 PARAMETER ASSUMPTIONS.

SINCE TOO MUCH HARDWARE WOULD NEED TO BE TURNED ON TO SIZE THE REST OF THE PARAMETERS; THE PROGRAM MUST ASSUME THE REMAINING VARIATIONS. THE RESULT IF NOT TO YOUR SPECIFIC CONFIGURATION MAY BE ALTERED BY HAND. IN THIS WAY 95% OF THE PARAMETER SETUP WAS DONE BY THE PROGRAM AND 5% BY YOU.

THEREFORE:

- 1) ALL FOUR LINES ARE ASSUMED TO BE TESTED.
- 2) DEFAULT BAUD RATE IS SET TO 17 (19.2 KBAUD).
- 3) MODE OF OPERATION IS "INTERNAL MODE".

FOR ALL PARAMETER ADJUSTMENTS PLEASE REFER TO SECTION 8.4 FOR GREATER DETAIL.

9.0 RUNNING THE DZV11 DIAGNOSTIC UNDER APT

9.1.1 THE APT INTERFACE

THE DZV DIAGNOSTICS HAVE BEEN DESIGNED TO BE COMPATIBLE WITH THE APT (AUTOMATED PRODUCT TEST) SYSTEM. THE DZV LOGIC TEST DIAGNOSTICS (DVDZA, AND DVDZB) CAN BE RUN AS STANDALONE DIAGNOSTICS OR IN EITHER OF THE APT MODES. DVDZC, HOWEVER IS DESIGNED AS A STANDALONE DIAGNOSTIC ONLY AND REQUIRES DIRECT OPERATOR PARTICIPATION.

9.1.2 SETTING UP THE DIAGNOSTIC USING APT

THE DIAGNOSTIC USES SEVERAL VARIABLES IN THE REGION SUBTITLED "APT MAILBOX-ETABLE". THESE VARIABLES ARE:

\$SWREG -(1142)	USED AS THE SOFTWARE SWITCH REGISTER WHILE RUNNING UNDER APT.
\$VECT1 -(1170)	USED TO SPECIFY THE FIRST VECTOR ADDRESS
\$BASE -(1174)	USED TO INDICATE BOTTOM ADDRESS OF DZV11 UNDER TEST
\$DEVN -(1176)	A BIT MAP REPRESENTING WHICH DZV11'S WILL BE TESTED
\$CDW1 -(1200)	USED TO INDICATE WHICH LINES TO RUN ON ALL DZV11'S
\$CDW2 -(1202)	USED TO INDICATE THE DEFAULT TEST MODE. SET TO 0 FOR INTERNAL TESTING, 200 FOR EXTERNAL LOOP BACK (H325 INSTALLED), OR SET TO 100000 FOR STAGGERED LOOP BACK TESTING (H329 INSTALLED).
\$DDW0 -(1204)	EACH OF THE \$DDW WORDS DESCRIBES THE PARAMETERS (LPR) FOR A PARTICULAR DZV11, GOING UP TO 16 DZV11'S

9.1.3 RUNNING UNDER APT

ALL OF THE VARIABLES MENTIONED IN SECTION 9.1.2 SHOULD BE SET UP PRIOR TO RUNNING THE DIAGNOSTIC UNDER APT.

NOTE

BE SURE \$BASE POINTS TO THE FIRST DZV11 BEFORE RUNNING

BASED ON THESE VALUES, THE DIAGNOSTIC WILL SET UP THE STATUS TABLE. THE USER IS THEN FREE TO MONITOR UNDER APT AS NORMAL.

10.0

PROGRAM DESCRIPTION.

THIS PROGRAM WAS ASSEMBLED USING THE PDP-11 MAINDEC SYSMAC
PACKAGE (MAINDEC-11-DZQAC-C3), JAN 19, 1977.

46 INITIAL ADDRESS OF THE STACK POINTER *** 1120 ***
51 MISCELLANEOUS DEFINITIONS
63 GENERAL PURPOSE REGISTER DEFINITIONS
75 PRIORITY LEVEL DEFINITIONS
85 "SWITCH REGISTER" SWITCH DEFINITIONS
113 DATA BIT DEFINITIONS (BIT00 TO BIT15)
141 BASIC "CPU" TRAP VECTOR ADDRESSES
358 BITS 15-11=CPU TYPE
11/04=01,11/05=02,11/20=03,11/40=04,11/45=05
11/70=06,P0Q=07,Q=10
BIT 10=REAL TIME CLOCK
BIT 9=FLOATING POINT PROCESSOR
BIT 8=MEMORY MANAGEMENT
366 MEM.TYPE BYTE -- (HIGH BYTE)
900 NSEC CORE=001
300 NSEC BIPOLAR=002
500 NSEC MOS=003
371 MEM.LAST ADDR.=3 BYTES,THIS WORD AND LOW OF "TYPE" ABO
410 THIS TABLE CONTAINS VARIOUS COMMON STORAGE LOCATIONS
USED IN THE PROGRAM.
462 THIS TABLE CONTAINS THE INFORMATION FOR EACH ERROR THAT CAN OCCUR.
THE INFORMATION IS OBTAINED BY USING THE INDEX NUMBER FOUND IN
LOCATION \$ITEMB. THIS NUMBER INDICATES WHICH ITEM IN THE TABLE IS PERTINENT.
NOTE1: IF \$ITEMB IS 0 THE ONLY PERTINENT DATA IS (\$ERRPC).
NOTE2: EACH ITEM IN THE TABLE CONTAINS 4 POINTERS EXPLAINED AS FOLLOWS:
468 EM ::POINTS TO THE ERROR MESSAGE
DH ::POINTS TO THE DATA HEADER
DT ::POINTS TO THE DATA
DF ::POINTS TO THE DATA FORMAT


```

1010 INCREMENT THE PASS NUMBER ($PASS)
      IF THERES A MONITOR GO TO IT
      IF THERE ISN'T JUMP TO CYCLE

1072 THIS ROUTINE CONTROLS THE LOOPING OF SUBTESTS. IT WILL INCREMENT
      AND LOAD THE TEST NUMBER($TSTNM) INTO THE DISPLAY REG.(DISPLAY<7:0>)
      AND LOAD THE ERROR FLAG ($ERFLG) INTO DISPLAY<15:08>
      THE SWITCH OPTIONS PROVIDED BY THIS ROUTINE ARE:
      SW14=1 LOOP ON TEST
      SW11=1 INHIBIT ITERATIONS
      CALL
            SCOPE                ;;SCOPE=IOT

1147 ROUTINE TO TYPE ASCIZ MESSAGE. MESSAGE MUST TERMINATE WITH A 0 BYTE.
      THE ROUTINE WILL INSERT A NUMBER OF NULL CHARACTERS AFTER A LINE FEED.
      NOTE1: $NULL CONTAINS THE CHARACTER TO BE USED AS THE FILLER CHARACTER.
      NOTE2: $FILLS CONTAINS THE NUMBER OF FILLER CHARACTERS REQUIRED.
      NOTE3: $FILLC CONTAINS THE CHARACTER TO FILL AFTER.

      CALL:
      1) USING A TRAP INSTRUCTION
            TYPE      ,MESADR                ;;MESADR IS FIRST ADDRESS OF AN ASCIZ STRING
      OR
            TYPE
            MESADR

1931 ROUTINE USED TO SET UP THE DIAGNOSTIC VIA APT.
      IF BIT7 IN THE ENVIRONMENT MODE ($ENVN) BYTE IS SET,
      THE PROGRAM WILL LOAD ITS PARAMETERS FROM THE ETABLÉ.

1963 ROUTINE USED TO 'AUTO SIZE' THE DZV11
      CSR AND VECTOR.
      NOTE: THE CSR MAY BE ANY WHERE IN THE FLOATING
            ADDRESS RANGE (160000:163770)
            AND THE VECTOR MAY BE ANY WHERE IN THE
            FLOATING VECTOR RANGE (300:770)

2071 ***** TEST 1 *****
      THIS TEST VERIFIES OVERRUN AND SILO ALARM
      ONE LINE AT A TIME - BASED UPON VALID LINES
      AS EACH OF THE FIRST 16 CHARS ARE SENT; SILO ALARM IS
      TESTED TO BE CLEARED. ON THE 16TH CHAR THE PROGRAM THEN
      EXPECTS SILO ALARM TO SET. THEN THE ENTIRE
      SILO IS FILLED AND AN OVERRUN IS EXPECTED ON THE 65TH
      CHAR PULLED OUT OF THE SILO.
      ERROR PRINTOUTS WILL REPORT TRANSMITTING LINE NO.
      USING SWITCH NINE FOR THIS TEST SENDS 20. CHARACTERS
      ON DZV LINE PREVIOUSLY SELECTED CONTINUOUSLY WHILE SW09=1.
      USED TO SCOPE SILO ALARM PULSES, ETC.

```

2192 ***** TEST 2 *****
THIS TEST THAT "SILO ENABLE" WILL INHIBIT
RECEIVER INTERRUPTS AND THAT ON THE
16TH CHAR THAT "SILO ALARM" WILL CAUSE AN
INTERRUPT WITH "RIE" SET.
THIS WILL DO ALL SELECTED LINES ONE AT A TIME.
ERROR PRINTOUTS WILL REPORT TRANSMITTING LINE NO.

2264 ***** TEST 3 *****
THIS TEST RUNS ALL LINES FULL BORE
BASED UPON QUALIFIED LINES
..THIS IS AN INTERRUPT TEST ON THE RECEIVER AND
TRANSMITTER

2397 ***** TEST 4 *****
DZV11 RELATIVE TIMING TEST.
EACH SELECTED LINE WILL IN TURN RUN 16. CHARS
AT ALL BAUD RATES AND THEN THE HIGHEST BAUD
WITH ALL CHAR LENGTHS. EACH NEW PARAMETER SHOULD
DECREASE IN TIME FROM THE PREVIOUS PARAMETERS SELECTED.
THE TIME IS CHECKED AGAINST THE LAST PARAMETER USED
AND A LOWER TIME IS EXPECTED ON THE CURRENT PARAMETER.
PARAMETERS ARE:
EIGHT BITS/PER/CHAR - TWO STOP BITS AT
50, 75, 110, 134.5, 150, 300, 600, 1200, 1800, 2000
2400, 3600, 4800, 7200, 9600 BAUD.
19.2 K BAUD - TWO STOP BITS AT
SEVEN, SIX, FIVE BITS/PER/CHAR.
AFTER EACH LINE HAS FINISHED ALL THE ABOVE PARAMETERS
THE NEXT SELECTED LINE IS THEN TESTED.
WHEN RUNNING UNDER THE APT MANUFACTURING SYSTEM
THIS TEST IS ONLY RUN THE FIRST PASS

2491 ***** TEST 5 *****
THE MAIN FUNCTION OF THIS TEST IS TO VERIFY
THAT "PE" (PARITY ERROR) CAN BE FLAGGED BY
THE UARTS. THIS TEST WILL NOT BE DONE UNLESS
YOU ARE IN "STAGGERED" MODE.
40(8) CHARS ARE USED FOR THIS TEST.
ALL SELECTED LINES WILL BE ENABLED AT THE SAME TIME.
THIS TEST FIRST CHECKS EVEN PARITY FOR ODD LINES AND
ODD PARITY FOR EVEN LINES, THEN IT CHECKS THE REVERSE.

10-AUG-81 10:56

::GPA MACY11 30G(1063) ^{F 2} 10-AUG-81 11:11 PAGE 25

SEQ 0018

[illegible]

000001

001120

000011
000012
000015

```

::GPA PRGFRT ^?MAINDEC-11-DVDZBA/<200>/FOUR LINE ASYNC MUX TESTS, PART 2 OF 2?,DVDZBA
::GPA .HEADER <MD-11-DVDZB-A>,1977
::TITLE CVDZB-B
::*COPYRIGHT (C) 1977,1981
::*DIGITAL EQUIPMENT CORP.
::*MAYNARD, MASS. 01754
::*
::*
::*THIS PROGRAM WAS ASSEMBLED USING THE PDP-11 MAINDEC SYSMAC
::*PACKAGE (MAINDEC-11-DZQAC-C5), JAN, 1981.
::*
$TN=1
:STARTING PROCEDURE
:LOAD PROGRAM
:LOAD ADDRESS 000200
:PRESS START
:PROGRAM WILL TYPE
: 'CVDZBB/<200>/FOUR LINE ASYNC MUX TESTS, PART 2 OF 2'
:PROGRAM WILL TYPE 'RUNNING' TO INDICATE THAT TESTING HAS STARTED
:AT THE END OF A PASS, PROGRAM WILL TYPE PASS COMPLETE MESSAGE
:AND THEN RESUME TESTING

.REM !
:SWITCH REGISTER OPTIONS
:-----

SW15=100000      :=1,HALT ON ERROR
SW14=40000       :=1,LOOP ON CURRENT TEST
SW13=20000       :=1,INHIBIT ERROR TIMEOUT
SW12=10000       :=1,DELETE TIMEOUT/BELL ON ERROR.
SW11=4000        :=1,INHIBIT ITERATIONS
SW10=2000        :=1,ESCAPE TO NEXT TEST ON ERROR
SW09=1000        :=1,LOOP WITH CURRENT DATA
SW08=400         :=1,LOOP ON ERROR
SW07=200         :=1, DO 'AUTO SIZING' ON INITIAL START UP.
SW06=100         :=1, DESELECT SPECIFIC DEVICES
                 :=1, NOTE: THIS MUST NOT EXCEED ORIGINAL COUNT

SW05=40
SW04=20          :=1, SELECT DELAY PARAMETER
SW03=10          :=1, SELECT SPECIFIC PARAMETERS
SW02=4           :=1, LOCK ON TEST SELECT
SW01=2           :=1, RESTART PROGRAM AT SELECTED TEST
SW00=1           :=1, SELECT DEVICE ADDRESS, VECTOR, ETC.

!
.SBTTL BASIC DEFINITIONS

::*INITIAL ADDRESS OF THE STACK POINTER *** 1120 ***
STACK= 1120
.EQUIV EMT,ERROR      ::BASIC DEFINITION OF ERROR CALL
.EQUIV IOT,SCOPE      ::BASIC DEFINITION OF SCOPE CALL

::*MISCELLANEOUS DEFINITIONS
HT= 11              ::CODE FOR HORIZONTAL TAB
LF= 12              ::CODE FOR LINE FEED
CR= 15              ::CODE FOR CARRIAGE RETURN

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-1
 CVDZBB.P11 10-AUG-81 10:56 BASIC DEFINITIONS

SEQ 0019

(2)	000200	CRLF= 200	::CODE FOR CARRIAGE RETURN-LINE FEED
(2)	177776	PS= 177776	::PROCESSOR STATUS WORD
(2)		.EQUIV PS,PSW	
(2)	177774	STKLMT= 177774	::STACK LIMIT REGISTER
(2)	177772	PIRQ= 177772	::PROGRAM INTERRUPT REQUEST REGISTER
(2)	177570	DSWR= 177570	::HARDWARE SWITCH REGISTER
(2)	177570	DDISP= 177570	::HARDWARE DISPLAY REGISTER

.*GENERAL PURPOSE REGISTER DEFINITIONS

(2)	000000	R0= X0	::GENERAL REGISTER
(2)	000001	R1= X1	::GENERAL REGISTER
(2)	000002	R2= X2	::GENERAL REGISTER
(2)	000003	R3= X3	::GENERAL REGISTER
(2)	000004	R4= X4	::GENERAL REGISTER
(2)	000005	R5= X5	::GENERAL REGISTER
(2)	000006	R6= X6	::GENERAL REGISTER
(2)	000007	R7= X7	::GENERAL REGISTER
(2)	000006	SP= X6	::STACK POINTER
(2)	000007	PC= X7	::PROGRAM COUNTER

.*PRIORITY LEVEL DEFINITIONS

(2)	000000	PR0= 0	::PRIORITY LEVEL 0
(2)	000040	PR1= 40	::PRIORITY LEVEL 1
(2)	000100	PR2= 100	::PRIORITY LEVEL 2
(2)	000140	PR3= 140	::PRIORITY LEVEL 3
(2)	000200	PR4= 200	::PRIORITY LEVEL 4
(2)	000240	PR5= 240	::PRIORITY LEVEL 5
(2)	000300	PR6= 300	::PRIORITY LEVEL 6
(2)	000340	PR7= 340	::PRIORITY LEVEL 7

.*'SWITCH REGISTER' SWITCH DEFINITIONS

(2)	100000	SW15= 100000
(2)	040000	SW14= 40000
(2)	020000	SW13= 20000
(2)	010000	SW12= 10000
(2)	004000	SW11= 4000
(2)	002000	SW10= 2000
(2)	001000	SW09= 1000
(2)	000400	SW08= 400
(2)	000200	SW07= 200
(2)	000100	SW06= 100
(2)	000040	SW05= 40
(2)	000020	SW04= 20
(2)	000010	SW03= 10
(2)	000004	SW02= 4
(2)	000002	SW01= 2
(2)	000001	SW00= 1
(2)		.EQUIV SW09,SW9
(2)		.EQUIV SW08,SW8
(2)		.EQUIV SW07,SW7
(2)		.EQUIV SW06,SW6
(2)		.EQUIV SW05,SW5
(2)		.EQUIV SW04,SW4
(2)		.EQUIV SW03,SW3
(2)		.EQUIV SW02,SW2
(2)		.EQUIV SW01,SW1

CVDZB-B MACY11 306(1063) 10-AUG-81 11:11 PAGE 25-2
 CVDZBB.P11 10-AUG-81 10:56 BASIC DEFINITIONS

SEQ 0020

```

(2)      .EQUIV SW00,SW0
(2)
(2)      ;*DATA BIT DEFINITIONS (BIT00 TO BIT15)
(2)      100000      BIT15= 100000
(2)      040000      BIT14= 40000
(2)      020000      BIT13= 20000
(2)      010000      BIT12= 10000
(2)      004000      BIT11= 4000
(2)      002000      BIT10= 2000
(2)      001000      BIT09= 1000
(2)      000400      BIT08= 400
(2)      000200      BIT07= 200
(2)      000100      BIT06= 100
(2)      000040      BIT05= 40
(2)      000020      BIT04= 20
(2)      000010      BIT03= 10
(2)      000004      BIT02= 4
(2)      000002      BIT01= 2
(2)      000001      BIT00= 1
(2)      .EQUIV BIT09,BIT9
(2)      .EQUIV BIT08,BIT8
(2)      .EQUIV BIT07,BIT7
(2)      .EQUIV BIT06,BIT6
(2)      .EQUIV BIT05,BIT5
(2)      .EQUIV BIT04,BIT4
(2)      .EQUIV BIT03,BIT3
(2)      .EQUIV BIT02,BIT2
(2)      .EQUIV BIT01,BIT1
(2)      .EQUIV BIT00,BIT0
(2)
(2)      ;*BASIC "CPU" TRAP VECTOR ADDRESSES
(2)      000004      ERRVEC= 4      ;;TIME OUT AND OTHER ERRORS
(2)      000010      RESVEC= 10     ;;RESERVED AND ILLEGAL INSTRUCTIONS
(2)      000014      TBITVEC=14     ;;"T" BIT
(2)      000014      TRTVEC= 14     ;;TRACE TRAP
(2)      000014      BPTVEC= 14     ;;BREAKPOINT TRAP (BPT)
(2)      000020      IOTVEC= 20     ;;INPUT/OUTPUT TRAP (IOT) **SCOPE**
(2)      000024      PWRVEC= 24     ;;POWER FAIL
(2)      000030      EMTVEC= 30     ;;EMULATOR TRAP (EMT) **ERROR**
(2)      000034      TRAPVEC=34     ;;"TRAP" TRAP
(2)      000060      TKVEC= 60      ;;TTY KEYBOARD VECTOR
(2)      000064      TPVEC= 64      ;;TTY PRINTER VECTOR
(2)      000240      PIRQVEC=240    ;;PROGRAM INTERRUPT REQUEST VECTOR
(1)
(1)
(1)      ;INSTRUCTION DEFINITIONS
(1)      :-----
(1)
(1)      005746      PUSH1SP=5746   ;DECREMENT PROCESSOR STACK 1 WORD
(1)      005726      POP1SP=5726    ;INCREMENT PROCESSOR STACK 1 WORD
(1)      010046      PUSHRO=10046    ;SAVE R0 ON STACK
(1)      012600      POPRO=12600     ;RESTORE R0 FROM STACK
(1)      024646      PUSH2SP=24646   ;DECREMENT STACK TWICE
(1)      022626      POP2SP=22626    ;INCREMENT STACK TWICE
(1)      000200      MASK=BIT7       ;SET INTERRUPT MASK (INHIBIT FURTHER INTERRUPTS)
(1)      000000      CLEAR=0         ;ALLOW INTERRUPTS (CLEAR PROCESSOR STATUS)

```

```

(1)
(1)
(1)      :DZV11 CONTROL AND STATUS REGISTER DEFINITIONS
(1)      : (DZVCSR)      BIT DEFINITIONS
(1)      :-----
(1)
(1)      000010      MAINT = BIT3      :MAINTENANCE MODE ENABLE
(1)      000020      DCLR=BIT4      :DEVICE CLEAR
(1)      000040      MSENAB=BIT5     :MASTER SCAN ENABLE
(1)      000100      RIE=BIT6      :RECEIVER INTERRUPT ENABLE
(1)      000200      RDONE=BIT7     :RECEIVER DONE
(1)      010000      SILOEN= BIT12   :SILO ALARM ENABLE
(1)      020000      SILOAL = BIT13  :SILO ALARM
(1)      040000      TIE=BIT14      :TRANSMITTER INTERRUPT ENABLE
(1)      100000      TRDY=BIT15     :TRANSMITTER READY
(1)
(1)      :DZVCSR WORD DEFINITIONS
(1)      :-----
(1)      000000      TL0=0          :TRANSMIT LINE 0
(1)      000400      TL1=BIT8      :TRANSMIT LINE 1
(1)      001000      TL2=BIT9      :TRANSMIT LINE 2
(1)      001400      TL3=BIT9!BIT8 :TRANSMIT LINE 3
(1)
(1)      :DZVRBUF BIT DEFINITIONS
(1)      :-----
(1)      010000      PARER=BIT12    :PARITY ERROR
(1)      020000      FRMERR=BIT13   :FRAME ERROR
(1)      040000      OVRUN=BIT14    :OVERRUN ERROR
(1)      100000      DVALID=BIT15   :DATA VALID
(1)
(1)      :DZVRBUF WORD DEFINITIONS
(1)      :-----
(1)      000000      RL0=0          :RECEIVER LINE 0
(1)      000400      RL1=BIT8      :RECEIVER LINE 1
(1)      001000      RL2=BIT9      :RECEIVER LINE 2
(1)      001400      RL3=BIT9!BIT8 :RECEIVER LINE 3
(1)
(1)      :DZVLPR WORD DEFINITIONS
(1)      :-----
(1)      000000      LP0=0          :LINE PARAMETER 0
(1)      000001      LP1=BIT0      :LINE PARAMETER 1
(1)      000002      LP2=BIT1      :LINE PARAMETER 2
(1)      000003      LP3=BIT1!BIT0 :LINE PARAMETER 3
(1)
(1)      000000      FIVE=0         :FIVE BITS/CHAR, 1 STOP BIT
(1)      000010      SIX=BIT3      :SIX BITS/CHAR, 1 STOP BIT
(1)      000020      SEVEN=BIT4     :SEVEN BITS/CHAR, 1 STOP BIT
(1)      000030      EIGHT=BIT4!BIT3 :EIGHT BITS/CHAR, 1 STOP BIT
(1)      000040      FIVES=BIT5     :FIVE BITS/CHAR, 2 STOP BITS
(1)      000050      SIXS=BIT5!BIT3 :SIX BITS/CHAR, 2 STOP BITS
(1)      000060      SEVENS=BIT5!BIT4 :SEVEN BITS/CHAR, 2 STOP BITS
(1)      000070      EIGHTS=BIT5!BIT4!BIT3 :EIGHT BITS/CHAR, 2 STOP BITS

```


(1)			
(1)	000100	PARITY=BIT6	:PARITY ENABLED
(1)	000200	ODDPAR=BIT7	:ODD PARITY ENABLED
(1)	000000	ONESTOP=0	:ONE STOP BIT ENABLED
(1)	000040	TWOSTOP=BIT5	:TWO STOP BITS ENABLED
(1)	000000	EVEPAR=0	:EVEN PARITY ENABLED
(1)	010000	RCVON=BIT12	:ENABLE RECEIVER (RECEIVER ON)
(1)			
(1)	000000	S50=0	:SPEED 50 BAUD
(1)	000400	S75=BIT8	:SPEED 75 BAUD
(1)	001000	S110=BIT9	:SPEED 110 BAUD
(1)	001400	S134=BIT9!BIT8	:SPEED 134.5 BAUD
(1)	002000	S150=BIT10	:SPEED 150 BAUD
(1)	002400	S300=BIT10!BIT8	:SPEED 300 BAUD
(1)	003000	S600=BIT10!BIT9	:SPEED 600 BAUD
(1)	003400	S1200=BIT10!BIT9!BIT8	:SPEED 1200 BAUD
(1)	004000	S1800=BIT11	:SPEED 1800 BAUD
(1)	004400	S2000=BIT11!BIT8	:SPEED 2000 BAUD
(1)	005000	S2400=BIT11!BIT9	:SPEED 2400 BAUD
(1)	005400	S3600=BIT11!BIT9!BIT8	:SPEED 3600 BAUD
(1)	006000	S4800=BIT11!BIT10	:SPEED 4800 BAUD
(1)	006400	S7200=BIT11!BIT10!BIT8	:SPEED 7200 BAUD
(1)	007000	S9600=BIT11!BIT10!BIT9	:SPEED 9600 BAUD
(1)	007400	S19200=BIT11!BIT10!BIT9!BIT8	:SPEED 19200 BAUD
(1)			
(1)		:DZVTCR BIT DEFINITIONS	
(1)		-----	
(1)	000001	TCR0=BIT0	:ENABLE TRANSMISSION ON LINE 0
(1)	000002	TCR1=BIT1	:ENABLE TRANSMISSION ON LINE 1
(1)	000004	TCR2=BIT2	:ENABLE TRANSMISSION ON LINE 2
(1)	000010	TCR3=BIT3	:ENABLE TRANSMISSION ON LINE 3
(1)	000400	DTR0=BIT8	:DATA TERMINAL READY FOR LINE 0
(1)	001000	DTR1=BIT9	:DATA TERMINAL READY FOR LINE 1
(1)	002000	DTR2=BIT10	:DATA TERMINAL READY FOR LINE 2
(1)	004000	DTR3=BIT11	:DATA TERMINAL READY FOR LINE 3
(1)			
(1)		:DZVMSR BIT DEFINITIONS	
(1)		-----	
(1)	000001	RING0=BIT0	:RING INDICATED ON LINE 0
(1)	000002	RING1=BIT1	:RING INDICATED ON LINE 1
(1)	000004	RING2=BIT2	:RING INDICATED ON LINE 2
(1)	000010	RING3=BIT3	:RING INDICATED ON LINE 3
(1)	000400	C00=BIT8	:CARRIER PRESENT ON LINE 0
(1)	001000	C01=BIT9	:CARRIER PRESENT ON LINE 1
(1)	002000	C02=BIT10	:CARRIER PRESENT ON LINE 2
(1)	004000	C03=BIT11	:CARRIER PRESENT ON LINE 3
(1)			
(1)		:DZVTDR BIT DEFINITIONS	
(1)		-----	
(1)	000400	BRK0=BIT8	:BREAK FOR LINE 0
(1)	001000	BRK1=BIT9	:BREAK FOR LINE 1
(1)	002000	BRK2=BIT10	:BREAK FOR LINE 2
(1)	004000	BRK3=BIT11	:BREAK FOR LINE 3

(1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)
 (1)

TABLE OF LOOP AROUND FUNCTIONS (H325)

I	-----	^
V		^
REC		TRANS
DATA		DATA
I	-----	^
V		^
CO		RTS
I	-----	^
V		^
RING		DTR

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11
 CVDZBB.P11 10-AUG-81 10:56

PAGE 25-6 TRAPCATCHER FOR UNEXPECTED INTERRUPTS

SEQ 0024

```

(1) ;*****
(1) ;-----
(1) ;TRAPCATCHER FOR ILLEGAL INTERRUPTS
(1) ;THE STANDARD 'TRAP CATCHER' IS PLACED
(1) ;BETWEEN ADDRESS 0 TO ADDRESS 776.
(1) ;IT LOOKS LIKE 'PC+2 HALT'.
(1) ;-----
(1) ;*****
(1)
(1) 000000      .=0
(1) ;STANDARD INTERRUPT VECTORS
(1) ;-----
(1)
(1) 000020      .=20
(1) 000020 004362      .SCOPE      ;SCOPE LOOP HANDLER
(1) 000022 000200      MASK        ;HANDLE AT PRIORITY 7
(1) 000024 007372      $PWRDN      ;POWER FAIL HANDLER
(1) 000026 000340      340         ;SERVICE AT PRIORITY LEVEL 7
(1) 000030 006500      $ERROR      ;ERROR HANDLER
(1) 000032 000340      340         ;SERVICE AT PRIORITY LEVEL 7
(1) 000034 006272      .TRPSRV     ;GENERAL HANDLER DISPATCH SERVICE
(1) 000036 000340      340         ;SERVICE AT PRIORITY LEVEL 7
(2) .SBTTL ACT11 HOOKS
(2)
(3) ;*****
(2) ;HOOKS REQUIRED BY ACT11
(2) $SVPC=.      ;SAVE PC
(2) 000046 000046      .=46
(2) 000046 004316      $ENDAD      ;;1)SET LOC.46 TO ADDRESS OF $ENDAD IN .SEOP
(2) 000052 000052      .=52
(2) 000052 000000      .WORD 0      ;;2)SET LOC.52 TO ZERO
(2) 000052 000040      .=$SVPC     ;; RESTORE PC
(1)
(1) 000174 000174      .=174
(1) 000174 000000      DISPREG:0    ;SOFTWARE DISPLAY REGISTER FOR SWITCHLESS 11S
(1) 000176 000000      SWREG: 0     ;SOFTWARE SWITCH REGISTER FOR SWITCHLESS 11S
(1) 000200 000200      .=200
(1) 000200 000137 002116      JMP .START ;GO TO START OF PROGRAM
(1)
(2)
(2) 001000 001000      .=1000
(2) 001000 005200 053103 055104 MTITLE: .ASCIZ <200><12>/CVDZBB/<200>/FOUR LINE ASYNC MUX TESTS, PART 2 OF 2/<200>
(2)

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-7
CVDZBB.P11 10-AUG-81 10:56

PROGRAM PARAMETERS, VARIABLES, AND TRAP CALLS.

SEQ 0025

```

(3)          001120          . =1120
(4)          ::*****
(4)          :SBTTL  APT MAILBOX-ETABLE
(4)          ::*****
(4)          :EVEN
(4) 001120 $MAIL:          ::APT MAILBOX
(4) 001120 000000 $MSGTY: .WORD  AMSGTY  ::MESSAGE TYPE CODE
(4) 001122 000000 $FATAL: .WORD  AFATAL  ::FATAL ERROR NUMBER
(4) 001124 000000 $TESTN: .WORD  ATESTN  ::TEST NUMBER
(4) 001126 000000 $PASS:  .WORD  APASS   ::PASS COUNT
(4) 001130 000000 $DEVCT: .WORD  ADEVCT  ::DEVICE COUNT
(4) 001132 000000 $UNIT:  .WORD  AUNIT   ::I/O UNIT NUMBER
(4) 001134 000000 $MSGAD: .WORD  AMSGAD  ::MESSAGE ADDRESS
(4) 001136 000000 $MSGLG: .WORD  AMSGLG  ::MESSAGE LENGTH
(4) 001140 $ETABLE:      ::APT ENVIRONMENT TABLE
(4) 001140 000 $ENV: .BYTE  AENV   ::ENVIRONMENT BYTE
(4) 001141 000 $ENVN: .BYTE  AENVN  ::ENVIRONMENT MODE BITS
(4) 001142 000000 $SWREG: .WORD  ASWREG  ::APT SWITCH REGISTER
(4) 001144 000000 $USWR:  .WORD  AUSWR   ::USER SWITCHES
(4) 001146 000000 $CPUOP: .WORD  ACPUOP  ::CPU TYPE, OPTIONS
(4)          :*          BITS 15-11=CPU TYPE
(4)          :*          11/04=01,11/05=02,11/20=03,11/40=04,11/45=05
(4)          :*          11/70=06,PDQ=07,Q=10
(4)          :*          BIT 10=REAL TIME CLOCK
(4)          :*          BIT 9=FLOATING POINT PROCESSOR
(4)          :*          BIT 8=MEMORY MANAGEMENT
(4) 001150 000 $MAMS1: .BYTE  AMAMS1  ::HIGH ADDRESS,M.S. BYTE
(4) 001151 000 $MTYP1: .BYTE  AMTYP1  ::MEM. TYPE,BLK#1
(4)          :*          MEM.TYPE BYTE -- (HIGH BYTE)
(4)          :*          900 NSEC CORE=001
(4)          :*          300 NSEC BIPOLAR=002
(4)          :*          500 NSEC MOS=003
(4) 001152 000000 $MADR1: .WORD  AMADR1  ::HIGH ADDRESS,BLK#1
(4)          :*          MEM.LAST ADDR.=3 BYTES,THIS WORD AND LOW OF "TYPE" ABOVE
(4) 001154 000 $MAMS2: .BYTE  AMAMS2  ::HIGH ADDRESS,M.S. BYTE
(4) 001155 000 $MTYP2: .BYTE  AMTYP2  ::MEM.TYPE,BLK#2
(4) 001156 000000 $MADR2: .WORD  AMADR2  ::MEM.LAST ADDRESS,BLK#2
(4) 001160 000 $MAMS3: .BYTE  AMAMS3  ::HIGH ADDRESS,M.S.BYTE
(4) 001161 000 $MTYP3: .BYTE  AMTYP3  ::MEM.TYPE,BLK#3
(4) 001162 000000 $MADR3: .WORD  AMADR3  ::MEM.LAST ADDRESS,BLK#3
(4) 001164 000 $MAMS4: .BYTE  AMAMS4  ::HIGH ADDRESS,M.S.BYTE
(4) 001165 000 $MTYP4: .BYTE  AMTYP4  ::MEM.TYPE,BLK#4
(4) 001166 000000 $MADR4: .WORD  AMADR4  ::MEM.LAST ADDRESS,BLK#4
(4) 001170 000300 $VECT1: .WORD  AVECT1  ::INTERRUPT VECTOR#1,BUS PRIORITY#1
(4) 001172 000000 $VECT2: .WORD  AVECT2  ::INTERRUPT VECTOR#2BUS PRIORITY#2
(4) 001174 160010 $BASE:  .WORD  ABASE   ::BASE ADDRESS OF EQUIPMENT UNDER TEST
(4) 001176 000001 $DEVN:  .WORD  ADEVN   ::DEVICE MAP
(4) 001200 000017 $CDW1:  .WORD  ACDW1   ::CONTROLLER DESCRIPTION WORD#1
(4) 001202 000000 $CDW2:  .WORD  ACDW2   ::CONTROLLER DESCRIPTION WORD#2
(4) 001204 017470 $DDW0:  .WORD  ADDW0   ::DEVICE DESCRIPTOR WORD#0
(4) 001206 017470 $DDW1:  .WORD  ADDW1   ::DEVICE DESCRIPTOR WORD#1
(4) 001210 017470 $DDW2:  .WORD  ADDW2   ::DEVICE DESCRIPTOR WORD#2
(4) 001212 017470 $DDW3:  .WORD  ADDW3   ::DEVICE DESCRIPTOR WORD#3
(4) 001214 017470 $DDW4:  .WORD  ADDW4   ::DEVICE DESCRIPTOR WORD#4
(4) 001216 017470 $DDW5:  .WORD  ADDW5   ::DEVICE DESCRIPTOR WORD#5

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-9
 CVDZBB.P11 10-AUG-81 10:56 COMMON TAGS

SEQ 0027

```

(3)      .SBTTL  COMMON TAGS
(3)
(4)      ::*****
(3)      ::THIS TABLE CONTAINS VARIOUS COMMON STORAGE LOCATIONS
(3)      ::USED IN THE PROGRAM.
(3)
(3)      SCMTAG:                                ::START OF COMMON TAGS
(3)      001244                                ::CONTAINS THE TEST NUMBER
(3)      001244 000000                          ::CONTAINS ERROR FLAG
(3)      001246 000                            ::CONTAINS SUBTEST ITERATION COUNT
(3)      001247 000                            ::CONTAINS SCOPE LOOP ADDRESS
(3)      001250 000000                          ::CONTAINS SCOPE RETURN FOR ERRORS
(3)      001252 000000                          ::CONTAINS TOTAL ERRORS DETECTED
(3)      001254 000000                          ::CONTAINS ITEM CONTROL BYTE
(3)      001256 000000                          ::CONTAINS MAX. ERRORS PER TEST
(3)      001260 000                            ::CONTAINS PC OF LAST ERROR INSTRUCTION
(3)      001261 001                            ::CONTAINS ADDRESS OF 'GOOD' DATA
(3)      001262 000000                          ::CONTAINS ADDRESS OF 'BAD' DATA
(3)      001264 000000                          ::CONTAINS 'GOOD' DATA
(3)      001266 000000                          ::CONTAINS 'BAD' DATA
(3)      001270 000000                          ::RESERVED--NOT TO BE USED
(3)      001272 000000
(3)      001274 000000
(3)      001276 000000
(3)      001300 000
(3)      001301 000
(3)      001302 000000
(3)      001304 177570
(3)      001306 177570
(3)      001310 177560
(3)      001312 177562
(3)      001314 177564
(3)      001316 177566
(3)      001320 000
(3)      001321 002
(3)      001322 012
(3)      001323 000
(3)      001324 000000
(3)
(5)      001326 000000
(5)      001330 000000
(5)      001332 000000
(5)      001334 000000
(5)      001336 000000
(5)      001340 000000
(5)      001342 000000
(5)      001344 000000
(5)      001346 000000
(5)      001350 000000
(5)      001352 000000
(3)      001354 000000
(3)      001356 077
(3)      001357 015
(3)      001360 000012

      $CMTAG:                                ::START OF COMMON TAGS
      $STSTM: .WORD 0                        ::CONTAINS THE TEST NUMBER
      $SERFLG: .BYTE 0                      ::CONTAINS ERROR FLAG
      $ICNT: .WORD 0                       ::CONTAINS SUBTEST ITERATION COUNT
      $LPADR: .WORD 0                      ::CONTAINS SCOPE LOOP ADDRESS
      $LPERR: .WORD 0                      ::CONTAINS SCOPE RETURN FOR ERRORS
      $ERTTL: .WORD 0                      ::CONTAINS TOTAL ERRORS DETECTED
      $ITEMB: .BYTE 0                      ::CONTAINS ITEM CONTROL BYTE
      $ERMAX: .BYTE 1                      ::CONTAINS MAX. ERRORS PER TEST
      $ERRPC: .WORD 0                      ::CONTAINS PC OF LAST ERROR INSTRUCTION
      $GDADR: .WORD 0                      ::CONTAINS ADDRESS OF 'GOOD' DATA
      $BDADR: .WORD 0                      ::CONTAINS ADDRESS OF 'BAD' DATA
      $GDDAT: .WORD 0                      ::CONTAINS 'GOOD' DATA
      $BDDAT: .WORD 0                      ::CONTAINS 'BAD' DATA
      .WORD 0                              ::RESERVED--NOT TO BE USED
      .WORD 0
      $AUTOB: .BYTE 0                      ::AUTOMATIC MODE INDICATOR
      $INTAG: .BYTE 0                      ::INTERRUPT MODE INDICATOR
      .WORD 0
      $SWR: .WORD DSWR                     ::ADDRESS OF SWITCH REGISTER
      $DISPLAY: .WORD DDISP                ::ADDRESS OF DISPLAY REGISTER
      $TKS: 177560                          ::TTY KBD STATUS
      $TKB: 177562                          ::TTY KBD BUFFER
      $TPS: 177564                          ::TTY PRINTER STATUS REG. ADDRESS
      $TPB: 177566                          ::TTY PRINTER BUFFER REG. ADDRESS
      $NULL: .BYTE 0                       ::CONTAINS NULL CHARACTER FOR FILLS
      $FILLS: .BYTE 2                      ::CONTAINS # OF FILLER CHARACTERS REQUIRED
      $FILLC: .BYTE 12                     ::INSERT FILL CHARS. AFTER A 'LINE FEED'
      $TPFLG: .BYTE 0                      ::"TERMINAL AVAILABLE" FLAG (BIT<07>=0=YES)
      $REGAD: .WORD 0                      ::CONTAINS THE ADDRESS FROM
      .WORD 0                              ::WHICH ($REG0) WAS OBTAINED
      $REG0: .WORD 0                       ::CONTAINS (($REGAD)+0)
      $REG1: .WORD 0                       ::CONTAINS (($REGAD)+2)
      $REG2: .WORD 0                       ::CONTAINS (($REGAD)+4)
      $REG3: .WORD 0                       ::CONTAINS (($REGAD)+6)
      $REG4: .WORD 0                       ::CONTAINS (($REGAD)+10)
      $REG5: .WORD 0                       ::CONTAINS (($REGAD)+12)
      $TMP0: .WORD 0                       ::USER DEFINED
      $TMP1: .WORD 0                       ::USER DEFINED
      $TMP2: .WORD 0                       ::USER DEFINED
      $TMP3: .WORD 0                       ::USER DEFINED
      $TMP4: .WORD 0                       ::USER DEFINED
      $TIMES: 0                            ::MAX. NUMBER OF ITERATIONS
      $QUES: .ASCII /?/                   ::QUESTION MARK
      $CRLF: .ASCII <15>                  ::CARRIAGE RETURN
      $LF: .ASCII <12>                    ::LINE FEED

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-10
 CVDZBB.P11 10-AUG-81 10:56 ERROR POINTER TABLE

SEQ 0028

```

(3)      .SBTTL  ERROR POINTER TABLE
(3)
(3)      ;*THIS TABLE CONTAINS THE INFORMATION FOR EACH ERROR THAT CAN OCCUR.
(3)      ;*THE INFORMATION IS OBTAINED BY USING THE INDEX NUMBER FOUND IN
(3)      ;*LOCATION $ITEMB. THIS NUMBER INDICATES WHICH ITEM IN THE TABLE IS PERTINENT.
(3)      ;*NOTE1:      IF $ITEMB IS 0 THE ONLY PERTINENT DATA IS ($ERRPC).
(3)      ;*NOTE2:      EACH ITEM IN THE TABLE CONTAINS 4 POINTERS EXPLAINED AS FOLLOWS:
(3)
(3)      ;*      EM      ::POINTS TO THE ERROR MESSAGE
(3)      ;*      DH      ::POINTS TO THE DATA HEADER
(3)      ;*      DT      ::POINTS TO THE DATA
(3)      ;*      DF      ::POINTS TO THE DATA FORMAT
(3)
(3)      $ERRTB:
(3)
(2)      ;PROGRAM CONTROL PARAMETERS
(2)      ;-----
(2)
(2)      001362      000000      NEXT:      0      ;ADDRESS OF NEXT TEST TO BE EXECUTED
(2)      001364      000000      LOCK:      0      ;ADDRESS FOR LOCK ON CURRENT TEST,TIGHT LOOP
(2)
(2)      ;PROGRAM VARIABLES
(2)      ;-----
(2)
(2)      001366      000017      LINE:      17      ;DEFAULT ALL FOUR LINES RUNNING
(2)      001370      017470      PAR:      17470      ;PARAMETERS: 8 BITS/CHAR,2 STOP BITS,19200 BAUD,NO PARIT
(2)      001372      000000      MODE:      0      ;DEFAULT MAINTENANCE MODE
(2)      001374      000000      SAVLIN: 0      ;LINE NUMBER
(2)      001376      000000      XMTLIN: 0      ;TRANSMISSION LINE NUMBER
(2)      001400      000000      XMTCNT: 0      ;COUNT OF WORDS IN A TRANSMISSION PATTERN
(2)      001402      000000      REGIST: 0      ;DEVICE ADDRESS STORAGE LOCATION
(2)      001404      000000      SAVPC: 0      ;PROGRAM COUNTER STORAGE
(2)      001406      000001      DZVACTV: .BLKW 1      ;*DZV11'S SELECTED ACTIVE.
(2)      001410      000001      SAVACTV: .BLKW 1      ;*A BIT MAP OF DZV11'S IN THE SYSTEM
(2)      001412      000001      RUN:      1      ;*POINTER ONE PAST RUNNING DEVICE.
(2)      001414      000001      DZVNUM: .BLKB 1      ;*OCTAL NUMBER OF DZV11'S IN THE SYSTEM.
(2)      001415      001      SAVNUM: .BYTE 1      ;*WORKABLE NUMBER.
(2)      001416      000001      SAVNO: .BLKB 1      ;*OCTAL NUMBER OF DZV11'S BEING TESTED
(2)      001420      001420      .EVEN
(2)      001420      001500      ACTIVE: DZV.MAP      ;TABLE POINTER.

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-11
CVDZBB.P11 10-AUG-81 10:56 ERROR POINTER TABLE

SEQ 0029

```

(2)
(2)
(2)
(2)
(2) 001422 000
(2) 001423 000
(2) 001424 000
(2) 001425 000
(2)
(2)
(2) 001426 000000
(2) 001430 000000
(2) 001432 000000
(2) 001434 000000
(2) 001436 000000
(2) 001440 000000
(2) 001442 000000
(2) 001444 000000
(2) 001446
(2)
(2)
(3)
(2)
(3)
(2) 001446
(2) 000024 000024
(2) 000024 000200
(2) 000044 000044
(2) 000044 001446
(2) 001446
(3)
(2)
(2)
(2)
(2) 001446
(2) 001446 000000
(2) 001450 001120
(2) 001452 000132
(2) 001454 000137
(2) 001456 000000
(2) 001460 000052
(1)
(1)
(1)
(1) 001500 001500
(3)
(3) 001500 000001
(3) 001502 000001
(3) 001504 000001
(3) 001506 000001
(3) 001510 000001
(3)
(3) 001512 000001
(3) 001514 000001
(3) 001516 000001

```

:PROGRAM CONTROL FLAGS
 :-----
 INIFLG: .BYTE 0 :PROGRAM INITIALIZATION FLAG
 HDRFLG: .BYTE 0 :PROGRAM INITIALIZATION FLAG FOR HEADER MAP
 MNTFLG: .BYTE 0 :MAINTENANCE BIT SET FLAG
 DONFLG: .BYTE 0 :TRANSMISSION COMPLETION FLAG
 .EVEN
 :DATA VARIABLES
 TD0: .WORD 0
 TD1: .WORD 0
 TD2: .WORD 0
 TD3: .WORD 0
 TR0: .WORD 0
 TR1: .WORD 0
 TR2: .WORD 0
 TR3: .WORD 0
 STOP:
 .SBTTL APT PARAMETER BLOCK

:*****
 :SET LOCATIONS 24 AND 44 AS REQUIRED FOR APT
 :*****
 .SX= :SAVE CURRENT LOCATION
 =24 :SET POWER FAIL TO POINT TO START OF PROGRAM
 200 :FOR APT START UP
 =44 :POINT TO APT INDIRECT ADDRESS PNTR.
 \$APTHDR :POINT TO APT HEADER BLOCK
 =.SX :RESET LOCATION COUNTER
 :*****
 :SETUP APT PARAMETER BLOCK AS DEFINED IN THE APT-PDP11 DIAGNOSTIC
 :INTERFACE SPEC.

\$APTHD:
 \$SHIBTS: .WORD 0 :TWO HIGH BITS OF 18 BIT MAILBOX ADDR.
 \$MBADR: .WORD \$MAIL :ADDRESS OF APT MAILBOX (BITS 0-15)
 \$TSTM: .WORD 90. :RUN TIM OF LONGEST TEST
 \$PASTM: .WORD 95. :RUN TIME IN SECS. OF 1ST PASS ON 1 UNIT (QUICK VERIFY)
 \$UNITM: .WORD 0. :ADDITIONAL RUN TIME (SECS) OF A PASS FOR EACH ADDITIONAL UNIT
 .WORD \$ETEND-\$MAIL/2 :LENGTH MAILBOX-ETABLE(WORDS)
 :DZV11 STATUS TABLE AND ADDRESS ASSIGNMENTS
 :-----

.=1500
 DZV.MAP:
 DZCR0: .BLKW 1 :CONTROL STATUS REGISTER FOR DZV11 NUMBER 0
 DZVC0: .BLKW 1 :RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 0
 LINE0: .BLKW 1 :ALL LINES SELECTED
 PAR0: .BLKW 1 :PARAMETERS
 MANT0: .BLKW 1 :MAINTENANCE MODE FOR THIS DEVICE
 DZCR1: .BLKW 1 :CONTROL STATUS REGISTER FOR DZV11 NUMBER 1
 DZVC1: .BLKW 1 :RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 1
 LINE1: .BLKW 1 :ALL LINES SELECTED

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-12
 CVDZBB.P11 10-AUG-81 10:56 APT PARAMETER BLOCK

SEQ 0030

(3) 001520 000001	PAR1: .BLKW 1	:PARAMETERS
(3) 001522 000001	MANT1: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001524 000001	DZCR2: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 2
(3) 001526 000001	DZVC2: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 2
(3) 001530 000001	LINE2: .BLKW 1	:ALL LINES SELECTED
(3) 001532 000001	PAR2: .BLKW 1	:PARAMETERS
(3) 001534 000001	MANT2: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001536 000001	DZCR3: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 3
(3) 001540 000001	DZVC3: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 3
(3) 001542 000001	LINE3: .BLKW 1	:ALL LINES SELECTED
(3) 001544 000001	PAR3: .BLKW 1	:PARAMETERS
(3) 001546 000001	MANT3: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001550 000001	DZCR4: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 4
(3) 001552 000001	DZVC4: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 4
(3) 001554 000001	LINE4: .BLKW 1	:ALL LINES SELECTED
(3) 001556 000001	PAR4: .BLKW 1	:PARAMETERS
(3) 001560 000001	MANT4: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001562 000001	DZCR5: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 5
(3) 001564 000001	DZVC5: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 5
(3) 001566 000001	LINE5: .BLKW 1	:ALL LINES SELECTED
(3) 001570 000001	PAR5: .BLKW 1	:PARAMETERS
(3) 001572 000001	MANT5: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001574 000001	DZCR6: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 6
(3) 001576 000001	DZVC6: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 6
(3) 001600 000001	LINE6: .BLKW 1	:ALL LINES SELECTED
(3) 001602 000001	PAR6: .BLKW 1	:PARAMETERS
(3) 001604 000001	MANT6: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001606 000001	DZCR7: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 7
(3) 001610 000001	DZVC7: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 7
(3) 001612 000001	LINE7: .BLKW 1	:ALL LINES SELECTED
(3) 001614 000001	PAR7: .BLKW 1	:PARAMETERS
(3) 001616 000001	MANT7: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001620 000001	DZCR10: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 10
(3) 001622 000001	DZVC10: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 10
(3) 001624 000001	LINE10: .BLKW 1	:ALL LINES SELECTED
(3) 001626 000001	PAR10: .BLKW 1	:PARAMETERS
(3) 001630 000001	MANT10: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001632 000001	DZCR11: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 11
(3) 001634 000001	DZVC11: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 11
(3) 001636 000001	LINE11: .BLKW 1	:ALL LINES SELECTED
(3) 001640 000001	PAR11: .BLKW 1	:PARAMETERS
(3) 001642 000001	MANT11: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE
(3) 001644 000001	DZCR12: .BLKW 1	:CONTROL STATUS REGISTER FOR DZV11 NUMBER 12
(3) 001646 000001	DZVC12: .BLKW 1	:RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 12
(3) 001650 000001	LINE12: .BLKW 1	:ALL LINES SELECTED
(3) 001652 000001	PAR12: .BLKW 1	:PARAMETERS
(3) 001654 000001	MANT12: .BLKW 1	:MAINTENANCE MODE FOR THIS DEVICE

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-13
 CVDZBB.P11 10-AUG-81 10:56 APT PARAMETER BLOCK

SEQ 0031

(3)					
(3)	001656	000001	DZCR13:	.BLKW	1
(3)	001660	000001	DZVC13:	.BLKW	1
(3)	001662	000001	LINE13:	.BLKW	1
(3)	001664	000001	PAR13:	.BLKW	1
(3)	001666	000001	MANT13:	.BLKW	1
(3)					
(3)	001670	000001	DZCR14:	.BLKW	1
(3)	001672	000001	DZVC14:	.BLKW	1
(3)	001674	000001	LINE14:	.BLKW	1
(3)	001676	000001	PAR14:	.BLKW	1
(3)	001700	000001	MANT14:	.BLKW	1
(3)					
(3)	001702	000001	DZCR15:	.BLKW	1
(3)	001704	000001	DZVC15:	.BLKW	1
(3)	001706	000001	LINE15:	.BLKW	1
(3)	001710	000001	PAR15:	.BLKW	1
(3)	001712	000001	MANT15:	.BLKW	1
(3)					
(3)	001714	000001	DZCR16:	.BLKW	1
(3)	001716	000001	DZVC16:	.BLKW	1
(3)	001720	000001	LINE16:	.BLKW	1
(3)	001722	000001	PAR16:	.BLKW	1
(3)	001724	000001	MANT16:	.BLKW	1
(3)					
(3)	001726	000001	DZCR17:	.BLKW	1
(3)	001730	000001	DZVC17:	.BLKW	1
(3)	001732	000001	LINE17:	.BLKW	1
(3)	001734	000001	PAR17:	.BLKW	1
(3)	001736	000001	MANT17:	.BLKW	1
(1)					
(1)	001740	177777	DZV.END:		177777

;CONTROL STATUS REGISTER FOR DZV11 NUMBER 13
 ;RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 13
 ;ALL LINES SELECTED
 ;PARAMETERS
 ;MAINTENANCE MODE FOR THIS DEVICE
 ;CONTROL STATUS REGISTER FOR DZV11 NUMBER 14
 ;RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 14
 ;ALL LINES SELECTED
 ;PARAMETERS
 ;MAINTENANCE MODE FOR THIS DEVICE
 ;CONTROL STATUS REGISTER FOR DZV11 NUMBER 15
 ;RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 15
 ;ALL LINES SELECTED
 ;PARAMETERS
 ;MAINTENANCE MODE FOR THIS DEVICE
 ;CONTROL STATUS REGISTER FOR DZV11 NUMBER 16
 ;RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 16
 ;ALL LINES SELECTED
 ;PARAMETERS
 ;MAINTENANCE MODE FOR THIS DEVICE
 ;CONTROL STATUS REGISTER FOR DZV11 NUMBER 17
 ;RECEIVER AND BASE VECTOR FOR DZV11 NUMBER 17
 ;ALL LINES SELECTED
 ;PARAMETERS
 ;MAINTENANCE MODE FOR THIS DEVICE

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-14
 CVDZBB.P11 10-AUG-81 10:56 APT PARAMETER BLOCK

SEQ 0032

```

(1)                                     :DEFINITIONS FOR TRAP SUBROUTINE CALLS
(1)                                     :POINTERS TO SUBROUTINES CAN BE FOUND
(1)                                     :IN THE TABLE IMMEDIATELY FOLLOWING THE DEFINITIONS
(1)                                     :*****
(1)                                     :-----
(1) TRPTAB:
(3) 001742 104400 ADVANCE=TRAP+0 ;CALL TO ADVANCE TO NEXT TEST( OR SCOPE THIS ONE)
(2) 001742 006366 .ADVANCE
(3) 104401 SCOP1=TRAP+1 ;CALL TO LOOP ON CURRENT DATA HANDLER
(2) 001744 004626 .SCOP1
(3) 104402 TYPE=TRAP+2 ;CALL TO TELETYPE OUTPUT ROUTINE
(2) 001746 004652 .TYPE
(3) 104403 INSTR=TRAP+3 ;CALL TO ASCII STRING INPUT ROUTINE
(2) 001750 005472 .INSTR
(3) 104404 INSTER=TRAP+4 ;CALL TO INPUT ERROR HANDLER
(2) 001752 005576 .INSTER
(3) 104405 PARAM=TRAP+5 ;CALL TO NUMERICAL DATA INPUT ROUTINE
(2) 001754 005616 .PARAM
(3) 104406 SETFLG=TRAP+6 ;CALL TO SET FLAG ROUTINE
(2) 001756 010230 .SETFLG
(3) 104407 SAV05=TRAP+7 ;CALL TO REGISTER SAVE ROUTINE
(2) 001760 006016 .SAV05
(3) 104410 RES05=TRAP+10 ;CALL TO REGISTER RESTORE ROUTINE
(2) 001762 006056 .RES05
(3) 104411 CONVRT=TRAP+11 ;CALL TO DATA OUTPUT ROUTINE
(2) 001764 006110 .CONVRT
(3) 104412 CNVRT=TRAP+12 ;CALL TO DATA OUTPUT ROUTINE WITHOUT CR/LF.
(2) 001766 006114 .CNVRT
(3) 104413 DEVICE.CLR=TRAP+13 ;CALL TO ISSUE A DEVICE CLEAR
(2) 001770 006314 .DEVICE.CLR
(3) 104414 DELAY=TRAP+14 ;CALL TO DELAY FOR FAST CPU'S
(2) 001772 006346 .DELAY
(3) 104415 PARMD=TRAP+15 ;CONVERT DECIMAL STRING TO OCTAL
(2) 001774 011234 .PARMD
(3) 104416 PAWCH=TRAP+16 ;SET FLAG ECHO OR C OLE
(2) 001776 010350 .PAWCH
(3) 104417 DCLASM=TRAP+17 ;CLEAR DEVICE, SET MAINT. BIT IF I MODE
(2) 002000 006334 .DCLASM
(3) 104420 SHIFT=TRAP+20 ;CALL TO ROTATE LINE POINTER
(2) 002002 006400 .SHIFT
(3) 104421 LPRSET=TRAP+21 ;CALL TO SET UP LPR DEVICE REGISTER
(2) 002004 006416 .LPRSET
(3) 104422 BUFSET=TRAP+22 ;CALL TO ZERO BUFFER AREA
(2) 002006 006456 .BUFSET
(1)
(1) :-----
(1) :*****

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-15
 CVDZBB.P11 10-AUG-81 10:56 APT PARAMETER BLOCK

SEQ 0033

```

(1)                                     :DZV11 VECTOR AND REGISTER INDIRECT POINTERS
(1)                                     :WORKING AREA
(1)
(1) 002010 160040 DZVCSR: 160040 :R/W
(1) 002012 160041 HDZVCSR:160041 :R/W
(1) 002014 160042 DZVRBUF:160042 :READ ONLY
(1) 002016 160043 HDZVRBUF:160043 :READ ONLY
(1) 002020 160042 DZVLPR: 160042 :WRITE ONLY
(1) 002022 160043 HDZVLPR:160043 :WRITE ONLY
(1) 002024 160044 DZVTCR: 160044 :R/W
(1) 002026 160045 HDZVTCR:160045 :R/W
(1) 002030 160046 DZVMSR: 160046 :READ ONLY
(1) 002032 160047 HDZVMSR:160047 :READ ONLY
(1) 002034 160046 DZVTDR: 160046 :WRITE ONLY
(1) 002036 160047 HDZVTDR:160047 :WRITE ONLY
(1)
(1)                                     :DEFAULT DZV VECTORS
(1)
(1) 002040 000300 DZVRIV: 300 :REC INTR VECTOR
(1) 002042 000302 DZVRIS: 302 :REC INTR STATUS
(1) 002044 000304 DZVTIV: 304 :XMIT INTR VECTOR
(1) 002046 000306 DZVTIS: 306 :XMIT INTR STATUS
(1)
(1)

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-16
CVDZBB.P11 10-AUG-81 10:56 APT PARAMETER BLOCK

SEQ 0034

(1)			:TIME TABLE FOR RELATIVE TIMING TESTS
(1)			-----
(1)	002050		TMTBL:
(1)	002050	000000	T50: 0
(1)	002052	000000	T75: 0
(1)	002054	000000	T110: 0
(1)	002056	000000	T134: 0
(1)	002060	000000	T150: 0
(1)	002062	000000	T300: 0
(1)	002064	000000	T600: 0
(1)	002066	000000	T1200: 0
(1)	002070	000000	T1800: 0
(1)	002072	000000	T2000: 0
(1)	002074	000000	T2400: 0
(1)	002076	000000	T3600: 0
(1)	002100	000000	T4800: 0
(1)	002102	000000	T7200: 0
(1)	002104	000000	T9600: 0
(1)	002106	000000	TEIGHT: 0
(1)	002110	000000	TSEVEN: 0
(1)	002112	000000	TSIX: 0
(1)	002114	000000	TFIVE: 0

```
(1)                                     :PROGRAM INITIALIZATION
(1)                                     :LOCK OUT INTERRUPTS
(1)                                     :SET UP PROCESSOR STACK
(1)                                     :SET UP POWER FAIL VECTOR
(1)                                     :CLEAR PROGRAM CONTROL FLAGS AND COUNTS
(1)                                     :TYPE TITLE MESSAGE
(1)
(1) .START:
(1) 002116 000005 RESET ;CLEAR THE WORLD. START NEW ENVIRONMENT
(1) 002116 012706 001120 MOV #STACK,SP ;SET UP STACK
(1) 002120 106427 000200 MTPS #MASK ;LOCK OUT INTERRUPTS
(1) 002130 012737 007372 000024 MOV #SPWRDN,a#24 ;SET UP POWER FAIL VECTOR
(1) 002136 005037 001126 CLR $PASS ;CLEAR PASS COUNT
(1) 002142 105037 001247 CLRB $ERFLG ;CLEAR ERROR FLAG
(1) 002146 012737 001500 001420 MOV #DZV.MAP,ACTIVE ;GET MAP POINTER.
(1) 002154 012737 000001 001412 MOV #1,RUN ;POINT POINTER TO FIRST DEVICE.
(1) 002162 005037 001256 CLR $ERTTL ;CLEAR ERROR COUNT
(1) 002166 005037 001262 CLR $ERRPC ;CLEAR LAST ERROR POINTER
(1) 002172 005037 001246 CLR $TSTNM ;SET UP FOR TEST 1
(1) 002176 012737 002116 001252 MOV #.START,$LPADR ;SET UP FOR POWER FAIL BEFORE TESTING STARTS
(1)
(1) ;SET UP FOR SMALL 11 SWITCH REGISTER COMPATIBILITY
(1) 002204 012737 000176 001304 MOV #SWREG,SWR ;POINT TO SOFTWARE SWR
(1) 002212 012737 000174 001306 MOV #DISPREG,DISPLAY ;POINT TO SOFTWARE DISPLAY REGISTER
(1) 002220 004737 017126 CALL FALCON ;CHECK FOR FALCON (KXT11) ::GPA
(1) 002224 001402 BEQ 1000$ ;BR IF NOT ::GPA
(1) 002226 004737 000570 CALL FALCINI ;YES, INIT FOR FALCON. ::GPA
(1) 002232 1000$: TSTB INIFLG ;HAVE WE ALREADY BEEN HERE TODAY?
(1) 002232 105737 001422 BNE 10$ ;IF SO, SKIP PRINTING THE TITLE
(1) 002236 001010 CMP a#42,#SENDAD ;IF RUNNING UNDER ACT
(1) 002240 023727 000042 004316 BEQ 1$ ;DON'T PRINT TITLE
(1) 002246 001402 TYPE ,MTITLE ;PRINT THE DIAGNOSTIC'S TITLE
(1) 002250 104402 001000 DECB INIFLG ;SET THE ONCE ONLY FLAG
(1) 002254 105337 001422 1$: TSTB $ENVM ;DETERMINE WHETHER APT SIZING SHOULD BE DONE
(1) 002260 105737 001141 10$: BPL 15$ ;IF NOT, GO CHECK FOR AUTO-SIZING
(1) 002264 100004 JSR PC,SETAPT ;OTHERWISE, GO DO APT SIZING FROM ETABLE
(1) 002266 004737 011236 JMP 105$ ;GO PRINT DZV STATUS TABLE
(1) 002272 000137 003606 15$: TST a#42 ;CHAINED UNDER XXDP ?? ::GPA
(1) 002276 005737 000042 BEQ 16$ ;BR IF NOT ::GPA
(1) 002302 001404 CALL SETAPT ;YES, SET-UP FROM ETABLE ::GPA
(1) 002304 004737 011236 JMP 105$ ;AND PROCEED ::GPA
(1) 002310 000137 003606 16$: CALL GETSWR ;GET AN INITIAL SWR ::GPA
(1) 002314 004737 007154 BIT #SW00,aSWR ;RESELECT ?
(1) 002320 032777 000001 176756 BNE 20$ ;IF YES, GO SET UP THE INFORMATION
(1) 002326 001002 JMP 55$ ;IF NO, SKIP THE INTERROGATION
(1) 002330 000137 002632 20$: MOV #DZV.MAP,R0 ;POINT TO THE BEGINNING OF THE MAP TABLE
(1) 002334 012700 001500 CLRB HDRFLG ;MAKE SURE A MAP GETS PRINTED
(1) 002340 105037 001423 25$: CLR (R0)+ ;CLEAR A TABLE LOCATION
(1) 002344 005020 CMP R0,#DZV.END ;HAVE THE TABLE BOUNDARIES BEEN EXCEEDED?
(1) 002346 020027 001740 BNE 25$ ;IF NOT,CLEAR THE NEXT LOCATION IN THE TABLE
(1) 002352 001374 DECIB INIFLG ;INSURE NO AUTO SIZING IF QUESTIONS ANSWERED!
(1) 002354 105337 001422
(1)
(1) ;THE FOLLOWING ARE PARAMETERS USED TO FILL IN THE MAP
(1) ;TABLE AND SET UP THE DIAGNOSTIC.
```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-18
 CVDZBB.P11 10-AUG-81 10:56 PROGRAM INITIALIZATION AND START UP.

SEQ 0036

```

(1)
(1)
(1) 002360 002360 :GET THE BASE ADDRESS OF THE DZV11'S
(2) 002360 104403 GETCSR= . : POINTER FOR FALCON TWEAKER. ;;GPA
(2) 002362 003052 INSTR :CALL THE STRING INPUT ROUTINE
(2) 002364 104405 91$ :POINTER TO MESSAGE TO BE PRINTED
(2) 002366 160000 PARAM :CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 002370 163770 160000 :LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002372 001500 163770 :HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002374 007 DZCRO :POINTER TO MAP LOCATION TO BE FILLED
(2) 002375 001 .BYTE 7 :MASK OF INVALID BITS FOR THIS PARAMETER
(1) 002376 013737 001500 001174 .BYTE 1 :NUMBER OF PARAMETERS TO STORE
MOV DZCRO,$BASE :COPY BASE ADDRESS TO ETABLE

(1)
(1)
(1) 002404 002404 :GET THE BASE VECTOR ADDRESS
(2) 002406 104403 GETVEC= . : POINTER FOR FALCON TWEAKER. ;;GPA
(2) 002410 003116 INSTR :CALL THE STRING INPUT ROUTINE
(2) 002412 104405 92$ :POINTER TO MESSAGE TO BE PRINTED
(2) 002414 000300 PARAM :CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 002416 000776 300 :LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002420 001502 776 :HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002421 003 DZVCO :POINTER TO MAP LOCATION TO BE FILLED
(2) 002422 001 .BYTE 3 :MASK OF INVALID BITS FOR THIS PARAMETER
(1) 002422 013737 001502 001170 .BYTE 1 :NUMBER OF PARAMETERS TO STORE
MOV DZVCO,$VECT1 :COPY VECTOR TO ETABLE

(1)
(1)
(2) 002430 104403 :GET THE MODE OF OPERATION (E,I,S)
(2) 002432 003345 INSTR :CALL THE STRING INPUT ROUTINE
(2) 002434 104406 96$ :POINTER TO THE MESSAGE TO BE PRINTED
(2) 002436 001510 SETFLG :CALL THE MAINTENANCE FLAG SETUP ROUTINE
MANT0 :THIS IS THE FLAG BEING SETUP

(1)
(1)
(2) 002440 104403 :GET THE NUMBER OF DZV11'S RUNNING
(2) 002442 003302 INSTR :CALL THE STRING INPUT ROUTINE
(2) 002444 104405 95$ :POINTER TO MESSAGE TO BE PRINTED
(2) 002446 000001 PARAM :CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 002450 000020 1 :LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002452 001344 16. :HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002454 000 STMP1 :POINTER TO MAP LOCATION TO BE FILLED
(2) 002455 001 .BYTE 0 :MASK OF INVALID BITS FOR THIS PARAMETER
. BYTE 1 :NUMBER OF PARAMETERS TO STORE

(1)
(1) 002456 012737 000017 001504 MOV #17,LINE0 :SET UP DEFAULT LINES
(1) 002464 012737 017470 001506 MOV #17470,PAR0 :SET UP DEFAULT LPR PARAMETER

(1)
(1) 002472 032777 000010 176604 BIT #SW03,@SWR :RECEIVER ON; 19.2 KBAUD; 2STOP BITS; 8 BIT/CHAR
(1) 002500 001402 BEQ 30$ :DO YOU WANT PARAMETERS?
(1) 002502 004737 002662 JSR PC,65$ :IF NO, SKIP THE PARAMETER CALL
(1) 002506 012737 000001 001410 30$: MOV #1,SAVACTV :GET PARAMETERS
(1) 002514 113737 001344 001414 :INITIALIZE ACTIVE DEVICE SELECTION PARAMETER
(1) 002522 005337 001344 35$: MOV STMP1,DZVNUM :COPY THE NUMBER OF DEVICES
(1) 002526 001404 DEC STMP1 :STMP1 CONTAINS THE COUNT OF UNINITIALIZED
(1) 002530 000261 BEQ 40$ :SELECTED DEVICES
(1) 002532 006137 001410 SEC :SET A BIT FLAG TO INDICATE AN ACTIVE DEVICE
(1) 002536 000771 BR 35$ :POINT TO THE NEXT DEVICE
(1) 002540 013737 001410 001346 40$: MOV SAVACTV,$STMP2 :GO DO THIS PROCEDURE AGAIN
(1) 002546 012700 001500 MOV #DZCRO,R0 :# OF TIMES
:SET A POINTER TO THE SPECIFIED INFORMATION

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-19
 CVDZBB.P11 10-AUG-81 10:56 PROGRAM INITIALIZATION AND START UP.

SEQ 0037

```

(1) 002552 012701 001512      MOV      #DZCR1,R1      ;POINT R1 TO THE REST OF THE MAP TABLE
(1) 002556 012702 001204      MOV      #SDDW0,R2      ;POINT TO ETABLE'S DEVICE DESCRIPTOR WORDS
(1) 002562 000241              CLC                      ;INITIALIZE THE 'C' BIT FOR A ROTATION
(1) 002564 006037 001346      ROR      STMP2          ;SKIP MAPPING SETUP FOR DEVICE 0- IT'S DONE
(1) 002570 006237 001346      45$:  ASR      STMP2          ;ISOLATE A SELECTION FLAG IN THE 'C' BIT
(1) 002574 103404              BCS      50$          ;IS THIS DEVICE SELECTED? IF YES, GO LOAD TABLE
(1) 002576 012711 177777      MOV      #-1,(R1)        ;TERMINATE THE LIST
(1) 002602 000137 003550      JMP      100$        ;GO TO THE NEXT BLOCK
(1) 002606 012011              50$:  MOV      (R0)+,(R1)      ;ADDRESS
(1) 002610 062721 000010      ADD      #10,(R1)+      ;POINT TO THE NEXT DZV11 ADDRESS VALUE
(1) 002614 012011              MOV      (R0)+,(R1)      ;VECTOR
(1) 002616 062721 000010      ADD      #10,(R1)+      ;POINT TO THE NEXT VECTOR VALUE
(1) 002622 012021              MOV      (R0)+,(R1)+      ;LINES
(1) 002624 012021              MOV      (R0)+,(R1)+      ;PARAMETERS
(1) 002626 012021              MOV      (R0)+,(R1)+      ;MAINTENANCE MODE
(1) 002630 000757              BR       45$
(1) 002632 032777 000010 176444 55$:  BIT      #SW03,ASWR      ;ASK PARAMETERS ?
(1) 002640 001002              BNE      60$          ;IF NO, GO DO AUTO SIZING
(1) 002642 000137 003550      JMP      100$        ;GO SET UP FOR AUTO SIZING
(1) 002646 004737 002662      60$:  JSR      PC,65$      ;GO ASK PARAMETERS
(1) 002652 105337 001422      DECB     INIFLG      ;INSURE NO AUTO SIZE IF QUESTIONS ANSWERED
(1) 002656 000137 003606      JMP      105$        ;GO TO THE NEXT BLOCK
(1)
(1)
(1)
(1) 002662              65$:
(2) 002662 104403              INSTR          ;CALL THE STRING INPUT ROUTINE
(2) 002664 003157              93$          ;POINTER TO MESSAGE TO BE PRINTED
(2) 002666 104405              PARAM          ;CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 002670 000001              1          ;LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002672 000017              17         ;HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002674 001504              LINE0          ;POINTER TO MAP LOCATION TO BE FILLED
(2) 002676 360              .BYTE      360      ;MASK OF INVALID BITS FOR THIS PARAMETER
(2) 002677 001              .BYTE      1        ;NUMBER OF PARAMETERS TO STORE
(1) 002700 105037 001423      CLRB     HDRFLG      ;MAKE SURE THE CHANGES ARE PRINTED
(1)
(1)
(1)
(1)
(1) 002704 005737 001510      TST      MANT0        ;IS STAGGERED THE MODE OF OPERATION?
(1) 002710 100021              BPL      85$          ;IF NOT, SKIP THIS SEGMENT
(1) 002712 013703 001504      MOV      LINE0,R3      ;GET A SCRATCH COPY OF THE ACTIVE LINES
(1) 002716 006003              70$:  ROR      R3          ;GET A LINE SELECTION BIT(EVEN NUMBER LINE)
(1) 002720 103410              BCS      80$          ;IF IT IS SELECTED, CHECK TO SEE IF THE NEXT IS TOO
(1) 002722 001414              BEQ      85$          ;IF ALL HAVE BEEN CHECKED, CONTINUE PROCESSING
(1) 002724 006203              ASR      R3          ;IF IT IS 0,CHECK TO SEE IF THE NEXT IS TOO
(1) 002726 103373              BCC      70$          ;IF THIS ONE'S 0 TOO, GO CHECK THE NEXT PAIR
(1) 002730 104402 001356      75$:  TYPE     ,SQUES      ;THIS IS AN INCORRECT PARAMETER
(1) 002734 104402 010154      TYPE     ,MBADLN      ;LET THE USER KNOW ABOUT IT
(1) 002740 000750              BR       65$          ;GO GET THE CORRECT PARAMETER
(1) 002742 001772              80$:  BEQ      75$          ;IF ANOTHER FLAG ISN'T SET, THERE'S AN ERROR
(1) 002744 006203              ASR      R3          ;GET THE NEXT FLAG
(1) 002746 103370              BCC      75$          ;IF IT ISN'T SET, THERE'S AN ERROR
(1) 002750 000241              CLC                      ;INITIALIZE THE 'C' BIT FOR TESTING OF THE NEXT PAIR
(1) 002752 000761              BR       70$          ;GO TEST THE NEXT PAIR OF FLAGS

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-20
 CVDZBB.P11 10-AUG-81 10:56 PROGRAM INITIALIZATION AND START UP.

SEQ 0038

```

(1)                                     :GET THE LINE PARAMETER REGISTER ARGUMENT
(1)
(1) 002754 85$: INSTR                     :CALL THE STRING INPUT ROUTINE
(2) 002754 104403 94$                     :POINTER TO MESSAGE TO BE PRINTED
(2) 002756 003232 PARAM                   :CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 002760 104405 0                       :LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002762 000000 17                     :HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 002764 000017 PARO                   :POINTER TO MAP LOCATION TO BE FILLED
(2) 002766 001506 .BYTE 0                :MASK OF INVALID BITS FOR THIS PARAMETER
(2) 002770 000 .BYTE 1                   :NUMBER OF PARAMETERS TO STORE
(2) 002771 001 MOV #LINE0,R2             :POINT TO THE LINE SELECTION PARAMETER
(1) 002772 012702 001504 MOV #PAR0,R3    :POINT TO THE CHOSEN PARAMETERS
(1) 002776 012703 001506 MOV (R3),R4     :USE BAUD RATE AS AN INDEX IN DELAY TABLE
(1) 003002 011304 ASL R4                  :ALIGN INDEX ON WORD BOUNDARY
(1) 003004 006304 MOV DLYTBL(R4),DLYCNT :SET THE DELAY COUNT FOR THIS BAUD RATE
(1) 003006 016437 017066 006364 SWAB (R3) :PLACE IN HIGH BYTE
(1) 003014 000313 BIS #10070,(R3)        :PLACE EXTRA PARAMETERS INTO LOC
(1) 003016 052713 010070 90$: MOV (R2),12(R2) :LOAD THE LINES
(1) 003022 011262 000012 MOV (R3),12(R3) :LOAD THE PARAMETERS
(1) 003026 011363 000012 ADD #12,R2      :POINT TO THE NEXT SET
(1) 003032 062702 000012 ADD #12,R3      :... OF BOTH PARAMETERS
(1) 003036 062703 000012 CMP R3,#PAR17   :HAVE THE TABLE BOUNDARIES BEEN EXCEEDED?
(1) 003042 020327 001734 BNE 90$         :IF NOT, GO LOAD SOME MORE PARAMETERS
(1) 003046 001365 RTS PC                 :RETURN TO CALLING BLOCK
(1) 003050 000207 .ASCIIZ <200>/1ST CSR ADDRESS (160000:163770): /
(1) 003052 030600 052123 041440 91$: .ASCIIZ <200>/1ST VECTOR ADDRESS (300:770): /
(1) 003116 030600 052123 053040 92$: .ASCIIZ <200>/LINES ACTIVE BY BIT <IN OCTAL>(001:17): /
(1) 003157 200 044514 042516 93$: .ASCIIZ <200>/DEFAULT BAUD RATE <IN OCTAL>(00:17): /
(1) 003232 042200 043105 052501 94$: .ASCIIZ <200>/# OF DZV11'S <IN OCTAL> (1:20): /
(1) 003302 021600 047440 020106 95$: .ASCIIZ <200>/MAINTENANCE MODE/
(1) 003345 200 040515 047111 96$: .ASCIIZ <200>/ [EXTERNAL <H325> (E)]/
(1) 003366 020200 042533 052130 .ASCIIZ <200>/ [INTERNAL <DZVCSR03=1>(I)]/
(1) 003422 020200 044533 052116 .ASCIIZ <200>/ [STAGGERED <H329> (S)]: /
(1) 003457 200 055440 052123 97$: .ASCIIZ <200>/ENTER DELAY PARAMETER: /
(1) 003516 042600 052116 051105 .EVEN
(1) 003550 003550 100$: CMPB #377,INIFLG :ONLY DO AUTO SIZE ON 1ST START
(1) 003550 122737 000377 001422 BNE 105$ :
(1) 003556 001013 BIT #BIT7,BSWR :BIT7=1??
(1) 003560 032777 000200 175516 BNE 105$ :BR IF NO AUTO SIZE
(1) 003566 001007 TST KXTFLAG :KXT11 ?? :GPA
(1) 003570 005737 017142 BEQ 1001$ : SKIP NEXT IF NOT :GPA
(1) 003574 001402 JMP 20$ : YES, DON'T AUTO-SIZE :GPA
(1) 003576 000137 002334 1001$: :GPA
(1) 003602 JSR PC,AUTO.SIZE :GO DO THE AUTO SIZE
(1) 003602 004737 011364 105$: TSTB HDRFLG :HAS THE TABLE BEEN TYPED YET?
(1) 003606 105737 001423 BNE 120$ :IF SO, DON'T TYPE IT AGAIN
(1) 003612 001021 DECB HDRFLG :INDICATE THAT THE TABLE WILL BE TYPED
(1) 003614 105337 001423 TYPE ,XHEAD :TYPE MAP HEADER
(1) 003620 104402 010126 MOV #DZV.MAP,R0 :SET POINTER
(1) 003624 012700 001500 110$: MOV R0,$TMP1 :POINT TO THE MAP LOCATION
(1) 003630 010037 001344 MOV (R0)+,$TMP2 :SET DATA
(1) 003634 012037 001346 CMP #-1,$TMP2 :END OF LIST?
(1) 003640 022737 177777 001346 BEQ 120$ :BR IF YES
(1) 003646 001403 115$: CONVRT :CALL THE OCTAL TO ASCII CONVERSION ROUTINE
(1) 003650 104411

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-21
CVDZBB.P11 10-AUG-81 10:56

PROGRAM INITIALIZATION AND START UP.

SEQ 0039

(1)	003652	010216				XSTATQ		:CONVERT THE DATA AT THIS ADDRESS
(1)	003654	000765				BR	110\$	:GO PRINT THE NEXT PARAMETER
(1)	003656	013737	001410	001406	120\$:	MOV	SAVACTV,DZVACTV	:COPY BIT MAP OF ACTIVE DEVICES
(1)	003664	113737	001414	001416		MOVB	DZVNUM,SAVNO	:COPY NO. OF DEVICES IN THE SYSTEM
(1)	003672	032777	000100	175404		BIT	#SW06,@SWR	:DESELECT SPECIFIC DEVICES??
(1)	003700	001431				BEQ	135\$	:BR IF NO.
(1)	003702				121\$:			
(2)	003702	104403				INSTR		:CALL THE STRING INPUT ROUTINE
(2)	003704	010044				MNEW		:POINTER TO MESSAGE TO BE PRINTED
(2)	003706	104405				PARAM		:CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2)	003710	000001				1		:LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2)	003712	177777				177777		:HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2)	003714	001406				DZVACTV		:POINTER TO MAP LOCATION TO BE FILLED
(2)	003716	000				.BYTE	0	:MASK OF INVALID BITS FOR THIS PARAMETER
(2)	003717	001				.BYTE	1	:NUMBER OF PARAMETERS TO STORE
(1)	003720	023737	001406	001410		CMP	DZVACTV,SAVACTV	:IS VALUE VALID?
(1)	003726	101403				BLOS	122\$	:IF YES BRANCH
(1)	003730	104402	007716			TYPE	MERR3	:IF NOT TYPE ERROR
(1)	003734	000762				BR	121\$	:THEN REASK QUESTION
(1)	003736	105037	001416		122\$:	CLRB	SAVNO	:INITIALIZE NO. OF ACTIVE DEVICES
(1)	003742	013737	001406	001344		MOV	DZVACTV,\$TMP1	:COPY BIT MAP OF ACTIVE DEVICES
(1)	003750	006237	001344		126\$:	ASR	\$TMP1	:ROTATE OUT AN ACTIVE BIT
(1)	003754	103002				BCC	127\$	:IF NOT ACTIVE SKIP RECORDING IT
(1)	003756	105237	001416			INCB	SAVNO	:INCREMENT NO. OF ACTIVE DEVICES
(1)	003762	001372			127\$:	BNE	126\$	:IF NOT DONE GO CONTINUE
(1)	003764	032777	000020	175312	135\$:	BIT	#SW04,@SWR	:CHECK TO SEE IF DELAY COUNT CHANGES
(1)	003772	001407				BEQ	140\$	:IF NOT, GO CLEAR VECTOR AREA
(2)	003774	104403				INSTR		:CALL THE STRING INPUT ROUTINE
(2)	003776	003516				97\$		:POINTER TO MESSAGE TO BE PRINTED
(2)	004000	104405				PARAM		:CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2)	004002	000001				1		:LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2)	004004	177777				177777		:HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2)	004006	006364				DLYCNT		:POINTER TO MAP LOCATION TO BE FILLED
(2)	004010	000				.BYTE	0	:MASK OF INVALID BITS FOR THIS PARAMETER
(2)	004011	001				.BYTE	1	:NUMBER OF PARAMETERS TO STORE
(1)	004012	012700	000300		140\$:	MOV	#300,R0	:PREPARE TO CLEAR THE FLOATING
(1)	004016	012701	000302			MOV	#302,R1	:VECTOR AREA. 300-776
(1)	004022	010120			145\$:	MOV	R1,(R0)+	:START PUTTING 'PC+2 - HALT'
(1)	004024	005021				CLR	(R1)+	:IN VECTOR AREA.
(1)	004026	022021				CMP	(R0)+,(R1)+	:POP POINTERS
(1)	004030	005737	017142			TST	KXTFLAG	: IF FALCON...
(1)	004034	001403				BEQ	1002\$	
(1)	004036	020027	000400			CMP	R0,#400	:...QUIT AT 400.
(1)	004042	000402				402		: SKIP NEXT
(1)	004044				1002\$:			
(1)	004044	022700	001000			CMP	#1000,R0	:ALL DONE??
(1)	004050	001364				BNE	145\$	:BR IF NO.
(1)								
(1)						:TEST START AND RESTART		
(1)						:-----		
(1)								
(1)	004052	012706	001120			.BEGIN: MOV	#STACK,SP	:SET UP STACK
(1)	004056	106427	000200			MTPS	#MASK	:LOCK OUT INTERRUPTS
(1)	004062	005737	000042			TST	#42	:IS PROGRAM UNDER MONITOR CONTROL
(1)	004066	001015				BNE	2\$	:BR IF YES
(1)	004070	032777	000004	175206		BIT	#BIT2,@SWR	:CHECK FOR LOCK ON TEST

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-22
 CVDZBB.P11 10-AUG-81 10:56 PROGRAM INITIALIZATION AND START UP.

SEQ 0040

(1)	004076	001406				BEQ	1\$		:BR IF NO LOCK DESIRED.
(1)	004100	104402	007742			TYPE	,MLOCK		:TYPE LOCK SELECTED.
(1)	004104	012737	000240	004374		MOV	#NOP,TTST		:ADJUST SCOPE ROUTINE.
(1)	004112	000403				BR	2\$		:CONTINUE ALONG.
(1)	004114	013737	004622	004374	1\$:	MOV	BRW,TTST		:PREPARE NORMAL SCOPE ROUTINE
(1)	004122	012737	010530	001252	2\$:	MOV	#CYCLE,\$LPADR		:START AT "CYCLE" FIND WHICH DEVICE TO TEST
(1)	004130	113737	001416	001415		MOVB	SAVNO,SAVNUM		:COPY NO. OF ACTIVE DEVICES
(1)	004136	104402	007633			TYPE	,MR		:TYPE "RUNNING"
(1)	004142	000177	175104			JMP	@\$LPADR		:START TESTING
2729					::GPA	PRGEND	DZV11,<END PASS DVDZB-A >,10.		

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-23
 CVDZBB.P11 10-AUG-81 10:56 END OF PASS ROUTINE

SEQ 0041

```

2730      :END OF PASS
(2)      :TYPE NAME OF TEST
(2)      :UPDATE PASS COUNT
(2)      :CHECK FOR EXIT TO ACT-11
(2)      :RESTART TEST
(3)      .SBTTL  END OF PASS ROUTINE
(3)
(4)      :*****
(3)      :*INCREMENT THE PASS NUMBER ($PASS)
(3)      :*IF THERES A MONITOR GO TO IT
(3)      :*IF THERE ISN'T JUMP TO CYCLE
(3)
(3)      $EOP:
(5)      004146 000004 001262      SCOPE
(5)      004146 005037 001247      CLR      $ERRPC      :CLEAR LAST ERROR PC
(5)      004150 105037 001247      CLRB     $ERFLG      :CLEAR ERROR FLAG
(5)      004154 104402 007607      TYPE     ,MEPASS     :TYPE END PASS
(5)      004160 104402 007771      TYPE     ,MCSRX      :TYPE CSR
(5)      004170 104412 004332      CNVRT    ,XCSR       :SHOW IT
(5)      004174 104402 007777      TYPE     ,MVECX      :TYPE VECTOR
(5)      004200 104412 004340      CNVRT    ,XVEC       :SHOW IT
(5)      004204 005237 001126      INC      $PASS      :RAISE PASS COUNT
(5)      004210 104402 010005      TYPE     ,MPASSX     :TYPE PASSES
(5)      004214 104412 004346      CNVRT    ,XPASS      :SHOW IT
(5)      004220 005337 001126      DEC      $PASS      :RESTORE PASS COUNT
(5)      004224 104402 010016      TYPE     ,MERRX     :TYPE ERRORS
(5)      004230 104412 004354      CNVRT    ,XERR       :SHOW IT
(5)      004234 005237 001130      INC      $DEVCT     :INC DEVCNT FOR APT
(5)      004240 105377 001415      DECB     SAVNUM     :ARE ALL DEVICES TESTED?
(5)      004244 001030 001415      BNE      $DOAGN     :BR IF NO.
(5)      004246 113737 001416 001415      MOVB     SAVNO,SAVNUM :RESTORE THE COUNT
(3)      004254 005037 001354 001415      CLR      $TIMES     :ZERO THE NUMBER OF ITERATIONS
(3)      004260 005237 001126      INC      $PASS      :INCREMENT THE PASS NUMBER
(3)      004264 042737 100000 001126      BIC      #100000,$PASS :DON'T ALLOW A NEG. NUMBER
(3)      004272 005327      DEC      (PC)+      :LOOP?
(3)      004274 000001      SEOPCT: .WORD 1
(3)      004276 003013      BGT      $DOAGN     :YES
(3)      004300 012737      MOV      (PC)+,a(PC)+ :RESTORE COUNTER
(3)      004302 000001      SENDCT: .WORD 1
(3)      004304 004274      $EOPCT
(3)      004306 013700 000042      $GET42: MOV      a#42,R0      :GET MONITOR ADDRESS
(3)      004312 001405      BEQ      $DOAGN     :BRANCH IF NO MONITOR
(3)      004314 000005      RESET
(3)      004316 004710      SENDAD: JSR      PC,(R0)   :CLEAR THE WORLD
(3)      004320 000240      NOP
(3)      004322 000240      NOP      :GO TO MONITOR
(3)      004324 000240      NOP      :SAVE ROOM
(3)      004326      SDOAGN:      :FOR
(3)      004326 000137      JMP      a(PC)+      :ACT11
(3)      004330 010530      SRTNAD: .WORD  CYCLE      :RETURN
(2)
(2)      004332 000001      XCSR: 1
(2)      004334 006      .BYTE 6,2
(2)      004336 002010      DZVCSR
(2)      004340 000001      XVEC: 1
(2)      004342 003      .BYTE 3,2

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-24
CVDZBB.P11 10-AUG-81 10:56 END OF PASS ROUTINE

(2)	004344	002040	
(2)	004346	000001	
(2)	004350	006	002
(2)	004352	001126	
(2)	004354	000001	
(2)	004356	006	002
(2)	004360	001256	

```

DZVRIV
XPASS: 1 .BYTE 6.2
$PASS
XERR: 1 .BYTE 6.2
$ERTTL

```

```

;SCOPE LOOP AND ITERATION HANDLER
;-----

```

.SBTTL SCOPE HANDLER ROUTINE

```

*****
;:THIS ROUTINE CONTROLS THE LOOPING OF SUBTESTS. IT WILL INCREMENT
;AND LOAD THE TEST NUMBER($TSTNM) INTO THE DISPLAY REG.(DISPLAY<7:0>)
;AND LOAD THE ERROR FLAG ($ERFLG) INTO DISPLAY<15:08>
;THE SWITCH OPTIONS PROVIDED BY THIS ROUTINE ARE:
;SW14=1          LOOP ON TEST
;SW11=1          INHIBIT ITERATIONS
;CALL
;SCOPE           ;;SCOPE=IOT

```

(3)	004362		
(5)	004362	005037	001262
(5)	004366	022716	012072
(5)	004372	001413	
(5)	004374	000406	
(5)	004376	105777	174706
(5)	004402	100067	
(5)	004404	017766	174702
(3)	004412	032777	040000
(3)	004420	001060	

```

$SCOPE: CLR $ERRPC ;CLEAR LAST ERROR PC.
.SCOPE: CMP #TST1+2,(SP) ;IS THIS THE SCOPE AT THE BEGINNING OF TST1?
TTST: BEQ $XTSTR ;IF SO, DON'T LOOP ON IT
BR 1$ ;GOTO 1$ (IF LOCK SW02=1; THIS LOC =240)
TSTB @STKS ;KEYBOARD DONE?
BPL $OVER ;BR IF NO. (LOCK: HIT KEY TO GOTO NEXT TEST)
MOV @STKB,-2(SP) ;CLEAR DONE BIT
1$: BIT #BIT14,@SWR ;LOOP ON PRESENT TEST?
BNE $OVER ;YES IF SW14=1
;#####START OF CODE FOR THE XOR TESTER#####
$XTSTR: BR 6$ ;IF RUNNING ON THE "XOR" TESTER CHANGE
;THIS INSTRUCTION TO A "NOP" (NOP=240)
MOV @ERRVEC,-(SP) ;SAVE THE CONTENTS OF THE ERROR VECTOR
MOV #5$,@ERRVEC ;SET FOR TIMEOUT
TST @#177060 ;TIME OUT ON XOR?
MOV (SP)+,@ERRVEC ;RESTORE THE ERROR VECTOR
BR $SVLAD ;GO TO THE NEXT TEST
5$: CMP (SP)+,(SP)+ ;CLEAR THE STACK AFTER A TIME OUT
MOV (SP)+,@ERRVEC ;RESTORE THE ERROR VECTOR
BR $OVER ;LOOP ON THE PRESENT TEST
6$;#####END OF CODE FOR THE XOR TESTER#####
2$: TSTB SERFLG ;HAS AN ERROR OCCURRED?
BEQ 3$ ;BR IF NO
4$: CLRB SERFLG ;ZERO THE ERROR FLAG
CLR $TIMES ;CLEAR THE NUMBER OF ITERATIONS TO MAKE
3$: BIT #BIT11,@SWR ;INHIBIT ITERATIONS?
BNE 1$ ;BR IF YES
TST $PASS ;IF FIRST PASS OF PROGRAM
BEQ 1$ ;INHIBIT ITERATIONS
INC $ICNT ;INCREMENT ITERATION COUNT
CMP $TIMES,$ICNT ;CHECK THE NUMBER OF ITERATIONS MADE
BGE $OVER ;BR IF MORE ITERATION REQUIRED

```

(3)	004422	000416		
(3)				
(3)	004424	013746	000004	
(3)	004430	012737	004450	000004
(3)	004436	005737	177060	
(3)	004442	012637	000004	
(3)	004446	000436		
(3)	004450	022626		
(3)	004452	012637	000004	
(3)	004456	000441		
(3)	004460			
(3)	004460	105737	001247	
(3)	004464	001404		
(3)	004466	105037	001247	
(3)	004472	005037	001354	
(3)	004476	032777	004000	174600
(3)	004504	001011		
(3)	004506	005737	001126	
(3)	004512	001406		
(3)	004514	005237	001250	
(3)	004520	023737	001354	001250
(3)	004526	002015		

```
(3) 004530 012737 000001 001250 1$: MOV #1,$ICNT ;;REINITIALIZE THE ITERATION COUNTER
(3) 004536 013737 004624 001354 $MXCNT,$TIMES ;;SET NUMBER OF ITERATIONS TO DO
(3) 004544 105237 001246 $SVLAD: INCB $STNMN ;;COUNT TEST NUMBERS
(3) 004550 113737 001246 001124 MOV $STNMN,$TESTN ;;SET TEST NUMBER IN APT MAILBOX
(3) 004556 011637 001252 MOV ($SP),$LPADR ;;SAVE SCOPE LOOP ADDRESS
(3) 004562 013777 001246 174516 $OVER: MOV $STNMN,$DISPLAY ;;DISPLAY TEST NUMBER
(3) 004570 013716 001252 MOV $LPADR,($SP) ;;FUDGE RETURN ADDRESS
(5) 004574 004737 007126 JSR PC,SERV.G ;;FIND OUT IF ^G WAS TYPED
(5) 004600 105037 001424 CLR B MNTFLG ;;CLEAR THE MAINTENANCE BIT SETTER AFTER EACH TEST
(5) 004604 005737 001372 TST MODE ;;HAS THE MODE BEEN CHANGED?
(5) 004610 001003 BNE 4$ ;;IF NOT INTERNAL , GO DO A TEST
(5) 004612 112737 000010 001424 MOVB #MAINT,MNTFLG ;;IF INTERNAL MODE NOW, SET THE MAINTENANCE BIT
(5) 004620 000002 4$: RTI ;;GO DO THE TEST
(5) 004622 000406 BRW: 406
(3) 004624 000005 $MXCNT: 5 ;;MAX. NUMBER OF ITERATIONS
(1)
(1) ;CHECK FOR FREEZE ON CURRENT DATA
(1) ;-----
(1)
(1) 004626 032777 001000 174450 .SCOP1: BIT #SW09,@SWR ;;IS SW09=1(SET)?
(1) 004634 001405 BEQ 1$ ;;BR IF NOT SET.
(1) 004636 005737 001364 TST LOCK ;;IS THERE A TIGHT LOOP SPECIFIED?
(1) 004642 001402 BEQ 1$ ;;IF NO, RETURN
(1) 004644 013716 001364 MOV LOCK,($SP) ;;IF YES, GOTO THE ADDRESS IN LOCK.
(1) 004650 000002 1$: RTI ;;GO BACK.
(1)
(1) 004652 032777 010000 174424 .TYPE: BIT #SW12,@SWR ;;INHIBIT ALL PRINTOUT??
(1) 004660 001403 BEQ $TYPE ;;IF NOT, GO TYPE
(1) 004662 062716 000002 ADD #2,($SP) ;;SKIP OVER MESSAGE POINTER
(1) 004666 000002 RTI ;;RETURN TO WHERE PROCEDURE WAS INVOKED
(2)
(2) .SBTTL TYPE ROUTINE
(2)
(2) *****
(2) *ROUTINE TO TYPE ASCIZ MESSAGE. MESSAGE MUST TERMINATE WITH A 0 BYTE.
(2) *THE ROUTINE WILL INSERT A NUMBER OF NULL CHARACTERS AFTER A LINE FEED.
(2) *NOTE1: $NULL CONTAINS THE CHARACTER TO BE USED AS THE FILLER CHARACTER.
(2) *NOTE2: $FILLS CONTAINS THE NUMBER OF FILLER CHARACTERS REQUIRED.
(2) *NOTE3: $FILLC CONTAINS THE CHARACTER TO FILL AFTER.
(2) *
(2) *CALL:
(2) *1) USING A TRAP INSTRUCTION
(2) * TYPE ,MESADR ;;MESADR IS FIRST ADDRESS OF AN ASCIZ STRING
(2) *OR
(2) * TYPE MESADR
(2) *
(2)
(2) 004670 105737 001323 $TYPE: TSTB $TPFLG ;;IS THERE A TERMINAL?
(2) 004674 100002 BPL 1$ ;;BR IF YES
(2) 004676 000000 HALT ;;HALT HERE IF NO TERMINAL
(2) 004700 000430 BR 3$ ;;LEAVE
(2) 004702 010046 1$: MOV R0,-($SP) ;;SAVE R0
(2) 004704 017600 000002 MOV @2($SP),R0 ;;GET ADDRESS OF ASCIZ STRING
(2) 004710 122737 000001 001140 CMPB #APTENV,$ENV ;;RUNNING IN APT MODE
(2) 004716 001011 BNE 62$ ;;NO,GO CHECK FOR APT CONSOLE
(2) 004720 132737 000100 001141 BITB #APTPOOL,$ENVM ;;SPOOL MESSAGE TO APT
```


Address	Instruction	Comment	Label
(2) 004726	001405	BEQ	62\$
(2) 004730	010037	MOV	R0,61\$
(2) 004734	004737	JSR	PC,\$ATY3
(2) 004740	000000	.WORD	0
(2) 004742	132737	BITB	#APTC\$UP,\$ENV
(2) 004750	001003	BNE	60\$
(2) 004752	112046	MOVB	(R0)+,-(SP)
(2) 004754	001005	BNE	4\$
(2) 004756	005726	TST	(SP)+
(2) 004760	012600	MOV	(SP)+,R0
(2) 004762	062716	ADD	#2,(SP)
(2) 004766	000002	RTI	
(2) 004770	122716	CMPB	#HT,(SP)
(2) 004774	001430	BEQ	8\$
(2) 004776	122716	CMPB	#CRLF,(SP)
(2) 005002	001006	BNE	5\$
(2) 005004	005726	TST	(SP)+
(2) 005006	104402	TYPE	
(2) 005010	001357	\$CRLF	
(2) 005012	105037	CLRB	\$CHAPCNT
(2) 005016	000755	BR	2\$
(2) 005020	004737	JSR	PC,\$TYPEC
(2) 005024	123726	CMPB	\$FILLC,(SP)+
(2) 005030	001350	BNE	2\$
(2) 005032	013746	MOV	\$NULL,-(SP)
(2) 005036	105366	DECB	1(SP)
(2) 005042	002770	BLT	6\$
(2) 005044	004737	JSR	PC,\$TYPEC
(2) 005050	105337	DECB	\$CHARCNT
(2) 005054	000770	BR	7\$
(2) 005056	112716	000040	8\$: MOVB #' ,(SP)
(2) 005062	004737	005102	9\$: JSR PC,\$TYPEC
(2) 005066	132737	000007	BITB #7,\$CHARCNT
(2) 005074	001372	BNE 9\$	
(2) 005076	005726	TST (SP)+	
(2) 005100	000724	BR 2\$	
(2) 005102		\$TYPEC:	
(2) 005102	105777	174202	TSTB @STKS
(2) 005106	100022	BPL 10\$	
(2) 005110	017746	174176	MOV @STKB,-(SP)
(2) 005114	042716	177600	BIC #177600,(SP)
(2) 005120	122716	000023	CMPB #\$XOFF,(SP)
(2) 005124	001012	BNE 102\$	
(2) 005126		101\$:	
(2) 005126	105777	174156	TSTB @STKS
(2) 005132	100375	BPL 101\$	
(2) 005134	117716	174152	MOVB @STKB,(SP)
(2) 005140	042716	177600	BIC #177600,(SP)
(2) 005144	122716	000021	CMPB #\$XON,(SP)
(2) 005150	001366	BNE 101\$	
(2) 005152		102\$:	
(2) 005152	005726	TST (SP)+	

CVDZB-B MACY11 306(1063) 10-AUG-81 11:11 PAGE 25-27
CVDZBB.P11 10-AUG-81 10:56 TYPE ROUTINE

SEQ 0045

```

(2) 005154      105777 174134      10$:      TSTB      @STPS      ::WAIT UNTIL PRINTER IS READY      :MJD001
(2) 005154      105777 174134      BPL      10$      :MJD001
(2) 005160      105777 174126      MOV      2(SP),@STPB  ::LOAD CHAR TO BE TYPED INTO DATA REG.
(2) 005162      105777 000002 174126      CMPB      #CR,2(SP)  ::IS CHARACTER A CARRIAGE RETURN?
(2) 005170      122766 000015 000002      BNE      1$      ::BRANCH IF NO
(2) 005176      001003      CLRB      $CHARCNT  ::YES--CLEAR CHARACTER COUNT
(2) 005200      105037 005220      BR      $TYPEX  ::EXIT
(2) 005204      000406      1$:      CMPB      #LF,2(SP)  ::IS CHARACTER A LINE FEED?
(2) 005206      122766 000012 000002      BEQ      $TYPEX  ::BRANCH IF YES
(2) 005214      001402      INCB      (PC)+  ::COUNT THE CHARACTER
(2) 005216      105227      $CHARCNT: .WORD 0  ::CHARACTER COUNT STORAGE
(2) 005220      000000      $TYPEX: RTS      PC
(2) 005222      000207

.SBTTL  APT COMMUNICATIONS ROUTINE

(2)
(2)
(3) *****
(2) 005224      112737 000001 005470  $ATY1:  MOV      #1,$FFLG  ::TO REPORT FATAL ERROR
(2) 005232      112737 000001 005466  $ATY3:  MOV      #1,$MFLG  ::TO TYPE A MESSAGE
(2) 005240      000403      BR      $ATYC
(2) 005242      112737 000001 005470  $ATY4:  MOV      #1,$FFLG  ::TO ONLY REPORT FATAL ERROR
(2) 005250      005250      $ATYC:
(4) 005250      010046      MOV      R0,-(SP)  ::PUSH R0 ON STACK
(4) 005252      010146      MOV      R1,-(SP)  ::PUSH R1 ON STACK
(2) 005254      105737 005466      TSTB      $MFLG  ::SHO'D TYPE A MESSAGE?
(2) 005260      001450      BEQ      5$      ::IF NOT: BR
(2) 005262      122737 000001 001140      CMPB      #APTENV,$ENV  ::OPERATING UNDER APT?
(2) 005270      001031      BNE      3$      ::IF NOT: BR
(2) 005272      132737 000100 001141      BITB      #APTPOOL,$ENV  ::SHO'D SPOOL MESSAGES?
(2) 005300      001425      BEQ      3$      ::IF NOT: BR
(2) 005302      017600 000004      MOV      @4(SP),R0  ::GET MESSAGE ADDR.
(2) 005306      062766 000002 000004      ADD      #2,4(SP)  ::BUMP RETURN ADDR.
(2) 005314      005737 001120      1$:      TST      $MSGTYPE  ::SEE IF DONE W/ LAST XMISSION?
(2) 005320      001375      BNE      1$      ::IF NOT: WAIT
(2) 005322      010037 001134      MOV      R0,$MSGAD  ::PUT ADDR IN MAILBOX
(2) 005326      105720      2$:      TSTB      (R0)+  ::FIND END OF MESSAGE
(2) 005330      001376      BNE      2$
(2) 005332      163700 001134      SUB      $MSGAD,R0  ::SUB START OF MESSAGE
(2) 005336      006200      ASR      R0  ::GET MESSAGE LGTH IN WORDS
(2) 005340      010037 001136      MOV      R0,$MSGGLT  ::PUT LENGTH IN MAILBOX
(2) 005344      012737 000004 001120      MOV      #4,$MSGTYPE  ::TELL APT TO TAKE MSG.
(2) 005352      000413      BR      5$
(2) 005354      017637 000004 005400  3$:      MOV      @4(SP),4$  ::PUT MSG ADDR IN JSR LINKAGE
(2) 005362      062766 000002 000004      ADD      #2,4(SP)  ::BUMP RETURN ADDRESS
(4) 005370      013746 177776      MOV      177776,-(SP)  ::PUSH 177776 ON STACK
(2) 005374      004737 004670      JSR      PC,$TYPE  ::CALL TYPE MACRO
(2) 005400      000000      4$:      .WORD 0
(2) 005402      5$:
(2) 005402      105737 005470      10$:      TSTB      $FFLG  ::SHO'D REPORT FATAL ERROR?
(2) 005406      001416      BEQ      12$      ::IF NOT: BR
(2) 005410      005737 001140      TST      $ENV  ::RUNNING UNDER APT?
(2) 005414      001413      BEQ      12$      ::IF NOT: BR
(2) 005416      005737 001120      11$:      TST      $MSGTYPE  ::FINISHED LAST MESSAGE?
(2) 005422      001375      BNE      11$      ::IF NOT: WAIT
(2) 005424      017637 000004 001122      MOV      @4(SP),$FATAL  ::GET ERROR #
(2) 005432      062766 000002 000004      ADD      #2,4(SP)  ::BUMP RETURN ADDR.

```


(2) 005440 005237 001120
 (2) 005444 105037 005470
 (2) 005450 105037 005467
 (2) 005454 105037 005466
 (4) 005460 012601
 (4) 005462 012600
 (2) 005464 000207
 (2) 005466 000
 (2) 005467 000
 (2) 005470 000
 (2) 005472
 (2) 000200
 (2) 000001
 (2) 000100
 (2) 000040

12\$: INC MSGTYPE
 CLRB \$FFLG
 CLRB \$LFLG
 CLRB \$MFLG
 MOV (SP)+,R1
 MOV (SP)+,R0
 RTS PC
 \$MFLG: .BYTE 0
 \$LFLG: .BYTE 0
 \$FFLG: .BYTE 0
 .EVEN
 APTSIZE=200
 APTENV=001
 APTSPool=100
 APTCSUP=040

::TELL APT TO TAKE ERROR
 ::CLEAR FATAL FLAG
 ::CLEAR LOG FLAG
 ::CLEAR MESSAGE FLAG
 ::POP STACK INTO R1
 ::POP STACK INTO R0
 ::RETURN
 ::MESSG. FLAG
 ::LOG FLAG
 ::FATAL FLAG

:STRING INPUT ROUTINE

(1) 005472 010346
 (1) 005474 010446
 (1) 005476 017637 000004 005514
 (1) 005504 062766 000002 000004
 (1) 005512 104402
 (1) 005514 000000
 (1) 005516 012704 010424
 (1) 005522 012703 000007
 (1) 005526 105777 173556
 (1) 005532 100375
 (1) 005534 117714 173552
 (1) 005540 142714 000200
 (1) 005544 122427 000015
 (1) 005550 001417
 (1) 005552 105777 173536
 (1) 005556 100375
 (1) 005560 017777 173526 173530
 (1) 005566 005303
 (1) 005570 001356
 (1) 005572 012604
 (1) 005574 012603
 (1) 005576 010346
 (1) 005600 010446
 (1) 005602 104402 001356
 (1) 005606 000741
 (1) 005610 012604
 (1) 005612 012603
 (1) 005614 000002

.INSTR: MOV R3,-(SP) :SAVE R3 ON STACK
 MOV R4,-(SP) :SAVE R4 ON STACK
 MOV @4(SP),MSG :GET THE ADDRESS OF THE MESSAGE TO BE PRINTED
 ADD #2,4(SP) :POINT TO INSTRUCTION AFTER ADDRESS POINTER
 .INST1: TYPE :PRINT THE MESSAGE
 .MSG: 0 :MESSAGE IS POINTED TO FROM HERE
 MOV #INBUF,R4 :POINT R4 TO THE INPUT BUFFER
 MOV #7,R3 :SET THE MAXIMUM NUMBER OF CHARACTERS ALLOWED
 1\$: TSTB @ \$TKS :HAS A CHARACTER BEEN RECEIVED?
 BPL 1\$:IF NO, KEEP WAITING FOR IT
 MOVB @ \$TKB,(R4) :IF YES, SAVE IT IN THE INPUT BUFFER
 BICB #200,(R4) :KEEP ONLY THE 7-BIT ASCII INFORMATION
 CMPB (R4)+,#15 :IS THIS CHARACTER A LINE FEED?
 BEQ INSTR2 :IF SO, TERMINATE THE INPUT SEQUENCE
 2\$: TSTB @ \$TPS :IF NOT, CHECK TO SEE IF THE CHARACTER CAN PRINT
 BPL 2\$:IF WE CAN'T, WAIT UNTIL WE CAN
 MOV @ \$TKB,@ \$TPB :ECHO THE CHARACTER BACK
 DEC R3 :REDUCE THE NUMBER OF CHARACTERS RECEIVED
 BNE 1\$:IF WE DON'T HAVE 7, GO GET SOME MORE
 MOV (SP)+,R4 :IF WE HAVE 7, RESTORE R4
 MOV (SP)+,R3 :RESTORE R3
 .INSTE: MOV R3,-(SP) :SAVE R3 ON THE STACK
 MOV R4,-(SP) :SAVE R4 ON THE STACK
 TYPE \$QUES :PRINT A QUESTION MARK... WHAT'S GOING ON?
 BR .INST1 :GO PRINT THE MESSAGE AGAIN
 INSTR2: MOV (SP)+,R4 :RESTORE R4
 MOV (SP)+,R3 :RESTORE R3
 RTI :RETURN TO THE MAIN PROCEDURE

:CONVERT ASCII STRING TO OCTAL

(1) 005616 010546
 (1) 005620 010446
 (1) 005622 016605 000004
 (1) 005626 012537 006006
 (1) 005632 012537 006010

.PARAM: MOV R5,-(SP) :SAVE R5 ON THE STACK
 MOV R4,-(SP) :SAVE R4 ON THE STACK
 MOV 4(SP),R5 :GET THE SETUP INFORMATION POINTER
 MOV (R5)+,LOLIM :SET THE LOW LIMIT FOR THE INPUT
 MOV (R5)+,HILIM :SET THE HIGH LIMIT FOR THE INPUT

CVDZB-B MACY11 306(1063) 10-AUG-81 11:11 PAGE 25-29
 CVDZBB.P11 10-AUG-81 10:56 APT COMMUNICATIONS ROUTINE

SEQ 0047

```

(1) 005636 012537 006012      MOV      (R5)+,DEVADR      ;SAVE THE ADDRESS WHERE THE RESULT WILL BE STORED
(1) 005642 112537 006014      MOV      (R5)+,LOBITS      ;GET THE MASK OF THE INCORRECT BITS
(1) 005646 112537 006015      MOV      (R5)+,ADRCNT      ;GET THE COUNT OF ITEMS TO BE STORED
(1) 005652 010566 000004      MOV      R5,4(SP)      ;POINT TO WHERE MAIN LINE PROGRAM WILL RESUME
(1) 005656 005005      PARAM1: CLR      R5      ;INITIALIZE THE ASCII TO OCTAL RESULT WORD
(1) 005660 012704 010424      MOV      #INBUF,R4      ;POINT TO THE INPUT BUFFER
(1) 005664 122714 000015      CMPB     #15,(R4)      ;IS THIS CHARACTER A CARRIAGE RETURN?
(1) 005670 001420      BEQ      PARERR      ;IF SO, PRINT THE MESSAGE AGAIN
(1) 005672 121427 000060      1$: CMPB     (R4),#60      ;IS THIS CHARACTER BELOW THE NUMERIC RANGE?
(1) 005676 002415      BLT      PARERR      ;IF SO, GO PRINT THE MESSAGE AGAIN
(1) 005700 121427 000067      CMPB     (R4),#67      ;IS THIS CHARACTER ABOVE THE NUMERIC RANGE?
(1) 005704 003012      BGT      PARERR      ;IF SO, GO PRINT THE MESSAGE AGAIN
(1) 005706 142714 000060      BICB     #60,(R4)      ;ISOLATE THE NUMBER THE CHARACTER REPRESENTS
(1) 005712 152405      BISB     (R4)+,R5      ;CONCATENATE THESE BITS TO THE ALREADY EXISTING STRING
(1) 005714 122714 000015      CMPB     #15,(R4)      ;IS THE NEXT CHARACTER A CARRIAGE RETURN?
(1) 005720 001406      BEQ      LIMITS      ;IF SO, GO SEE IF NUMBER IS WITHIN LIMITS
(1) 005722 006305      ASL      R5      ;CLEAR BIT POSITION 0, MOVE EXISTING STRING TO LEFT
(1) 005724 006305      ASL      R5      ;CLEAR POSITION 1, MOVE STRING TO LEFT AGAIN
(1) 005726 006305      ASL      R5      ;MOVE THE STRING ONE MORE TIME TO MAKE ROOM FOR
(1)                                ;NEXT THREE BITS
(1) 005730 000760      BR       1$      ;GO GET THE NEXT CHARACTER
(1) 005732 104404      PARERR: INSTER      ;THERE WAS AN ERROR... GO PRINT MESSAGE AGAIN
(1) 005734 000750      BR       PARAM1      ;TRY GETTING THE PARAMETERS AGAIN
(1)                                ;TEST TO SEE IF NUMBER IS WITHIN LIMITS
(1)                                ;-----
(1) 005736 020537 006010      LIMITS: CMP     R5,HILIM      ;DOES RESULT EXCEED ITS MAXIMUM CORRECT VALUE?
(1) 005742 101373      BHI      PARERR      ;IF YES, GO PRINT THE MESSAGE AGAIN
(1) 005744 020537 006006      CMP     R5,LOLIM      ;IS THE RESULT LOWER THAN ALLOWED?
(1) 005750 103770      BLO      PARERR      ;IF YES, GO PRINT THE MESSAGE AGAIN
(1) 005752 133705 006014      BITB     LOBITS,R5      ;ARE ANY INCORRECT BITS SET IN THE RESULT?
(1) 005756 001365      BNE      PARERR      ;IF SO, GO PRINT THE MESSAGE AGAIN
(1)                                ;STORE NUMBER AT SPECIFIED ADDRESS
(1) 005760 013704 006012      1$: MOV      DEVADR,R4      ;POINT TO THE LOCATION WHERE THE RESULT WILL BE STORED
(1) 005764 010524      MOV      R5,(R4)+      ;STORE THE RESULT
(1) 005766 062705 000002      ADD      #2,R5      ;CALCULATE THE NEXT DATUM
(1) 005772 105337 006015      DECB     ADRCNT      ;REDUCE COUNT OF STORED RESULTS. IS IT EXCEEDED?
(1) 005776 001372      BNE      1$      ;IF NOT, GO STORE THE NEXT DATUM
(1) 006000 012604      MOV      (SP)+,R4      ;RESTORE R4
(1) 006002 012605      MOV      (SP)+,R5      ;RESTORE R5
(1) 006004 000002      RTI      ;RETURN TO THE MAIN PROGRAM
(1) 006006 000000      LOLIM: 0      ;LOWEST ACCEPTABLE VALUE
(1) 006010 000000      HILIM: 0      ;HIGHEST ACCEPTABLE
(1) 006012 000000      DEVADR: 0      ;LOCATION WHERE RESULT WILL BE STORED
(1) 006014 000      LOBITS: .BYTE 0      ;INCORRECT BITS MASK
(1) 006015 000      ADRCNT: .BYTE 0      ;COUNT OF ITEMS TO BE STORED
(1)                                ;SAVE PC OF TEST THAT FAILED AND R0-R5
(1)                                ;-----
(1) 006016 016637 000004 001404 .SAV05: MOV      4(SP),SAVPC      ;SAVE R7 (PC)

```



```

(1)                                     ;SAVE R0-R5
(1)
(1) 006024 010537 001340      SV05:  MOV     R5,$REG5      ;SAVE R5
(1) 006030 010437 001336      MOV     R4,$REG4      ;SAVE R4
(1) 006034 010337 001334      MOV     R3,$REG3      ;SAVE R3
(1) 006040 010237 001332      MOV     R2,$REG2      ;SAVE R2
(1) 006044 010137 001330      MOV     R1,$REG1      ;SAVE R1
(1) 006050 010037 001326      MOV     R0,$REG0      ;SAVE R0
(1) 006054 000002              RTI                  ;LEAVE.
(1)
(1)                                     ;RESTORE R0-R5
(1)
(1) 006056 013700 001326      .RES05: MOV     $REG0,R0      ;RESTORE R0
(1) 006062 013701 001330      MOV     $REG1,R1      ;RESTORE R1
(1) 006066 013702 001332      MOV     $REG2,R2      ;RESTORE R2
(1) 006072 013703 001334      MOV     $REG3,R3      ;RESTORE R3
(1) 006076 013704 001336      MOV     $REG4,R4      ;RESTORE R4
(1) 006102 013705 001340      MOV     $REG5,R5      ;RESTORE R5
(1) 006106 000002              RTI                  ;LEAVE
(1)
(1)                                     ;CONVERT OCTAL NUMBER TO ASCII AND OUTPUT TO TELEPRINTER
(1) -----
(1)
(1) 006110 104402 001357      .CONVR: TYPE     $CRLF      ;PRINT A CARRIAGE RETURN
(1) 006114 010046              .CNVRT: MOV     R0,-(SP)      ;SAVE R0
(1) 006116 010146              MOV     R1,-(SP)      ;SAVE R1
(1) 006120 010346              MOV     R3,-(SP)      ;SAVE R3
(1) 006122 010446              MOV     R4,-(SP)      ;SAVE R4
(1) 006124 010546              MOV     R5,-(SP)      ;SAVE R5
(1) 006126 017601 000012      MOV     @12(SP),R1      ;PLACE THE ADDRESS OF THE ARGUMENTS IN R1
(1) 006132 062766 000002      ADD     #2,12(SP)      ;POINT TO WHERE MAIN PROGRAM WILL RESUME
(1) 006140 012137 006264      MOV     (R1)+,WRDCNT    ;GET NUMBER OF WORDS TO BE PRINTED
(1) 006144 112105      1$:  MOV     (R1)+,R5      ;GET THE NUMBER OF CHARACTERS TO BE PRINTED
(1) 006146 112100      MOV     (R1)+,R0      ;GET THE NUMBER OF SPACES TO PRINT
(1) 006150 013104      MOV     @R1+,R4      ;COPY THE WORD TO BE CONVERTED
(1) 006152 110537 006266      MOV     R5,CHRCNT      ;COPY THE CHARACTER COUNT
(1) 006156 010403      3$:  MOV     R4,R3      ;COPY THE ARGUMENT WORD AGAIN
(1) 006160 042703 177770      BIC     #^C<7>,R3      ;ISOLATE THREE BITS TO BE TREATED AS A CHARACTER
(1) 006164 062703 000060      ADD     #060,R3      ;MAKE AN ASCII CHARACTER OUT OF THEM
(1) 006170 110346      MOV     R3,-(SP)      ;SAVE THAT CHARACTER
(1) 006172 006004      ROR     R4      ;MOVE THE NEXT THREE BITS INTO PLACE
(1) 006174 006204      ASR     R4      ;MOVE THEM AGAIN
(1) 006176 006204      ASR     R4      ;AND FINALLY A THIRD TIME
(1) 006200 005305      DEC     R5      ;REDUCE CHARACTER COUNT.ARE ALL CHARACTERS
(1)                                     ;BUILT?
(1) 006202 001365      BNE     3$      ;IF NO, GO BUILD THE NEXT ONE.
(1) 006204 012703 010466      MOV     #MDATA,R3      ;NOW POINT TO WHERE NUMBER WILL BE PRINTED FROM
(1) 006210 112623      4$:  MOV     (SP)+,(R3)+      ;STORE THE CHARACTER, STARTING WITH THE MOST
(1) 006212 105337 006266      DECB    CHRCNT      ;REDUCE COUNT. ARE ALL CHARACTERS TRANSFERRED?
(1) 006216 001374      BNE     4$      ;IF NO, GO TRANSFER ANOTHER
(1) 006220 105700      TSTB    R0      ;ARE ANY SPACES TO BE PRINTED?
(1) 006222 001404      BEQ     6$      ;IF NO, DON'T SET UP ANY
(1) 006224 112723 000040      5$:  MOV     #040,(R3)+      ;ADD A SPACE TO THE OUTPUT BUFFER
(1) 006230 105300      DECB    R0      ;REDUCE THE COUNT. SHOULD WE PRINT MORE?
(1) 006232 001374      BNE     5$      ;IF YES, GO ADD ANOTHER SPACE
(1) 006234 105013      6$:  CLRB    (R3)      ;TERMINATE THE OUTPUT BUFFER WITH A ZERO

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-31
 CVDZBB.P11 10-AUG-81 10:56 APT COMMUNICATIONS ROUTINE

SEQ 0049

```

(1) 006236 104402 010466      TYPE      ,MDATA      ;PRINT THE STRING WE JUST BUILT
(1) 006242 005337 006264      DEC      WRDCNT      ;REDUCE THE WORD COUNT. ARE ANY MORE WORDS LEFT?
(1) 006246 001336              BNE      1$          ;IF YES, GO CONVERT THEM
(1) 006250 012605              MOV      (SP)+,R5      ;RESTORE R5
(1) 006252 012604              MOV      (SP)+,R4      ;RESTORE R4
(1) 006254 012603              MOV      (SP)+,R3      ;RESTORE R3
(1) 006256 012601              MOV      (SP)+,R1      ;RESTORE R1
(1) 006260 012600              MOV      (SP)+,R0      ;RESTORE R0
(1) 006262 000002              RTI                      ;RETURN TO THE MAIN PROGRAM
(1) 006264 000000      WRDCNT: 0
(1) 006266      000          CHRCNT: .BYTE
(1) 006267      000          SPACNT: .BYTE 0
(1)                                ;NUMBER OF CHARACTERS TO PRINT
(1)                                ;NUMBER OF SPACES TO PRINT
(1) 006270 000000      BINWRD: 0

(1)                                ;TRAP DISPATCH SERVICE
(1)                                ;ARGUMENT OF TRAP IS EXTRACTED
(1)                                ;AND USED AS OFFSET TO OBTAIN POINTER
(1)                                ;TO SELECTED SUBROUTINE

(1) 006272 010046              .TRPSR: MOV      R0,-(SP)      ;SAVE R0. USE R0 TO FIND TRAP ROUTINE
(1) 006274 016600 000002      MOV      2(SP),R0      ;GET TRAP ADDRESS
(1) 006300 005740              TST      -(R0)          ;GET TRAP
(1) 006302 111000              MOVB     (R0),R0      ;GET RIGHT BYTE OF TRAP(TRAP OFFSET)
(1) 006304 006300              ASL      R0          ;POSITION OFFSET FOR TABLE INDEXING
(1) 006306 016000 001742      MOV      .TRPTAB(R0),R0 ;PLACE INDEXED ADDRESS OF TABLE IN R0
(1) 006312 000200              RTS      R0          ;TRANSFER TO THAT ADDRESS AND RESTORE OLD R0

(1)                                ;DEVICE CLEAR ROUTINE
(1)                                ;ISSUE A DEVICE CLEAR
(1)                                ;-----
(1) 006314              .DEVICE.CLR:
(1) 006314 052777 000020 173466  BIS      #DCLR,ADZVCSR      ;SET DCLR
(1) 006322 032777 000020 173460 1$: BIT      #DCLR,ADZVCSR      ;DID IT CLEAR?
(1) 006330 001374              BNE      1$          ;BR IF NO
(1) 006332 000002              RTI                      ;EXIT ROUTINE

(1)                                ;ROUTINE TO HANDLE MAINTENANCE BIT SETTING WITH DEVICE CLEAR
(1)                                ;-----
(1) 006334 104413              .DCLASM: DEVICE.CLR      ;ISSUE A DEVICE CLEAR
(1) 006336 153777 001424 173444  BISB     MNTFLG,ADZVCSR      ;LOAD THE MAINTENANCE BIT IF IT IS I MODE
(1) 006344 000002              RTI                      ;RETURN TO CALLING ROUTINE

(1) 006346              .DELAY:
(1) 006346 010046              MOV      R0,-(SP)      ;SAVE R0
(1) 006350 013700 006364      MOV      DLYCNT,R0      ;SET COUNT
(1) 006354 005300              1$: DEC      R0          ;DELAY
(1) 006356 001376              BNE      1$          ;
(1) 006360 012600              MOV      (SP)+,R0      ;RESTORE R0
(1) 006362 000002              RTI                      ;LEAVE ROUTINE
(1) 006364 000001      DLYCNT: .WORD 1      ;PATCHABLE LOC FOR MORE TIME

(1)                                ;ADVANCE TO NEXT TEST HANDLER
(1)                                ;-----
(1)
(1)

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-32
 CVDZBB.P11 10-AUG-81 10:56 APT COMMUNICATIONS ROUTINE

SEQ 0050

(1)	006366	013716	001362	.ADVANCE:MOV	NEXT,(SP)	:CRUNCH STACK WITH ADDRESS OF SCOPE CALL
(1)	006372	005037	001364	CLR	LOCK	:RESET TIGHT LOOP ADDRESS
(1)	006376	000002		RTI		:CHECK TO SEE IF OLD TEST GETS REPEATED
(1)						
(1)						:ROUTINE TO SHIFT LINE POINTER
(1)						:AND SWITCH TESTS IF NECESSARY
(1)						-----
(1)	006400	106302		.SHIFT: ASLB	R2	:POINT TO THE NEXT LINE
(1)	006402	032702	000020	BIT	#BIT4,R2	:HAVE WE PASSED ALL LINE POINTERS?
(1)	006406	001402		BEQ	1\$	:IF NOT, RETURN TO THE TEST
(1)	006410	022626		POP2SP		:REMOVE THE TRAP CALL FROM THE STACK
(1)	006412	104400		ADVANCE		:GO TO THE NEXT TEST
(1)	006414	000002		1\$: RTI		:RETURN TO THE PRESENT TEST
(1)						

```

(1)                                     ;LINE PARAMETER REGISTER SETUP ROUTINE
(1)
(1) 006416 010146                      .LPRSET:MOV R1,-(SP)      ;SAVE CONTENTS OF R1
(1) 006420 010246                      MOV R2,-(SP)      ;SAVE CONTENTS OF R2
(1) 006422 013701 001370                MOV PAR,R1        ;MOVE DEFAULT PARAM. INTO R1
(1) 006426 012702 000001                MOV #1,R2          ;INIT. FOR LINE 1
(1) 006432 010177 173362                1$: MOV R1,@DZVLPR    ;LOAD PARAM. REGISTER
(1) 006436 005201                      INC R1            ;SET R1 FOR NEXT LINE
(1) 006440 106302                      ASLB R2           ;SET R2 FOR NEXT LINE
(1) 006442 032702 000020                BIT #BIT4,R2      ;ALL LINES DONE?
(1) 006446 001771                      BEQ 1$           ;IF NO LOAD NEXT LINE
(1) 006450 012602                      MOV (SP)+,R2       ;RELOAD R2
(1) 006452 012601                      MOV (SP)+,R1       ;RELOAD R1
(1) 006454 000002                      RTI              ;RETURN
(1)
(1)                                     ;ROUTINE TO ZERO DATA BUFFER
(1)
(1) 006456 010046                      .BUFSET:MOV R0,-(SP) ;SAVE CONTENTS OF R0
(1) 006460 012700 001426                MOV #TD0,R0       ;SET R0 TO TOP OF BUFFER
(1) 006464 005020                      1$: CLR (R0)+      ;CLEAR BUFFER LOCATION
(1) 006466 022700 001446                CMP #STOP,R0      ;IS BUFFER ALL CLEARED
(1) 006472 001374                      BNE 1$           ;IF NOT CLEAR NEXT LOCATION
(1) 006474 012600                      MOV (SP)+,R0       ;RELOAD R0
(1) 006476 000002                      RTI              ;RETURN
(1)
(1)                                     ;ERROR HANDLER
(1) -----
(1)
(1) 006500 004737 007126                $ERROR: JSR PC,SERV.G ;FIND OUT IF <^G> WAS HIT
(1) 006504 032777 010000 172572        BIT #SW12,@SWR     ;BELL ON ERROR?
(1) 006512 001406                      BEQ XBX          ;BR IF NO BELL
(1) 006514 105777 172574                TSTB @STPS       ;TTY READY.
(1) 006520 100003                      BPL XBX          ;DON'T WAIT IF TTY NOT READY.
(1) 006522 112777 000207 172566        MOVB #207,@STPB    ;PUSH A BELL AT THE TTY.
(1) 006530 032777 020000 172546        XB$: BIT #SW13,@SWR ;DELETE ERROR PRINT OUT?
(1) 006536 001113                      BNE HALTS        ;BR IF NO PRINT OUT WANTED.
(1) 006540 021637 001262                CMP (SP),$ERRPC  ;WAS THIS ERROR FOUND LAST TIME?
(1) 006544 001404                      BEQ 1$           ;BR IF YES
(1) 006546 011637 001262                MOV (SP),$ERRPC  ;RECORD BEING HERE
(1) 006552 105037 001247                CLRB $ERFLG     ;PREPARE HEADER
(1) 006556 104407                      1$: SAVO5        ;SAVE ALL PROC REGISTERS
(1) 006560 011605                      MOV (SP),R5      ;GET THE PC OF ERROR
(1) 006562 162705 000002                SUB #2,R5        ;GET ADDRESS OF TRAP CALL
(1) 006566 011504                      MOV (R5),R4      ;GET ERROR INSTRUCTION
(1) 006570 110437 001260                MOVB R4,$ITEMB   ;COPY TEST NUMBER FOR APT HANDLING
(1) 006574 006304                      ASL R4           ;MULT BY TWO
(1) 006576 061504                      ADD (R5),R4      ;DOUBLE IT
(1) 006600 006304                      ASL R4           ;MULT AGAIN
(1) 006602 042704 177001                BIC #177001,R4   ;CLEAR JUNK
(1) 006606 062704 015216                ADD #.ERRTAB,R4  ;GET POINTER
(1) 006612 012437 006736                MOV (R4)+,ERRMSG ;GET ERROR MESSAGE
(1) 006616 012437 006750                MOV (R4)+,DATAHD ;GET DATA HEADRER
(1) 006622 011437 006762                MOV (R4),DATABP  ;GET DATA TABLE
(1) 006626 105737 001247                TSTB $ERFLG     ;TYPE HEADER
(1) 006632 001403                      BEQ TYPMSG       ;BR IF YES
(1) 006634 005737 006762                TST DATABP      ;DOES DATA TABLE EXIST?

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-34
 CVDZBB.P11 10-AUG-81 10:56 APT COMMUNICATIONS ROUTINE

SEQ 0052

```

(1) 006640 001044
(1) 006642 104402 001357
(1) 006646 104402 001357
(1) 006652 005737 001364
(1) 006656 001402
(1) 006660 104402 010041
(1) 006664 104402 010027
(1) 006670 104412 007120
(1) 006674 104402 010121
(1) 006700 104412 007112
(1) 006704 104402 007771
(1) 006710 104412 004332
(1) 006714 104402 001357
(1) 006720 112737 177777 001247
(1) 006726 005737 006736
(1) 006732 001402
(1) 006734 104402
(1) 006736 000000
(1) 006740
(1) 006740 005737 006750
(1) 006744 001402
(1) 006746 104402
(1) 006750 000000
(1) 006752 005737 006762
(1) 006756 001402
(1) 006760 104411
(1) 006762 000000
(1) 006764 104410
(1) 006766 122737 000001 001140
(1) 006774 001007
(1) 006776 113737 001260 007010
(1) 007004 004737 005242
(1) 007010 000000
(1) 007012 000777
(1) 007014 022737 004316 000042
(1) 007022 001403
(1) 007024 005777 172254
(1) 007030 100004
(1) 007032 016677 000002 172246
(1) 007040 000000
(1) 007042 005237 001256
(1) 007046 004737 007126
(1) 007052 032777 000400 172224
(1) 007060 001007
(1) 007062 032777 002000 172214
(1) 007070 001407
(1) 007072 013737 001362 001252
(1) 007100 012706 001120
(1) 007104 000177 172142
(1) 007110 000002
(1) 007112 000001
(1) 007114 006 002
(1) 007116 001404
(1) 007120 000001
(1) 007122 002 002
(1) 007124 001246

TYPMSG: BNE TYPDAT :BR IF YES.
          TYPE ,SCRLF :TYPE A CARRIAGE RETURN
          TYPE ,SCRLF :AND TYPE ANOTHER
          TST LOCK
          BEQ 1$
          TYPE ,MASTEK
1$:      TYPE ,MTSTN
          CNVRT ,XTSTN :SHOW IT
          TYPE ,MERRPC :TYPE PC.
          CNVRT ,ERTABO :SHOW IT
          TYPE ,MCSRX
          CNVRT ,XCSR
          TYPE ,SCRLF
          MOVB #-1, SERFLG :GIVE A CR/LF
          TST ERRMSG :NO MORE HEADER UNLESS NO DATA TABLE.
          BEQ WTBS.FM :IS THERE AN ERROR MESSAGE?
          TYPE :BR IF NO.
          :TYPE
          :ERROR MESSAGE
          :
          :DATA HEADER?
          :BR IF NO
          :TYPE
          :DATA HEADER
          :DATA TABLE?
          :BR IF NO.
          :SHOW
          :DATA TABLE
          :RESTORE PROC REGISTERS
          :IS APT RUNNING?
          :SKIP APT CALL IF NOT
          :COPY ERROR NUMBER
          :CALL APT SERVICE
          :ERROR NUMBER STUCK HERE
          :LOCK UP HERE
          :CHECK TO SEE IF IN ACT-11 MODE
          :IF SO, HANDLE ACCORDINGLY
          :HALT ON ERROR?
          :BR IF NO HALT ON ERROR
          :SHOW ERROR PC IN DATA DISPLAY
          :HALT
          :UPDATE ERROR COUNT
          :FIND OUT IF ^G WAS TYPED
          :GOTO TOP OF TEST?
          :BR IF YES
          :GOTO NEXT TEST?
          :BR IF NO
          :SET FOR NEXT TEST
          :RESET SP
          :GOTO SPECIFIED TEST
          :RETURN

ERRMSG: 0
WTBS.FM: TST DATAHD
          BEQ TYPDAT
          TYPE
DATAHD: 0
TYPDAT: TST DATABP
          BEQ RESREG
          CNVRT
DATABP: 0
RESREG: RES05
HALTS: CMPB #APTENV, $ENV
        BNE 1$
        MOVB $ITEMB, 5$
        JSR PC, $ATY4
        .WORD 0
5$:      BR 10$
10$:     BR #SENDAD, @#42
15$:     CMP 20$
        BEQ 20$
        TST @SWR
        BPL EXITER
20$:     MOV 2(SP), @DISPLAY
        HALT
EXITER: INC $ERTTL
        JSR PC, SERV.G
        BIT #SW08, @SWR
        BNE 1$
        BIT #SW10, @SWR
        BEQ 2$
        MOV NEXT, $LPADR
1$:      MOV #STACK, SP
        JMP @SLPADR
2$:      RTI
ERTABO: 1
        .BYTE 6,2
        SAVPC
XTSTN: 1
        .BYTE 2,2
        $TSTNM

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-35
 CVDZBB.P11 10-AUG-81 10:56 APT COMMUNICATIONS ROUTINE

SEQ 0053

```

(1) 007126 017746 172160      SERV.G: MOV    @STKB,-(SP)      ;OTHERWISE, GET THE LAST CHARACTER TYPED
(1) 007132 042716 000200      BIC    #BIT7,(SP)      ;STRIP PARITY(EIGHTH) BIT
(1) 007136 122726 000007      CMPB   #7,(SP)+      ;IS IT ^G?
(1) 007142 001076              BNE     6$              ;IF NOT, IGNORE INPUT
(1) 007144 032777 004000 172136 BIT    #4000,@STKS      ;RX BUSY?
(1) 007152 001365              BNE     SERV.G          ;BR IF YES
(1) 007154 007154              GETSWR=                      ;;GPA
(1) 007154 017737 172124 007362 1$: MOV    @SWR,90$      ;SAVE (SWR).
(1) 007162 104402 007342      TYPE   .89$      ;TYPE HEADER FOR OLD SWITCH REGISTER
(1) 007166 104412 007354      CNVRT   .88$      ;TYPE THE NUMBER ITSELF
(1) 007172 104402 007364      TYPE   .91$      ;AFTER HAVING CONVERTED IT TO ASCII
(1) 007176 105037 007370      CLRB   92$      ;CLEAR SWR CHANGE FLAG
(1) 007202 005077 172076      CLR    @SWR      ;CLEAR THE SOFTWARE SWITCH REGISTER
(1) 007206 105777 172076      3$: TSTB   @STKS      ;WAIT FOR DONE.
(1) 007212 100375              BPL     3$              ;CONTINUE WAITING FOR IT
(1) 007214 017746 172072      MOV    @STKB,-(SP)      ;PUT THE CHARACTER ON THE STACK
(1) 007220 042716 000200      BIC    #BIT7,(SP)      ;STRIP PARITY BIT
(1) 007224 122726 000015      CMPB   #15,(SP)+      ;IS IT THE CARRIAGE RETURN CHAR?
(1) 007230 001433              BEQ     4$              ;IF SO, GO PRINT CRLF
(1) 007232 105777 172056      2$: TSTB   @STPS      ;IS THE OUTPUT BUFFER AVAILABLE
(1) 007236 100375              BPL     2$              ;IF NOT, WAIT FOR IT TO BE READY
(1) 007240 105237 007370      INCB   92$      ;INDICATE THAT THE SWR WAS CHANGED
(1) 007244 014677 172046      MOV    -(SP),@STPB      ;PLACE THE CHARACTER THERE(ECHO BACK)
(1) 007250 000241              CLC              ;GET READY TO ROTATE
(1) 007252 006177 172026      ROL     @SWR      ;MOVE THE EXISTING BITS OVER
(1) 007256 006177 172022      ROL     @SWR      ;TO MAKE ROOM FOR THE INCOMING
(1) 007262 006177 172016      ROL     @SWR      ;THREE BITS FROM THIS CHARACTER
(1) 007266 103735              BCS     1$              ;ERROR
(1) 007270 022627 000060      CMP     (SP)+,#60      ;IS IT LOWER THAN 0?
(1) 007274 002732              BLT     1$              ;IF SO, GO ASK AGAIN
(1) 007276 026627 177776 000067 CMP     -2(SP),#67      ;IS IT HIGHER THAN 7?
(1) 007304 003326              BGT     1$              ;IF SO, GO ASK AGAIN
(1) 007306 042746 177770      BIC     #^C<7>,-(SP)    ;ISOLATE INFORMATION BITS
(1) 007312 052677 171766      BIS     (SP)+,@SWR      ;ADD THEM TO THE SWITCH REGISTER
(1) 007316 000733              BR      3$              ;GO CHECK FOR THE NEXT CHARACTER
(1) 007320 105737 007370      4$: TSTB   92$      ;HAS THE SWR BEEN CHANGED?
(1) 007324 001003              BNE     5$              ;IF YES GO TYPE CRLF
(1) 007326 013777 007362 171750 5$: MOV    90$,@SWR      ;IF NOT RESTORE SWR
(1) 007334 104402 001357      6$: TYPE   $CRLF      ;TYPE A CARRIAGE RETURN AND LINE FEED
(1) 007340 000207              RTS     PC              ;RETURN TO CALLING PROCEDURE
(1) 007342 020200 051450 051127 89$: .ASCIIZ <200>? (SWR)=/?
(1) 007354 000001              .EVEN
(1) 007356 006      000      88$: 1
(1) 007360 007362              .BYTE   6,0
(1) 007362 000000      90$: .WORD   0
(1) 007364 036457 000057      91$: .ASCIIZ  ?/=/?
(1) 007370 000      92$: .BYTE   0
(1) 007372              .EVEN
(2) .SBTTL POWER DOWN AND UP ROUTINES
(2)
(3)
(2) *****
(2) :POWER DOWN ROUTINE
(2) $PWRDN: MOV    $SILLUP,@PWRVEC ;;SET FOR FAST UP
(2) 007400 012737 000340 000026 MOV    #340,@PWRVEC+2 ;;PRIO:7

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-36
CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0054

```

(4) 007406 010046      MOV      R0,-(SP)      ;;PUSH R0 ON STACK
(4) 007410 010146      MOV      R1,-(SP)      ;;PUSH R1 ON STACK
(4) 007412 010246      MOV      R2,-(SP)      ;;PUSH R2 ON STACK
(4) 007414 010346      MOV      R3,-(SP)      ;;PUSH R3 ON STACK
(4) 007416 010446      MOV      R4,-(SP)      ;;PUSH R4 ON STACK
(4) 007420 010546      MOV      R5,-(SP)      ;;PUSH R5 ON STACK
(4) 007422 017746 171656 MOV      @SWR,-(SP)      ;;PUSH @SWR ON STACK
(2) 007426 010637 007542 MOV      SP,$SAVR6      ;;SAVE SP
(2) 007432 012737 007444 000024 MOV      #SPWRUP,@#PWRVEC ;;SET UP VECTOR
(2) 007440 000000      HALT
(2) 007442 000776      BR      .-2      ;;HANG UP
(2)
(3) *****
(2) :POWER UP ROUTINE
(2) 007444 012737 007536 000024 $PWRUP: MOV      #SILLUP,@#PWRVEC ;;SET FOR FAST DOWN
(2) 007452 013706 007542      MOV      $SAVR6,SP      ;;GET SP
(2) 007456 005037 007542      CLR      $SAVR6      ;;WAIT LOOP FOR THE TTY
(2) 007462 005237 007542 1$: INC      $SAVR6      ;;WAIT FOR THE INC
(2) 007466 001375      BNE      1$      ;;OF WORD
(4) 007470 012677 171610      MOV      (SP)+,@SWR      ;;POP STACK INTO @SWR
(4) 007474 012605      MOV      (SP)+,R5      ;;POP STACK INTO R5
(4) 007476 012604      MOV      (SP)+,R4      ;;POP STACK INTO R4
(4) 007500 012603      MOV      (SP)+,R3      ;;POP STACK INTO R3
(4) 007502 012602      MOV      (SP)+,R2      ;;POP STACK INTO R2
(4) 007504 012601      MOV      (SP)+,R1      ;;POP STACK INTO R1
(4) 007506 012600      MOV      (SP)+,R0      ;;POP STACK INTO R0
(2) 007510 012737 007372 000024 MOV      #SPWRDN,@#PWRVEC ;;SET UP THE POWER DOWN VECTOR
(2) 007516 012737 000340 000026 MOV      #340,@#PWRVEC+2 ;;PRIO:7
(2) 007524 104402      TYPE      MPFAIL      ;;REPORT THE POWER FAILURE
(2) 007526 007544 $PWRMG: .WORD      MPFAIL      ;;POWER FAIL MESSAGE POINTER
(2) 007530 012716      MOV      (PC)+,(SP)      ;;RESTART AT RESTART
(2) 007532 011070 $PWRAD: .WORD      RESTART      ;;RESTART ADDRESS
(2) 007534 000002      RTI
(2) 007536 000000 $SILLUP: HALT      ;;THE POWER UP SEQUENCE WAS STARTED
(2) 007540 000776      BR      .-2      ;; BEFORE THE POWER DOWN WAS COMPLETE
(2) 007542 000000      $SAVR6: 0      ;;PUT THE SP HERE
(2) 007544 050200 051127 043040 MPFAIL: .ASCIZ      <200>/PWR FAILED. RESTART AT LAST TEST /
(2) 007607 200 047105 020104 MEPASS: .ASCIZ      <200>/END PASS CVDZB-B /
(2) 007633 200 052522 047116 MR: .ASCIZ      <200>/RUNNING /
(2) 007647 200 051120 043517 MERR2: .ASCIZ      <200>/PROGRAM INDICATES NO DEVICES PRESENT./
(2) 007716 044600 051516 043125 MERR3: .ASCIZ      <200>/INSUFFICIENT DATA!/
(2) 007742 046200 041517 020113 MLOCK: .ASCIZ      <200>/LOCK ON SELECTED TEST/
(2) 007771 103 051123 020072 MCSRX: .ASCIZ      /CSR: /
(2) 007777 126 041505 020072 MVECX: .ASCIZ      /VEC: /
(2) 010005 120 051501 042523 MPASSX: .ASCIZ      /PASSES: /
(2) 010016 051105 047522 051522 MERRX: .ASCIZ      /ERRORS: /
(2) 010027 124 051505 020124 MTSTN: .ASCIZ      /TEST NO: /
(2) 010041 052 000040 MASTEK: .ASCIZ      /* /
(2) 010044 052200 050131 020105 MNEW: .ASCIZ      <200>/TYPE A BIT MAP OF DZV11'S DESIRED ACTIVE: /
(2) 010121 120 035103 000040 MERRPC: .ASCIZ      /PC: /
(2) 010126 046600 050101 047440 XHEAD: .ASCIZ      <200>/MAP OF DZV11 STATUS/<200>
(2) 010154 044600 046114 043505 MBADLN: .ASCIZ      <200>/ILLEGAL ENTRY IN STAGGERED MODE/<200>
(2)
(2) 010216 000002      .EVEN
(2) 010220 006 003 XSTATQ: 2
(2) 010222 001344      .BYTE      6,3
      $TMP1

```

CVDZB-B MACY11 306(1063) 10-AUG-81 11:11 PAGE 25-37
 CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0055

```

(2) 010224 006 002 .BYTE 6,2
(2) 010226 001346 $TMP2
(1) .EVEN
(2) ;THIS ROUTINE ESTABLISHES WHICH MAINTENANCE MODE THE DEVICE IS IN
(2) ;-----
(2) ;E=EXTERNAL LOOP BACK
(2) ;I=INTERNAL LOOP BACK
(2) ;S=STAGGERED LOOP BACK
(2) 010230 017605 000000 .SETFLG:MOV @ (SP),R5 ;PICK UP ADDRESS OF TAG
(2) 010234 042737 000040 010424 BIC #40,INBUF ;STRIP LOWER CASE
(2) 010242 122737 000105 010424 CMPB #'E,INBUF ;IS IT EXTERNAL LOOP BACK ?
(2) 010250 001005 BNE 4$ ;NO
(2) 010252 013715 010342 MOV 1$, (R5) ;YES STORE INFO
(2) 010256 105037 001424 CLRB MNTFLG ;SET MAINT BIT =0
(2) 010262 000422 BR 7$ ;GET OUT
(2) 010264 122737 000111 010424 4$: CMPB #'I,INBUF ;IS IT INTERNAL LOOP BACK ?
(2) 010272 001006 BNE 5$ ;NO
(2) 010274 013715 010344 MOV 2$, (R5) ;YES STORE INFO
(2) 010300 112737 000010 001424 MOVB #MAINT,MNTFLG ;SET UP THE MAINTENANCE FLAG LOADER
(2) 010306 000410 BR 7$ ;GET OUT
(2) 010310 122737 000123 010424 5$: CMPB #'S,INBUF ;IS IT STAGGERED LOOP BACK ?
(2) 010316 001007 BNE 6$ ;WHAT ?
(2) 010320 013715 010346 MOV 3$, (R5) ;YES STORE INFO
(2) 010324 105037 001424 CLRB MNTFLG ;ZERO BITS
(2) 010330 062716 000002 7$: ADD #2, (SP) ;POP AROUND
(2) 010334 000002 RTI
(2) 010336 104404 6$: INSTER ;RETRY
(2) 010340 000733 BR .SETFLG ;DITTO
(2) 010342 000200 1$: .WORD 200 ;EXTERNAL = E
(2) 010344 000000 2$: .WORD 0 ;INTERNAL = I
(2) 010346 100000 3$: .WORD 100000 ;STAGGERED = S

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-38
 CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0056

```

(2)                                     ;COMPARE THE FIRST CHARACTER IN THE TELETYPE INPUT
(2)                                     ;BUFFER TO THE CHARACTERS 'E' AND 'C'.
(2)                                     ;IF THE CHARACTER IS 'E' CLEAR THE FLAG
(2)                                     ;IF THE CHARACTER IS 'C' SET THE FLAG
(2)
(2) 010350 017605 000000 .PAWCH:MOV @ (SP),R5
(2) 010354 142737 000040 010424 BICB #40,INBUF ;SET FOR LOWER CASE INPUT
(2) 010362 122737 000105 010424 CMPB #'E,INBUF ;IS IT 'E' ?
(2) 010370 001002 BNE 1$
(2) 010372 105015 CLRB (R5) ;000
(2) 010374 000406 BR 2$
(2) 010376 122737 000103 010424 1$: CMPB #'C,INBUF ;IS IT 'C' ?
(2) 010404 001005 BNE 3$
(2) 010406 112715 177777 MOVB #-1,(R5) ;3177
(2) 010412 062716 000002 2$: ADD #2,(SP)
(2) 010416 000002 RTI
(2) 010420 104404 3$: INSTER ;RETRY
(2) 010422 000752 BR .PAWCH
(2)
(2)                                     ;BUFFERS FOR INPUT-OUTPUT
(2)
(2) 010424 000000 INBUF: 0
(2) 010466 .=.+40
(2) ; TEMP: 0 ; TEMP AREA UNUSED. ;:GPA
(2) ; .=.+40 ; DELETED TO CONSERVE SPACE. ;:GPA
(2) 010466 000000 MDATA: 0
(2) 010530 .=.+40
(2)

```

```

(2)
(2)
(2)
(2)
(2)
(2)
(2)
(2)
(2)
(2)
(2) 010530 005737 001406      CYCLE: TST      DZVACTV      ;ARE ANY DZV11'S TO BE TESTED?
(2) 010534 001004              BNE      1$          ;BR IF OK.
(2) 010536 104402 007647      TYPE      ,MERR2        ;NO DZV11'S SELECTED!!
(2) 010542 000000              HALT                     ;STOP THE SHOW.
(2) 010544 000776              BR      -2              ;DISQUALIFY CONT. SW.
(2) 010546 013737 004624 001354 1$: MOV      $MXCNT,$TIMES ;RESTORE THE NUMBER OF ITERATIONS TO MAKE
(2) 010554 033737 001412 001406 BIT      RUN,DZVACTV ;IS THIS ONE 'ACTIVE'
(2) 010562 001017              BNE      2$          ;BR IF GOOD ONE FOUND.
(2) 010564 006137 001412      ROL      RUN            ;UPDATE POINTER
(2) 010570 005537 001412      ADC      RUN            ;CATCH CARRY FROM RUN
(2) 010574 062737 000012 001420 ADD      #12,ACTIVE ;UPDATE ADDRESS POINTER.
(2) 010602 022737 001740 001420 CMP      #DZV.END,ACTIVE ;HAVE WE PASSED THE END OF THE MAP?
(2) 010610 001356              BNE      1$          ;IF NO, KEEP GOING; NOT ALL TESTED FOR.
(2) 010612 012737 001500 001420 MOV      #DZV.MAP,ACTIVE ;RESET ADDRESS POINTER.
(2) 010620 000752              BR      1$          ;KEEP LOOKING FOR ACTIVE DZV11
(2) 010622 006137 001412      ROL      RUN            ;UPDATE POINTER.
(2) 010626 005537 001412      ADC      RUN            ;CATCH CARRY.
(2) 010632 013700 001420      MOV      ACTIVE,R0       ;GET ADDRESS POINTER.
(2) 010636 062737 000012 001420 ADD      #12,ACTIVE ;UPDATE.
(2) 010644 022737 001740 001420 CMP      #DZV.END,ACTIVE
(2) 010652 001003              BNE      3$          ;ALL DONE?
(2) 010654 012737 001500 001420 MOV      #DZV.MAP,ACTIVE ;BR IF NO.
(2) 010662 012037 001174      MOV      (R0)+,$BASE ;RESTORE POINTER.
(2) 010666 012037 002040      MOV      (R0)+,DZVRIV ;LOAD SYSTEM CTRL. REG
(2) 010672 012037 001366      MOV      (R0)+,LINE ;LOAD VECTOR
(2) 010676 012037 001370      MOV      (R0)+,PAR ;SET UP DZV LINES ACTIVE
(2) 010702 012037 001372      MOV      (R0)+,MODE ;SET UP PARAMETERIZATION
(2) 010706 105037 001424      CLRB     MNTFLG ;RESET MAINT. FLAG IF
(2) 010712 005737 001372      TST      MODE ;RUNNING TESTS
(2) 010716 001003              BNE      9$          ;IN
(2) 010720 112737 000010 001424 MOVB     #MAINT,MNTFLG ;INTERNAL MAINT. MODE
(2) 010726 004737 011074      JSR      PC,DZVLEV ;SET UP
(2) 010732 005737 000042      TST      2#42 ;ARE WE UNDER MONITOR CONTROL?
(2) 010736 001051              BNE      7$          ;IF YES, SKIP THIS SETUP
(2) 010740 032777 000002 170336 BIT      #SW01,$SWR ;IF SW01=1, GET STARTING TEST #
(2) 010746 001445              BEQ      7$          ;BR IF NO TEST IS TO BE INPUTTED
(2) 010750 104402 001357      TYPE      ,$CRLF
(2) 010754 104403              INSTR                     ;CALL THE STRING INPUT ROUTINE
(2) 010756 010027              MTSTN                    ;POINTER TO MESSAGE TO BE PRINTED
(2) 010760 104405              PARAM                     ;CALL THE OCTAL TO ASCII CONVERT ROUTINE
(2) 010762 000001              1 ;LOWEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 010764 001000              1000 ;HIGHEST LEGITIMATE VALUE OF EXPECTED RESPONSE
(2) 010766 001246              $STNM ;POINTER TO MAP LOCATION TO BE FILLED
(2) 010770 000              .BYTE 0 ;MASK OF INVALID BITS FOR THIS PARAMETER
(2) 010771 001              .BYTE 1 ;NUMBER OF PARAMETERS TO STORE
(2) 010772 012700 012070      MOV      #TST1,R0

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-40
CVDZBB.P11 10-AUG-81 10:56

POWER DOWN AND UP ROUTINES

SEQ 0058

```

(2) 010776 022710 000004      5$:  CMP      #4,(R0)
(2) 011002 001020              BNE      6$
(2) 011004 022760 012737 000002  CMP      #12737,2(R0)
(2) 011012 001014              BNE      6$
(2) 011014 023760 001246 000004  CMP      $TSTNM,4(R0)      :IS THIS THE TEST ?
(2) 011022 001010              BNE      6$      :IF NOT, DON'T PROCESS NUMBER
(2) 011024 010037 001252      MOV      R0,$LPADR      :SAVE PC
(2) 011030 062737 000002 001252  ADD      #2,$LPADR      :POP OVER PREVIOUS SCOPE
(2) 011036 104402 001357      TYPE     $CRLF
(2) 011042 000412              BR       8$
(2) 011044 005720              6$:  TST      (R0)+
(2) 011046 020027 014222      CMP      R0,$TLAST+10
(2) 011052 001351              BNE      5$
(2) 011054 104402 001356      TYPE     $QUES
(2) 011060 000733              BR       4$
(2) 011062 012737 012070 001252 7$:  MOV      #TST1,$LPADR      :PREPARE TEST ADDRESS
(2) 011070 000177 170156      8$:  RESTART:JMP    @SLPADR      :GO START TESTING.***WARNING!***
(2)                                :THIS JUMP IS USED BY POWER UP ROUTINE!!!!
(2)                                :THIS UTILITY SETS UP CSR'S,SETS UP VECTORS.
(2) 011074 013700 002040      DZVLEV: MOV    DZVRIV,R0      :PLACE THE BASE VECTOR ADDRESS IN R0
(2) 011100 062700 000002      ADD      #2,R0      :CALCULATE THE RECEIVER INTERRUPT STATUS ADDR.
(2) 011104 010037 002042      MOV      R0,DZVRIS      :STORE IT HERE
(2) 011110 062700 000002      ADD      #2,R0      :CALCULATE THE TRANSMITTER INTERRUPT VECTOR
(2) 011114 010037 002044      MOV      R0,DZVTIV      :STORE IT HERE
(2) 011120 062700 000002      ADD      #2,R0      :CALCULATE THE TRANSMITTER VECTOR STATUS ADDRESS
(2) 011124 010037 002046      MOV      R0,DZVTIS      :STORE IT HERE
(2)                                :THIS SEGMENT SETS UP POINTERS FOR THE GIVEN DZV11. $BASE IS THE BASE ADDRESS
(2)                                :OF THE DEVICE
(2) 011130 013700 001174      MOV      $BASE,R0      :COPY THE ADDRESS BEING LOADED
(2) 011134 010037 002010      MOV      R0,DZVCSR      :XXX0
(2) 011140 005200              INC      R0
(2) 011142 010037 002012      MOV      R0,HDZVCSR      :XXX1
(2) 011146 005200              INC      R0
(2) 011150 010037 002014      MOV      R0,DZVRBUF      :XXX2
(2) 011154 010037 002020      MOV      R0,DZVLPR      :XXX2
(2) 011160 005200              INC      R0
(2) 011162 010037 002016      MOV      R0,HDZVRBUF      :XXX3
(2) 011166 010037 002022      MOV      R0,HDZVLPR      :XXX3
(2) 011172 005200              INC      R0
(2) 011174 010037 002024      MOV      R0,DZVTCR      :XXX4
(2) 011200 005200              INC      R0
(2) 011202 010037 002026      MOV      R0,HDZVTCR      :XXX5
(2) 011206 005200              INC      R0
(2) 011210 010037 002030      MOV      R0,DZVMSR      :XXX6
(2) 011214 010037 002034      MOV      R0,DZVTDR      :XXX6
(2) 011220 005200              INC      R0
(2) 011222 010037 002032      MOV      R0,HDZVMSR      :XXX7
(2) 011226 010037 002036      MOV      R0,HDZVTDR      :XXX7
(2) 011232 000207      RTS      PC

```

```
(2) 011234 000002
(2)
(2) .PARMD: RTI
(2) .REM 8
(2)
(2) .PARMD: MOV (SP),R5
(2) MOV (R5)+,6$
(2) MOV (R5)+,7$
(2) MOV (R5)+,8$
(2) MOVB (R5)+,9$
(2) MOVB (R5)+,10$
(2) MOV R5,(SP)
(2) 2$: CLR R5
(2) MOV #INBUF,R4
(2) CMPB #15,(R4)
(2) BEQ 3$
(2) 1$: CMPB (R4),#0
(2) BLT 3$
(2) CMPB (R4),#9
(2) BGT 3$
(2) BICB #0,(R4)
(2) CLR R2
(2) BISB (R4)+,R2
(2) ADD R2,R5
(2) CMPB #15,(R4)
(2) BEQ 4$
(2) ASL R5 ;X2
(2) MOV R5,R2 ;SAVE X2
(2) ASL R5 ;X4
(2) ASL R5 ;X8
(2) ADD R2,R5 ;TIMES 10
(2) BR 1$
(2) 3$: INSTER
(2) BR 2$
(2)
(2) ;TEST TO SEE IF NUMBER IS WITHIN LIMITS
(2)
(2) 4$: CMP R5,7$
(2) BHI 3$
(2) CMP R5,6$
(2) BLO 3$
(2) BITB 9$,R5
(2) BNE 3$
(2)
(2) ;STORE NUMBER AT SPECIFIED ADDRESS
(2)
(2) 5$: MOV 8$,R4
(2) MOV R5,(R4)+
(2) ADD #2,R5
(2) DECB 10$
(2) BNE 5$
(2) RTI
(2) 6$: 0
(2) 7$: 0
(2) 8$: 0
(2) 9$: .BYTE 0
(2) 10$: .BYTE 0
```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-42
CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0060

(2)

; END OF .PARMD DELETE RANGE

8

;;GPA

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-43
 CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0061

```

(2)                                     :*ROUTINE USED TO SET UP THE DIAGNOSTIC VIA APT.
(2)                                     :*IF BIT7 IN THE ENVIRONMENT MODE (SEVM) BYTE IS SET,
(2)                                     :*THE PROGRAM WILL LOAD ITS PARAMETERS FROM THE ETABLE.
(2)
(2) 011236 012700 001500      SETAPT: MOV    #DZV.MAP,R0      :POINT TO THE DEVICE MAP TABLE
(2) 011242 013701 001174      MOV    $BASE,R1      :BUILD DEVICE ADDRESSES IN R1
(2) 011246 013702 001170      MOV    $VECT1,R2      :BUILD DEVICE VECTORS IN R2
(2) 011252 042702 177007      BIC    #^C<770>,R2      :STRIP AWAY OTHER INFORMATION
(2) 011256 012704 001204      MOV    #SDDW0,R4      :POINT TO THE BEGINNING OF DEVICE PARAMETERS
(2) 011262 013705 001176      MOV    $DEVN,R5      :GET THE MAP OF ACTIVE DEVICES
(2) 011266 105037 001414      CLRB   DZVNUM      :INITIALIZE THE NO. OF ACTIVE DEVICES
(2) 011272 005037 001410      CLR    SAVACTV      :CLEAR THE ACTIVE BIT MAP
(2) 011276 006005              1$:  ROR    R5      :GET A DEVICE SELECTION BIT
(2) 011300 103407              BCS    3$          :IF IT IS SELECTED, GO SET UP A MAP
(2) 011302 001422              BEQ    5$          :IF NO MORE ARE SELECTED, GET OUT OF SETUP
(2) 011304 005724              TST    (R4)+      :POINT TO NEXT DEVICE DESCRIPTOR
(2) 011306 062701 000010      2$:  ADD    #10,R1      :SET UP THE NEXT ADDRESS
(2) 011312 062702 000010      ADD    #10,R2      :SET UP THE NEXT VECTOR GROUP
(2) 011316 000767              BR     1$          :GO SEE IF MORE DEVICES REMAIN
(2) 011320 006137 001410      3$:  ROL    SAVACTV      :SET BIT IN ACTIVE DEVICE MAP
(2) 011324 105237 001414      INCB   DZVNUM      :INCREMENT NO. OF ACTIVE DEVICES
(2) 011330 010120              MOV    R1,(R0)+      :LOAD DEVICE ADDRESS
(2) 011332 010220              MOV    R2,(R0)+      :LOAD THE VECTOR ADDRESS
(2) 011334 013720 001200      MOV    $CDW1,(R0)+      :GET THE NUMBER OF LINES IN OPERATION
(2) 011340 012420              MOV    (R4)+,(R0)+      :LOAD DEVICE PARAMETERS
(2) 011342 013720 001202      MOV    $CDW2,(R0)+      :LOAD DEFAULT TESTING MODE
(2) 011346 000757              BR     2$          :GO BUILD THE NEXT ADDRESS
(2) 011350 012710 177777      5$:  MOV    #-1,(R0)      :TERMINATE THE DEVICE MAP
(2) 011354 012737 001142 001304  MOV    #SSWREG,SWR      :SET TO SOFTWARE APT SWITCH REGISTER
(2) 011362 000207              RTS    PC          :RETURN TO PRINT STATUS TABLE

```

```

(2)                                     :*ROUTINE USED TO "AUTO SIZE" THE DZV11
(2)                                     :*CSR AND VECTOR.
(2)                                     :*NOTE: THE CSR MAY BE ANY WHERE IN THE FLOATING
(2)                                     :*      ADDRESS RANGE (160000:163770)
(2)                                     :*      AND THE VECTOR MAY BE ANY WHERE IN THE
(2)                                     :*      FLOATING VECTOR RANGE (300:770)
(2)                                     :*

```

```

(2)
(2) 011364 000005              AUTO.SIZE: RESET      :INSURE A BUS INIT.
(2) 011366 105337 001422      DECB   INIFLG      :SHOW THAT I WAS HERE
(2) 011372 012702 001500      CSRMAP: MOV    #DZV.MAP,R2      :LOAD MAP POINTER.
(2) 011376 012703 001204      MOV    #SDDW0,R3      :POINT TO ETABLE DEVICE DESCRIPTOR WORDS
(2) 011402 005022              1$:  CLR    (R2)+      :ZERO ENTIRE MAP
(2) 011404 022702 001740      CMP    #DZV.END,R2      :ALL DONE?
(2) 011410 001374              BNE    1$          :BR IF NO
(2) 011412 105037 001414      CLRB   DZVNUM      :SET OCTAL NUMBER OF DZV11'S TO 0
(2) 011416 012702 001500      MOV    #DZV.MAP,R2      :SET FOR FIRST ADDRESS TO BE TESTED
(2) 011422 012701 160000      MOV    #160000,R1      :SET FOR NON-EXISTENT DEVICE TIME OUT
(2) 011426 012737 011672 000004  MOV    #6$,&#4      :TRY TO SET MASTER SCAN ENABLE
(2) 011434 052711 000040 000004  BIS    #BIT5,(R1)      :TRY TO TRANSMIT ON ANY LINE
(2) 011440 052761 000017 000004  BIS    #17,4(R1)      :USE R0 AS A COUNTER
(2) 011446 005000              CLR    R0          :HAS TRANSMITTER READY COME UP?
(2) 011450 005711              7$:  TST    (R1)

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-44
 CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0062

(2)	011452	100403				BMI	8\$		:IF SO, GO GET A FINAL CHECK
(2)	011454	005300				DEC	R0		:REDUCE COUNT. TIME UP?
(2)	011456	001374				BNE	7\$		:IF NOT, KEEP WAITING
(2)	011460	000437				BR	3\$		:ASSUME IT'S NOT A DZV11
(2)	011462	032761	000017	000004	8\$:	BIT	#17,4(R1)		:ARE ANY TCR BITS STILL SET? THEY SHOULD BE
(2)	011470	001433				BEQ	3\$		:IF IT'S NOT, ASSUME IT'S NOT A DZV11
(2)	011472	032711	000040			BIT	#BIT5,(R1)		:IS MASTER SCAN ENABLE STILL SET?
(2)	011476	001430				BEQ	3\$		:IF NOT, ASSUME IT'S NOT A DZV11
(2)	011500	052711	000020			BIS	#20,(R1)		:SET DEVICE CLEAR
(2)	011504	000240				NOP			
(2)	011506	032711	000040			BIT	#40,(R1)		:DID SCANNER CLEAR
(2)	011512	001022				BNE	3\$		:IF NOT ASSUME IT IS NOT DZV
(2)	011514	005061	000004			CLR	4(R1)		:GET RID OF TCR BITS
(2)									:AT THIS POINT IT IS ASSUMED THAT R1 HOLDS A DZV11 CSR ADDRESS.
(2)	011520	010122				MOV	R1,(R2)+		:STORE CSR IN CORE TABLE.
(2)	011522	005722				TST	(R2)+		:POP OVER VECTOR STORE AREA
(2)	011524	012722	000017			MOV	#17,(R2)+		:SET THE DEFAULT LINE SELECTION PARAMETER
(2)	011530	012712	017470			MOV	#17470,(R2)		:SET THE DEFAULT PARAMETERS
(2)	011534	012223				MOV	(R2)+,(R3)+		:COPY PARAMETERS INTO ETABLE DESCRIPTOR
(2)	011536	005022				CLR	(R2)+		:SET THE DEFAULT MODE OF OPERATION
(2)	011540	012712	177777			MOV	#-1,(R2)		:TERMINATE LIST
(2)	011544	105237	001414			INCB	DZVNUM		:UPDATE DEVICE COUNTER
(2)	011550	122737	000020	001414		CMPB	#20,DZVNUM		:ARE MAX. NO. OF DEV FOUND?
(2)	011556	001405				BEQ	100\$		:YES DON'T LOOK FOR ANY MORE.
(2)	011560	062701	000010		3\$:	ADD	#10,R1		:UPDATE CSR POINTER ADDRESS
(2)	011564	022701	164000			CMP	#164000,R1		
(2)	011570	001321				BNE	2\$		:BR IF MORE ADDRESS TO CHECK.
(2)	011572				100\$:				
(2)	011572	105737	001414			TSTB	DZVNUM		:WERE ANY DZV11'S FOUND AT ALL?
(2)	011576	001430				BEQ	5\$		:ERROR AUTO SIZER FOUND NO DZV11'S IN THIS SYS.
(2)	011600	113701	001414			MOVB	DZVNUM,R1		
(2)	011604	012737	000001	001410		MOV	#1,SAVACTV		:CREATE A BIT MAP OF
(2)	011612	005301			4\$:	DEC	R1		:THE DEVICES IN THE SYSTEM
(2)	011614	001404				BEQ	98\$		
(2)	011616	000261				SEC			
(2)	011620	006137	001410			ROL	SAVACTV		
(2)	011624	000772				BR	4\$		
(2)	011626	013737	001500	001174	98\$:	MOV	DZCRO,\$BASE		:POINT TO THE ADDRESS OF FIRST DEVICE
(2)	011634	013737	001510	001202		MOV	MANTO,\$CDW2		:INDICATE TO ETABLE WHAT MODE IS BEING USED
(2)	011642	012737	000006	000004	99\$:	MOV	#6,\$#4		:RESTORE TRAP VECTOR
(2)	011650	013737	001410	001176		MOV	SAVACTV,\$DEVN		:SAVE ACTIVE REGISTER
(2)	011656	000410				BR	VECMAP		:GO FIND THE VECTOR NOW.
(2)	011660	104402	007647		5\$:	TYPE	,MERR2		:NOTIFY OPR THAT NO DZV11'S FOUND.
(2)	011664	005000				CLR	R0		:MAKE DATA DISPLAY ZERO
(2)	011666	000000				HALT			:STOP THE SHOW
(2)	011670	000776				BR	-2		:DISABLE CONT. SW.
(2)	011672	012716	011560		6\$:	MOV	#3\$,(SP)		:ENTERED BY NON-EXISTENT TIME-OUT
(2)	011676	000002				RTI			:RETURN TO MAINSTREAM
(2)									
(2)	011700	012737	000200	000022	VECMAP:	MOV	#MASK,\$#22		:SET IOT TRAP PRIORITY
(2)	011706	012737	012022	000020		MOV	#4\$,\$#20		:SET IOT TRAP VECTOR
(2)	011714	012702	001500			MOV	#DZV.MAP,R2		:SET SOFTWARE POINTER
(2)	011720	012700	000300			MOV	#300,R0		:FLOATING VECTORS START HERE.
(2)	011724	012701	000302			MOV	#302,R1		:PC OF IOT INSTR.
(2)	011730	010120			1\$:	MOV	R1,(R0)+		:START FILLING VECTOR AREA
(2)	011732	012721	000004			MOV	#4,(R1)+		:WITH .+2; IOT

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-45
 CVDZBB.P11 10-AUG-81 10:56 POWER DOWN AND UP ROUTINES

SEQ 0063

(2)	011736	022021				CMP	(R0)+(R1)+	:ADD 2 TO R0 +R1
(2)	011740	020127	001000			CMP	R1,#1000	:HAS THE VECTOR AREA BEEN EXCEEDED?
(2)	011744	101771				BLOS	1\$	:BR IF MORE TO FILL
(2)	011746	013704	001410			MOV	SAVACTV,R4	:STORE TEMPORARILY
(2)	011752	006004		2\$:		ROR	R4	:BRING OUT A BIT
(2)	011754	103036				BCC	5\$	:BR IF ALL DONE
(2)	011756	106427	000000			MTPS	#0	:ZERO CPU PRIO
(2)	011762	012772	040040	000000		MOV	#BIT14+BIT5,a(R2)	:SET TIE AND MAS SCAN
(2)	011770	011201				MOV	(R2),R1	:GET CSR
(2)	011772	112761	000017	000004		MOVB	#17,4(R1)	:SET THE TCR BITS FOR ALL LINES
(2)								:ATTEMPT TO FORCE AN INTERRUPT
(2)	012000	005200				INC	R0	:STALL
(2)	012002	001376				BNE	.-2	:FOR TIME TO INTERRUPT
(2)	012004	012762	000300	000002		MOV	#300,2(R2)	:NO INTERRUPT ASSUME 300 AND FIX DZV11 LATER
(2)	012012	000005				RESET		:INIT
(2)	012014	062702	000012		3\$:	ADD	#12,R2	:POP SOFTWARE POINTER
(2)	012020	000754				BR	2\$	:KEEP GOING
(2)	012022	011662	000002		4\$:	MOV	(SP),2(R2)	:GET VECTOR ADDRESS
(2)	012026	162762	000010	000002		SUB	#10,2(R2)	:POINT BACK TO THE CORRECT VECTOR
(2)	012034	042762	000007	000002		BIC	#7,2(R2)	:CLEAR JUNK
(2)	012042	022626				POP2SP		:POP IOT JUNK OFF STACK
(2)	012044	012716	012014			MOV	#3\$,(SP)	:SET FOR RETURN
(2)	012050	000002				RTI		
(2)	012052	013737	001502	001170	5\$:	MOV	DZVC0,\$VECT1	:COPY VECTOR OF FIRST DEVICE INTO ETABLE
(2)	012060	012737	004362	000020		MOV	#.SCOPE,IOTVEC	:RESTORE THE SCOPE TRAP
(2)	012066	000207				RTS	PC	:ALL DONE WITH "AUTO SIZING"

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-46
CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0064

2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2748
(5)
(4)
(2)
(2)
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786

012070 000004
012072 012737 000001 001246
012100 012737 012532 001362
012106 012737 012446 001364
012114 104417
012116 104421
012120 005037 001374
012124 104422
012126 012702 000001
012132 052777 010040 167650
012140 030237 001366
012144 001533
012146 013700 001374
012152 006300
012154 010277 167644
012160 105777 167624
012164 100001
012166 104020
012170 005003
012172 005004
012174 005777 167610
012200 100404
012202 104414
012204 005204
012206 001372
012210 104003
012212 116077 001426 167614
012220 005260 001426
012224 020327 000017
012230 105006
012232 032777 020000 167550
012240 001413
012242 104013
012244 000411
012246 005004
012250 032777 020000 167532
012256 001004
012260 104414
012262 005204
012264 001371

```

***** TEST 1 *****
*THIS TEST VERIFIES OVERRUN AND SILO ALARM
*ONE LINE AT A TIME - BASED UPON VALID LINES
*AS EACH OF THE FIRST 16 CHARS ARE SENT; SILO ALARM IS
*TESTED TO BE CLEARED. ON THE 16TH CHAR THE PROGRAM THEN
*EXPECTS SILO ALARM TO SET. THEN THE ENTIRE
*SILO IS FILLED AND AN OVERRUN IS EXPECTED ON THE 65TH
*CHAR PULLED OUT OF THE SILO.
*ERROR PRINTOUTS WILL REPORT TRANSMITTING LINE NO.
*USING SWITCH NINE FOR THIS TEST SENDS 20. CHARACTERS
*ON DZV LINE PREVIOUSLY SELECTED CONTINUOUSLY WHILE SW09=1.
*USED TO SCOPE SILO ALARM PULSES, ETC.

::* TEST 1
*****
TST1: SCOPE
MOV #1,STSTNM ;LOAD THE NUMBER OF THIS TEST
MOV #TST2,NEXT ;POINT TO THE START OF THE NEXT TEST
MOV #18$,LOCK ;SET FOR LOOP
DCLASM ;SET DCLR IN CSR AND SET MNTFLG
LPRSET ;LOAD LINE PARAMETERS
CLR SAVLIN ;INIT LINE INDICATOR
BUFSET ;ZERO DATA BUFFER
MOV #1,R2 ;LINE POINTER
BIS #MSENAB!SILOEN,ADZVCSR ;START SCANNER & SET SILO ENABLE
3$: BIT R2,LINE ;VALID LINE?
BEQ 21$ ;IF NOT GO TO NEXT LINE
MOV SAVLIN,R0 ;MAKE OFFSET
ASL R0 ;MAKE POWER OF TWO
MOV R2,ADZVTDR ;SET TCR BIT
4$: TSTB ADZVCSR ;REC DONE = 1 ?
BPL +4
ERROR 20 ;REC DONE SHOULD NOT = 1
CLR R3 ;SET CHARACTER COUNT
5$: CLR R4
6$: TST ADZVCSR ;IS TRDY SET?
BMI 7$ ;IF YES, LOAD CHAR.
DELAY ;WAIT FOR TRDY TO SET
INC R4 ;INC DELAY COUNTER
7$: ERROR 3 ;*TRDY FAILED TO SET
MOVB TD0(R0),ADZVTDR ;LOAD A CHARACTER
INC TD0(R0) ;SET UP NEXT CHARACTER
CMP R3,#15. ;16 CHARACTERS ?
BHS 8$
BIT #SILOAL,ADZVCSR ;SILO ALARM = 0 ?
BEQ 10$ ;YES
ERROR 13 ;*SILO ALARM SHOULD NOT = 1
;UNTIL 16. DATA CHARACTERS
BR 10$
8$: CLR R4
9$: BIT #SILOAL,ADZVCSR
BNE 10$
INC R4
BNE 9$

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-47
CVDZBB.P11 10-AUG-81 10:56 DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0065

```

2787 012266 104014          ERROR 14          : *SILO ALARM FAILED TO SET!
2788                                     : SILO ALARM SHOULD =1 AFTER 16.
2789                                     : DATA CHARACTERS
2790 012270 005203          10$: INC R3          : INC CHAR COUNT
2791 012272 022703 000102    CMP #66.,R3       : FINISHED SENDING CHARACTERS ?
2792 012276 001335          BNE 5$             : NO
2793 012300 005004          CLR R4
2794 012302 104414          DELAY
2795 012304 105204          INCB R4
2796 012306 001375          BNE -4
2797                                     : NOW LETS READ THE SILO
2798 012310 013705 001374    MOV SAVLIN,R5      : MAKE EXPECTED LINE #
2799 012314 005737 001372    TST MODE          : IS THIS TEST IN STAGGERED MODE?
(1) 012320 100006          BPL 13$             : IF NOT, SKIP STAGGERED SETUP
(1)
(1)
(1)
(1) 012322 006205          ASR R5              : GET THE LAST BIT INTO THE CARRY BIT
(1) 012324 103402          BCS 11$             : IF IT IS SET, GO CLEAR IT
(1) 012326 000261          SEC                 : IF IT IS CLEAR SET IT HERE
(1) 012330 000401          BR 12$              : SKIP THE CLEARING
(1) 012332 000241          11$: CLC            : CLEAR THE CARRY BIT (INVERSION OF LINE PARITY)
(1) 012334 006105          12$: ROL R5         : GET THE NEW BIT BACK INTO R5
2800 012336 000305          13$: SWAB R5       : PUT IN UPPER BYTE
2801 012340 052705 100000    BIS #DVALID,R5    : ADD DATA VALID
2802 012344 017704 167444    14$: MOV @DZVRBUF,R4 : ACTUAL
2803 012350 020405          CMP R4,R5          : ACTUAL VS. EXPECTED
2804 012352 001401          BEQ 15$            : YES
2805 012354 104006          ERROR 6            : *DATA/CONTENTS DID NOT COMPARE
2806 012356 032777 020000 167424 15$: BIT #SILOAL,@DZVCSR : SILO ALARM= 0 ?
2807 012364 001401          BEQ 16$            : YES
2808 012366 104016          ERROR 16           : READING DZVRBUF DID NOT CLEAR SILO ALARM
2809 012370 005205          16$: INC R5         : UP CHARACTER
2810 012372 120527 000077    CMPB R5,#63.      : LAST SILO CHAR ?....64TH CHAR
2811 012376 101762          BLOS 14$
2812 012400 005205          INC R5              : ADD 1 MORE FOR THE CLOBBED CHAR
2813 012402 052705 040000    BIS #OVRUN,R5     : ADD OVERRUN TO EXPECTED
2814 012406 120527 000101    CMPB R5,#65.      : LAST CHARACTER ?
2815 012412 001754          BEQ 14$
2816 012414 017704 167374    MOV @DZVRBUF,R4   : FOR GOOD MEASURE
2817 012420 005704          TST R4             : DATA VALID SHOULD = 0
2818 012422 100001          BPL 17$            : YES
2819 012424 104017          ERROR 17           : DATA VALID SHOULD = 0
2820 012426 040277 167372    17$: BIC R2,@DZVTICR : CLR TCR BIT
2821 012432 104401          SCOP1              : LOOP?
2822 012434 005237 001374    21$: INC SAVLIN    : INC EXPECTED LINE
2823 012440 104420          SHIFT              : NEXT LINE
2824 012442 000137 012140    JMP 3$           : YES
2825
2826                                     : TIGHT SCOPE LOOP FOR THIS TEST. SENDS 20. CHARACTERS
2827                                     : ON DZV LINE PREVIOUSLY SELECTED CONTINUOUSLY WHILE SW09=1.
2828                                     : USED TO SCOPE SILO ALARM PULSES, ETC.
2829
2830 012446 052777 010040 167334 18$: BIS #MSENAB!SILOEN,@DZVCSR : SETUP DEVICE
2831 012454 012777 012522 167362    MOV #20$,@DZVTIV : SETUP TRANSMITTER VECTOR
2832 012462 012701 000024          MOV #20.,R1      : TEMPORARY COUNT OF CHARACTER BURST

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-48
CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0066

```

2833 012466 050277 167332      BIS      R2,ADZVTCR      ;ENABLE LINE
2834 012472 052777 040000 167310  BIS      #TIE,ADZVCSR      ;ENABLE INTERRUPTS
2835 012500 106427 000000      MTPS      #0      ;LOWER PRIORITY
2836 012504 000001      WAIT      ;ALLOW INTERRUPTS
2837 012506 077102      SOB      R1,19$      ;REDUCE COUNT. ALL CHARACTERS SENT?
2838 012510 042777 050040 167272  BIC      #SILOEN!MSENAB!TIE,ADZVCSR ;RESET SILO COUNTER, CLEAR STROBE
2839 012516 104401      SCOP1      ;LOOP AGAIN?
2840 012520 000742      BR      17$      ;IF NOT, RETURN TO WHERE YOU LEFT OFF
2841 012522 112777 000252 167304 20$:  MOVB     #252,ADZVTDR      ;SEND A CHARACTER
2842 012530 000002      RTI      ;ALLOW MORE CHARACTERS TO COME
2843      ;***** TEST 2 *****
2844      ;*THIS TEST THAT "SILO ENABLE" WILL INHIBIT
2845      ;*RECEIVER INTERRUPTS AND THAT ON THE
2846      ;*16TH CHAR THAT "SILO ALARM" WILL CAUSE AN
2847      ;*INTERRUPT WITH "RIE" SET.
2848      ;*THIS WILL DO ALL SELECTED LINES ONE AT A TIME.
2849      ;*ERROR PRINTOUTS WILL REPORT TRANSMITTING LINE NO.
2851      ;** TEST 2
2852      ;*****
(5)      ;*****
(4)      ;*****
(2) 012532 000004      TST2:   SCOPE
(2) 012534 012737 000002 001246      MOV      #2,$TSTNM      ;LOAD THE NUMBER OF THIS TEST
(2) 012542 012737 013032 001362      MOV      #TST3,NEXT      ;POINT TO THE START OF THE NEXT TEST
2852 012550 012737 012574 001364      MOV      #3$,LOCK      ;SET FOR LOOP
2853 012556 104417      DCLASM      ;SET DCLR IN CSR AND SET MNTFLG
2854 012560 104421      LPRSET      ;LOAD LINE PARAMETERS
2855 012562 005037 001374      CLR      SAVLIN      ;INIT LINE INDICATOR
2856 012566 104422      BUFSET      ;ZERO DATA BUFFER
2857 012570 012702 000001      MOV      #1,R2      ;LINE POINTER
2858 012574 012777 013004 167236 3$:  MOV      #11$,ADZVRIV      ;SET FOR UNEXPECTED INTER.
2859 012602 012777 000200 167232      MOV      #MASK,ADZVRIS      ;SET PRIO.
2860 012610 052777 010140 167172      BIS      #MSENAB!SILOEN!RIE,ADZVCSR
2861      ;START SCANNER & SET SILO ENABLE
2862 012616 030237 001366      BIT      R2,LINE      ;VALID LINE?
2863 012622 001477      BEQ      18$      ;IF NOT GO TO NEXT LINE
2864 012624 005777 167164      TST      ADZVRBUF      ;EMPTY THE SILO
2865 012630 100775      BMI      -4      ;BR IF DATA VALID IS SET!
2866 012632 106427 000000      MTPS      #0      ;SET PROCESSOR PRIORITY TO 0
2867 012636 013700 001374      MOV      SAVLIN,R0      ;MAKE OFFSET
2868 012642 006300      ASL      R0      ;MAKE POWER OF TWO
2869 012644 010277 167154      MOV      R2,ADZVTCR      ;SET TCR BIT
2870 012650 005004      CLR      R4
2871 012652 005777 167132 5$:  TST      ADZVCSR
2872 012656 100404 6$:  BMI      7$
2873 012660 104414      DELAY
2874 012662 005204      INC      R4
2875 012664 001372      BNE      6$
2876 012666 104003      ERROR      3
2877 012670 116077 001426 167136 7$:  MOVB     TDO(R0),ADZVTDR ;*TRDY FAILED TO SET
2878 012676 005260 001426      INC      TDO(R0)      ;LOAD A CHARACTER
2879 012702 022760 000017 001426      CMP      #15.,TDO(R0)      ;SET UP NEXT CHARACTER
2880 012710 001406      BEQ      8$      ;15 CHARS YET?
2881 012712 032777 020000 167070      BIT      #SILOAL,ADZVCSR ;SILO ALARM = 0 ?
2882 012720 001401      BEQ      +4      ;YES
2883 012722 104013      ERROR      13      ;*SILO ALARM SHOULD NOT = 1
2884      ;UNTIL 16. DATA CHARACTERS
2885 012724 000752      BR      6$

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 25-49
 CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0067

2886	012726	012777	013012	167104	8\$:	MOV	#12\$,ADZVRIV	:SET NEW VECTOR
2887	012734	005777	167050			TST	ADZVCSR	:READY FOR 16TH CHAR
2888	012740	100375				BPL	.-4	
2889	012742	016077	001426	167064		MOV	ID0(R0),ADZVTDR	:LOAD THE 16TH CHAR.
2890	012750	005004				CLR	R4	
2891	012752	032777	020000	167030	9\$:	BIT	#SILOAL,ADZVCSR	
2892	012760	001005				BNE	10\$	
2893	012762	104414				DELAY		
2894	012764	005204				INC	R4	
2895	012766	001371				BNE	9\$	
2896	012770	104014				ERROR	14	:*SILO ALARM FAILED TO SET!
2897	012772	000410				BR	17\$	:SILO ALARM SHOULD =1 AFTER 16.
2898								:DATA CHARACTERS
2899	012774	000240			10\$:	NOP		:STALL
2900	012776	000240				NOP		
2901	013000	104027				ERROR	27	:SILO ALARM NOT INTERRUPTING.
2902	013002	000404				BR	17\$	:CONTINUE TEST.
2903	013004	022626			11\$:	POP2SP		:FAKE RTI
2904	013006	104012				ERROR	12	:RX SHOULD NOT INTERRUPT
2905	013010	000401				BR	17\$	:CONTINUE
2906	013012	022626			12\$:	POP2SP		:GOOD INTERRUPT TO HERE.
2907	013014	040277	167004		17\$:	BIC	R2,ADZVTDR	:CLR TCR BIT
2908	013020	104401				SCOP1		:LOOP?
2909	013022	005237	001374		18\$:	INC	SAVLIN	:INC EXPECTED LINE
2910	013026	104420				SHIFT		:NEXT LINE
2911	013030	000661				BR	3\$	:YES

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11
 CVDZBB.P11 10-AUG-81 10:56

PAGE 26
 DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0068

2913
 2914
 2915
 2916
 2917
 2919
 (5)
 (4)
 (2)
 (2)
 2920
 2921
 2922
 2923
 2924
 2925
 2926
 2927
 2928
 2929
 2930
 2931
 2932
 2933
 2934
 2935
 2936
 2937
 2938
 2939
 2940
 2941
 2942
 2943
 2944
 2945
 2946
 2947
 2948
 2949
 2950
 2951
 2952
 2953
 2954
 2955
 2956
 2957
 2958
 2959
 2960
 2961
 2962
 2963
 2964
 2965

013032	000004		
013034	012737	000003	001246
013042	012737	013574	001362
013050	104417		
013052	013737	001366	013572
013060	013737	001366	013312
013066	104421		
013070	104422		
013072	012777	013314	166740
013100	012777	000200	166734
013106	012777	013200	166730
013114	012777	000200	166724
013122	052777	040140	166660
013130	113777	001366	166666
013136	106427	000000	
013142	005037	013176	
013146	104414		
013150	105737	013572	
013154	001002		
013156	000137	013520	
013162	005237	013176	
013166	001367		
013170	104007		
013172	104011		
013174	104400		
013176	000000		
013200	117703	166606	
013204	042703	177774	
013210	010304		
013212	010337	001374	
013216	005777	166566	
013222	100401		
013224	104003		
013226	012702	000001	
013232	105303		
013234	100402		
013236	006302		
013240	000774		
013242	030237	001366	
013246	001001		
013250	104015		
013252	030237	013312	
013256	001003		
013260	040277	166540	
013264	000411		

```

***** TEST 3 *****
*THIS TEST RUNS ALL LINES FULL BORE
*BASED UPON QUALIFIED LINES
*...THIS IS AN INTERRUPT TEST ON THE RECEIVER AND
*TRANSMITTER

::* TEST 3
*****
TST3:  SCOPE
      MOV #3,$TSTNM      ;LOAD THE NUMBER OF THIS TEST
      MOV #TST4,NEXT     ;POINT TO THE START OF THE NEXT TEST
      DCLASM             ;SET DCLR IN CSR AND SET MNTFLG
      MOV LINE,RXTCR     ;SET IMAGE OF TCR BITS
      MOV LINE,XTXCR     ;SET IMAGE OF TCR BITS
      LPRSET             ;LOAD LINE PARAMETERS
      BUFSET             ;ZERO DATA BUFFER
      MOV #RXSVC,$DZVRIV ;SET UP REC INTR VECTOR
      MOV #MASK,$DZVRIS  ;STATUS
      MOV #TXSVC,$DZVTIV ;SET UP TRANS INTR VECTOR
      MOV #MASK,$DZVTIS  ;STATUS
      BIS #MSENAB!RIE!TIE,$DZVCSR ;SET MASTER SCAN ENABLE
      MOVB LINE,$DZVTXCR ;SET TCR BITS
      MTPS #CLEAR        ;ALLOW INTERRUPTS

SNAP:  CLR 4$            ;CLEAR DELAY COUNTER
2$:    DELAY
      TSTB RXTCR         ;WAIT FOR RECEIVERS TO FINISH
      BNE 3$             ;WAIT FOR ALL RECIEVERS TO FINISH
      JMP OUT
3$:    INC 4$            ;INCREMENT DELAY COUNTER
      BNE 2$             ;DELAY FINISHED?
      ERROR 7            ;*TRANSMITTER FAILED TO INTERRUPT
      ERROR 11           ;*RECEIVER FAILED TO INTERRUPT
      ADVANCE            ;LEAVE THIS TEST
4$:    0

:TRANS INTR SVC ROUTINE
TXSVC: MOVB $DZVCSR,R3   ;FIND LINE NO.
      BIC #^C<3>,R3     ;ISOLATE LINE NO.
      MOV R3,R4          ;SAVE LINE NO.
      MOV R3,$AVLIN      ;SAVE LINE NO.
      TST $DZVCSR        ;TRANS READY SET ?
      BMI +4
      ERROR 3            ;*TRANSMITTER FAILED
      MOV #1,R2          ;SET UP POSITION POINTER
3$:    DECB R3           ;IS IT THIS LINE ?
      BMI 4$            ;YES
      ASL R2             ;UP THE LINE #
      BR 3$             ;GO 'ROUND AGAIN
4$:    BIT R2,LINE       ;VALID LINE?
      BNE +4            ;YES
      ERROR 15          ;NO,INVALID LINE!!!!
      BIT R2,XTXCR       ;DATA FINISHED?
      BNE 6$            ;IF NOT SEND CHAR.
      BIC R2,$DZVTXCR    ;CLEAR TCR BIT
      BR 5$             ;RETURN

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 26-1
CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0069

2966	013266	006304		6\$:	ASL	R4	:MAKE POWER OF 2
2967	013270	116477	001426		MOVB	TDO(R4),@DZVTDR	:LOAD CHARACTER
2968	013276	105264	001426		INCB	TDO(R4)	:SET UP NEXT CHARACTER
2969	013302	001002			BNE	5\$	:LAST CHARACTER ?
2970	013304	040237	013312		BIC	R2,TXTCR	:INDICAT LINE FINISHED
2971	013310	000002		5\$:	RTI		
2972							
2973	013312	000000			TXTCR:	0	
2974							
2975					:REC INTR SVC ROUTINE		
2976	013314	105777	166470		RXSVC:	TSTB @DZVCSR	:REC DONE ?
2977	013320	100401			BMI	.+4	:YES
2978	013322	104004			ERROR	4	:FALSE INTERRUPT
2979	013324	032777	020000	166456	BIT	#SILOAL,@DZVCSR	:SILO ALARM?
2980	013332	001401			BEQ	.+4	:NO
2981	013334	104013			ERROR	13	:SILO ALARM SHOULD NOT =1
2982	013336	017704	166452		MOV	@DZVRBUF,R4	:SAVE IT
2983	013342	010403			MOV	R4,R3	
2984	013344	000303			SWAB	R3	
2985	013346	042703	177774		BIC	#^C<3>,R3	:STRIP JUNK
2986	013352	010337	001374		MOV	R3,SAVLIN	:SAVE LINE NUMBER
2987	013356	005704			TST	R4	:DATA VALID?
2988	013360	100401			BMI	4\$	:IF YES SKIP ERROR PRINTOUT
2989	013362	104023			ERROR	23	:YOU LOSE ...DATA VALID WAS'NT SET
2990	013364	032704	040000	4\$:	BIT	#OVRUN,R4	:TEST FOR OVERRUN
2991	013370	001401			BEQ	1\$	:IF NO OVERRUN SKIP ERROR
2992	013372	104024			ERROR	24	:DATA OVERRUN
2993	013374	032704	020000	1\$:	BIT	#FRMERR,R4	:DATA FRAMING ERROR
2994	013400	001401			BEQ	2\$	:IF NO FRAMING ERROR CONTINUE
2995	013402	104025			ERROR	25	:FRAMING ERROR
2996	013404	032704	010000	2\$:	BIT	#PARER,R4	:TEST FOR PARITY ERROR
2997	013410	001401			BEQ	3\$	:BRANCH IF NO ERROR
2998	013412	104026			ERROR	26	:TYPE OUT PARITY ERROR
2999	013414	012702	000001	3\$:	MOV	#1,R2	:SET UP POSITION POINTER
3000	013420	105303		5\$:	DECB	R3	
3001	013422	100402			BMI	6\$	:RE POSITION POINTER
3002	013424	006302			ASL	R2	:GO 'ROUND AGAIN
3003	013426	000774			BR	5\$	:LINE VALID ?
3004	013430	030237	001366	6\$:	BIT	R2,LINE	:YES
3005	013434	001001			BNE	.+4	:INVALID LINE #
3006	013436	104015			ERROR	15	:GET THE LINE NUMBER AGAIN
3007	013440	013703	001374		MOV	SAVLIN,R3	:USE R3 AS A POINTER IN THE DATA TABLE
3008	013444	006303			ASL	R3	:DOES THE DATA CHARACTER COMPARE ?
3009	013446	126304	001436		CMPB	TRO(R3),R4	:YES
3010	013452	001410			BEQ	7\$	:MOVE LINE NO INTO EXPECTED
3011	013454	013705	001374		MOV	SAVLIN,R5	:ADJUST TO HIGH BYTE
3012	013460	000305			SWAB	R5	:SET DVALID IN EXPECTED
3013	013462	052705	100000		BIS	#DVALID,R5	:SET DATA IN EXPECTED
3014	013466	056305	001436		BIS	TRO(R3),R5	:*NO, DATA DOES NOT COMPARE
3015	013472	104005			ERROR	5	:SET UP FOR NEXT CHARACTER
3016	013474	005263	001436	7\$:	INC	TRO(R3)	:ALL CHARS DONE?
3017	013500	105763	001436		TSTB	TRO(R3)	
3018	013504	001002			BNE	.+6	
3019	013506	040237	013572		BIC	R2,RXTCR	:ZERO LINE DONE INDICATOR.
3020	013512	012716	013142		MOV	#SNAP,(SP)	:RESET THE BACKGROUND TIMING LOOP
3021	013516	000002			RTI		


```

3022
3023
3024      :FINISH UP ROUTINE
3025 013520 106427 000200      OUT:  MTPS      #MASK      ;STOP ALL INTERRUPTS
3026 013524 104413      DEVICE.CLR      ;CLEAR ALL INTERRUPTS AWAY
3027 013526 005003      CLR      R3
3028 013530 005037 001374      CLR      SAVLIN
3029 013534 012702 000001      MOV      #1,R2
3030 013540 030237 001366      1$:  BIT      R2,LINE      ;VALID LINE ?
3031 013544 001405      BEQ      2$      ;NO
3032 013546 022763 000400 001436      CMP      #400,TR0(R3)      ;RECEIVED A BINARY COUNT PATTERN ?
3033 013554 001401      BEQ      +4      ;YES
3034 013556 104030      ERROR      30      ;THE LINE FAILED TO RECEIVE A FULL
3035      ;BINARY COUNT PATTERN
3036 013560 005237 001374      2$:  INC      SAVLIN      ;SET UP FOR NEXT LINE
3037 013564 005723      TST      (R3)+      ;ADD 2
3038 013566 104420      SHIFT
3039 013570 000763      BR      1$      ;SET UP NEXT LINE POINTER
3040 013572 000000      RXTCR: 0      ;FINISHED ?
3041      ;RX IMAGE OF TCR BITS
3042
3043      :***** TEST 4 *****
3044      :*DZV11 RELATIVE TIMING TEST.
3045      :*EACH SELECTED LINE WILL IN TURN RUN 16. CHARS
3046      :*AT ALL BAUD RATES AND THEN THE HIGHEST BAUD
3047      :*WITH ALL CHAR LENGTHS. EACH NEW PARAMETER SHOULD
3048      :*DECREASE IN TIME FROM THE PREVIOUS PARAMETERS SELECTED.
3049      :*THE TIME IS CHECKED AGAINST THE LAST PARAMETER USED
3050      :* AND A LOWER TIME IS EXPECTED ON THE CURRENT PARAMETER.
3051      :*PARAMETERS ARE:
3052      :* EIGHT BITS/PER/CHAR - TWO STOP BITS AT
3053      :* 50, 75, 110, 134.5, 150, 300, 600, 1200, 1800, 2000
3054      :* 2400, 3600, 4800, 7200, 9600 BAUD.
3055      :* 19.2 K BAUD - TWO STOP BITS AT
3056      :* SEVEN, SIX, FIVE BITS/PER/CHAR.
3057      :*AFTER EACH LINE HAS FINISHED ALL THE ABOVE PARAMETERS
3058      :*THE NEXT SELECTED LINE IS THEN TESTED.
3059      :*WHEN RUNNING UNDER THE APT MANUFACTURING SYSTEM
3060      :*THIS TEST IS ONLY RUN THE FIRST PASS
3061
3062      :*: TEST 4
3063      :*****
3064      :TST4:  SCOPE
3065      :MOV      #4,$TSTNM      ;LOAD THE NUMBER OF THIS TEST
3066      :MOV      #TST5,NEXT      ;POINT TO THE START OF THE NEXT TEST
3067      :MOV      #3$,$LOCK      ;USE THIS ADDRESS IF A TIGHT SCOPE LOOP IS SELECTED
3068      :BITB      #1,$ENV      ;RUNNING UNDER APT?
3069      :BEQ      10$      ;IF NOT CONTINUE WITH TEST
3070      :TST      $PASS      ;IF YES IS THIS FIRST PASS
3071      :BEQ      10$      ;IF NOT 1ST PASS SKIP TEST
3072      :JMP      @NEXT
3073      :MOV      #2,$TIMES      ;SET UP FOR 2 ITERATIONS
3074      :CLR      OFFSET      ;RESET THIS VARIABLE
3075      :CLR      SAVLIN      ;RESET LINE NUMBER INDICATOR
3076      :CLR      XMTLIN      ;USE THIS WORD TO TELL WHAT LINE TRANSMITTED
3077      :MOV      #1,R2      ;USE R2 AS A BIT POINTER
3078      :MOV      #RCVON!$S0!EIGHT!TWO$STOP,R3 ;BUILD TEMPORARY PARAMETERS

```

CVDZB-B MACY11 306(1063) 10-AUG-81 11:11 PAGE 26-3
CVDZBB.P11 10-AUG-81 10:56 DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0071

3074	013674	030237	001366	1\$:	BIT	R2,LINE	:IS THIS LINE ACTIVE?
3075	013700	001014			BNE	3\$	:IF SO, GO GET STARTED
3076	013702	012703	010070	2\$:	MOV	#RCVON!S50!EIGHT!TWOSTOP,R3	:LOAD PARAMETERS TEMPORARILY
3077	013706	005237	001376		INC	XMTLIN	:POINT TO THE NEXT LINE TO TRANSMIT
3078	013712	042703	000007		BIC	#7,R3	:MAKE SURE TEMPORARY PARAMETERS POINT TO 0
3079	013716	053703	001376		BIS	XMTLIN,R3	:ADD DESIRED LINE NUMBER
3080	013722	005037	015214		CLR	OFFSET	
3081	013726	104420			SHIFT		:POINT TO THE NEXT LINE
3082	013730	000761			BR	1\$	:PROCESS THE NEXT LINE
3083	013732			3\$:			
(1)	013732	104417			DCLASM		:CLEAR DEVICE AND SET MAINT BIT IF I MODE
3084	013734	042703	010000		BIC	#RCVON,R3	:ZERO PARAMTERS FOR TX LINE
3085	013740	010377	166054		MOV	R3,ADZVLPR	:LOAD PARAMTERS FOR TX
3086	013744	005737	001372		TST	MODE	:STAGGERED?
3087	013750	100007			BPL	100\$	:BR IF NO
3088	013752	000241			CLC		:SET UP LINE
3089	013754	006003			ROR	R3	
3090	013756	103002			BCC	98\$	:BR IF LINE WAS EVEN
3091	013760	000241			CLC		:PREPARE TO MKE LINE EVEN
3092	013762	000401			BR	99\$	:CONTINUE
3093	013764	000261		98\$:	SEC		:PREPARE TO MAKE LINE ODD
3094	013766	006103		99\$:	ROL	R3	:SET ALTERED LINE
3095	013770	052703	010000	100\$:	BIS	#RCVON,R3	:SET RX ON
3096	013774	010377	166020		MOV	R3,ADZVLPR	:LOAD RX PARAMETERS
3097	014000	010337	001374		MOV	R3,SAVLIN	:SET FOR RECEIV. LINE
3098	014004	042737	177774	001374	BIC	#^C<3>,SAVLIN	:ISOLATE LINE NO.
3099	014012	042703	000003		BIC	#3,R3	:CLEAR OLD LINE #
3100	014016	053703	001376		BIS	XMTLIN,R3	:SET LINE UP AGAIN
3101	014022	010337	001402		MOV	R3,REGIST	:SAVE PARAMETERS FOR PRINTOUT
3102	014026	104422			BUFSET		:ZERO DATA BUFFER
3103	014030	005037	001342		CLR	\$TMP0	:USE \$TMP0 TO COUNT TOTAL NUMBER OF TRANSMISSIONS
3104	014034	005037	001344		CLR	\$TMP1	:INITIALIZE THE TIMER
3105	014040	005037	001350		CLR	\$TMP3	:INITIALIZE THESE BITS ALSO
3106	014044	012737	000020	001400	MOV	#20,XMTCNT	:SET HOW MANY CHARACTERS TO TRANSMIT
3107	014052	012777	014642	165764	MOV	#XMTSRV,ADZVTIV	
3108	014060	012777	015012	165752	MOV	#RXISR1,ADZVRIV	
3109	014066	012777	000200	165746	MOV	#MASK,ADZVRIS	
3110	014074	012777	000200	165744	MOV	#MASK,ADZVTIS	
3111	014102	110277	165716		MOVB	R2,ADZVTCR	:START THE VALID LINE
3112	014106	052777	040140	165674	BIS	#TIE!RIE!MSENAB,ADZVCSR	
3113	014114	106427	000000		MTPS	#0	:LOWER THE PRIORITY TO ALLOW INTERRUPTS
3114	014120	032777	000100	165662	4\$:	BIT	#RIE,ADZVCSR
3115	014126	001407			BEQ	5\$	:IS ROUTINE DONE?
3116	014130	005237	001344		INC	\$TMP1	:WHEN ALL IS DONE RX IE IS CLEARED IN ISR.
3117	014134	001371			BNE	4\$	:INCREMENT TIMER
3118	014136	005237	001350		INC	\$TMP3	:WHEN IT OVERFLOWS
3119	014142	001366			BNE	4\$	:CATCH CARRY
3120	014144	104011			ERROR	11	:CONTINUE TEST
3121	014146	004737	007126		JSR	PC,SERV.G	:INTERRUPTS NOT FINISHED
3122	014152	104401			SCOP1		:<^G>?
3123	014154	062737	000002	015214	ADD	#2,OFFSET	:LOOP?
3124	014162	022703	017400		CMP	#17400,R3	
3125	014166	003006			BGT	6\$	
3126	014170	032703	000030		BIT	#BIT4+BIT3,R3	:IS CHARACTER SIZE DONE?
3127	014174	001642			BEQ	2\$	
3128	014176	162703	000010		SUB	#BIT3,R3	

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11
CVDZBB.P11 10-AUG-81 10:56

PAGE 26-4
DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0072

3129 014202 000653
3130 014204 062703 000400
3131 014210 000650
3132

6\$: BR 3\$
ADD #400,R3
BR 3\$

***** TEST 5 *****

THE MAIN FUNCTION OF THIS TEST IS TO VERIFY
THAT 'PE' (PARITY ERROR) CAN BE FLAGGED BY
THE UARTS. THIS TEST WILL NOT BE DONE UNLESS
YOU ARE IN 'STAGGERED' MODE.
40(8) CHARS ARE USED FOR THIS TEST.
ALL SELECTED LINES WILL BE ENABLED AT THE SAME TIME.
THIS TEST FIRST CHECKS EVEN PARITY FOR ODD LINES AND
ODD PARITY FOR EVEN LINES, THEN IT CHECKS THE REVERSE.

::* TEST 5

TST5: SCOPE

(5)	014212	000004			MOV	#5,\$TSTNM	:LOAD THE NUMBER OF THIS TEST
(3)	014214	012737	000005	001246	MOV	#\$EOP,NEXT	:POINT TO THE END-OF-PASS HANDLER
(2)	014222	012737	004146	001362	TST	MODE	:IS THIS STAGGERED MODE?
(1)	014230	005737	001372		BPL	17\$	:IF NOT, DON'T DO THIS TEST
(1)	014234	100131			CLRB	DONFLG	:SET UP FOR FIRST TEST PASS
(1)	014236	105037	001425		14\$: DEVICE.CLR		:SET DCLR IN CSR
(1)	014242	104413			MOV	PAR,R1	:USE R1 TO BUILD PARAMETERS TO BE LOADED
(1)	014244	013701	001370		BIC	#ODDPAR,R1	:MAKE SURE ODD PARITY ISN'T SET
(1)	014250	042701	000200		BIS	#PARITY,R1	:MAKE SURE PARITY IS TURNED ON
(1)	014254	052701	000100		MOV	#1,R2	:USE R2 AS A LINE POINTER
(1)	014260	012702	000001		1\$: BIT	R2,LINE	:IS THIS A VALID LINE?
(1)	014264	030237	001366		BEQ	3\$	:IF NOT, SKIP TO THE NEXT LINE
(1)	014270	001420			TSTB	DONFLG	:FIRST PASS THROUGH TEST?
(1)	014272	105737	001425		BNE	15\$	:IF NO BRANCH
(1)	014276	001004			BIT	#BIT0,R1	:IS THIS LINE AN ODD LINE?
(1)	014300	032701	000001		BNE	2\$	:IF IT'S ODD, USE EVEN PARITY
(1)	014304	001006			BR	16\$	:IF EVEN SET FOR ODD PARITY
(1)	014306	000403			15\$: BIT	#BIT0,R1	:IF THE LINE IS EVEN SET FOR EVEN PAR.
(1)	014310	032701	000001		BEQ	2\$	:GO LOAD PARAMETER
(1)	014314	001402			16\$: BIS	#ODDPAR,R1	:IF IT'S ODD, USE ODD PARITY
(1)	014316	052701	000200		2\$: MOV	R1,\$DZVLPR	:LOAD THE LINE PARAMETER REGISTER
(1)	014322	010177	165472		BIC	#ODDPAR,R1	:SET UP THE NEXT PARITY TO EVEN
(1)	014326	042701	000200		3\$: INC	R1	:POINT TO THE NEXT LINE
(1)	014332	005201			ASL	R2	
(1)	014334	006302			BIT	#BIT4,R2	:ALL LINES DONE?
(1)	014336	032702	000020		BEQ	1\$	:IF NOT, GO CHECK THE NEXT LINE
(1)	014342	001750			CLR	SAVLIN	:CLEAR THE LINE NUMBER INDICATOR
(1)	014344	005037	001374		CLR	\$TMP0	:USE \$TMP0 TO COUNT TOTAL NUMBER OF TRANSMISSIONS
(1)	014350	005037	001342		CLR	R3	:USE R3 TO COUNT TOTAL NUMBER OF RECEPTIONS
(1)	014354	005003			MOV	#40,\$XMT CNT	:TRANSMIT A BINARY COUNT PATTERN(00-40)
(1)	014356	012737	000040	001400	BUFSET		:ZERO BUFFER AREA
(2)	014366	012777	014642	165450	MOV	#\$XMTSRV,\$DZVTIV	:SET UP THE TRANSMITTER INTERRUPT VECTOR
(2)	014374	012777	014522	165436	MOV	#\$9\$,\$DZVRIV	:SET UP THE RECEIVER INTERRUPT VECTOR
(2)	014402	012777	000200	165432	MOV	#\$MASK,\$DZVRIS	:SET THE INTERRUPT VECTOR STATUS
(2)	014410	012777	000200	165430	MOV	#\$MASK,\$DZVTIS	:SET TRANSMITTER INTERRUPT PRIORITY
(2)	014416	052777	040140	165364	BIS	#\$RIE!,\$DZVCSR	:ENABLE THE DEVICE
(1)	014424	113777	001366	165372	MOV	LINE,\$DZVTCR	:ENABLE ALL SELECTED LINES
(1)	014432	106427	000000		MTPS	#0	:ALLOW INTERRUPTS
(1)	014436	005037	014514		4\$: CLR	7\$	
(1)	014442	005037	014516		CLR	8\$	
(1)	014446	032777	000100	165334	5\$: BIT	#\$RIE,\$DZVCSR	:WHEN RX DONE; RIE WILL =0

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11
CVDZBB.P11 10-AUG-81 10:56

PAGE 26-5
DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0073

(1)	014454	001407		BEQ	6\$	:BR IF ALL DONE
(1)	014456	005237	014514	INC	7\$	
(1)	014462	001371		BNE	5\$	
(1)	014464	105237	014516	INCB	8\$	
(1)	014470	100366		BPL	5\$	
(1)	014472	104011		ERROR	11	:*RX FAILED TO FINISH (INTERRUPT)
(1)	014474	106427	000200	6\$: MTPS	#MASK	:SHUT OFF INTERRUPTS
(1)	014500	105737	001425	TSTB	DONFLG	:IS THIS SECOND TEST PASS
(1)	014504	001005		BNE	17\$	:IF SO GET OUT
(1)	014506	105237	001425	INCB	DONFLG	:INDICATE FIRST TEST PASS DONE
(1)	014512	000653		BR	14\$	:START OVER
(1)	014514	000000		7\$: 0		
(1)	014516	000000		8\$: 0		
(1)	014520	104400		17\$: ADVANCE		
(1)						
(1)						
(1)						
(1)						
(1)						
(1)						
(1)						
(1)	014522	017704	165266	9\$: MOV	@DZVRBUF,R4	:GET THE CHARACTER
(1)	014526	010401		MOV	R4,R1	:COPY THE RECEIVED INFORMATION
(1)	014530	000301		SWAB	R1	:GET THE LINE NUMBER IN THE LOWER BYTE
(1)	014532	042701	177774	BIC	#^C<3>,R1	:ISOLATE THE LINE NUMBER
(1)	014536	010137	001374	MOV	R1,SAVLIN	:SET LINE INDIC. TO RECEIVING LINE
(1)	014542	005704		TST	R4	:IS DATA VALID SET?
(1)	014544	100401		BMI	10\$	:IF YES DON'T PRINT ERROR
(1)	014546	104023		ERROR	23	:DATA VALID NOT SET
(1)	014550	010105		10\$: MOV	R1,R5	:BUILD LINE NO. FOR
(1)	014552	000305		SWAB	R5	:EXPECTED DATA IN RECEIVER BUFFER
(1)	014554	006301		ASL	R1	:ADJUST R1 FOR OFFSET
(1)	014556	156105	001436	BISB	TR0(R1),R5	:LOAD CHARACTER IN EXPECTED
(1)	014562	052705	110000	BIS	#DVALID!PARER,R5	:BUILD WHAT WAS EXPECTED
(1)	014566	020405		CMP	R4,R5	:DOES RECEIVED=EXPECTED
(1)	014570	001401		BEQ	12\$	:IF YES DON'T PRINT ERROR
(1)	014572	104006		ERROR	6	:*ERROR- DID NOT GET CORRECT INFORMATION
(1)	014574	005261	001436	12\$: INC	TR0(R1)	:SET UP THE NEXT CHARACTER
(1)	014600	005203		INC	R3	:ADD TO THE TOTAL RECEIVED COUNT
(1)	014602	032777	040000 165200	BIT	#TIE,@DZVCSR	:ARE TRANSMISSIONS DONE?
(1)	014610	001011		BNE	13\$	:IF NO, GO RECEIVE SOME MORE
(1)	014612	023703	001342	CMP	\$TMP0,R3	:ARE ALL CHARACTERS RECEIVED?
(1)	014616	001006		BNE	13\$	:IF NO, GO RECEIVE SOME MORE
(1)	014620	042777	000100 165162	BIC	#RIE,@DZVCSR	:DISABLE RECEIVER INTERRUPTS
(1)	014626	012716	014474	MOV	#6\$, (SP)	:CRUNCH THE STACK
(1)	014632	000002		RTI		:RETURN AND FINISH
(1)	014634	012716	014436	13\$: MOV	#4\$, (SP)	:CRUNCH THE STACK
(1)	014640	000002		RTI		:GO BACK TO RECEIVER WAIT LOOP


```

3134
3135                                     ;TRANSMITTER INTERRUPT SERVICE
3136                                     ;-----
3137
3138 014642 117701 165144      XMTSRV: MOVB    @HDZVCSR,R1      ;GET THE LINE NUMBER.
3139 014646 042701 177774      BIC      #^C<3>,R1      ;CLEAR JUNK
3140 014652 013705 001374      MOV      SAVLIN,R5      ;SAVE REC. LINE NO.
3141 014656 010137 001374      MOV      R1,SAVLIN      ;LOAD TRANS LINE NO FOR ERROR PRINTOUT
3142 014662 006301          ASL      R1      ;ADJUST R1 FOR OFFSET
3143 014664 023761 001400 001426  CMP     XMTCNT,TDO(R1)  ;HAVE ALL CHAR. BEEN SENT
3144 014672 003414          BLE     6$      ;IF YES GO CLEAR TCR
3145 014674 005777 165110      TST      @DZVCSR      ;TRDY SET?
3146 014700 100401          BMI     2$      ;IF YES GO LOAD CHAR.
3147 014702 104003          ERROR    3      ;*TRANSMITTER NOT READY- FALSE INTERRUPT
3148 014704 116177 001426 165122 2$:  MOVB    TDO(R1),@DZVTDR ;LOAD THE CURRENT CHARACTER FOR THIS LINE
3149 014712 005261 001426      INC     TDO(R1)      ;SET UP NEXT CHARACTER FOR THIS LINE
3150 014716 005237 001342      INC     $TMP0      ;UP THE NUMBER OF TRANSMISSIONS
3151 014722 000415          BR      7$      ;GO RETURN
3152 014724 012700 000001      6$:  MOV      #1,R0      ;SET UP A DESELECTION POINTER
3153 014730 006201          ASR      R1      ;GET LINE NO. AGAIN
3154 014732 005301      12$:  DEC      R1      ;REDUCE THE COUNT. WAS THIS THE LINE?
3155 014734 100402          BMI     3$      ;IF SO, GO DISABLE THE ENABLE BIT FOR IT
3156 014736 006300          ASL      R0      ;MOVE THE POINTER TO THE NEXT LINE
3157 014740 000774          BR      12$      ;GO CHECK THE NEXT LINE
3158 014742 140077 165056      3$:  BICB    R0,@DZVTCR      ;DISABLE THE LINE POINTED TO BY R0
3159 014746 001003          BNE     7$      ;IF MORE LINES ARE ACTIVE, GO CONTINUE TRANSMIT
3160 014750 042777 040000 165032 7$:  BIC     #TIE,@DZVCSR      ;IF NOT, DISABLE TRANSMITTER INTERRUPTS
3161 014756 010537 001374      MOV     R5,SAVLIN      ;RESTORE RECEIV. LINE
3162 014762 000002          RTI          ;RETURN TO THE TIMING LOOP
3163
3164                                     ; RELATIVE TIME BUILDING ROUTINE
3165                                     ;-----
3166
3167 014764 012737 000002 001346 BUILD: MOV     #2,$TMP2      ;ROTATE 2 BITS BACK INTO $TMP1
3168 014772 006037 001350      1$:  ROR     $TMP3      ;GET THE BITS FROM $TMP3, THE HIGH BYTE
3169 014776 006037 001344      ROR     $TMP1      ;OF THE RELATIVE TIME COUNTER. PUT THEM BACK
3170 015002 005337 001346      DEC     $TMP2      ;INTO $TMP1 USING THE CARRY BIT WITH
3171          ROTATE INSTRUCTIONS
3172 015006 001371          BNE     1$      ;REDUCE COUNT. ALL BITS BACK? IF NOT, GET MORE
3173 015010 000207          RTS     PC      ;RETURN TO CALLING TEST
3174

```

:RECEIVER SERVICE ROUTINE

```

3176
3177
3178 015012 105777 164772 RXISR1: TSTB @DZVCSR ;IS THE RECEIVER REALLY READY?
3179 015016 100401 BMI 1$ ;IF SO, GO SERVICE IT
3180 015020 104004 ERROR 4 ;*ERROR- RECEIVER DONE FLAG ISN'T SET
3181 015022 017704 164766 1$: MOV @DZVRBUF,R4 ;SAVE THE RECEIVER INFORMATION
3182 015026 100401 BMI 2$ ;IF IT WAS VALID, GO PROCESS IT
3183 015030 104023 ERROR 23 ;ERROR- DATA VALID WASN'T SET
3184 015032 032704 040000 2$: BIT #OVRUN,R4 ;OVERRUN ERROR FLAG SET?
3185 015036 001401 BEQ 6$ ;IF NOT DON'T TYPE ERROR
3186 015040 104024 ERROR 24 ;OVERRUN ERROR
3187 015042 032704 020000 6$: BIT #FRMERR,R4 ;FRAMING ERROR FLAG SET?
3188 015046 001401 BEQ 9$ ;IF NOT DON'T TYPE ERROR
3189 015050 104025 ERROR 25 ;FRAMING ERROR
3190 015052 032704 010000 9$: BIT #PARER,R4 ;PARITY ERROR FLAG SET?
3191 015056 001401 BEQ 3$ ;IF NOT, GO CONTINUE PROCESSING
3192 015060 104026 ERROR 26 ;ERROR- RECEIVER ERROR FLAG SET
3193 015062 013701 001374 3$: MOV SAVLIN,R1 ;CALCULATE THE DATA OFFSET
3194 015066 006301 ASL R1 ;ALIGN IT ON A WORD BOUNDARY
3195 015070 120461 001436 CMPB R4,TR0(R1) ;IS THE CHARACTER WHAT IT SHOULD BE?
3196 015074 001407 BEQ 4$ ;IF SO,GO CONTINUE PROCESSING
3197 015076 116105 001436 MOVB TR0(R1),R5 ;GET WHAT WAS EXPECTED FOR ERROR REPORTING
3198 015102 042705 177400 BIC #^C<377>,R5 ;ELIMINATE PROPAGATED SIGN
3199 015106 042704 177400 BIC #^C<377>,R4 ;ISOLATE THE ACTUAL CHARACTER
3200 015112 104005 ERROR 5 ;*DATA ERROR
3201 015114 005261 001436 4$: INC TR0(R1) ;SET UP THE NEXT EXPECTED CHARACTER
3202 015120 122761 000020 001436 CMPB #20,TR0(R1) ;HAVE ALL CHARACTERS BEEN RECEIVED?
3203 015126 001031 BNE 8$ ;IF NOT RETURN
3204 015130 126137 001436 001342 CMPB TR0(R1),$TMP0 ;ALL CHARAC. RECEIVED?
3205 015136 001025 BNE 8$ ;IF SO,GO DETERMINE THE TIMING
3206 015140 004737 014764 JSR PC,BUILD ;GET THE RELATIVE TIME (SIGNIFICANT BITS)
3207 015144 013700 015214 MOV OFFSET,R0 ;GET POINTER
3208 015150 013760 001344 002050 MOV $TMP1,TMTBL(R0) ;SAVE THIS TEST'S TIME
3209 015156 005737 015214 TST OFFSET ;FIRST TEST?
3210 015162 001410 BEQ 7$ ;IF NOT, GO CHECK THE TIME
3211 015164 005740 TST -(R0) ;POINT TO THE PREVIOUS TIME TAKEN
3212 015166 026037 002050 001344 CMP TMTBL(R0),$TMP1 ;IS THIS TIME WHAT IT SHOULD BE?
3213 015174 101003 BHI 7$ ;IF SO, GO TO THE NEXT TEST
3214 015176 016005 002050 MOV TMTBL(R0),R5 ;PLACE WHAT WAS EXPECTED IN R5
3215 015202 104021 ERROR 21 ;TIMING ERROR
3216 015204 042777 000140 164576 7$: BIC #RIE!MSENAB,@DZVCSR ;DISABLE THE DEVICE
3217 015212 000002 8$: RTI ;RETURN TO THE PROGRAM
3218 015214 000000 OFFSET: 0

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 27
 CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS. COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0076

			:ERROR TABLE	
3220				
3221	015216	000000	.ERRTAB: 0	:ERROR 0
3222	015220	000000	0	
3223	015222	000000	0	
3224				
3225	015224	015444	EM1	:ERROR
3226	015226	016570	DH1	
3227	015230	016770	DT1	
3228				
3229	015232	015517	EM2	:ERROR 2
3230	015234	016614	DH2	
3231	015236	017002	DT2	
3232				
3233	015240	015545	EM3	:ERROR 3
3234	015242	016647	DH3	
3235	015244	017020	DT3	
3236				
3237	015246	015604	EM4	:ERROR 4
3238	015250	016647	DH3	
3239	015252	017020	DT3	
3240				
3241	015254	015633	EM5	:ERROR 5
3242	015256	016661	DH4	
3243	015260	017026	DT4	
3244				
3245	015262	015662	EM6	:ERROR 6
3246	015264	016661	DH4	
3247	015266	017026	DT4	
3248				
3249	015270	000000	0	
3250	015272	000000	0	
3251	015274	000000	0	
3252				
3253	015276	000000	0	
3254	015300	000000	0	
3255	015302	000000	0	
3256				
3257	015304	015721	EM11	:ERROR 11
3258	015306	016647	DH3	
3259	015310	017020	DT3	
3260				
3261	015312	000000	0	
3262	015314	000000	0	
3263	015316	000000	0	
3264				
3265	015320	015757	EM13	:ERROR 13
3266	015322	016647	DH3	
3267	015324	017020	DT3	
3268				
3269	015326	016010	EM14	:ERROR 14
3270	015330	016647	DH3	
3271	015332	017020	DT3	
3272				
3273	015334	016042	EM15	:ERROR 15
3274	015336	000000	0	
3275	015340	000000	0	

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 27-1
 CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0077

3276			
3277	015342	016104	EM16
3278	015344	016647	DH3
3279	015346	017020	DT3
3280			
3281	015350	016156	EM17 ;ERROR 17
3282	015352	016647	DH3
3283	015354	017020	DT3
3284			
3285	015356	016214	EM20
3286	015360	016647	DH3
3287	015362	017020	DT3
3288			
3289	015364	016255	EM21 ;ERROR 21
3290	015366	016710	DH5
3291	015370	017044	DT5
3292			
3293	015372	000000	0
3294	015374	000000	0
3295	015376	000000	0
3296			
3297	015400	016305	EM23 ;ERROR 23
3298	015402	016647	DH3
3299	015404	017020	DT3
3300			
3301	015406	016335	EM24
3302	015410	016647	DH3
3303	015412	017020	DT3
3304			
3305	015414	016363	EM25
3306	015416	016647	DH3
3307	015420	017020	DT3
3308			
3309	015422	016413	EM26
3310	015424	016647	DH3
3311	015426	017020	DT3
3312			
3313	015430	016442	EM27
3314	015432	016647	DH3
3315	015434	017020	DT3
3316			
3317	015436	016510	EM30
3318	015440	016647	DH3
3319	015442	017020	DT3

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 28
CVDZBB.P11 10-AUG-81 10:56

DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0078

```

3321      ;ERROR MESSAGES
3325 015444 047200 020117 052502 EM1: .ASCIZ <200>/NO BUS REPLY RESPONSE FROM DZV11 REGISTER/
3326 015517      200 042522 044507 EM2: .ASCIZ <200>/REGISTER R/W FAILURE?
3327 015545      200 051124 047101 EM3: .ASCIZ <200>/TRANSMIT READY (TRDY) NOT SET/
3328 015604 051200 041505 044505 EM4: .ASCIZ <200>/RECEIVER DONE NOT SET/
3329 015633      200 040504 040524 EM5: .ASCIZ <200>/DATA COMPARISON ERROR/
3330 015662 042200 053132 030461 EM6: .ASCIZ <200>/DZV11 *RECEIVER BUFFER* ERROR/
3331 015721      200 042522 042503 EM11: .ASCIZ <200>/RECEIVER FAILED TO INTERRUPT/
3332 015757      200 044523 047514 EM13: .ASCIZ <200>/SILO ALARM SET TOO SOON/
3333 016010 051600 046111 020117 EM14: .ASCIZ <200>/SILO ALARM FAILED TO SET/
3334 016042 040600 052103 047511 EM15: .ASCIZ <200>/ACTION DETECTED ON INVALID LINE./
3335 016104 051200 040505 044504 EM16: .ASCIZ <200>/READING DZVRBUF DID NOT CLEAR SILO ALARM/
3336 016156 042200 052101 020101 EM17: .ASCIZ <200>/DATA VALID SHOULD NOT BE SET/
3337 016214 051200 041505 044505 EM20: .ASCIZ <200>/RECEIVER DONE SHOULD NOT BE SET/
3338 016255      200 042522 040514 EM21: .ASCIZ <200>/RELATIVE TIMING ERROR./
3339 016305      200 040504 040524 EM23: .ASCIZ <200>/DATA VALID IS NOT SET!/
3340 016335      200 040504 040524 EM24: .ASCIZ <200>/DATA OVERRUN IS SET!/
3341 016363      200 051106 046501 EM25: .ASCIZ <200>/FRAMING ERROR OCCURRED/
3342 016413      200 040520 044522 EM26: .ASCIZ <200>/PARITY ERROR OCCURRED/
3343 016442 051600 046111 020117 EM27: .ASCIZ <200>/SILO ALARM FAILED TO CAUSE INTERRUPT/
3344 016510 046200 047111 020105 EM30: .ASCIZ <200>/LINE DID NOT RECEIVE FULL BINARY COUNT PATTERN/
3345
3346 016570 052200 040522 020120 DH1: .ASCIZ <200>/TRAP PC DZV11 REG/
3347 016614 042600 050130 041505 DH2: .ASCIZ <200>/EXPECTED FOUND REGISTER/
3348 016647      200 044514 042516 DH3: .ASCIZ <200>/LINE NO./
3349 016661      200 054105 042520 DH4: .ASCIZ <200>/EXPECTED FOUND LINE/
3350 016710 052200 020130 044514 DH5: .ASCIZ <200>/TX LINE PREVIOUS TIME ACTUAL TIME PARAMETER/
3351
3352      016770      .EVEN
3356      ;DATA TABLES FOR ERROR MESSAGES
3357 016770 000002      DT1: 2
3358 016772      006      003      .BYTE 6,3
3359 016774 001330      $REG1
3360 016776      006      001      .BYTE 6,1
3361 017000 001326      $REG0
3362
3363 017002 000003      DT2: 3
3364 017004      006      004      .BYTE 6,4
3365 017006 001340      $REG5
3366 017010      006      001      .BYTE 6,1
3367 017012 001336      $REG4
3368 017014      006      001      .BYTE 6,1
3369 017016 001326      $REG0
3370
3371 017020 000001      DT3: 1
3372 017022      003      001      .BYTE 3,1
3373 017024 001374      SAVLIN
3374
3375 017026 000003      DT4: 3
3376 017030      006      004      .BYTE 6,4
3377 017032 001340      $REG5
3378 017034      006      001      .BYTE 6,1
3379 017036 001336      $REG4
3380 017040      003      001      .BYTE 3,1
3381 017042 001374      SAVLIN
3382

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 28-1
 CVDZBB.P11 10-AUG-81 10:56 DZV11 DEVICE DIAGNOSTICS.

COPYRIGHT 1977 DIGITAL EQUIP. CORP.

SEQ 0079

3383 017044 000004
 3384 017046 003 005
 3385 017050 001374
 3386 017052 006 011
 3387 017054 001340
 3388 017056 006 007
 3389 017060 001344
 3390 017062 006 001
 3391 017064 001402

DT5: 4
 .BYTE 3,5
 SAVLIN
 .BYTE 6,9.
 \$REG5
 .BYTE 6,7
 \$TMP1
 .BYTE 6,1
 REGIST

:TABLE OF DELAY TIMES FOR INDIVIDUAL BAUD RATES
 :-----

3398
 3399
 3400
 3401 017066 002450
 3402 017070 001560
 3403 017072 001120
 3404 017074 000750
 3405 017076 000660
 3406 017100 000330
 3407 017102 000150
 3408 017104 000060
 3409 017106 000040
 3410 017110 000030
 3411 017112 000020
 3412 017114 000010
 3413 017116 000001
 3414 017120 000001
 3415 017122 000001
 3416 017124 000001
 3417
 3418
 3419

DLYTBL: 2450
 1560
 1120
 750
 660
 330
 150
 60
 40
 30
 20
 10
 1
 1
 1
 1

:TIME FOR 50 BAUD
 :TIME FOR 75 BAUD
 :TIME FOR 110 BAUD
 :TIME FOR 134 BAUD
 :TIME FOR 150 BAUD
 :TIME FOR 300 BAUD
 :TIME FOR 600 BAUD
 :TIME FOR 1200 BAUD
 :TIME FOR 1800 BAUD
 :TIME FOR 2000 BAUD
 :TIME FOR 2400 BAUD
 :TIME FOR 3600 BAUD
 :TIME FOR 4800 BAUD
 :TIME FOR 7200 BAUD
 :TIME FOR 9600 BAUD
 :TIME OF DELAY FOR 19200 BAUD

:DELAYS WERE COMPUTED TO ALLOW MAXIMUM TIME AT EACH BAUD RATE
 :FOR ALL TESTS TO FUNCTION CORRECTLY ON A LSI11.

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 29
 CVDZBB.P11 10-AUG-81 10:56 FALCON (KXT-11) UPGRADE ROUTINES.

::GPA

SEQ 0080

```

3421 .SBTTL FALCON (KXT-11) UPGRADE ROUTINES. ::GPA
3422
3423 THE FOLLOWING ROUTINES HAVE BEEN ADDED TO ALLOW DIAGNOSTIC(S)
3424 TO RUN ON A FALCON (KXT-11) BASED SYSTEM.
3425 TO DETERMINE WHETHER WE'RE A FALCON OR NOT, WE'LL SIZE THE 1ST 3/4 OF
3426 THE I/O PAGE (28K TO 31K). FALCON HAS 2KW LOCAL RAM AT 28K(+4) TO 30K
3427 AND A MACRO-ODT AT 30K TO 31K. CONSEQUENTLY, ALL I/O DEVICES MUST
3428 BE PLACED BETWEEN 174000 AND 177776. ADDITIONALLY, WE'LL STRAP THE
3429 EMT AND TRAP SERVICE LEVEL TO PRI6, AND SET THE HALT VECTOR SO THAT
3430 WE CAN STOP THE SUCKER !!
3431
3432 TO MINIMIZE THE IMPACT OF THESE CHANGES ON FINAL PROGRAM SIZE, THE
3433 BULK OF THIS CODE IS PLACED IN THE FLOATING VECTOR SPACE (400-776).
3434 IF THE CPU AT HAND IS A FALCON (KXT11), IT STAYS THERE (NO HARM DONE).
3435 OTHERWISE, THE AREA IS RESTORED TO ITS ORIGINAL "TRAP-CATCHER" STATE.
3436
3437 FALCON: INC #1 ; ONCE-ONLY !!! ::GPA
3438 BNE 1$ ; ::GPA
3439 CALL KXTCHK ; EXECUTE FALCON CHECK ::GPA
3440 1$: TST (PC)+ ; TEST FALCON FLAG... ::GPA
3441 KXTFLAG: 0 ;...NZ = FALCON... ::GPA
3442 RETURN ;...AND RETURN TO CALLER... ::GPA
3443
3444 SSVPC= ; ::GPA
3445 = 400 ; RESTORE FROM 374:376 AT END ::GPA
3446 KXTCHK: CLR KXTFLAG ; ASSUME NOT FALCON. ::GPA
3447 MOV @#4,-(SP) ; SAVE ERROR VECTOR. ::GPA
3448 MOV #2$,@#4 ; SET A TRAP CATCHER. ::GPA
3449 MOV #160010,R0 ; FALCON RAM STARTS AT 28K+4. ::GPA
3450 1$: TST (R0)+ ; ::GPA
3451 240 ; ::GPA
3452 CMP R0,#174000 ; SIZE TO 31K. ::GPA
3453 BLO 1$ ; ::GPA
3454 MOV R0,KXTFLAG ; MUST BE FALCON, SET THE FLAG ::GPA
3455 MOV #40,R0 ; GET PRI1 BIT... ::GPA
3456 BIC R0,@#6 ;...AND LOWER BUS-ERROR... ::GPA
3457 BIC R0,@#16 ;...BPT... ::GPA
3458 BIC R0,@#22 ;...IOT... ::GPA
3459 BIC R0,@#32 ;...EMT... ::GPA
3460 BIC R0,@#36 ;...AND TRAP SERVICE TO PRI6 ::GPA
3461 MOV #170000,@#140 ; ENABLE "BREAK" HALT. ::GPA
3462 MOV (SP)+,@#4 ; RESTORE ERROR VECTOR... ::GPA
3463 RETURN ;...AND RETURN. ::GPA
3464
3465 2$: MOV #3$,(SP) ; TRAP -- NOT A FALCON... ::GPA
3466 RTI ;...CONTINUE. ::GPA
3467 3$: MOV (SF)+,@#4 ; RESET ERROR VECTOR ::GPA
3468 MOV #402,R0 ; SET-UP TO RESTORE FLOATING... ::GPA
3469 MOV @#376,R1 ;...VECTORS (400 - 776). ::GPA
3470 MOV SP,R2 ; SAVE STACK POINTER IN R2 ::GPA
3471 MOV #6$,R4 ;
3472 4$: MOV -(R4),-(SP) ; PUSH THE RESTORE CODE... ::GPA
3473 CMP R4,#5$ ;...ONTO THE STACK. ::GPA
3474 BHI 4$ ; ::GPA
3475 MOV SP,PC ; AND EXECUTE IT. ::GPA

```

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 29-1
 CVDZBB.P11 10-AUG-81 10:56 FALCON (KXT-11) UPGRADE ROUTINES.

::GPA

SEQ 0081

```

3477
3478
3479
3480 000546 010060 177776
3481 000552 010110
3482 000554 022020
3483 000556 020027 000776
3484 000562 101771
3485 000564 010206
3486 000566 000207
3487 000570
3488
3489
3490
3491
3492
3493
3494
3495
3496 000570 023727 001174 160010
3497 000576 001003
3498 000600 012737 174040 001174
3499 000606 023727 001170 000300
3500 000614 001003
3501 000616 012737 000370 001170
3502 000624 012737 000670 002362
3503 000632 012737 174000 002366
3504 000640 012737 177770 002370
3505 000646 012737 000732 002406
3506 000654 005037 002412
3507 000660 012737 000370 002414
3508 000666 000207
3509
3510 000670 030600 052123 041440
3511 000732 030600 052123 053040
3512
3513
3514 000002
3518
3519 017146
3520 000001
3524

: THIS CODE IS RELOCATED TO AND EXECUTED IN THE STACK AREA.
5$:  MOV R0,-2(R0)      : RESTORE +2...
      MOV R1,(R0)       : ...HALT (OR IOT).
      CMP (R0)+(R0)+    :
      CMP R0,#776       :
      BLOS 5$           : LOOP 'TIL DONE
      MOV R2,SP         : THEN RESTORE SP...
      RETURN           : ...AND RETURN TO CALLER
6$:
: IF FALCON, THIS AREA IS FREE FOR ANY PROGRAM UNIQUE
: CHANGES OR DATA STRUCTURES.
: BE SURE IT DOESN'T GET SCREWED UP !!
: INIT $BASE AND $VECT1 AND TWEAK THE '$GETPAR' CALLING
: SEQUENCE TO ACCEPT THE VALID FALCON RANGE.
FALCINI: CMP $BASE,#ABASE : IS $BASE VIRGIN ??
          BNE 1$          : SKIP NEXT IF NOT
          MOV #174040,$BASE : YES, SET ENGINEERING DEFAULT
1$:      CMP $VECT1,#AVECT1 : IS $VECT1 VIRGIN ??
          BNE 2$          : SKIP NEXT IF NOT
          MOV #370,$VECT1  : YES, SET ENGINEERING DEFAULT
2$:      MOV #3$,GETCSR+2   : SUBSTITUTE CSR TEXT...
          MOV #174000,GETCSR+6
          MOV #177770,GETCSR+10 : ...AND VALID RANGE.
          MOV #4$,GETVEC+2   : SUBSTITUTE VECTOR TEXT...
          CLR GETVEC+6
          MOV #370,GETVEC+10 : ...AND VALID RANGE.
          RETURN           : RETURN TO CALLER.
3$:      .ASCIIZ <200>'1ST CSR ADDRESS (174000:177770) '
4$:      .ASCIIZ <200>'1ST VECTOR ADDRESS (000:370) '
          .EVEN
$FREE= <1000-.>/2      : FREE WORDS LEFT.
          .=$SVPC
CORMAX:
.END

```


CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 30
 CVDZBB.P11 10-AUG-81 10:56 SYMBOL TABLE

SEQ 0082

ABASE = 160010
 ACDW1 = 000017
 ACDW2 = 000000
 ACPUOP = 000000
 ACTIVE = 001420
 ADDW0 = 017470
 ADDW1 = 017470
 ADDW10 = 017470
 ADDW11 = 017470
 ADDW12 = 017470
 ADDW13 = 017470
 ADDW14 = 017470
 ADDW15 = 017470
 ADDW2 = 017470
 ADDW3 = 017470
 ADDW4 = 017470
 ADDW5 = 017470
 ADDW6 = 017470
 ADDW7 = 017470
 ADDW8 = 017470
 ADDW9 = 017470
 ADEVCT = 000000
 ADEVN = 000001
 ADRCNT = 006015
 ADVANC = 104400
 AENV = 000000
 AENVN = 000000
 AFATAL = 000000
 AMADR1 = 000000
 AMADR2 = 000000
 AMADR3 = 000000
 AMADR4 = 000000
 AMAMS1 = 000000
 AMAMS2 = 000000
 AMAMS3 = 000000
 AMAMS4 = 000000
 AMSGAD = 000000
 AMSGLG = 000000
 AMSGTY = 000000
 AMTYP1 = 000000
 AMTYP2 = 000000
 AMTYP3 = 000000
 AMTYP4 = 000000
 APASS = 000000
 APRIOR = 000000
 APTCSU = 000040
 APTENV = 000001
 APTSIZ = 000200
 APTSPO = 000100
 ASWREG = 000000
 ATESTN = 000000
 AUNIT = 000000
 AUSWR = 000000

AUTO.S = 011364
 AVECT1 = 000300
 AVECT2 = 000000
 BINWRD = 006270
 BIT0 = 000001
 BIT00 = 000001
 BIT01 = 000002
 BIT02 = 000004
 BIT03 = 000010
 BIT04 = 000020
 BIT05 = 000040
 BIT06 = 000100
 BIT07 = 000200
 BIT08 = 000400
 BIT09 = 001000
 BIT1 = 000002
 BIT10 = 002000
 BIT11 = 004000
 BIT12 = 010000
 BIT13 = 020000
 BIT14 = 040000
 BIT15 = 100000
 BIT2 = 000004
 BIT3 = 000010
 BIT4 = 000020
 BIT5 = 000040
 BIT6 = 000100
 BIT7 = 000200
 BIT8 = 000400
 BIT9 = 001000
 BPTVEC = 000014
 BRK0 = 000400
 BRK1 = 001000
 BRK2 = 002000
 BRK3 = 004000
 BRW = 004622
 BUFSET = 104422
 BUILD = 014764
 CHRCNT = 006266
 CLEAR = 000000
 CNVRT = 104412
 CONVRT = 104411
 CORMAX = 017146
 CO0 = 000400
 CO1 = 001000
 CO2 = 002000
 CO3 = 004000
 CR = 000015
 CRLF = 000200
 CSRMAP = 011372
 CYCLE = 010530
 DATABP = 006762
 DATAHD = 006750

DCLASM = 104417
 DCLR = 000020
 DDISP = 177570
 DELAY = 104414
 DEVADR = 006012
 DEVICE = 104413
 DH1 = 016570
 DH2 = 016614
 DH3 = 016647
 DH4 = 016661
 DH5 = 016710
 DISPLA = 001306
 DISPRE = 000174
 DLYCNT = 006364
 DLYTBL = 017066
 DONFLG = 001425
 DSWR = 177570
 DTR0 = 000400
 DTR1 = 001000
 DTR2 = 002000
 DTR3 = 004000
 DT1 = 016770
 DT2 = 017002
 DT3 = 017020
 DT4 = 017026
 DT5 = 017044
 DVALID = 100000
 DZCR0 = 001500
 DZCR1 = 001512
 DZCR10 = 001620
 DZCR11 = 001632
 DZCR12 = 001644
 DZCR13 = 001656
 DZCR14 = 001670
 DZCR15 = 001702
 DZCR16 = 001714
 DZCR17 = 001726
 DZCR2 = 001524
 DZCR3 = 001536
 DZCR4 = 001550
 DZCR5 = 001562
 DZCR6 = 001574
 DZCR7 = 001606
 DZVACT = 001406
 DZVCSR = 002010
 DZVC0 = 001502
 DZVC1 = 001514
 DZVC10 = 001622
 DZVC11 = 001634
 DZVC12 = 001646
 DZVC13 = 001660
 DZVC14 = 001672
 DZVC15 = 001704

DZVC16 = 001716
 DZVC17 = 001730
 DZVC2 = 001526
 DZVC3 = 001540
 DZVC4 = 001552
 DZVC5 = 001564
 DZVC6 = 001576
 DZVC7 = 001610
 DZVLEV = 011074
 DZVLPR = 002020
 DZVMSR = 002030
 DZVNUM = 001414
 DZVRBU = 002014
 DZVRIS = 002042
 DZVRIV = 002040
 DZVTCR = 002024
 DZVTDR = 002034
 DZVTIS = 002046
 DZVTIV = 002044
 DZV.EN = 001740
 DZV.MA = 001500
 EIGHT = 000030
 EIGHTS = 000070
 EMTVEC = 000030
 EM1 = 015444
 EM11 = 015721
 EM13 = 015757
 EM14 = 016010
 EM15 = 016042
 EM16 = 016104
 EM17 = 016156
 EM2 = 015517
 EM20 = 016214
 EM21 = 016255
 EM23 = 016305
 EM24 = 016335
 EM25 = 016363
 EM26 = 016413
 EM27 = 016442
 EM3 = 015545
 EM30 = 016510
 EM4 = 015604
 EM5 = 015633
 EM6 = 015662
 ERRMSG = 006736
 ERRVEC = 000004
 ERTABO = 007112
 EVEPAR = 000000
 EXITER = 007042
 FALCIN = 000570
 FALCON = 017126
 FIVE = 000000
 FIVES = 000040

FRMERR = 020000
 GETCSR = 002360
 GETSWR = 007154
 GETVEC = 002404
 HALTS = 006766
 HDRFLG = 001423
 HDZVCS = 002012
 HDZVLP = 002022
 HDZVMS = 002032
 HDZVRB = 002016
 HDZVTC = 002026
 HDZVTD = 002036
 HILIM = 006010
 HT = 000011
 INBUF = 010424
 INIFLG = 001422
 INSTER = 104404
 INSTR = 104403
 INSTR2 = 005610
 IOTVEC = 000020
 KXTCHK = 000400
 KXTFLA = 017142
 LF = 000012
 LIMITS = 005736
 LINE = 001366
 LINE0 = 001504
 LINE1 = 001516
 LINE10 = 001624
 LINE11 = 001636
 LINE12 = 001650
 LINE13 = 001662
 LINE14 = 001674
 LINE15 = 001706
 LINE16 = 001720
 LINE17 = 001732
 LINE2 = 001530
 LINE3 = 001542
 LINE4 = 001554
 LINE5 = 001566
 LINE6 = 001600
 LINE7 = 001612
 LOBITS = 006014
 LOCK = 001364
 LOLIM = 006006
 LPRSET = 104421
 LP0 = 000000
 LP1 = 000001
 LP2 = 000002
 LP3 = 000003
 MAINT = 000010
 MANT0 = 001510
 MANT1 = 001522
 MANT10 = 001630

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 30-1
 CVDZBB.P11 10-AUG-81 10:56 SYMBOL TABLE

SEQ 0083

MANT11	001642	PAR14	001676	SAVLIN	001374	S150	= 002000	TYPMSG	006642
MANT12	001654	PAR15	001710	SAVNO	001416	S1800	= 004000	T110	002054
MANT13	001666	PAR16	001722	SAVNUM	001415	S19200	= 007400	T1200	002066
MANT14	001700	PAR17	001734	SAVPC	001404	S2000	= 004400	T134	002056
MANT15	001712	PAR2	001532	SAV05	= 104407	S2400	= 005000	T150	002060
MANT16	001724	PAR3	001544	SCOP1	= 104401	S300	= 002400	T1800	002070
MANT17	001736	PAR4	001556	SERV.G	007126	S3600	= 005400	T2000	002072
MANT2	001534	PAR5	001570	SETAPT	011236	S4800	= 006000	T2400	002074
MANT3	001546	PAR6	001602	SETFLG	= 104406	S50	= 000000	T300	002062
MANT4	001560	PAR7	001614	SEVEN	= 000020	S600	= 003000	T3600	002076
MANT5	001572	PAUCH	= 104416	SEVENS	= 000060	S7200	= 006400	T4800	002100
MANT6	001604	PIRQ	= 177772	SHIFT	= 104420	S75	= 000400	T50	002050
MANT7	001616	PIRQVE	= 000240	SILQAL	= 020000	S9600	= 007000	T600	002064
MASK	= 000200	POPRO	= 012600	SILQEN	= 010000	TBITVE	= 000014	T7200	002102
MASTEK	010041	POP1SP	= 005726	SIX	= 000010	TCR0	= 000001	T75	002052
MBADLN	010154	POP2SP	= 022626	SIXS	= 000050	TCR1	= 000002	T9600	002104
MCSRX	007771	PR0	= 000000	SNAP	013142	TCR2	= 000004	VECMAP	011700
MDATA	010466	PR1	= 000040	SPACNT	006267	TCR3	= 000010	WRDCNT	006264
MEPASS	007607	PR2	= 000100	STACK	= 001120	TD0	001426	WTBS.F	006740
MERRPC	010121	PR3	= 000140	STKLMT	= 177774	TD1	001430	XBX	006530
MERRX	010016	PR4	= 000200	STOP	001446	TD2	001432	XCSR	004332
MERR2	007647	PR5	= 000240	SV05	006024	TD3	001434	XERR	004354
MERR3	007716	PR6	= 000300	SWR	001304	TEIGHT	002106	XHEAD	010126
MLOCK	007742	PR7	= 000340	SWREG	000176	TFIVE	002114	XMTCNT	001400
MNEW	010044	PS	= 177776	SW0	= 000001	TIE	= 040000	XMTLIN	001376
MNTFLG	001424	PSW	= 177776	SW00	= 000001	TKVEC	= 000060	XMTSRV	014642
MODE	001372	PUSHRO	= 010046	SW01	= 000002	TLAST	= 014212	XPASS	004346
MPASSX	010005	PUSH1S	= 005746	SW02	= 000004	TL0	= 000000	XSTATQ	010216
MPFAIL	007544	PUSH2S	= 024646	SW03	= 000010	TL1	= 000400	XTSTN	007120
MR	007633	PWRVEC	= 000024	SW04	= 000020	TL2	= 001000	XVEC	004340
MSENAB	= 000040	RCVON	= 010000	SW05	= 000040	TL3	= 001400	XX	= 160210
MTITLE	001000	RDONE	= 000200	SW06	= 000100	TMTBL	002050	YY	= 000500
MTSTN	010027	REGIST	001402	SW07	= 000200	TPVEC	= 000064	ZZ	= 000020
MVECX	007777	RESREG	006764	SW08	= 000400	TRAPVE	= 000034	\$APTHD	001446
NEXT	001362	RESTAR	011070	SW09	= 001000	TRDY	= 100000	\$ATYC	005250
ODDPAR	= 000200	RESVEC	= 000010	SW1	= 000002	TRTVEC	= 000014	\$ATY1	005224
OFFSET	015214	RES05	= 104410	SW10	= 002000	TR0	001436	\$ATY3	005232
ONESTO	= 000000	RIE	= 000100	SW11	= 004000	TR1	001440	\$ATY4	005242
OUT	013520	RING0	= 000001	SW12	= 010000	TR2	001442	\$AUTOB	001300
OVRRUN	= 040000	RING1	= 000002	SW13	= 020000	TR3	001444	\$BASE	001174
PAR	001370	RING2	= 000004	SW14	= 040000	TSEVEN	002110	\$BDADR	001266
PARAM	= 104405	RING3	= 000010	SW15	= 100000	TSIX	002112	\$BDDAT	001272
PARAM1	005656	RLO	= 000000	SW2	= 000004	TST1	012070	\$CDW1	001200
PARER	= 010000	RL1	= 000400	SW3	= 000010	TST2	012532	\$CDW2	001202
PARERR	005732	RL2	= 001000	SW4	= 000020	TST3	013032	\$CHARC	005220
PARITY	= 000100	RL3	= 001400	SW5	= 000040	TST4	013574	\$CMTAG	001244
PARMD	= 104415	RUN	001412	SW6	= 000100	TST5	014212	\$CM1	= 000006
PAR0	001506	RXISR1	015012	SW7	= 000200	TTST	004374	\$CM2	= 000014
PAR1	001520	RXSVC	013314	SW8	= 000400	TWOSTO	= 000040	\$CM3	= 000006
PAR10	001626	RXTCR	013572	SW9	= 001000	TXSVC	013200	\$CM4	= 000005
PAR11	001640	R6	= 0000006	S110	= 001000	TXTCR	013312	\$CPUOP	001146
PAR12	001652	R7	= 0000007	S1200	= 003400	TYPDAT	006752	\$CRLF	001357
PAR13	001664	SAVACT	001410	S134	= 001400	TYPE	= 104402	\$DDW0	001204

CVDZB-B MACY11 30G(1063) 10-AUG-81 11:11 PAGE 30-2
 CVDZBB.P11 10-AUG-81 10:56 SYMBOL TABLE

SEQ 0084

SDDW1 001206	SETABL 001140	\$MFLG 005466	\$SVLAD 004544	\$Y = 000023
SDDW10 001230	SETEND 001244	\$MSGAD 001134	\$SVPC = 017146	\$SGET4= 000000
SDDW11 001232	\$FATAL 001122	\$MSGLG 001136	\$SWR = 164000	= 017146
SDDW12 001234	\$FFLG 005470	\$MSGTY 001120	\$SWREG 001142	.ADVAN 006366
SDDW13 001236	\$FILLC 001322	\$MTYP1 001151	\$SWRMK= 000000	.BEGIN 004052
SDDW14 001240	\$FILLS 001321	\$MTYP2 001155	\$TESTN 001124	.BUFSE 006456
SDDW15 001242	\$FLIP = 177777	\$MTYP3 001161	\$TIMES 001354	.CNVRT 006114
SDDW2 001210	\$FREE = 000002	\$MTYP4 001165	\$TKB 001312	.CONVR 006110
SDDW3 001212	\$GDADR 001264	\$MXCNT 004624	\$TKS 001310	.DCLAS 006334
SDDW4 001214	\$GDDAT 001270	\$N = 000005	\$TMP0 001342	.DELAY 006346
SDDW5 001216	\$GET42 004306	\$NULL 001320	\$TMP1 001344	.DEVIC 006314
SDDW6 001220	\$HD = 000001	\$NWTST= 000000	\$TMP2 001346	.ERRTA 015216
SDDW7 001222	\$HIBTS 001446	\$OVER 004562	\$TMP3 001350	.INSTE 005576
SDDW8 001224	\$ICNT 001250	\$PASS 001126	\$TMP4 001352	.INSTR 005472
SDDW9 001226	\$ILLUP 007536	\$PASTM 001454	\$TN = 000006	.INST1 005512
SDEVCT 001130	\$INTAG 001301	\$PWAD 007532	\$TPB 001316	.LPRSE 006416
SDEVN 001176	\$ITEMB 001260	\$PWADN 007372	\$TPFLG 001323	.MSG 005514
SDOAGN 004326	\$LF 001360	\$PWIMG 007526	\$TPS 001314	.PARAM 005616
SE = 000007	\$LFLG 005467	\$PWUP 007444	\$TSTM 001452	.PARMD 011234
SENDAD 004316	\$LPADR 001252	\$QUES 001356	\$TSTM 001246	.PAWCH 010350
SENDCT 004302	\$LPERR 001254	\$REGAD 001324	\$TYPE 004670	.RES05 006056
SENV 001140	\$MADR1 001152	\$REG0 001326	\$TYPEC 005102	.SAV05 006016
SENVN 001141	\$MADR2 001156	\$REG1 001330	\$TYPEX 005222	.SCOPE 004362
SEOP 004146	\$MADR3 001162	\$REG2 001332	\$UNIT 001132	.SCOP1 004626
SEOPCT 004274	\$MADR4 001166	\$REG3 001334	\$UNITM 001456	.SETFL 010230
SERFLG 001247	\$MAIL 001120	\$REG4 001336	\$USWR 001144	.SHIFT 006400
SERMAX 001261	\$MAMS1 001150	\$REG5 001340	\$VECT1 001170	.START 002116
SERROR 006500	\$MAMS2 001154	\$RTNAD 004330	\$VECT2 001172	.TRPSR 006272
SERRPC 001262	\$MAMS3 001160	\$SAVR6 007542	\$XOFF = 000023	.TRPTA 001742
SERRTB 001362	\$MAMS4 001164	\$SCOPE 004362	\$XON = 000021	.TYPE 004652
SERTTL 001256	\$MBADR 001450	\$SETUP= 000000	\$XTSTR 004422	.\$X = 001446

. ABS. 017146 000 OVR RW REL GBL I

ERRORS DETECTED: 0

CVDZBB,CVDZBB=CVDZBB
 RUN-TIME: 21 13 .7 SECONDS
 RUN-TIME RATIO: 195/35=5.5
 CORE USED: 37K (73 PAGES)