

DU11

OFF-LINE COMBINED TEST
CZDUFD0

AH-8697D-MC

COPYRIGHT © 73-78

FICHE 1 OF 1

JAN 1979

digital

MADE IN USA

1	2	3	4	5
6	7	8	9	10
11	12	13	14	15
16	17	18	19	20
21	22	23	24	25
26	27	28	29	30
31	32	33	34	35
36	37	38	39	40
41	42	43	44	45
46	47	48	49	50
51	52	53	54	55
56	57	58	59	60
61	62	63	64	65
66	67	68	69	70
71	72	73	74	75
76	77	78	79	80
81	82	83	84	85
86	87	88	89	90
91	92	93	94	95
96	97	98	99	100

I D E N T I F I C A T I O N

PRODUCT CODE: AC-8696D-MC

PRODUCT NAME: CZDUFDO DU11 OFFLINE COMBINED TESTS

RELEASE DATE: JUN 1978

MAINTAINER : DIAGNOSTICS

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

THE SOFTWARE DESCRIBED IN THIS DOCUMENT IS FURNISHED UNDER A LICENSE AND MAY ONLY BE USED OR COPIED IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE.

DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR THE USE OF RELIABILITY OF ITS SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL.

COPYRIGHT (C) 1973, 1978 BY DIGITAL EQUIPMENT CORPORATION

GENERAL DESCRIPTION

THIS DIAGNOSTIC CAN CHAIN 16 DU11'S. THIS MEANS THAT 16 DEVICES CAN BE SEQUENTIALLY EXERCISED. THE DIAGNOSTIC MAKES ONE PASS BEFORE PROCEEDING TO THE NEXT DEVICE, AND CONTINUES EXERCISING ALL DEVICES IN THIS FASHION UNTIL HALTED.

1. THE DU11 OFFLINE COMBINED TESTS VERIFY THAT THE TRANSMITTER AND RECEIVER CAN TALK THRU THE EXTERNAL MODEM CABLE PROVIDING THAT THE H315 CONNECTOR IS ON

2. REQUIREMENTS

PDP-11 FAMILY STANDARD COMPUTER WITH OR WITHOUT HARDWARE SWITCH REGISTER (LOC. 177570)

DU11 SYNCHRONOUS/ISOCRONOUS OPTION

ONE CONSOLE TELETYPE OR EQUIVALENT

- 2.2 STORAGE

THE PROGRAM LOADS AND RUNS IN 4K OF MEMORY.

3. LOADING PROCEDURE

THE STANDARD PROCEDURE FOR LOADING ABSOLUTE BINARY TAPES IS TO BE USED.

STARTING ADDRESS FOR ABSOLUTE LOADER

4K	017500
8K	037500
12K	057500
16K	077500
20K	117500
24K	137500
28K	157500

4. STARTING PROCEDURE

NOTE:

BEFORE PROCEEDING IT IS IMPORTANT TO
TO REALIZE IF ONE DOESNOT
HAVE THE DU11 SET UP TO THE
DEFAULT PARAMETERS (SEE SECTION

8 OF THIS DOCUMENT) , THEN ONE MUST
SET SW00 = 1, AND ANSWER THE PARAMETER
QUESTION ROUTINE.

4.1 CONTROL SWITCH SETTINGS

NOTE: SOFTWARE SWITCH REGISTER IS DEFINED AS LOC. 176, WHILE
THE SOFTWARE DISPLAY REGISTER IS DEFINED AS LOC. 174.

4.1.1 AFTER PROGRAM LOAD (INITIAL PROGRAM START) ALL CONSOLE SWITCHES DOWN

4.1.2 TO MODIFY DEVICE VECTOR AND CONTROL REGISTER ADDRESSES AFTER PROGRAM RESTART OR TO RUN MULTIPLE DEVICES

SW00=1

4.1.3 TO START PROGRAM AT SELECTED TEST AFTER A PROGRAM RESTART (ONLY IN SINGLE DEVICE TESTS)

SW01=1

4.1.4 TO LOCK ON SELECTED TEST AFTER A PROGRAM RESTART (ONLY IN SINGLE DEVICE TESTS)

SW02=1

NOTE1: IN GENERAL SW01 WILL BE USED WHEN SW02=1 IS USED

NOTE2: WITHOUT SW01=1 'LOCK ON TEST' WILL DEFAULT TO TEST 1
STARTING ADDRESS

4.2

THE STARTING ADDRESS FOR ALL TESTS IS 000200

THE RETARTING ADDRESS FOR ALL TESTS IS 000200

THE STARTING ADDRESS TO ENTER A SELECTED TEST IS 000200

THE STARTING ADDRESS TO LOCK ON TEST IS 000200

4.3 PROGRAM AND/OR OPERATOR ACTION

4.3.1 INITIAL PROGRAM START

4.3.1.1 LOAD PROGRAM INTO MEMORY WITH ABSOLUTE LOADER

4.3.1.2 LOAD ADDRESS 000200

4.3.1.3 CLEAR CONSOLE SWITCHES

4.3.1.4 PRESS START

4.3.1.5 THE PROGRAM WILL TYPE 'DU11 CZDUF-D TAPE F' (ONCE ONLY)

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING

WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.1.7 THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT IS ABOUT
TO START TESTING ,AND THEN TESTING WILL BEGIN

4.3.2 PROGRAM RESTART WITH ALL SWITCHES DOWN

4.3.2.1 THE PROGRAM WILL TYPE 'R' AND WILL COMMENCE TESTING

4.3.3 PROGRAM RESTART WITH SW00=1

4.3.3.1 LOAD ADDRESS 000200

4.3.3.2 SET SW00=1

4.3.3.3 PRESS START

NOTE:IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.3.4 THE PROGRAM WILL TYPE "1ST DEVICE: RECEIVER CONTROL REGISTER
ADDRESS" AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.5 TYPE IN THE ADDRESS OF THE FIRST RECEIVER CONTROL
REGISTER ADDRESS OF THE DU11 TO BE TESTED
FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ADDRESS IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.4

4.3.3.6 THE PROGRAM WILL TYPE 'VECTOR ADDRESS-' AND WAIT FOR AN
INPUT FROM THE TELETYPE KEYBOARD

4.3.3.7 TYPE IN THE BASE RECEIVER INTERRUPT VECTOR ADDRESS
FOR THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ADDRESS IS TYPED ,THE PROGRAM WILL TYPE "?"
AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.6

4.3.3.8 THE PROGRAM WILL TYPE 'ARE YOU RUNNING MULTIPLE DEVICES ?'
(Y OR N)-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.9 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY A
<CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS GIVEN, THE PROGRAM WILL TYPE "?"
AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.8

IF A 'NO' ANSWER IS GIVEN: JUMP TO SECTION 4.3.3.12
IF A 'YES' ANSWER IS GIVEN:THE NEXT QUESTION IS ASKED

4.3.3.10 THE PROGRAM WILL TYPE 'LAST DEVICE:RECEIVER CONTROL
REGISTER ADDRESS-' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.11 TYPE IN THE ADDRESS OF THE LAST RECEIVER CONTROL REGISTER
ADDRESS OF THE DU11 TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?'
AND WILL THEN REPEAT THE MESSAGE OF 4.3.3.10
NOTE:ALL ADDRESSES SHALL BE CONTIGUOUS

4.3.3.11.1 IF AN 'OUT OF RANGE' ADDRESS IS TYPED
IE. MORE THAN 16 (10) DEVICES AWAY (UPWARDS).....THE
PROGRAM WILL TYPE 'OUT OF RANGE:RETYPE LAST DEVICE RXCSR ADDRESS-'
AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.11.2 TYPE IN THE ADDRESS OF THE LAST RECEIVER CONTROL
REGISTER ADDRESS OF THE DU11 TO BE TESTED FOLLOWED
BY A <CARRIAGE RETURN>

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?'
AND WILL REPEAT THE MESSAGE OF 4.3.3.11.1

IF A DEVICE ADDRESS LOWER THAN 1ST DEVICE ADDRESS IS TYPED.....
....SCHOOLS OUT.....THERE IS NO PROTECTION FOR THIS.
THE PROGRAM WILL DEFAULT TO TWO DEVICES ACTIVE (UPWARDS FROM
1ST DEVICE ADDRESS).THE SAME APPLIES TO IDENTICAL ADDRESSES
TYPED FOR FIRST AND LAST DEVICE.
OBSERVE LOCATION @ ACTREG: SEE SECTION 7.2

4.3.3.12 THE PROGRAM WILL TYPE 'DU PRIORITY LEVEL-' AND
WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.13 TYPE IN THE APPROPRIATE DEVICE PRIORITY LEVEL OF THE
DU11 OR DU11'S TO BE TESTED FOLLOWED BY A <CARRIAGE RETURN>
(NOTE THAT ALL MULTIPLE DEVICES MUST BE AT THE SAME PRIORITY
LEVEL). IE '5'

IF AN INCORRECT LEVEL IS TYPED ,THE PROGRAM WILL TYPE '?'
AND REPEAT THE MESSAGE OF 4.3.3.12

4.3.3.14 THE PROGRAM WILL TYPE '# OF SYNC CHARS
SELECTED (1 OR 2)-' AND WAIT FOR AN INPUT FROM THE TELETYPE
KEYBOARD

4.3.3.15 TYPE IN THE APPROPRIATE ANSWER '1' OR '2' FOLLOWED
BY A <CARRIAGE RETURN>.(NOTE:ALL MULTIPLE DEVICES MUST
BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE '?'
AND WILL REPEAT THE MESSAGE OF 4.3.3.14

4.3.3.16 THE PROGRAM WILL TYPE '' IS SEC XMIT JUMPER #6 IN ? (Y OR N)-''
AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.17 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE THAT ALL MULTIPLE DEVICES
MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE ''?''
AND WILL REPEAT THE MESSAGE OF 4.3.3.16

4.3.3.18 THE PROGRAM WILL TYPE ''IS SEC REC JUMPER # 5 IN ?
(Y OR N)-'' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.19 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE ''?''
AND WILL REPEAT THE MESSAGE OF 4.3.3.18

4.3.3.20 THE PROGRAM WILL TYPE ''IS OPT CLR ENABLE JUMPER
4 IN ? (Y OR N)-'' AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.3.21 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED
BY A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE ''?''
AND WILL REPEAT THE MESSAGE OF 4.3.3.20

4.3.3.22 THE PROGRAM WILL TYPE ''ARE YOU RUNNING IN MAINT.
MODE EXTERNAL ? ANDDO YOU HAVE THE EXTERNAL MODEM
BYPASS JUMPER CONNECTOR ON ? (Y OR N)-'' AND WAIT FOR AN
INPUT FROM THE TELETYPE KEYBOARD

4.3.3.23 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY
A <CARRIAGE RETURN>. (NOTE: ALL MULTIPLE DEVICES MUST BE THE SAME)

IF AN INCORRECT ANSWER IS TYPED ,THE PROGRAM WILL TYPE ''?''
AND WILL REPEAT THE MESSAGE OF 4.3.3.22

4.3.3.24 THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT
HAS STARTED AND WILL COMMENCE TESTING AT TEST 1

4.3.4 PROGRAM RESTART WITH SW01=1
NOTE: THIS WILL ONLY WORK WHEN A SINGLE DEVICE IS SELECTED
...IT WILL NOT WORK IF MULTIPLE DEVICES ARE SELECTED

IF MULTIPLE DEVICES WERE PREVIOUSLY SELECTED,LOAD 000200,
AND SELECT SW00=1 AND ANSWER 'NO' TO THE MULTIPLE DEVICE QUESTION
SEE 4.3.3

4.3.4.1 LOAD 000200

4.3.4.2 SET SW01=1

4.3.4.3 PRESS START

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.4.4 THE PROGRAM WILL TYPE 'TEST PC-' AND WAIT FOR AN INPUT FROM
THE TELETYPE KEYBOARD

4.3.4.5 TYPE IN THE ADDRESS OF THE TEST AT WHICH THE PROGRAM IS TO
BE STARTED FOLLOWED BY A <CARRIAGE RETURN>

4.3.4.6 THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT THE SELECTED TEST

NOTE: CARE MUST BE TAKEN WHEN THIS FEATURE IS USED
SINCE THERE IS NO PROTECTION AGAINST SELECTING AN ADDRESS
THAT IS IN THE MIDDLE OF A TEST

4.3.5 PROGRAM RESTART WITH SW02 =1
NOTE: THIS WILL ONLY WORK WHEN A SINGLE DEVICE IS SELECTED
SEE NOTE IN 4.3.4 FOR MORE DETAILS

4.3.5.1 LOAD ADDRESS 000200

4.3.5.2 SET SW02 =1

NOTE: IT MAY BE ADVANTAGEOUS TO SET SW01=1 (OPTIONAL)

4.3.5.3 PRESS START

NOTE: IF THE SOFTWARE SWITCH REGISTER IS SELECTED THEN THE FOLLOWING
WILL BE TYPED AFTER THE PROGRAM IDENTIFIES ITSELF:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR'S OPTION)

4.3.5.4 THE PROGRAM WILL TYPE 'LOCK ON SELECTED TEST ? (Y OR N)-'
AND WAIT FOR AN INPUT FROM THE TELETYPE KEYBOARD

4.3.5.5 TYPE IN THE APPROPRIATE ANSWER YES OR NO FOLLOWED BY A
<CARRIAGE RETURN>

IF A NO ANSWER IS GIVEN: THIS LOCK ON TEST WILL BE IGNORED
AND THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT TEST 1

4.3.5.6 IF A YES ANSWER WAS GIVEN: THE PROGRAM WILL ACT AS FOLLOWS...
THE PROGRAM WILL TYPE 'R' TO INDICATE THAT IT HAS STARTED
TESTING AT TEST 1 AND WILL REMAIN IN TEST 1 UNTIL HALTED
OR IF ANY KEY IS STRUCK ON THE TELETYPE, THE PROGRAM
WILL FREEZE ON THE NEXT TEST UNTIL A KEY IS STRUCK ON
THE TELETYPE AND SO FORTH THRU THE PROGRAM. IF SW01 =1 IT
WILL PERFORM AS IN SECTION 4.3.4 ALLOWING ONE TO FREEZE
ON A SELECTED TEST RATHER THAN DEFAULTING TO TEST 1

4.4 STATUS MAP

THE STATUS MAP IS AN AREA OF THE DU11 DIAGNOSTICS, WHICH WILL ALLOW THE TRANSFER OF PARAMETERS BETWEEN DIAGNOSTICS. IF YOU WISH TO TEST A DU11, WHICH IS NOT AT THE DEFAULT VALUES, YOU NEED ONLY GO THROUGH THE TEDIOUS QUESTIONING AND ANSWERING ROUTINE ONCE.

THE FOLLOWING COMBINATIONS OF SWITCH REGISTER SETTINGS WILL ALLOW YOU ACCESS TO THE STATUS MAP.

- 1) SW07=1
- 2) START AT 200
- 3) THE DIAGNOSTIC WILL GO TO THE STATUS MAP AND BYPASS ALL OF THE QUESTIONING ROUTINE.

NOTE: IT IS EXTREMELY IMPORTANT THAT EITHER YOU HAVE JUST ANSWERED THESE QUESTIONS DURING A PRIOR DIAGNOSTIC OR THAT YOU HAVE MANUALLY ENTERED THE CORRECT VALUES FOR VECTOR ADDRESSES ETC., IN THE AREA DESIGNATED FOR THE STATUS MAP. IT IS IMPORTANT THAT THIS BE PERFORMED BEFORE STARTING AT 200.

THE DIAGNOSTIC HAS NO METHOD TO DETERMINE THAT THE STATUS MAP HAS INDEED BEEN LOADED CORRECTLY. THE DIAGNOSTIC ASSUMES THAT WHEN SW07=1 THE VALUES IN THE STATUS MAP ARE THE VALUES TO BE USED. THESE VALUES CAN BE THE WRONG VALUES, BUT THE DIAGNOSTIC WILL NOT REALIZE THAT A MISTAKE HAS BEEN MADE.

IF BOTH SW07 AND SW00 (SWITCH REGISTER SWITCHES) ARE SET (EQUAL TO 1), THE PROGRAM WILL IGNORE SW00 AND SEEING SW07 SET, THE VALUES FROM THE STATUS MAP WILL BE USED. TO USE THE DEFAULT VALUES FOR THE DU11'S THE OPERATOR MUST SET SW00=0 AND SW07=0. THE USE OF SW00 IS EXPLAINED IN GREATER DETAIL IN SECTION 4.3 OF THIS DOCUMENT.

THE FIRST TIME A PROGRAM IS LOADED OR THE FIRST TIME A PROGRAM IS ALTERED VIA THE PARAMETER RESELECTION QUESTION AND ANSWER ROUTINE, A PARTIAL STATUS MAP WILL BE PRINTED. THIS MAP WILL BE PRINTED ONCE FOR ANY COMBINATION OF SWITCHES EXCEPT SW01. RESTARTING THE PROGRAM WILL NOT PRINT OUT A MAP UNLESS THE PROGRAM PARAMETERS ARE BEING RESELECTED BY PUTTING SW00=1.(ON)

THE MAP WILL LOOK LIKE:

STATUS MAP

1300/ 177777

1302/ 000000

1304/ 177777

THE BYTES ARE DEFINED AS FOLLOWS:

1300 THE NUMBER OF SYNCHRONOUS CHARACTERS REQUIRED FOR
SYNCHRONIZATION.
1301 SEC TRANSMIT JUMPER
1302 SEC RECEIVER JUMPER
1303 OPTIONAL JUMPER
1304 MULTIPLE DEVICES (NO=0 , YES= 1)
1305 EXTERNAL MODEM BYPASS? (NO=0 , YES= 1)

IF THE BYTE IS 0 , THE JUMPER IS NOT CONNECTED
AND IF THE BYTE IS 377 ETC. THE JUMPER SHOULD BE CONNECTED.

5. OPERATING PROCEDURE

IF THE DIAGNOSTIC IS RUN ON A CPU WITHOUT A SWITCH
REGISTER THEN A SOFTWARE SWITCH REGISTER IS USED WHICH ALLOWS
THE USER THE SAME SWITCH OPTIONS AS THE HARDWARE SWITCH REGISTER.
IF THE HARDWARE SWITCH REGISTER DOES NOT EXIST OR IF ONE DOES
AND IT CONTAINS ALL ONES (177777) THEN THE SOFTWARE SWITCH
REGISTER (LOC. 176) IS USED.

CONTROL:

THIS PROGRAM ALSO SUPPORTS THE DYNAMIC LOADING OF THE SOFTWARE SWITCH
REGISTER (LOC. 176) FROM THE TTY. THIS CAN BE ACCOMPLISHED BY
DOING THE FOLLOWING:

- 1) TYPE CONTROL G <^G>; THIS WILL ALLOW THE TTY TO ENTER DATA INTO
LOC. 176 AT SELECTED POINTS WITHIN THE PROGRAM.
- 2) THE MACHINE WILL THEN TYPE: SWR=XXXXXXNEW= (XXXXXX IS THE OCTAL CONTENTS
OF THE SOFTWARE SWITCH REGISTER.)
- 3) AFTER THE "'NEW=" HAS BEEN TYPED THEN THE OPERATOR CAN DO ONE
OF THE FOLLOWING AT THE TTY:
 - A) TYPE A NUMBER TO BE LOADED INTO LOC. 176 FOLLOWED BY A <CR>.
(ONLY NUMBERS BETWEEN 0-7 WILL BE ACCEPTED AND ONLY 6 NUMBERS
WILL BE ALLOWED)
IF A <CR> IS THE FIRST KEY DEPRESSED THE SOFTWARE SWITCH
REGISTER CONTENTS WILL NOT BE CHANGED.
 - B) IF A CONTROL U <^U> IS DEPRESSED THEN THE PROGRAM WILL SEND YOU
BACK TO STEP 2.

5.1

OPERATIONAL SWITCH SETTINGS

SW15 =1 HALT ON ERROR
SW14 =1 LOOP ON CURRENT TEST
SW13 =1 INHIBIT ERROR TYPEOUT
SW11 =1 INHIBIT ITERATIONS

SW10 =1 ESCAPE TO NEXT TEST ON ERROR
SW08 =1 LOOP ON ERROR
SW07 =1 USE STATUS MAP PARAMETERS
SW02 =1 LOCK ON TEST
SW01 =1 RESTART PROGRAM AT SELECTED TEST
SW00 =1 RESELECT VECTOR AND CONTROL REGISTER ADDRESSES
&PARAMETERS AFTER A PROGRAM RESTART
TO INHIBIT 'END OF PASS' TYPEOUT - TURN TELETYPE OFF

6. ERRORS

6.1 ERROR HALTS
THERE ARE FOUR DISTINCT ERROR TYPEOUTS

NOTE: IF THE SOFTWARE SWITCH REGISTER IS TO BE CHANGED AFTER A HALT
THE THE OPERATOR IS REQUIRED TO TYPE A <^G> BEFORE DEPRESSING CONTINUE.
THE FOLLOWING WILL BE TYPED:
SWR=XXXXXX NEW= (REFER TO SECTION 5. FOR OPERATOR OPTION)

6.1.1 PC+2 = ERROR PC
WHERE PC +2 IS THE ADDRESS OF THE CALL TO THE ERROR HANDLER +2
REFER TO THE ABOVE 'HLT' IN DIAGNOSTIC FOR ERROR DESCRIPTION
CHECK ADDRESS @ RXCSR: TO LOCATE THE DEVICE PRESENTLY UNDER
TEST WHEN RUNNING MULTIPLE DEVICES

6.1.2 PC +2 = REGISTER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ
WHERE 16XXXX IS THE ADDRESS OF THE FAILING DEVICE REGISTER
WHERE YYYYYY IS THE EXPECTED CONTENTS OF THAT REGISTER
WHERE ZZZZZZ IS THE ACTUAL CONTENTS OF THAT REGISTER

6.1.3 PC +2 = RECEIVER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ
WHERE 16XXXX IS THE ADDRESS OF THE FAILING RECEIVER (RXDBUF) REGISTER
WHERE YYYYYY IS THE EXPECTED DATA CONTENTS OF THAT REGISTER
WHERE ZZZZZZ IS THE ACTUAL DATA CONTENTS OF THAT REGISTER

6.1.4 PC +2 = TRANSMITTER ERROR PC
REGISTER EXPECTED ACTUAL
16XXXX YYYYYY ZZZZZZ
WHERE 16XXXX IS THE ADDRESS OF THE FAILING TRANSMITTER (TXCSR) REGISTER
WHERE YYYYYY IS THE EXPECTED CONTENTS OF THAT REGISTER
WHERE ZZZZZZ IS THE ACTUAL CONTENTS OF THAT REGISTER

6.1.5 ERROR DESCRIPTIONS
SEE LISTINGS FOR DETAILS OF ERRORS

6.2 ERROR RECOVERY

6.2.1 SW15 =0
IF THE PROGRAM IS RUN WITH SW15 =0 ,NO OPERATOR ACTION IS
REQUIRED TO CONTINUE TESTING

6.2.2 SW15 =1
IF THE PROGRAM IS RUN WITH SW15 =1 ,TO CONTINUE TESTING
AFTER THE PROGRAM HAS HALTED ,PRESS THE PROCESSOR
CONSOLE "CONTINUE SWITCH"

NOTE: THE PC + 2 OF THE 'HLT' WILL BE DISPLAYED IN THE DATA LIGHTS

6.2.3 ILLEGAL INTERRUPTS
IF AN INTERRUPT OCCURS TO A VECTOR ADDRESS NOT SELECTED
DURING PROGRAM INITIALIZATION, THE PROGRAM WILL HALT IN
THE TRAPCATCHER. THE ADDRESS AT WHICH THE PROGRAM
HALTS IS 2 GREATER THAN THE ADDRESS TO WHICH THE INTERRUPT
OCCURED. THE PROGRAM MUST BE RESTARTED AT 000200 TO
RECOVER FROM THIS ERROR.

6.2.4 ADDITIONAL TROUBLESHOOTING AIDS ERRCNT: & PASCNT:
CHECK THESE TWO TAG LOCATIONS FOR TOTAL # OF ERRORS AND PASSES RESPECTIVELY.
LOADING 000200 AND RESTARTING WILL CLEAR THESE LOCATIONS.

6.3 END OF PASS ROUTINE
THIS TYPEOUT IS MENTIONED HERE FOR CONVENIENCE
IT IS IN THE FORM:

END OF PASS TAPE Y
16XXXX = DEVICE

WHERE Y IS THE TAPE LOADED

WHERE 16XXXX IS THE DEVICE'S BASE REGISTER ADDRESS

TO INHIBIT THIS TYPEOUT - TURN TELETYPE OFF

7. RESTRICTIONS

7.1 MULTIPLE DEVICES
UP TO 16(10) DEVICES MAY BE TESTED. HOWEVER, THEY
MUST HAVE CONTIGUOUS ADDRESSES AND VECTORS

NOTE: IF ALL DEVICES UNDER TEST HAVE THE SAME INTERRUPT VECTOR
YOU CAN CHANGE "ZERO: ADD #10,BASEIV ;NEXT BLOCK
(VECTORS)" TO "ZERO: ADD #0,BASEIV";
THEREBY THE VECTOR ADDRESSES WILL NOT BE
UPDATED AFTER EACH PASS.

7.2 DISQUALIFYING DEVICES WHEN RUNNING MULTIPLE DEVICES

WHEN RUNNING MULTIPLE DEVICES AN ACTIVE BIT IS SET
FOR EACH DEVICE RUNNING UNDER TEST IE. BIT 0 FOR
DEVICE 0 BIT 15 FOR DEVICE 15
TO DISQUALIFY DEVICES:

- 7.2.1 IF DEVICE 0 IS TO BE DISQUALIFIED, SIMPLY RESTART
PROGRAM WITH SW00 =1 AND OMIT THE FIRST DEVICE.
- 7.2.2 IF HOWEVER, DEVICES 1 THRU 15 OR ANY COMBINATION THEREOF
ARE TO BE DISQUALIFIED....LOAD THE LOCATION OF ACTREG:
OBSERVE THE ACTIVE BITS (ACTIVE =1, NONACTIVE = 0)
AND DEPOSIT 0 WHERE THOSE DEVICES ARE TO BE DISQUALIFIED
 - 7.2.2.1 TO RESTART...LOAD 000200 IN SWR AND DEPRESS START....
THE PROGRAM WILL CONTINUE WITH THE DEVICE IT WAS IN BEFORE HALTING.
 - 7.2.2.2ORLOAD 000200 WITH SW00 =1 AND DEPRESS START....
ANSWER THE QUESTION :1ST DEVICE : ETC.....
.....THE PROGRAM WILL CONTINUE WITH DEVICE 0
 - 7.2.2.3 IF ALL DEVICES ARE DISQUALIFIED BY MISTAKE THE PROGRAM
WILL TYPEOUT AN ERROR MESSAGE.....LOAD & START AT 000200
- 7.3 CABLE DELAYS
NOTE: EXTERNAL LOOP BACK TESTS ONLY (MODEM CABLE WITH H315 CONNECTOR ON)
- 7.3.1 TO PROVIDE SUFFICIENT DELAY FOR CLOCK SIGNAL OVER THE CABLE,
LOCATION 'HOLD:' MUST BE MODIFIED TO ACCOMODATE FOR FASTER MACHINES.
PRESENTLY 'HOLD:' =20 IS SUFFICIENT TIME ON AN 11/20 MACHINE.
IF RUNNING ON AN 11/40 OR AN 11/45 'HOLD:' MUST BE PATCHED TO 40

BASICALLY DON'T TRY TO EXCEED 10K TO 12K RATE USING THE EIA DRIVERS
- 7.4 TO USE THE 'XOR' TESTER, THE BRANCH AROUND THE 'XOR'
CODE MUST BE PATCHED TO A 'NOP'. (SEE LISTINGS FOR DETAILS)
- 8. DEFAULT PARAMETERS:
1ST DEVICE: RECEIVER CONTROL REGISTER ADDRESS- RXCSR: 160040

VECTOR ADDRESS- DURIV: 770

ARE YOU RUNNING MULTIPLE DEVICES ?- NO MULTD: 0

LAST DEVICE: RECEIVER CONTROL REGISTER ADDRESS- LASTADD: C

DU PRIORITY LEVEL- LEVEL 5 DUPRT: LEVEL 5

OF SYNC CHARS SELECTED - 2 SYNCNO: 377

IS SEC XMIT JUMPER # 6 IN ?- YES SEXMIT: 377

IS SEC REC JUMPER # 5 IN ?- YES SEREC: 377

IS OPT CLR ENABLE JUMPER # 4 IN ?- YES OPTCLR: 377

DO YOU HAVE THE EXTERNAL MODEM BYPASS JUMPER
CONNECTOR ON (H315)- YES

JMRBY: 377

9. PROGRAM DESCRIPTION
- 9.1 THIS PROGRAM PERFORMS THE OFFLINE COMBINED (TRANSMITTER & RECEIVER)
CABLE TESTING OF THE DEVICE
SEE LISTING FOR DETAILS
10. FLOW CHARTS: RECEIVER FLOW, TRANSMITTER FLOW, TRANSMITTER & RECEIVER FLOW
11. LISTINGS

CZDUF-D MACY11 30A(1052) 21-NOV-78 15:52 PAGE 15
CZDU11.PAR 21-NOV-78 15:17

B 2

SEQ 0014

675
676 000000' 000000G

D .

```
677 .ENABLE ABS
678
679 ;DU11 CZDUF-D TAPE F
680 ;COPYRIGHT 1973, DIGITAL EQUIPMENT CORP., MAYNARD, MASS. 01754
681
682 ;STARTING PROCEDURE
683 ;LOAD PROGRAM
684 ;PRESS START
685 ;PROGRAM WILL TYPE 'DU11 CZDUF-D TAPE F ''
686 ;PROGRAM WILL TYPE 'R' TO INDICATE THAT TESTING HAS STARTED
687 ;AT THE END OF A PASS, PROGRAM WILL TYPE 'END OF PASS TAPE F''
688 ;AND THEN RESUME TESTING
689
690
691 ;SWITCH REGISTER OPTIONS
692
693 100000 SW15=100000 ;=1,HALT ON ERROR
694 040000 SW14=40000 ;=1,LOOP ON CURRENT TEST
695 020000 SW13=20000 ;=1,INHIBIT ERROR TYPEOUT
696 010000 SW12=10000
697 004000 SW11=4000 ;=1,INHIBIT ITERATIONS
698 002000 SW10=2000 ;=1,ESCAPE TO NEXT TEST ON ERROR
699 001000 SW09=1000 ;=1,LOOP WITH CURRENT DATA
700 000400 SW08=400 ;=1,LOOP ON ERROR
701 000200 SW07=200 ;+ =1, USE STATUS MAP
702 000100 SW06=100
703 000040 SW05=40
704 000020 SW04=20
705 000010 SW03=10
706 000004 SW02=4
707 000002 SW01=2
708 000001 SW00=1
709
710 ;LOCK ON TEST SELECT
;RESTART PROGRAM AT SELECTED TEST
;RESELECT VECTOR AND CONTROL REGISTER
;ADDRESS AFTER PROGRAM RESTART
```


711		
712		;REGISTER DEFINITIONS
713		
714	000000	R0=%0 ;GENERAL REGISTER
715	000001	R1=%1 ;GENERAL REGISTER
716	000002	R2=%2 ;GENERAL REGISTER
717	000003	R3=%3 ;GENERAL REGISTER
718	000004	R4=%4 ;GENERAL REGISTER
719	000005	R5=%5 ;GENERAL REGISTER
720	000006	SP=%6 ;PROCESSOR STACK POINTER
721	000007	PC=%7 ;PROGRAM COUNTER
722		
723		;LOCATION EQUIVALENCIES
724		
725	177570	DSWR=177570 ;HARDWARE SWITCH REGISTER LOC.
726	177570	DLIGHTS=177570 ;HARDWARE DISPLAY REGISTER LOC.
727	177776	PS=177776 ;PROCESSOR STATUS WORD
728	001100	STACK=1100 ;START OF PROCESSOR STACK
729		
730		;INSTRUCTION DEFINITIONS
731		
732	005746	PUSH1SP=5746 ;DECREMENT PROCESSOR STACK 1 WORD =TST -(SP)
733	005726	POP1SP=5726 ;INCREMENT PROCESSOR STACK 1 WORD =TST (SP)+
734	010046	PUSHR0=10046 ;SAVE R0 ON STACK =MOV R0,-(SP)
735	012600	POPR0=12600 ;RESTORE R0 FROM STACK =MOV (SP)+,R0
736	024646	PUSH2SP=24646 ;DECREMENT STACK TWICE =CMP -(SP),-(SP)
737	022626	POP2SP=22626 ;INCREMENT STACK TWICE =CMP (SP)+,(SP)+
738		.EQUIV EMT,HLT ;BASIC DEFINITION OF ERROR CALL
739		
740		
741	100000	BIT15=100000
742	040000	BIT14=40000
743	020000	BIT13=20000
744	010000	BIT12=10000
745	004000	BIT11=4000
746	002000	BIT10=2000
747	001000	BIT9=1000
748	000400	BIT8=400
749	000200	BIT7=200
750	000100	BIT6=100
751	000040	BIT5=40
752	000020	BIT4=20
753	000010	BIT3=10
754	000004	BIT2=4
755	000002	BIT1=2
756	000001	BIT0=1
757		
758		;PROCESSOR LEVELS
759	000340	LEVEL7=340
760	000300	LEVEL6=300
761	000240	LEVEL5=240
762	000200	LEVEL4=200
763	000140	LEVEL3=140
764	000100	LEVEL2=100
765	000040	LEVEL1=040
766	000000	LEVEL0=000

```

767      ;REGISTER DEFINITIONS
768      ;RXCSR BIT DEFINITIONS
769      100000 DSC=BIT15      :DATA SET CHANGE
770      040000 RING=BIT14     :RING
771      020000 CTS=BIT13      :CLR TO SEND
772      010000 CARDET=BIT12   :CARRIER DETECT
773      004000 RECACT=BIT11    :REC ACTIVE
774      002000 SRD=BIT10      :SEC REC DATA
775      001000 DSR=BIT9       :DATA SET RDY
776      000400 STPSYN=BIT8    :STRIP SYNC
777      000200 RXDONE=BIT7     :REC DONE
778      000100 RINTEN=BIT6    :REC INTR ENABLE
779      000040 DSINTE=BIT5     :DSC INTR ENABL
780      000020 SYNSCH=BIT4    :SYNC SEARCH
781      000010 STD=BIT3       :SEC XMIT DATA
782      000004 RTS=BIT2       :REQ TO SEND
783      000002 DTR=BIT1       :DATA TERM RDY
784      000001 VOID=BIT0
785      ;RXDBUF BIT DEFINITIONS
786      100000 RXERR=BIT15     :REC ERROR
787      040000 OVRUN=BIT14     :OVERRUN
788      020000 FRMERR=BIT13    :FRAME ERROR
789      010000 PARER=BIT12     :PARITY ERROR
790      ;PARCSR BIT DEFINITIONS
791      001000 PAREN=BIT9       :PARITY ENABLE
792      000400 EVPAR=BIT8      :EVEN PARITY SENSE
793      ;PARCSR WRD DEFINITIONS
794      030000 SYNINT=30000    :SYNC EXTERNAL MODE
795      020000 SYNEXT=20000    :SYNC INTERNAL MODE
796      000000 ISYMOD=0        :ISOC MODE
797      000000 FIVE=0          :WORD LENGTH 5 BITS
798      002000 SIX=2000        :WORD LENGTH 6 BITS
799      004000 SEVEN=4000      :WORD LENGTH 7 BITS
800      006000 EIGHT=6000     :WORD LENGTH 8 BITS
801      000000 NOPAR=0        :NO PARITY
802      001000 ODDPAR=1000    :ODD PARITY
803      001400 EVEPAR=1400    :EVEN PARITY
804      ;TXCSR BIT DEFINITIONS
805      100000 DNA=BIT15       :DATA NOT AVAILABLE
806      040000 MTDATA=BIT14    :MAINT DATA
807      020000 CLK=BIT13       :CLK
808      002000 BITW=BIT10      :BIT WINDOW
809      000400 MRESET=BIT8     :MASTER RESET
810      000200 TXDONE=BIT7     :XMIT DONE
811      000100 TXINTE=BIT6    :XMIT INTR ENABLE
812      000040 DNAINTE=BIT5    :DNA INTR ENAB
813      000020 SEND=BIT4       :SEND
814      000010 HDXEN=BIT3      :HDX/FDX
815      000001 BREAK=BIT0     :BREAK
816      ;TXCSR WRD DEFINITIONS
817      000000 USER=0          :USER MODE
818      004000 MINT=4000       :MAINT INT MODE
819      010000 MEXT=10000      :MAINT EXT MODE
820      014000 SYSTST=14000    :SYSTEM TEST MODE
821      ;TRAPCATCHER FOR ILLEGAL INTERRUPTS
  
```



```

822                                     ;STANDARD INTERRUPT VECTORS
823
824
825                                     . =24
826 000024 010430                       .PFAIL                       ;POWER FAIL HANDLER
827 000026 000340                       340                       ;SERVICE AT LEVEL 7
828 000030 010160                       .HLT                       ;ERROR HANDLER
829 000032 000340                       340                       ;SERVICE AT LEVEL 7
830 000034 010126                       .TRPSRV                     ;GENERAL HANDLER DISPATCH SERVICE
831 000036 000340                       340                       ;SERVICE AT LEVEL 7
832
833                                     ;SOFTWARE SWITCH REGISTER
834
835                                     . =174
836 000174 000000                       DISPREG: .WORD 0           ;SOFTWARE DISPLAY REG.
837 000176 000000                       SWREG:  .WORD 0           ;SOFTWARE SWITCH REGISTER
838 000200 000167 001214                 JMP      .START         ;GO TO START OF PROGRAM
839
840
841                                     . =1100
842                                     . =1100
843
844                                     ;INDIRECT POINTERS
845
846 001100 177570                       SWR: 177570                 ;SWITCH REGISTER POINTER
847 001102 177570                       LIGHTS:177570                ;DISPLAY REGISTER POINTER
848 001104 177560                       TKCSR: 177560                ;TELETYPE KEYBOARD CONTROL REGISTER
849 001106 177562                       TKDBR: 177562                ;TELETYPE KEYBOARD DATA BUFFER
850 001110 177564                       TPCSR: 177564                ;TELEPRINTER CONTROL REGISTER
851 001112 177566                       TPDBR: 177566                ;TELEPRINTER DATA BUFFER
852
853                                     ;PROGRAM CONTROL PARAMETERS
854
855 001114 000000                       RTRN: 0                       ;SCOPE ADDRESS FOR LOOP ON TEST
856 001116 000000                       NEXT: 0                       ;ADDRESS OF NEXT TEST TO BE EXECUTED
857 001120 000000                       LOCK: 0                       ;ADDRESS FOR LOCK ON CURRENT DATA
858 001122 000000                       ICOUNT: 0                     ;NUMBER OF ITERATIONS THAT CURRENT TEST WILL BE EXECUTED
859 001124 000000                       LPCNT: 0                     ;NUMBER OF ITERATIONS COMPLETED
860 001126 000000                       TSTNO: 0                     ;NUMBER OF TEST IN PROGRESS
861 001130 000000                       PASCNT: 0                     ;NUMBER OF PASSES COMPLETED
862 001132 000000                       ERRCNT: 0                     ;TOTAL NUMBER OF ERRORS
863 001134 000000                       LSTERR: 0                     ;PC OF LAST ERROR CALL
864
865                                     ;PROGRAM VARIABLES
866
867 001136 000020                       HOLD: 20                      ;TEMPORARY STORAGE=DELAY TIME FOR CABLES
868 001140 000000                       SHIFT: 0                     ;TEMPORARY STORAGE= # OF SHIFTS PER CHAR
869 001142 000000                       COUNT: 0                     ;TEMPORARY STORAGE= # OF TIMES A CHAR WILL BE SENT
870 001144 000000                       TEMP1: 0                     ;TEMPORARY STORAGE
871 001146 000000                       TEMP2: 0                     ;TEMPORARY STORAGE
872 001150 000000                       TEMP3: 0                     ;TEMPORARY STORAGE
873 001152 000000                       TEMP4: 0                     ;TEMPORARY STORAGE
874 001154 000000                       TEMP5: 0                     ;TEMPORARY STORAGE
875 001156 000000                       SAVR0: 0                     ;R0 STORAGE
876 001160 000000                       SAVR1: 0                     ;R1 STORAGE
877 001162 000000                       SAVR2: 0                     ;R2 STORAGE

```

878 001164 000000
379 001166 000000
880 001170 000000
881 001172 000000
882 001174 000000

SAVR3: 0
SAVR4: 0
SAVR5: 0
SAVSP: 0
SAVPC: 0

;R3 STORAGE
;R4 STORAGE
;R5 STORAGE
;STACK POINTER STORAGE
;PROGRAM COUNTER STORAGE


```

883                                     ;PROGRAM CONVERSATIONAL PARAMETERS
884 001176 377 SYNCNO: .BYTE 377 ;# OF SYNC CHARS REQ'D FOR SYNC'ZATION
885 001177 377 SEXMIT: .BYTE 377 ;SEC XMIT JUMPER 'IN'
886 001200 377 SRECE: .BYTE 377 ;SEC REC JUMPER 'IN'
887 001201 377 OPTCLR: .BYTE 377 ;OPTIONAL JUMPER CLR 'IN'
888 001202 000 MULTD: .BYTE 0 ;NO MULTIPLE DEVICE FLAG
889 001203 377 JMRBY: .BYTE 377 ;EXTERNAL MODEM BYPASS JUMPER 'IN'
890 .EVEN
891
892                                     ;PROGRAM MULTIPLE DEVICE PARAMETERS
893 001204 000000 BASEADD: 0 ;PROG CONTROLLED 1ST DEVICE ADDR
894 001206 000000 KEEPADD: 0 ;SAVED 1ST DEVICE ADDR
895 001210 000000 LASTADD: 0 ;LAST DEVICE RXCSR ADDR
896 001212 000000 BASEIV: 0 ;PROG CONTROLLED IV
897 001214 000000 KEEPIV: 0 ;SAVED INTR VECTOR
898 001216 000000 ACTREG: 0 ;ACTIVE REGISTER ...MODIFY THIS
899 ;LOCATION TO DISQUALIFY OR QUALIFY
900 ;DEVICES (1= RUN...0= DON'T RUN)
901 001220 000000 ROTADD: 0 ;ROTATING POINTER FOR ACTREG..POINTS
902 ;TO DEVICE PRESENTLY UNDER TEST WHEN RUNNING MULTIPLE DE
903 ;*****
904
905 ; THESE ARE STORAGE FOR THE STATUS MAP PRINT OUT
906 001222 000000 FLAG:0 ; FLAGS FOR STATUS MAP PRINT OUT (SSP)
907 001224 000000 HOLD0: 0 ; HOLDS R0 IN STATUS MAP PRINT
908 001226 000000 HOLD1:0 ; R1 ETC.
909 001230 000000 COUNT1:0 ; FOR COUNTING 3 WORDS
910 001232 000002 TABLE : 2 ; FOR CONVRT ROUTINE
911 001234 003006 3006
912 001236 000000 0
913 001240 003006 3006
914 001242 000000 0
915 ;*****
916 ;PROGRAM CONTROL FLAGS
917
918
919 001244 000 INIFLG: .BYTE 0 ;PROGRAM INITIALIZATION FLAG
920 001245 000 STFLG: .BYTE 0 ;TEST START FLAG
921 001246 000 ERRFLG: .BYTE 0 ;ERROR OCCURED FLAG
922 001247 000 LOKFLG: .BYTE 0 ;LOCK ON CURRENT TEST FLAG
923 .EVEN
924
925
926 ;***** STATUS MAP *****
927
928 .=1300
929 001300 000001 STATUS: NOSYNC: .BLKB 1 ;SYNC CHARS
930 001301 000001 MITSEX: .BLKB 1 ;XMIT JUMPER
931 001302 000001 RESEC: .BLKB 1 ;REC SEC JUMPER
932 001303 000001 CLROPT: .BLKB 1 ;OPTIONAL JUMPER
933 001304 000001 DMULT: .BLKB 1 ;MULTIPLE DEVICE FLAG
934 001305 000001 BYJMR: .BLKB 1 ;EXTERNAL MODEM
935
936 ; MULTIPLE DEVICE PARAMETERS
937
938 001306 000001 ADDBASE: .BLKW 1 ;PROG CONTROLLED 1ST DEVICE ADDR
  
```

939	001310	000001	ADDKEEP: .BLKW 1	;SAVED 1ST DEVICE ADDR
940	001312	000001	ADDLAST: .BLKW 1	;LAST DEVICE RXCSR ADDR
941	001314	000001	IVBASE: .BLKW 1	;PROG CONTROLLED IV
942	001316	000001	IVKEEP: .BLKW 1	;SAVED INTR VECTOR
943	001320	000001	REGACT: .BLKW 1	;ACTIVE REGISTER
944	001322	000001	ADDROT: .BLKW 1	;ROTATING POINTER
945	001324	000001	PRTDU: .BLKW 1	;DU11 PRIORITY
946	001326	000001	RIVDU: .BLKW 1	;DU11 REC INTR VECTOR
947	001330	000001	TIVDU: .BLKW 1	;DU11 XMIT INTR VECTOR
948	001332	000001	TISDU: .BLKW 1	;DU11 XMIT INTR STATUS
949	001334	000001	RISDU: .BLKW 1	;DU11 REC INTR STATUS
950	001336	000001	L1ESS: .BLKW 1	;PRIORITY TO ALLOW INTR
951	001340	000001	CSRRX: .BLKW 1	; DEFAULT OR ALTERED PARAMETERS
952	001342	000001	CSRHRX: .BLKW 1	
953	001344	000001	BUFRXD: .BLKW 1	
954	001346	000001	BUFHRXD: .BLKW 1	
955	001350	000001	CSRPAR: .BLKW 1	
956	001352	000001	CSRHPAR: .BLKW 1	
957	001354	000001	CSRTX: .BLKW 1	
958	001356	000001	CSRHTX: .BLKW 1	
959	001360	000001	BUFTXD: .BLKW 1	
960	001362	000001	BUFHTXD: .BLKW 1	
961	001364	000001	BASEDU: .BLKW 1	;DU11 RXCSR BASE ADDR
962			.EVEN	

;DEFINITIONS FOR TRAP SUBROUTINE CALLS
 ;POINTERS TO SUBROUTINES CAN BE FOUND
 ;IN THE TABLE IMMEDIATELY FOLLOWING THE DEFINITIONS

967			.TRPTAB:	
968	001366		*****	
969			*****	
970			*****	
971		104400	SCOPE=TRAP+0	;CALL TO SCOPE LOOP AND ITERATION HANDLER
972	001366	006712	.SCOPE	
973		104401	SCOPE1=TRAP+1	;CALL TO LOOP ON CURRENT DATA HANDLER
974	001370	007076	.SCOPE1	
975		104402	TYPE=TRAP+2	;CALL TO TELETYPE OUTPUT ROUTINE
976	001372	007116	.TYPE	
977		104403	INSTR=TRAP+3	;CALL TO ASCII STRING INPUT ROUTINE
978	001374	007156	.INSTR	
979		104404	INSTER=TRAP+4	;CALL TO INPUT ERROR HANDLER
980	001376	007274	.INSTER	
981		104405	PARAM=TRAP+5	;CALL TO NUMERICAL DATA INPUT ROUTINE
982	001400	007326	.PARAM	
983		104406	SAV05=TRAP+6	;CALL TO REGISTER SAVE ROUTINE
984	001402	007542	.SAV05	
985		104407	RES05=TRAP+7	;CALL TO REGISTER RESTORE ROUTINE
986	001404	007602	.RES05	
987		104410	CONVRT=TRAP+10	;CALL TO DATA OUTPUT ROUTINE
988	001406	007634	.CONVRT	
989		104411	CNVRT=TRAP+11	;CALL TO DATA OUTPUT ROUTINE WITHOUT CR/LF
990	001410	007640	.CNVRT	
991		104412	SETFLG=TRAP+12	;CALL TO FLAG SET ROUTINE
992	001412	010060	.SETFLG	
993		104413	CKSWR=TRAP+13	;CALL TO ALLOW SWREG TO BE LOADED FROM TTY
994	001414	010574	.CKSWR	


```

995      104414
996 001416 010650
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007 001420 012767 000340 176350 .START: MOV #340,PS ;LOCK OUT INTERRUPTS
1008 001426 012706 001100 MOV #STACK,SP ;SET UP STACK
1009 001432 012737 010430 000024 MOV #,PFAIL,@#24 ;SET UP POWER FAIL VECTOR
1010 001440 005067 177460 CLR LPCNT ;CLEAR # OF ITERATION COMPLETED LOCATION
1011 001444 105067 177575 CLRB STFLG ;CLEAR START FLAG
1012 001450 005067 177454 CLR PASCNT ;CLEAR PASS COUNT
1013 001454 105067 177566 CLRB ERRFLG ;CLEAR ERROR FLAG
1014 001460 005067 177446 CLR ERRCNT ;CLEAR ERROR COUNT
1015 001464 005067 177444 CLR LSTERR ;CLEAR LAST ERROR POINTER
1016 001470 012767 000001 177430 MOV #1,TSTNO ;SET UP FOR TEST 1
1017 001476 012767 001420 177410 MOV #.START,RTRN ;SET UP FOR POWER FAIL BEFORE
1018 ;TESTING STARTS
1019 001504 105767 177534 TSTB INIFLG ;HAS INITIALIZATION BEEN PERFORMED
1020 001510 001004 BNE ONCE
1021 001512 104402 010750 TYPE ,MTITLE ;TYPE TITLE MESSAGE
1022 001516 105167 177522 COMB INIFLG ;IF NOT SET FLAG AND DO
1023 001522 012767 177570 177350 ONCE: MOV #DSWR,SWR ;RELOAD HARDWARE SWITCH REGISTER INTO POINTER
1024 001530 012767 177570 177344 MOV #DLIGHTS,LIGHTS ;RELOAD HARDWARE DISPLAY REGISTER INTO POINTER
1025 001536 013746 000006 MOV @#6,-(SP) ;SAVE VECTORS
1026 001542 013746 000004 MOV @#4,-(SP)
1027 001546 012737 001566 000004 MOV #64$,@#4 ;SET UP FOR TIMEOUT
1028 001554 022777 177777 177316 CMP #-1,@SWR ;REFERENCE HARDWARE SWITCH REGISTER
1029 001562 001402 BEQ 65$
1030 001564 000407 BR 66$
1031 001566 022626 64$: CMP (SP)+,(SP)+ ;ADJUST STACK
1032 001570 012767 000176 177302 65$: MOV #SWREG,SWR ;POINT TO SOFTWARE SWITCH REG
1033 001576 012767 000174 177276 MOV #DISPREG,LIGHTS ;POINT TO SOFT DISPLAY REG
1034 001604 012637 000004 66$: MOV (SP)+,@#4 ;RESTORE VECTORS
1035 001610 012637 000006 MOV (SP)+,@#6
1036 001614 005737 000042 TST @#42 ;UNDER MONITOR
1037 001620 001005 BNE MAP
1038 001622 022767 000176 177250 CMP #SWREG,SWR ;IS SWREG USED
1039 001630 001001 BNE MAP ; BRANCH TO CHECK FOR STATUS MAP
1040 001632 104414 CNTLU
1041 ;*****
1042 ; CODE FOR STATUS MAP
1043 ; CODE ADDED FOR REV. E OF DIAGNOSTICS
1044 ; IF SW07= 1 ,THEN YOU USE THE STATUS MAP PREVIOUSLY
1045 ; SETUP, OR REENTER QUESTIONING ROUTINE
1046
1047 001634 032777 000200 177236 MAP: BIT #SW07, @SWR ; IS SW07=1?
1048 001642 001537 BEQ $67 ; IF NOT, GO TO TEST FOR SW00=1
1049 ; NOW SET UP MAP VALUES FOR PROGRAM
1050 ; THESE VALUES FROM THE STATUS MAP WILL BE USED IN THE

```

```

1051      ; OPERATION OF THIS PROGRAM.
1052 001644 116767 177430 177324  MOVB NOSYNC ,SYNCRNO      ; SYNC CHAR
1053 001652 116767 177423 177317  MOVB MITSEX ,SEXMIT      ; XMIT JUMPER
1054 001660 116767 177416 177312  MOVB RESEC ,SEREC      ; SEC REC JUMPER
1055 001666 116767 177411 177305  MOVB CLROPT ,OPTCLR      ; OPTIONAL JUMPER
1056 001674 116767 177404 177300  MOVB DMULT ,MULTD      ; MULTIPLE DEVICE
1057 001702 116767 177377 177273  MOVB BYJMR ,JMRBY      ; EXTERNAL MODEM
1058 001710 016767 177372 177266  MOV ADDBASE ,BASEADD      ; PROG 1ST DEVICE ADDR
1059 001716 016767 177366 177262  MOV ADDKEEP ,KEEPADD      ; SAVED 1ST DEVICE ADDR
1060 001724 016767 177362 177256  MOV ADDLAST ,LASTADD      ; LAST DEVICE RXCSR ADDR
1061 001732 016767 177360 177254  MOV IVKEEP ,KEEPIV      ; SAVED INTR VECTOR
1062 001740 016767 177354 177250  MOV REGACT ,ACTREG      ; ACTIVE REGISTER
1063 001746 016767 177350 177244  MOV ADDROT ,ROTADD      ; ROTATING POINTER
1064 001754 016767 177334 177230  MOV IVBASE ,BASEIV      ; BASE INTR VECTOR
1065 001762 016767 177220 177214  MOV KEEPADD ,BASEADD      ; RELOAD BASEADD
1066 001770 016767 177332 011116  MOV RIVDU ,DURIV      ; REC INTR VECTOR
1067 001776 016767 177332 011112  MOV RISDU ,DURIS      ; REC INTR STATUS
1068 002004 016767 177320 011106  MOV TIVDU ,DUTIV      ; XMIT INTR VECTOR
1069 002012 016767 177314 011102  MOV TISDU ,DUTIS      ; XMIT INTR STATUS
1070 002020 016767 177312 010410  MOV L1ESS ,LESS1      ; PRIORITY TO ALLOW INTR
1071 002026 013737 001324 012434  MOV @#PRTDU ,@#DUPRT      ; PRIORITY RELOADED
1072 002034 016767 177324 010530  MOV BASEDU ,DUBASE
1073 002042 016767 177272 011020  MOV CSRRX ,RXCSR
1074 002050 016767 177266 011014  MOV CSRHRX ,HRXCSR
1075 002056 016767 177262 011010  MOV BUFRXD ,RXDBUF
1076 002064 016767 177256 011004  MOV BUFRXD ,HRXDBUF
1077 002072 016767 177252 011000  MOV CSRPAR ,PARCSR
1078 002100 016767 177246 010774  MOV CSRHPAR ,HPCRSR
1079 002106 016767 177242 010770  MOV CSRTX ,TXCSR
1080 002114 016767 177236 010764  MOV CSRHTX ,HTXCSR
1081 002122 016767 177232 010760  MOV BUFTXD ,TXDBUF
1082 002130 016767 177226 010754  MOV BUFTXD ,HTXDBUF
1083 002136 000167 000466  JMP .BEGIN      ; BRANCH TO BEGIN TESTING
1084 *****
1085 002142 032777 000001 176730 $67: BIT #SW00 ,@SWR      ; RESELECT VECTOR $ CONTROL REG?
1086 002150 001002  BNE 1$      ; BRANCH TO QUESTIONING
1087 002152 000167 000452  JMP .BEGIN      ; GO TO LOAD STATUS MAP ETC.
1088 002156 005037 001222 1$: CLR @#FLAG      ; CLEAR FLAG SO STATUS MAP PRINTS OUT
1089 002162 012700 000300  MOV #300,R0      ; RESTORE VECTOR AREA TO TRAPCATCHER
1090 002166 012701 000302  MOV #302,R1      ; START AT LOCATION 300
1091 002172 012702 000004  MOV #4,R2
1092 002176 010110 2$: MOV R1,(R0)
1093 002200 005011  CLR (R1)
1094 002202 060200  ADD R2,R0
1095 002204 060201  ADD R2,R1
1096 002206 022701 001000  CMP #1000,R1      ; END AT LOCATION 776
1097 002212 002771  BLT 2$
1098 002214 104403  INSTR      ; OUTPUT MESSAGE & GET INPUT STRING
1099 002216 011024  MREGAD      ; MESSAGE
1100 002220 104405  PARAM      ; CONVERT STRING
1101 002222 160000  160000      ; LOW LIMIT
1102 002224 167776  167776      ; HIGH LIMIT
1103 002226 012572  DUBASE      ; STORE AT THIS LOCATION
1104 002230 001      ; MASK
1105 002231 001      ; HOW MANY TIMES * 2
1106 002232 016767 010334 176746 .BYTE 1
      .BYTE 1
      MOV DUBASE,KEEPADD ;SAVE

```


1107	002240	004767	010174		JSR	PC,DUADDR	
1108	002244	016767	176736	176732	MOV	KEEPADD,BASEADD	;RESTORE FOR ROTATION
1109	002252	104403			INSTR		;OUTPUT MESSAGE & GET INPUT STRING
1110	002254	011002			MVECTO		;MESSAGE
1111	002256	104405			PARAM		;CONVERT STRING
1112	002260	000300			300		;LOW LIMIT
1113	002262	000776			776		;HIGH LIMIT
1114	002264	013114			DURIV		;STORE AT THIS LOCATION
1115	002266	001			1		;MASK
1116	002267	004			4		;HOW MANY TIMES + 2
1117	002270	016767	010620	176716	MOV	DURIV,KEEPIV	;SAVE
1118	002276	016767	010612	176706	MOV	DURIV,BASEIV	;SET UP FOR ROTATION
1119	002304	104403			INSTR		;OUTPUT MESSAGE & GET INPUT STRING
1120	002306	011105			MMULT		;MESSAGE
1121	002310	104412			SETFLG		;SET FLAG BASED UPON INPUT STRING
1122	002312	001202			MULTD		;THIS FLAG
1123	002314	105767	176662		TSTB	MULTD	;ARE THERE MULTIPLE DEVICES
1124							;ON THE SYSTEM ?
1125	002320	100406			BMI	BBB	;YES,ASK NEXT QUESTION
1126	002322	005067	176670		CLR	ACTREG	
1127	002326	005067	176666		CLR	ROTADD	
1128	002332	000167	000140		JMP	OUTMUL	;JUMP AROUND NEXT QUESTION
1129	002336				BBB:		
1130	002336	104403			INSTR		;OUTPUT MESSAGE & GET INPUT STRING
1131	002340	011164			MLASTD		;MESSAGE
1132	002342	104405			PARAM		;CONVERT STRING
1133	002344	160000			160000		;LOW LIMIT
1134	002346	167776			167776		;HIGH LIMIT
1135	002350	001210			LASTADD		;STORE AT THIS LOCATION
1136	002352	001			1		;MASK
1137	002353	001			1		;HOW MANY TIMES + 2
1138							;THE FOLLOWING ROUTINE SETS UP ACTREG FOR THE FIRST TIME
1139	002354	012767	000001	176636	1\$: MOV	#1,ROTADD	;SET UP POINTER
1140	002362	005067	176630		CLR	ACTREG	;CLR ACTIVE REGISTER
1141	002366	056767	176626	176622	2\$: BIS	ROTADD,ACTREG	;MAKE THIS DEVICE ACTIVE
1142	002374	000241			CLC		
1143	002376	006167	176616		ROL	ROTADD	;SET UP POINTER
1144	002402	103421			BCS	3\$	;ARE YOU OUT OF RANGE ?
1145	002404	062767	000010	176572	ADD	#10,BASEADD	;SET UP BASE ADDRESS
1146	002412	026767	176572	176564	CMP	LASTADD,BASEADD	;IS THIS THE LAST DEVICE ?
1147	002420	101362			BHI	2\$	;NO DO IT AGAIN
1148	002422	056767	176572	176566	BIS	ROTADD,ACTREG	;THIS ASSUMES THAT THERE ARE AT
1149							;LEAST TWO DEVICES WHEN YOU ANSWER YES TO
1150							;MULTIPLE DEVICE QUESTION
1151	002430	012767	000001	176562	4\$: MOV	#1,ROTADD	;SET UP FOR LATER USE IN END OF PASS ROUTINE
1152	002436	016767	176544	176540	MOV	KEEPADD,BASEADD	;DITTO
1153	002444	000414			BR	OUTMUL	;CONTINUE QUESTIONS
1154	002446	016767	176534	176530	3\$: MOV	KEEPADD,BASEADD	;RESTORE
1155	002454	104403			INSTR		;OUTPUT MESSAGE & GET INPUT STRING
1156	002456	011347			MRANGE		;MESSAGE
1157	002460	104405			PARAM		;CONVERT STRING
1158	002462	160000			160000		;LOW LIMIT
1159	002464	167776			167776		;HIGH LIMIT
1160	002466	001210			LASTADD		;STORE AT THIS LOCATION
1161	002470	001			1		;MASK
1162	002471	001			1		;HOW MANY TIMES + 2

```

1163 002472 000167 177656      JMP      1$      ;DO IT AGAIN
1164 002476      OUTMUL:
1165 002476 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1166 002500 011633      MLEVEL     ;MESSAGE
1167 002502 104405      PARAM      ;CONVERT STRING
1168 002504 000004      4          ;LOW LIMIT
1169 002506 000007      7          ;HIGH LIMIT
1170 002510 012434      DUPRT      ;STORE AT THIS LOCATION
1171 002512 000      .BYTE 0      ;MASK
1172 002513 001      .BYTE 1      ;HOW MANY TIMES + 2
1173 002514 004767 007644      JSR      PC,DULEV
1174      ;COMPARE THE FIRST CHARACTER IN THE TELETYPE INPUT
1175      ;BUFFER TO THE CHARACTERS '1' AND '2'.
1176      ;IF THE CHARACTER IS '1' CLEAR THE FLAG
1177      ;IF THE CHARACTER IS '2' SET THE FLAG
1178 002520      AAA:
1179 002520 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1180 002522 011660      MSYNC      ;MESSAGE
1181 002524 122767 000061 007472 3$: CMPB      #'1,INBUF      ;IS IT '1' ?
1182 002532 001003      BNE      1$
1183 002534 105067 176436      CLRB      SYNCNO      ;000
1184 002540 000412      BR      4$
1185 002542 122767 000062 007454 1$: CMPB      #'2,INBUF      ;IS IT '2' ?
1186 002550 001004      BNE      2$
1187 002552 112767 177777 176416      MOVB      #-1,SYNCNO      ;377
1188 002560 000402      BR      4$
1189 002562 104404      2$: INSTER      ;RETRY
1190 002564 000757      BR      3$
1191 002566 000240      4$: NOP
1192 002570 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1193 002572 011726      MWIRE6     ;MESSAGE
1194 002574 104412      SETFLG     ;SET FLAG BASED UPON INPUT STRING
1195 002576 001177      SEXMIT      ;THIS FLAG
1196 002600 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1197 002602 011774      MWIRE5     ;MESSAGE
1198 002604 104412      SETFLG     ;SET FLAG BASED UPON INPUT STRING
1199 002606 001200      SEREC      ;THIS FLAG
1200 002610 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1201 002612 012041      MWIRE4     ;MESSAGE
1202 002614 104412      SETFLG     ;SET FLAG BASED UPON INPUT STRING
1203 002616 001201      OPTCLR      ;THIS FLAG
1204 002620 104403      INSTR      ;OUTPUT MESSAGE & GET INPUT STRING
1205 002622 012115      MEXTJ      ;MESSAGE
1206 002624 104412      SETFLG     ;SET FLAG BASED UPON INPUT STRING
1207 002626 001203      JMRBY      ;THIS FLAG
1208
1209
1210      ;TEST START AND RESTART
1211
1212 002630 012767 000340 175140 .BEGIN: MOV      #340,PS      ;LOCK OUT INTERRUPTS
1213      ; ***** LOAD STATUS MAP *****
1214      ; THE VALUES NOW BEING LOADED INTO THE STATUS MAP WILL BE
1215      ; USED IN THIS PROGRAM AND WILL BE PASSED TO ANY
1216      ; OTHER DU11 PROGRAMS LOADED IMMEDIATELY FOLLOWING THIS PROG.
1217 002636 032777 000200 176234      BIT      #SW07      ,@SWR      ; SW07 SET , IF YES BRANCH
1218 002644 001132      BNE      HEREU

```


1219	002646	116767	176324	176424	MOVB SYNCNO	,NOSYNC	:SYNC CHARS
1220	002654	116767	176317	176417	MOVB SEXMIT	,MITSEX	:XMIT JUMPER
1221	002662	116767	176312	176412	MOVB SEREC	,RESEC	:SEC REC JUMPER
1222	002670	116767	176305	176405	MOVB OPTCLR	,CLROPT	:OPTIONAL JUMPER
1223	002676	116767	176300	176400	MOVB MULTD	,DMULT	: MULTIPLE DEVICES
1224	002704	116767	176273	176373	MOVB JMRBY	,BYJMR	:EXTERNAL MODEM
1225	002712	016767	176266	176366	MOV BASEADD	,ADDBASE	:PROG CONTROLLED 1ST ADDR
1226	002720	016767	176262	176362	MOV KEEPADD	,ADDKEEP	:SAVED 1ST DEVICE ADDR
1227	002726	016767	176256	176356	MOV LASTADD	,ADDLAST	:LAST DEVICE RXCSR ADDR
1228	002734	016767	176254	176354	MOV KEEPIV	,IVKEEP	:SAVED INTR VECTOR
1229	002742	016767	176244	176344	MOV BASEIV	,IVBASE	: RELOAD BASE INTR VECTOR
1230	002750	016767	176242	176342	MOV ACTREG	,REGACT	:ACTIVE REGISTER
1231	002756	016767	176236	176336	MOV ROTADD	,ADDROT	:ROTATING POINTER
1232	002764	013737	012434	001324	MOV @#DUPRT	,@#PRTDU	:DU11 PRIORITY
1233	002772	016767	010116	176326	MOV DURIV	,RIVDU	:REC INTR VECTOR
1234	003000	016767	010112	176326	MOV DURIS	,RISDU	: REC INTR STATUS
1235	003006	016767	010106	176314	MOV DUTIV	,TIVDU	: XMIT INTR VECTOR
1236	003014	016767	010102	176310	MOV DUTIS	,TISDU	: XMIT INTR STATUS
1237	003022	016767	007410	176306	MOV LESS1	,L1ESS	: PRIORITY TO ALLOW INTR
1238	003030	016767	007536	176326	MOV DUBASE	,BASEDU	:RXCSR BASE ADDRESS
1239	003036	016767	010026	176274	MOV RXCSR,	CSRRX	
1240	003044	016767	010022	176270	MOV HRXCSR,	CSRHRX	
1241	003052	016767	010016	176264	MOV RXDBUF,	BUFRXD	
1242	003060	016767	010012	176260	MOV HRXDBUF,	BUFHRXD	
1243	003066	016767	010006	176254	MOV PARCSR,	CSRPAR	
1244	003074	016767	010002	176250	MOV HPARCSR,	CSRHPAR	
1245	003102	016767	007776	176244	MOV TXCSR,	CSRTX	
1246	003110	016767	007772	176240	MOV HTXCSR,	CSRHTX	
1247	003116	016767	007766	176234	MOV TXDBUF,	BUFTXD	
1248	003124	016767	007762	176230	MOV HTXDBUF,	BUFHTXD	
1249					:*****		
1250					: THE FOLLOWING CODE WILL PRINT		
1251					: THE CONVERSATIONALLY SET JUMPER		
1252					: SETTINGS FROM THE STATUS MAP		
1253					: ON THE FIRST PASS OF		
1254					: THIS DIAGNOSTIC OR		
1255					: JUST AFTER THE QUESTIONING		
1256					: AND ANSWERING .		
1257					:*****		
1258							
1259	003132	005737	001222		HEREU:	TST @#FLAG	: TEST IF 1ST PASS
1260	003136	001402				BEQ SETFG	: IF FIRST PASS SET FLAG/PRINT
1261	003140	000167	000116			JMP THRU	: AROUND IF PASS > 1
1262	003144	104402	012172		SETFG:	TYPE ,MSTATUS	: PRINT 'STATUS MAP'
1263	003150	062737	000001	001222		ADD #1, @#FLAG	: SET FLAG ON 1ST PASS
1264	003156	010067	176042			MOV R0, HOLD0	: SAVE R0
1265	003162	010167	176040			MOV R1, HOLD1	: SAVE R1
1266	003166	012767	000003	176034		MOV #3, COUNT1	:COUNTER FOR WORDS PRINTED
1267	003174	012700	000002			MOV #BUFF1, R0	
1268	003200	012701	001300			MOV #STATUS, R1	: (BUFF1)=STATUS ETC.
1269	003204	010120			FILBUF:	MOV R1, (R0)+	: LOAD BUFF AS ABOVE
1270	003206	062701	000002			ADD #2, R1	: PREPARE STATUS ADDRESS
1271	003212	020127	001306			CMP R1, #STATUS+6	: CHECK IF 3 WORDS LOADED
1272	003216	001372				BNE FILBUF	: BACK TO LOAD NEXT ADDRESS
1273	003220	012700	000002			MOV #BUFF1, R0	: LOAD FOR PRINT OUT
1274	003224	010067	176006		UP:	MOV R0, TABLE+4	:LOAD ADDRESS TO PRINT

Address	Hex	Label	Op	Op2	Op3	Op4	Op5	Op6	Op7	Op8	Op9	Op10	Op11	Op12	Op13	Op14	Op15	Op16	Op17	Op18	Op19	Op20	Op21	Op22	Op23	Op24	Op25	Op26	Op27	Op28	Op29	Op30	Op31	Op32	Op33	Op34	Op35	Op36	Op37	Op38	Op39	Op40	Op41	Op42	Op43	Op44	Op45	Op46	Op47	Op48	Op49	Op50	Op51	Op52	Op53	Op54	Op55	Op56	Op57	Op58	Op59	Op60	Op61	Op62	Op63	Op64	Op65	Op66	Op67	Op68	Op69	Op70	Op71	Op72	Op73	Op74	Op75	Op76	Op77	Op78	Op79	Op80	Op81	Op82	Op83	Op84	Op85	Op86	Op87	Op88	Op89	Op90	Op91	Op92	Op93	Op94	Op95	Op96	Op97	Op98	Op99	Op100	Op101	Op102	Op103	Op104	Op105	Op106	Op107	Op108	Op109	Op110	Op111	Op112	Op113	Op114	Op115	Op116	Op117	Op118	Op119	Op120	Op121	Op122	Op123	Op124	Op125	Op126	Op127	Op128	Op129	Op130	Op131	Op132	Op133	Op134	Op135	Op136	Op137	Op138	Op139	Op140	Op141	Op142	Op143	Op144	Op145	Op146	Op147	Op148	Op149	Op150	Op151	Op152	Op153	Op154	Op155	Op156	Op157	Op158	Op159	Op160	Op161	Op162	Op163	Op164	Op165	Op166	Op167	Op168	Op169	Op170	Op171	Op172	Op173	Op174	Op175	Op176	Op177	Op178	Op179	Op180	Op181	Op182	Op183	Op184	Op185	Op186	Op187	Op188	Op189	Op190	Op191	Op192	Op193	Op194	Op195	Op196	Op197	Op198	Op199	Op200	Op201	Op202	Op203	Op204	Op205	Op206	Op207	Op208	Op209	Op210	Op211	Op212	Op213	Op214	Op215	Op216	Op217	Op218	Op219	Op220	Op221	Op222	Op223	Op224	Op225	Op226	Op227	Op228	Op229	Op230	Op231	Op232	Op233	Op234	Op235	Op236	Op237	Op238	Op239	Op240	Op241	Op242	Op243	Op244	Op245	Op246	Op247	Op248	Op249	Op250	Op251	Op252	Op253	Op254	Op255	Op256	Op257	Op258	Op259	Op260	Op261	Op262	Op263	Op264	Op265	Op266	Op267	Op268	Op269	Op270	Op271	Op272	Op273	Op274	Op275	Op276	Op277	Op278	Op279	Op280	Op281	Op282	Op283	Op284	Op285	Op286	Op287	Op288	Op289	Op290	Op291	Op292	Op293	Op294	Op295	Op296	Op297	Op298	Op299	Op300	Op301	Op302	Op303	Op304	Op305	Op306	Op307	Op308	Op309	Op310	Op311	Op312	Op313	Op314	Op315	Op316	Op317	Op318	Op319	Op320	Op321	Op322	Op323	Op324	Op325	Op326	Op327	Op328	Op329	Op330	Op331	Op332	Op333	Op334	Op335	Op336	Op337	Op338	Op339	Op340	Op341	Op342	Op343	Op344	Op345	Op346	Op347	Op348	Op349	Op350	Op351	Op352	Op353	Op354	Op355	Op356	Op357	Op358	Op359	Op360	Op361	Op362	Op363	Op364	Op365	Op366	Op367	Op368	Op369	Op370	Op371	Op372	Op373	Op374	Op375	Op376	Op377	Op378	Op379	Op380	Op381	Op382	Op383	Op384	Op385	Op386	Op387	Op388	Op389	Op390	Op391	Op392	Op393	Op394	Op395	Op396	Op397	Op398	Op399	Op400	Op401	Op402	Op403	Op404	Op405	Op406	Op407	Op408	Op409	Op410	Op411	Op412	Op413	Op414	Op415	Op416	Op417	
---------	-----	-------	----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--


```

1321                                     ::THIS TEST VERIFYS MATCH DETECT & DATA RDY
1322                                     ::FLAGS FOR EVERY POSSIBLE MATCH CHARACTER
1323                                     ::BY OBSERVING RECACT BIT
1324                                     ::IT WILL TAKE TWO SYNC * CHARACTERS TO GET RECACT BIT
1325                                     ::* DEPENDENT ON MONITOR .....
1326                                     ::IF ONE SYNC STRAP IS SELECTED, IT WILL
1327                                     ::ONLY TAKE ONE SYNC CHARACTER BEFORE RECACT TO
1328                                     ::ASSERT
1329                                     ::MODE: SYNC INTERNAL
1330                                     ::LENGTH: FIVE
1331                                     ::SYNC CHARACTER FOR MATCH: B/C
1332                                     ::THIS TEST USES THE TRANSMITTER AND RECEIVER CHIPS
1333
1334 003446 012767 000001 175452 TST1: MOV #1,TSTNO ;SAVE THIS
1335 003454 012767 003774 175434 MOV #TST2,NEXT ;GO TO THIS TEST WHEN THRU
1336 003462 012767 003576 175430 MOV #3$,LOCK ;SET UP FOR SCOPE LOOP
1337 003470 052777 000400 007406 BIS #MRESET,@TXCSR ;MASTER RESET
1338 003476 016703 007372 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1339 ;SET SYNC INTERNAL,FIVE,NO PARITY,0 SYNC REGISTER
1340 003502 012704 030000 MOV #SYNINT!FIVE!NOPAR,R4 ;CREATE PARAMETERS
1341 003506 012777 004020 007370 1$: MOV #MINT!SEND,@TXCSR ;SET SEND & MAINT INTER
1342 003514 010477 007360 MOV R4,@PARCSR ;LOAD CSR
1343 003520 052777 000020 007342 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1344 ;POKE CLK TO GET INTO SYNCHRONIZATION
1345 ;BOTH THE LOGIC & RECEIVER
1346 003526 052777 020000 007350 BIS #CLK,@TXCSR ;POKE CLK UP
1347 003534 042777 020000 007342 BIC #CLK,@TXCSR ;POKE CLK DOWN
1348 003542 110477 007342 MOV R4,@TXDBUF ;LOAD DATA CHARACTER
1349 ;POKE CLK TO GET TRANSMITTER & RECEIVER INTO SYNCHRONIZATION
1350 003546 052777 020000 007330 BIS #CLK,@TXCSR ;POKE CLK UP
1351 003554 042777 020000 007322 BIC #CLK,@TXCSR ;POKE CLK DOWN
1352 003562 032777 004000 007300 BIT #RECACT,@RXCSR ;RECACT ?
1353 003570 001401 BEQ 2$
1354 003572 104000 HLT ;RECACT SHOULD NOT BE SET
1355 003574 2$: BR 4$
1356 003574 000404 3$: MOV R4,@PARCSR ;LOAD PARCSR WITH PARAMETERS
1357 003576 010477 007276 MOV R4,@TXDBUF ;LOAD SYNC CHAR
1358 003602 110477 007302 MOV #2,COUNT ;# OF SYNC CHARS
1359 003606 012767 000002 175326 4$: TST @TXCSR ;DNA ?
1360 003614 005777 007264 5$: BPL 6$ ;BR IF NOT SET
1361 003620 100001 HLT ;DNA SHOULD NOT BE SET OR....
1362 003622 104000 6$:
1363 003624 ;IT SHOULD BE CLEARED FROM PREVIOUS READ
1364 MOV #5,SHIFT ;# OF SHIFTS
1365 003624 012767 000005 175306 7$: BIS #CLK,@TXCSR ;POKE CLK UP
1366 003632 BIC #CLK,@TXCSR ;POKE CLK DOWN
1367 003632 052777 020000 007244 DEC SHIFT ;# OF SHIFTS
1368 003640 042777 020000 007236 BNE 7$
1369 003646 005367 175266 DEC COUNT ;# OF SYNC CHARS
1370 003652 001367 BNE 7$
1371 003654 005367 175262 DEC COUNT ;# OF SYNC CHARS
1372 003660 001403 BEQ 8$
1373 ;TEST SYNCNO TO SEE HOW MANY SYNC CHARACTERS NEEDED
1374 003662 105767 175310 TSTB SYNCNO
1375 003666 100752 BMI 5$ ;TWO SYNC CHARACTERS..
1376 003670 032777 004000 007172 8$: BIT #RECACT,@RXCSR ;RECACT ?

```

1377	003676	001001			BNE	9\$	
1378	003700	104000			HLT		;RECACT FAILED TO SET,POSSIBLE
1379	003702			9\$:			
1380							;THAT THE RECEIVER FAILED TO MATCH
1381							;THE SYNC CHARACTER
1382	003702	017701	007166		MOV	@RXDBUF,R1	;SAVE ACTUAL
1383	003706	010400			MOV	R4,R0	;SAVE EXPECTED
1384	003710	042700	177400		BIC	#177400,R0	;CLR UPPER BYTE
1385	003714	020001			CMP	R0,R1	;DO THEY COMPARE ?
1386	003716	001401			BEQ	10\$	
1387	003720	104002			HLT	2	;IF RECACT FAILED ALONG WITH THIS
1388	003722			10\$:			
1389							;....IT PROBABLY IS A TRANSMITTER ERROR
1390							;HOWEVER,...IF ONLY THIS FAILED IT
1391							;PROBABLY IS A RECEIVER ERROR
1392	003722	104401					
1393					SCOPE1		
1394					;POKE CLK TO SEE DNA...DNA COMES UP ON THE FIRST		
1395					;BIT OF THE NEXT CHARACTER IF NO CHARACTER IS LOADED INTO		
1396	003724	052777	020000	007152	;TXDBUF		
1397	003732	005777	007146		BIS	#CLK,@TXCSR	;POKE CLK UP
1398	003736	100401			TST	@TXCSR	;DNA?
1399	003740	104000			BMI	11\$	
1400	003742				HLT		;DNA DID NOT ASSERT
1401				11\$:			
1402	003742	052777	000400	007134			;SET UP CONDITIONS FOR NEXT SYNC CHARACTER MATCH
1403	003750	032777	000020	007112	BIS	#MRESET,@TXCSR	;MASTER RESET
1404	003756	001401			BIT	#SYNSCH,@RXCSR	;SYNC SEARCH = 0 ?
1405	003760	104000			BEQ	12\$	
1406	003762				HLT		;SYNC SEARCH SHOULD BE NOT SET
1407	003762	005204					
1408	003764	122704	000040		12\$:		
1409	003770	001246			INC	R4	
1410	003772	104400			CMPB	#40,R4	;IS THIS THE LAST CHARACTER ?
					BNE	1\$	;NO
					SCOPE		


```

1411                                     ::THIS TEST VERIFYS MATCH DETECT & DATA RDY
1412                                     ::FLAGS FOR EVERY POSSIBLE MATCH CHARACTER
1413                                     ::BY OBSERVING RECACT BIT
1414                                     ::IT WILL TAKE TWO SYNC * CHARACTERS TO GET RECACT BIT
1415                                     ::* DEPENDENT ON MONITOR .....
1416                                     ::IF ONE SYNC STRAP IS SELECTED, IT WILL
1417                                     ::ONLY TAKE ONE SYNC CHARACTER BEFORE RECACT TO
1418                                     ::ASSERT
1419                                     ::MODE: SYNC INTERNAL
1420                                     ::LENGTH: SIX
1421                                     ::SYNC CHARACTER FOR MATCH: B/C
1422                                     ::THIS TEST USES THE TRANSMITTER AND RECEIVER CHIPS
1423
1424 003774 012767 000002 175124 TST2: MOV #2,TSTNO ;SAVE THIS
1425 004002 012767 004322 175106 MOV #TST3,NEXT ;GO TO THIS TEST WHEN THRU
1426 004010 012767 004124 175102 MOV #3$,LOCK ;SET UP FOR SCOPE LOOP
1427 004016 052777 000400 007060 BIS #MRESET,@TXCSR ;MASTER RESET
1428 004024 016703 007044 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1429                                     ;SET SYNC INTERNAL,SIX,NO PARITY,0 SYNC REGISTER
1430 004030 012704 032000 MOV #SYNINT!SIX!NOPAR,R4 ;CREATE PARAMETERS
1431 004034 012777 004020 007042 1$: MOV #MINT!SEND,@TXCSR ;SET SEND & MAINT INTER
1432 004042 010477 007032 MOV R4,@PARCSR ;LOAD CSR
1433 004046 052777 000020 007014 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1434                                     ;POKE CLK TO GET INTO SYNCHRONIZATION
1435                                     ;BOTH THE LOGIC & RECEIVER
1436 004054 052777 020000 007022 BIS #CLK,@TXCSR ;POKE CLK UP
1437 004062 042777 020000 007014 BIC #CLK,@TXCSR ;POKE CLK DOWN
1438 004070 110477 007014 MOV R4,@TXDBUF ;LOAD DATA CHARACTER
1439                                     ;POKE CLK TO GET TRANSMITTER & RECEIVER INTO SYNCHRONIZATION
1440 004074 052777 020000 007002 BIS #CLK,@TXCSR ;POKE CLK UP
1441 004102 042777 020000 006774 BIC #CLK,@TXCSR ;POKE CLK DOWN
1442 004110 032777 004000 006752 BIT #RECACT,@RXCSR ;RECACT ?
1443 004116 001401 BEQ 2$
1444 004120 104000 HLT ;RECACT SHOULD NOT BE SET
1445 004122 2$: BR 4$
1446 004122 000404 BR 4$
1447 004124 010477 006750 3$: MOV R4,@PARCSR ;LOAD PARCSR WITH PARAMETERS
1448 004130 110477 006754 MOV R4,@TXDBUF ;LOAD SYNC CHAR
1449 004134 012767 000002 175000 4$: MOV #2,COUNT ;# OF SYNC CHARS
1450 004142 005777 006736 5$: TST @TXCSR ;DNA ?
1451 004146 100001 BPL 6$ ;BR IF NOT SET
1452 004150 104000 HLT ;DNA SHOULD NOT BE SET OR....
1453 004152 6$:
1454                                     ;IT SHOULD BE CLEARED FROM PREVIOUS READ
1455 004152 012767 000006 174760 MOV #6,SHIFT ;# OF SHIFTS
1456 004160 7$: BIS #CLK,@TXCSR ;POKE CLK UP
1457 004160 052777 020000 006716 BIC #CLK,@TXCSR ;POKE CLK DOWN
1458 004166 042777 020000 006710 DEC SHIFT ;# OF SHIFTS
1459 004174 005367 174740 BNE 7$
1460 004200 001367 DEC COUNT ;# OF SYNC CHARS
1461 004202 005367 174734 BEQ 8$
1462 004206 001403 ;TEST SYNCNO TO SEE HOW MANY SYNC CHARACTERS NEEDED
1463 TSTB SYNCNO
1464 004210 105767 174762 BMI 5$ ;TWO SYNC CHARACTERS..
1465 004214 100752 8$: BIT #RECACT,@RXCSR ;RECACT ?
1466 004216 032777 004000 006644

```

1467	004224	001001			BNE	9\$	
1468	004226	104000			HLT		;RECACT FAILED TO SET,POSSIBLE
1469	004230			9\$:			
1470							;THAT THE RECEIVER FAILED TO MATCH
1471							;THE SYNC CHARACTER
1472	004230	017701	006640		MOV	@RXDBUF,R1	;SAVE ACTUAL
1473	004234	010400			MOV	R4,R0	;SAVE EXPECTED
1474	004236	042700	177400		BIC	#177400,R0	;CLR UPPER BYTE
1475	004242	020001			CMP	R0,R1	;DO THEY COMPARE ?
1476	004244	001401			BEQ	10\$	
1477	004246	104002			HLT	2	;IF RECACT FAILED ALONG WITH THIS
1478	004250			10\$:			
1479							;...IT PROBABLY IS A TRANSMITTER ERROR
1480							;HOWEVER,...IF ONLY THIS FAILED IT
1481							;PROBABLY IS A RECEIVER ERROR
1482	004250	104401					
1483					SCOPE1		
1484					;POKE CLK TO SEE DNA...DNA COMES UP ON THE FIRST		
1485					;BIT OF THE NEXT CHARACTER IF NO CHARACTER IS LOADED INTO		
1486	004252	052777	020000	006624	;TXDBUF		
1487	004260	005777	006620		BIS	#CLK,@TXCSR	;POKE CLK UP
1488	004264	100401			TST	@TXCSR	;DNA?
1489	004266	104000			BMI	11\$	
1490	004270				HLT		;DNA DID NOT ASSERT
1491				11\$:			
1492	004270	052777	000400	006606	;SET UP	CONDITIONS FOR NEXT SYNC CHARACTER MATCH	
1493	004276	032777	000020	006564	BIS	#MRESET,@TXCSR	;MASTER RESET
1494	004304	001401			BIT	#SYNSCH,@RXCSR	;SYNC SEARCH = 0 ?
1495	004306	104000			BEQ	12\$	
1496	004310				HLT		;SYNC SEARCH SHOULD BE NOT SET
1497	004310	005204					
1498	004312	122704	000100		12\$:		
1499	004316	001246			INC	R4	
1500	004320	104400			CMPB	#100,R4	;IS THIS THE LAST CHARACTER ?
					BNE	1\$	;NO
					SCOPE		


```

1501      ::THIS TEST VERIFYS MATCH DETECT & DATA RDY
1502      ::FLAGS FOR EVERY POSSIBLE MATCH CHARACTER
1503      ::BY OBSERVING RECACT BIT
1504      ::IT WILL TAKE TWO SYNC * CHARACTERS TO GET RECACT BIT
1505      ::* DEPENDENT ON MONITOR
1506      ::IF ONE SYNC STRAP IS SELECTED ,IT WILL
1507      ::ONLY TAKE ONE SYNC CHARACTER BEFORE RECACT TO
1508      ::ASSERT
1509      ::MODE: SYNC INTERNAL
1510      ::LENGTH: SEVEN
1511      ::SYNC CHARACTER FOR MATCH: B/C
1512      ::THIS TEST USES THE TRANSMITTER AND RECEIVER CHIPS
1513
1514 004322 012767 000003 174576 TST3: MOV #3,TSTNO ;SAVE THIS
1515 004330 012767 004650 174560 MOV #TST4,NEXT ;GO TO THIS TEST WHEN THRU
1516 004336 012767 004452 174554 MOV #3$,LOCK ;SET UP FOR SCOPE LOOP
1517 004344 052777 000400 006532 BIS #MRESET,@TXCSR ;MASTER RESET
1518 004352 016703 006516 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1519      ;SET SYNC INTERNAL,SEVEN,NO PARITY,0 SYNC REGISTER
1520 004356 012704 034000 MOV #SYNINT!SEVEN!NOPAR,R4 ;CREATE PARAMETERS
1521 004362 012777 004020 006514 1$: MOV #MINT!SEND,@TXCSR ;SET SEND & MAINT INTER
1522 004370 010477 006504 MOV R4,@PARCSR ;LOAD CSR
1523 004374 052777 000020 006466 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1524      ;POKE CLK TO GET INTO SYNCHRONIZATION
1525      ;BOTH THE LOGIC & RECEIVER
1526 004402 052777 020000 006474 BIS #CLK,@TXCSR ;POKE CLK UP
1527 004410 042777 020000 006466 BIC #CLK,@TXCSR ;POKE CLK DOWN
1528 004416 110477 006466 MOV R4,@TXDBUF ;LOAD DATA CHARACTER
1529      ;POKE CLK TO GET TRANSMITTER & RECEIVER INTO SYNCHRONIZATION
1530 004422 052777 020000 006454 BIS #CLK,@TXCSR ;POKE CLK UP
1531 004430 042777 020000 006446 BIC #CLK,@TXCSR ;POKE CLK DOWN
1532 004436 032777 004000 006424 BIT #RECACT,@RXCSR ;RECACT ?
1533 004444 001401 BEQ 2$
1534 004446 104000 HLT ;RECACT SHOULD NOT BE SET
1535 004450 2$:
1536 004450 000404 BR 4$
1537 004452 010477 006422 3$: MOV R4,@PARCSR ;LOAD PARCSR WITH PARAMETERS
1538 004456 110477 006426 MOV R4,@TXDBUF ;LOAD SYNC CHAR
1539 004462 012767 000002 174452 4$: MOV #2,COUNT ;# OF SYNC CHARS
1540 004470 005777 006410 5$: TST @TXCSR ;DNA ?
1541 004474 100001 BPL 6$ ;BR IF NOT SET
1542 004476 104000 HLT ;DNA SHOULD NOT BE SET OR....
1543 004500 6$:
1544      ;IT SHOULD BE CLEARED FROM PREVIOUS READ
1545 004500 012767 000007 174432 MOV #7,SHIFT ;# OF SHIFTS
1546 004506 7$:
1547 004506 052777 020000 006370 BIS #CLK,@TXCSR ;POKE CLK UP
1548 004514 042777 020000 006362 BIC #CLK,@TXCSR ;POKE CLK DOWN
1549 004522 005367 174412 DEC SHIFT ;# OF SHIFTS
1550 004526 001367 BNE 7$
1551 004530 005367 174406 DEC COUNT ;# OF SYNC CHARS
1552 004534 001403 BEQ 8$
1553      ;TEST SYNCNO TO SEE HOW MANY SYNC CHARACTERS NEEDED
1554 004536 105767 174434 TSTB SYNCNO
1555 004542 100752 BMI 5$ ;TWO SYNC CHARACTERS..
1556 004544 032777 004000 006316 8$: BIT #RECACT,@RXCSR ;RECACT ?

```

1557	004552	001001			BNE	9\$	
1558	004554	104000			HLT		;REACT FAILED TO SET,POSSIBLE
1559	004556					9\$:	
1560							;THAT THE RECEIVER FAILED TO MATCH
1561							;THE SYNC CHARACTER
1562	004556	017701	006312		MOV	@RXDBUF,R1	;SAVE ACTUAL
1563	004562	010400			MOV	R4,R0	;SAVE EXPECTED
1564	004564	042700	177400		BIC	#177400,R0	;CLR UPPER BYTE
1565	004570	020001			CMP	R0,R1	;DO THEY COMPARE ?
1566	004572	001401			BEQ	10\$	
1567	004574	104002			HLT	2	;IF REACT FAILED ALONG WITH THIS
1568	004576					10\$:	
1569							;...IT PROBABLY IS A TRANSMITTER ERROR
1570							;HOWEVER,...IF ONLY THIS FAILED IT
1571							;PROBABLY IS A RECEIVER ERROR
1572	004576	104401					
1573						SCOPE	
1574							;POKE CLK TO SEE DNA...DNA COMES UP ON THE FIRST
1575							;BIT OF THE NEXT CHARACTER IF NO CHARACTER IS LOADED INTO
1576	004600	052777	020000	006276			;TXDBUF
1577	004606	005777	006272		BIS	#CLK,@TXCSR	;POKE CLK UP
1578	004612	100401			TST	@TXCSR	;DNA?
1579	004614	104000			BMI	11\$	
1580	004616				HLT		;DNA DID NOT ASSERT
1581						11\$:	
1582	004616	052777	000400	006260			;SET UP CONDITIONS FOR NEXT SYNC CHARACTER MATCH
1583	004624	032777	000020	006236	BIS	#MRESET,@TXCSR	;MASTER RESET
1584	004632	001401			BIT	#SYNSCH,@RXCSR	;SYNC SEARCH = 0 ?
1585	004634	104000			BEQ	12\$	
1586	004636				HLT		;SYNC SEARCH SHOULD BE NOT SET
1587	004636	005204				12\$:	
1588	004640	122704	000200		INC	R4	
1589	004644	001246			CMPB	#200,R4	;IS THIS THE LAST CHARACTER ?
1590	004646	104400			BNE	1\$	;NO
					SCOPE		


```

1591                                     ::THIS TEST VERIFYS MATCH DETECT & DATA RDY
1592                                     ::FLAGS FOR EVERY POSSIBLE MATCH CHARACTER
1593                                     ::BY OBSERVING RECACT BIT
1594                                     ::IT WILL TAKE TWO SYNC * CHARACTERS TO GET RECACT BIT
1595                                     ::* DEPENDENT ON MONITOR .....
1596                                     ::IF ONE SYNC STRAP IS SELECTED, IT WILL
1597                                     ::ONLY TAKE ONE SYNC CHARACTER BEFORE RECACT TO
1598                                     ::ASSERT
1599                                     ::MODE: SYNC INTERNAL
1600                                     ::LENGTH: EIGHT
1601                                     ::SYNC CHARACTER FOR MATCH: B/C
1602                                     ::THIS TEST USES THE TRANSMITTER AND RECEIVER CHIPS
1603
1604 004650 012767 000004 174250 TST4: MOV #4,TSTNO ;SAVE THIS
1605 004656 012767 005176 174232 MOV #TST5,NEXT ;GO TO THIS TEST WHEN THRU
1606 004664 012767 005000 174226 MOV #3$,LOCK ;SET UP FOR SCOPE LOOP
1607 004672 052777 000400 006204 BIS #MRESET,@TXCSR ;MASTER RESET
1608 004700 016703 006170 MOV RXDBUF,R3 ;SET UP FOR ERROR MESSAGE
1609 ;SET SYNC INTERNAL,EIGHT,NO PARITY,0 SYNC REGISTER
1610 004704 012704 036000 MOV #SYNINT!EIGHT!NOPAR,R4 ;CREATE PARAMETERS
1611 004710 012777 004020 006166 1$: MOV #MINT!SEND,@TXCSR ;SET SEND & MAINT INTER
1612 004716 010477 006156 MOV R4,@PARCSR ;LOAD CSR
1613 004722 052777 000020 006140 BIS #SYNSCH,@RXCSR ;SET SYNC SEARCH
1614 ;POKE CLK TO GET INTO SYNCHRONIZATION
1615 ;BOTH THE LOGIC & RECEIVER
1616 004730 052777 020000 006146 BIS #CLK,@TXCSR ;POKE CLK UP
1617 004736 042777 020000 006140 BIC #CLK,@TXCSR ;POKE CLK DOWN
1618 004744 110477 006140 MOV R4,@TXDBUF ;LOAD DATA CHARACTER
1619 ;POKE CLK TO GET TRANSMITTER & RECEIVER INTO SYNCHRONIZATION
1620 004750 052777 020000 006126 BIS #CLK,@TXCSR ;POKE CLK UP
1621 004756 042777 020000 006120 BIC #CLK,@TXCSR ;POKE CLK DOWN
1622 004764 032777 004000 006076 BIT #RECACT,@RXCSR ;RECACT ?
1623 004772 001401 BEQ 2$
1624 004774 104000 HLT ;RECACT SHOULD NOT BE SET
1625 004776 2$:
1626 004776 000404 BR 4$
1627 005000 010477 006074 3$: MOV R4,@PARCSR ;LOAD PARCSR WITH PARAMETERS
1628 005004 110477 006100 MOV R4,@TXDBUF ;LOAD SYNC CHAR
1629 005010 012767 000002 174124 4$: MOV #2,COUNT ;# OF SYNC CHARS
1630 005016 005777 006062 5$: TST @TXCSR ;DNA ?
1631 005022 100001 BPL 6$ ;BR IF NOT SET
1632 005024 104000 HLT ;DNA SHOULD NOT BE SET OR....
1633 005026 6$:
1634 ;IT SHOULD BE CLEARED FROM PREVIOUS READ
1635 005026 012767 000010 174104 7$: MOV #8,,SHIFT ;# OF SHIFTS
1636 005034
1637 005034 052777 020000 006042 BIS #CLK,@TXCSR ;POKE CLK UP
1638 005042 042777 020000 006034 BIC #CLK,@TXCSR ;POKE CLK DOWN
1639 005050 005367 174064 DEC SHIFT ;# OF SHIFTS
1640 005054 001367 BNE 7$
1641 005056 005367 174060 DEC COUNT ;# OF SYNC CHARS
1642 005062 001403 BEQ 8$
1643 ;TEST SYNCNO TO SEE HOW MANY SYNC CHARACTERS NEEDED
1644 005064 105767 174106 TSTB SYNCNO
1645 005070 100752 BMI 5$ ;TWO SYNC CHARACTERS..
1646 005072 032777 004000 005770 8$: BIT #RECACT,@RXCSR ;RECACT ?

```

1647	005100	001001			BNE	9\$	
1648	005102	104000			HLT		;REACT FAILED TO SET,POSSIBLE
1649	005104			9\$:			
1650							;THAT THE RECEIVER FAILED TO MATCH
1651							;THE SYNC CHARACTER
1652	005104	017701	005764		MOV	@RXDBUF,R1	;SAVE ACTUAL
1653	005110	010400			MOV	R4,R0	;SAVE EXPECTED
1654	005112	042700	177400		BIC	#177400,R0	;CLR UPPER BYTE
1655	005116	020001			CMP	R0,R1	;DO THEY COMPARE ?
1656	005120	001401			BEQ	10\$	
1657	005122	104002			HLT	2	;IF REACT FAILED ALONG WITH THIS
1658	005124			10\$:			
1659							;...IT PROBABLY IS A TRANSMITTER ERROR
1660							;HOWEVER,...IF ONLY THIS FAILED IT
1661							;PROBABLY IS A RECEIVER ERROR
1662	005124	104401					
1663					SCOPE1		
1664							;POKE CLK TO SEE DNA...DNA COMES UP ON THE FIRST
1665							;BIT OF THE NEXT CHARACTER IF NO CHARACTER IS LOADED INTO
1666	005126	052777	020000	005750			
1667	005134	005777	005744		BIS	#CLK,@TXCSR	;POKE CLK UP
1668	005140	100401			TST	@TXCSR	;DNA?
1669	005142	104000			BMI	11\$	
1670	005144				HLT		;DNA DID NOT ASSERT
1671				11\$:			
1672	005144	052777	000400	005732			;SET UP CONDITIONS FOR NEXT SYNC CHARACTER MATCH
1673	005152	032777	000020	005710	BIS	#MRESET,@TXCSR	;MASTER RESET
1674	005160	001401			BIT	#SYNSCH,@RXCSR	;SYNC SEARCH = 0 ?
1675	005162	104000			BEQ	12\$	
1676	005164				HLT		;SYNC SEARCH SHOULD BE NOT SET
1677	005164	005204					
1678	005166	122704	000000		INC	R4	
1679	005172	001246			CMPB	#0,R4	;IS THIS THE LAST CHARACTER ?
1680	005174	104400			BNE	1\$	;NO
					SCOPE		


```

1681                                     ::THIS TEST PERFORMS A BINARY COUNT DATA PATTERN ON
1682                                     ::BOTH THE TRANSMITTER AND RECEIVER LOGIC
1683                                     ::MODE:SYNC EXTERNAL (SYNEXT)
1684                                     ::LENGTH:EIGHT PLUS PARITY
1685                                     ::PARITY:EVEPAR
1686                                     ::MAINT. MODE:MINT
1687
1688 005176 012767 000005 173722 TST5: MOV #5,TSTNO ;SAVE THIS
1689 005204 012767 005410 173704 MOV #TST6,NEXT ;GO TO THIS TEST WHEN THRU
1690 005212 052777 000400 005664 BIS #MRESET,@TXCSR ;MASTER RESET
1691 005220 012777 020000 005652 MOV #SYNEXT,@PARCSR ;SET THE MODE
1692 005226 052777 000400 005650 BIS #MRESET,@TXCSR ;MASTER RESET
1693
1694 ;SET MAINTENANCE MODE & SEND
1695 ;NOTE:BIT WINDOW&CLK ARE CLEARED (MTDATA=0)
1696 005234 012777 004020 005642 MOV #MINT!SEND,@TXCSR
1697
1698 ;SET MODE,# OF BITS,PARITY SENSE,& LOAD SYNC REG
1699 005242 012777 027426 005630 MOV #SYNEXT!EIGHT!EVEPAR!26,@PARCSR
1700 005250 016703 005620 MOV RXDBUF,R3 ;SETUP FOR ERROR MSG
1701 005254 005004 CLR R4 ;FOR DATA CHAR CREATION
1702 005256 110477 005626 MOV R4,@TXDBUF ;LOAD CHARACTER
1703 005262 052777 000020 005600 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
1704
1705 ;GET INTO SYNCHRONIZATION
1706 005270 052777 020000 005606 BIS #CLK,@TXCSR ;POKE CLK UP
1707 005276 042777 020000 005600 BIC #CLK,@TXCSR ;POKE CLK DOWN
1708 005304 012767 000011 173626 1$: MOV #9,SHIFT ;# OF SHIFTS
1709 005312 010400 MOV R4,R0 ;EXPECTED
1710 005314 052777 020000 005562 2$: BIS #CLK,@TXCSR ;POKE CLK UP
1711 005322 042777 020000 005554 BIC #CLK,@TXCSR ;POKE CLK DOWN
1712 005330 005367 173604 DEC SHIFT ;# OF SHIFTS
1713 005334 022767 000003 173576 CMP #3,SHIFT ;TIME TO LOAD NEXT CHAR ?
1714 005342 001003 BNE 3$ ;NO ?
1715 005344 005204 INC R4 ;GENERATE NEXT CHAR
1716 005346 110477 005536 MOV R4,@TXDBUF ;LOAD NEXT CHARACTER
1717 005352 005767 173562 3$: TST SHIFT ;IS IT 0 ?
1718 005356 001356 BNE 2$
1719 005360 105777 005504 TSTB @RXCSR ;RXDONE = 1 ?
1720 005364 100401 BMI 5$
1721 005366 104000 HLT ;RXDONE SHOULD BE SET
1722 005370
1723 005370 017701 005500 5$: MOV @RXDBUF,R1 ;ACTUAL
1724 005374 020001 CMP R0,R1 ;COMPARE EXP VS ACT
1725 005376 001401 BEQ 6$
1726 005400 104002 HLT 2 ;CHARACTERS SHOULD COMPARE
1727 005402
1728 005402 105704 6$: TSTB R4 ;LAST CHARACTER ?
1729 005404 001337 BNE 1$ ;NO
1730 005406 104400 4$: SCOPE

```

```

1731                                     ::THIS TEST PERFORMS A BINARY COUNT DATA PATTERN ON
1732                                     ::BOTH THE TRANSMITTER AND RECEIVER LOGIC
1733                                     ::MODE:SYNC EXTERNAL (SYNEXT)
1734                                     ::LENGTH:EIGHT PLUS PARITY
1735                                     ::PARITY:ODDPAR
1736                                     ::MAINT. MODE:MINT
1737                                     ::
1738 005410 012767 000006 173510 TST6: MOV #6,TSTNO ;SAVE THIS
1739 005416 012767 005622 173472      MOV #TST7,NEXT ;GO TO THIS TEST WHEN THRU
1740 005424 052777 000400 005452      BIS #MRESET,@TXCSR ;MASTER RESET
1741 005432 012777 020000 005440      MOV #SYNEXT,@PARCSR ;SET THE MODE
1742 005440 052777 000400 005436      BIS #MRESET,@TXCSR ;MASTER RESET
1743
1744                                     ;SET MAINTENANCE MODE & SEND
1745                                     ;NOTE:BIT WINDOW&CLK ARE CLEARED (MTDATA=0)
1746 005446 012777 004020 005430      MOV #MINT!SEND,@TXCSR
1747
1748                                     ;SET MODE,# OF BITS,PARITY SENSE,& LOAD SYNC REG
1749 005454 012777 027026 005416      MOV #SYNEXT!EIGHT!ODDPAR!26,@PARCSR
1750 005462 016703 005406      MOV RXDBUF,R3 ;SETUP FOR ERROR MSG
1751 005466 005004      CLR R4 ;FOR DATA CHAR CREATION
1752 005470 110477 005414      MOVB R4,@TXDBUF ;LOAD CHARACTER
1753 005474 052777 000020 005366      BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
1754                                     ;GET INTO SYNCRONIZATION
1755 005502 052777 020000 005374      BIS #CLK,@TXCSR ;POKE CLK UP
1756 005510 042777 020000 005366      BIC #CLK,@TXCSR ;POKE CLK DOWN
1757 005516 012767 000011 173414 1$: MOV #9,SHIFT ;# OF SHIFTS
1758 005524 010400      MOV R4,R0 ;EXPECTED
1759 005526      2$:
1760 005526 052777 020000 005350      BIS #CLK,@TXCSR ;POKE CLK UP
1761 005534 042777 020000 005342      BIC #CLK,@TXCSR ;POKE CLK DOWN
1762 005542 005367 173372      DEC SHIFT ;# OF SHIFTS
1763 005546 022767 000003 173364      CMP #3,SHIFT ;TIME TO LOAD NEXT CHAR ?
1764 005554 001003      BNE 3$ ;NO ?
1765 005556 005204      INC R4 ;GENERATE NEXT CHAR
1766 005560 110477 005324      MOVB R4,@TXDBUF ;LOAD NEXT CHARACTER
1767 005564 005767 173350      3$: TST SHIFT ;IS IT 0 ?
1768 005570 001356      BNE 2$
1769 005572 105777 005272      TSTB @RXCSR ;RXDONE = 1 ?
1770 005576 100401      BMI 5$
1771 005600 104000      HLT ;RXDONE SHOULD BE SET
1772 005602      5$:
1773 005602 017701 005266      MOV @RXDBUF,R1 ;ACTUAL
1774 005606 020001      CMP R0,R1 ;COMPARE EXP VS ACT
1775 005610 001401      BEQ 6$
1776 005612 104002      HLT 2 ;CHARACTERS SHOULD COMPARE
1777 005614      6$:
1778 005614 105704      TSTB R4 ;LAST CHARACTER ?
1779 005616 001337      BNE 1$ ;NO
1780 005620 104400      4$: SCOPE

```



```

1781                                     ::THIS TEST PERFORMS A BINARY COUNT DATA PATTERN ON
1782                                     ::BOTH THE TRANSMITTER AND RECEIVER LOGIC
1783                                     ::MODE:SYNC EXTERNAL (SYNEXT)
1784                                     ::LENGTH:EIGHT PLUS PARITY
1785                                     ::PARITY:EVEPAR
1786                                     ::MAINT. MODE:MEXT
1787                                     ::
1788 005622 012767 000007 173276 TST7: MOV #7,TSTNO ;SAVE THIS
1789 005630 012767 006102 173260 MOV #TST8,NEXT ;GO TO THIS TEST WHEN THRU
1790 005636 105767 173341 TSTB JMRBY ;JUMP AROUND TEST ?
1791 005642 100116 BPL 4$ ;YES ?
1792 005644 052777 000400 005232 BIS #MRESET,@TXCSR ;MASTER RESET
1793 005652 012777 020000 005220 MOV #SYNEXT,@PARCSR ;SET THE MODE
1794 005660 052777 000400 005216 BIS #MRESET,@TXCSR ;MASTER RESET
1795
1796 ;SET MAINTENANCE MODE & SEND
1797 ;NOTE:BIT WINDOW&CLK ARE CLEARED (MTDATA=0)
1798 005666 012777 010020 005210 MOV #MEXT!SEND,@TXCSR
1799
1800 ;SET MODE,# OF BITS,PARITY SENSE,& LOAD SYNC REG
1801 005674 012777 027426 005176 MOV #SYNEXT!EIGHT!EVEPAR!26,@PARCSR
1802 005702 016703 005166 MOV RXDBUF,R3 ;SETUP FOR ERROR MSG
1803 005706 005004 CLR R4 ;FOR DATA CHAR CREATION
1804 005710 110477 005174 MOV# R4,@TXDBUF ;LOAD CHARACTER
1805 005714 052777 000020 005146 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
1806
1807 ;GET INTO SYNCHRONIZATION
1808 BIS #CLK,@TXCSR ;POKE CLK UP
1809 005730 016702 173202 ;WAIT FOR CABLE & DRIVER DELAYS
1810 005734 005302 64$: MOV HOLD,R2 ;WAIT THIS AMT
1811 005734 001376 DEC R2 ;WAIT
1812 005736 001376 BNE 64$
1813 ;EXIT...
1814 005740 042777 020000 005136 BIC #CLK,@TXCSR ;POKE CLK DOWN
1815 ;WAIT FOR CABLE & DRIVER DELAYS
1816 005746 016702 173164 MOV HOLD,R2 ;WAIT THIS AMT
1817 005752 005302 65$: DEC R2 ;WAIT
1818 005752 001376 BNE 65$
1819 005754 001376 ;EXIT...
1820
1821 005756 012767 000011 173154 1$: MOV #9,SHIFT ;# OF SHIFTS
1822 005764 010400 MOV R4,R0 ;EXPECTED
1823 005766 052777 020000 005110 2$: BIS #CLK,@TXCSR ;POKE CLK UP
1824 ;WAIT FOR CABLE & DRIVER DELAYS
1825 MOV HOLD,R2 ;WAIT THIS AMT
1826 005774 016702 173136 66$: DEC R2 ;WAIT
1827 006000 BNE 66$
1828 006000 005302 ;EXIT...
1829 006002 001376 BIC #CLK,@TXCSR ;POKE CLK DOWN
1830 ;WAIT FOR CABLE & DRIVER DELAYS
1831 006004 042777 020000 005072 MOV HOLD,R2 ;WAIT THIS AMT
1832 006012 016702 173120 67$: DEC R2 ;WAIT
1833 006016 BNE 67$
1834 006016 005302
1835 006020 001376

```

1837					:EXIT...
1838	006022	005367	173112		DEC SHIFT ;# OF SHIFTS
1839	006026	022767	000003	173104	CMP #3,SHIFT ;TIME TO LOAD NEXT CHAR ?
1840	006034	001003			BNE 3\$;NO ?
1841	006036	005204			INC R4 ;GENERATE NEXT CHAR
1842	006040	110477	005044		MOVB R4,@TXDBUF ;LOAD NEXT CHARACTER
1843	006044	005767	173070	3\$:	TST SHIFT ;IS IT 0 ?
1844	006050	001346			BNE 2\$
1845	006052	105777	005012		TSTB @RXCSR ;RXDONE = 1 ?
1846	006056	100401			BMI 5\$
1847	006060	104000			HLT ;RXDONE SHOULD BE SET
1848	006062			5\$:	
1849	006062	017701	005006		MOV @RXDBUF,R1 ;ACTUAL
1850	006066	020001			CMP R0,R1 ;COMPARE EXP VS ACT
1851	006070	001401			BEQ 6\$
1852	006072	104002			HLT 2 ;CHARACTERS SHOULD COMPARE
1853	006074			6\$:	
1854					:CHECK OUT MODEM BYPASS JUMPER
1855	006074	105704			TSTB R4 ;LAST CHARACTER ?
1856	006076	001327			BNE 1\$;NO
1857	006100	104400		4\$:	SCOPE


```

1858      ::THIS TEST PERFORMS A BINARY COUNT DATA PATTERN ON
1859      ::BOTH THE TRANSMITTER AND RECEIVER LOGIC
1860      ::MODE:SYNC EXTERNAL (SYNEXT)
1861      ::LENGTH:EIGHT PLUS PARITY
1862      ::PARITY:ODDPAR
1863      ::MAINT. MODE:MEXT
1864
1865 006102 012767 000010 173016 TST8: MOV #8,TSTNO ;SAVE THIS
1866 006110 012767 006362 173000 MOV #.EOP,NEXT ;GO TO THIS TEST WHEN THRU
1867 006116 105767 173061 TSTB JMRBY ;JUMP AROUND TEST ?
1868 006122 100116 BPL 4$ ;YES ?
1869 006124 052777 000400 004752 BIS #MRESET,@TXCSR ;MASTER RESET
1870 006132 012777 020000 004740 MOV #SYNEXT,@PARCSR ;SET THE MODE
1871 006140 052777 000400 004736 BIS #MRESET,@TXCSR ;MASTER RESET
1872
1873 ;SET MAINTENANCE MODE & SEND
1874 ;NOTE:BIT WINDOW&CLK ARE CLEARED (MTDATA=0)
1875 006146 012777 010020 004730 MOV #MEXT!SEND,@TXCSR
1876
1877 ;SET MODE,# OF BITS,PARITY SENSE,& LOAD SYNC REG
1878 006154 012777 027026 004716 MOV #SYNEXT!EIGHT!ODDPAR!26,@PARCSR
1879 006162 016703 004706 MOV RXDBUF,R3 ;SETUP FOR ERROR MSG
1880 006166 005004 CLR R4 ;FOR DATA CHAR CREATION
1881 006170 110477 004714 MOV B R4,@TXDBUF ;LOAD CHARACTER
1882 006174 052777 000020 004666 BIS #SYNSCH,@RXCSR ;SET SEARCH SYNC
1883
1884 006202 052777 020000 004674 ;GET INTO SYNCHRONIZATION
1885 BIS #CLK,@TXCSR ;POKE CLK UP
1886 ;WAIT FOR CABLE & DRIVER DELAYS
1887 006210 016702 172722 MOV HOLD,R2 ;WAIT THIS AMT
1888 006214 005302 64$: DEC R2 ;WAIT
1889 006216 001376 BNE 64$
1890 ;EXIT...
1891 006220 042777 020000 004656 BIC #CLK,@TXCSR ;POKE CLK DOWN
1892 ;WAIT FOR CABLE & DRIVER DELAYS
1893 006226 016702 172704 MOV HOLD,R2 ;WAIT THIS AMT
1894 006232 65$: DEC R2 ;WAIT
1895 006232 005302 BNE 65$
1896 006234 001376 ;EXIT...
1897
1898 006236 012767 000011 172674 1$: MOV #9,SHIFT ;# OF SHIFTS
1899 006244 010400 MOV R4,R0 ;EXPECTED
1900 006246 2$:
1901 006246 052777 020000 004630 BIS #CLK,@TXCSR ;POKE CLK UP
1902 ;WAIT FOR CABLE & DRIVER DELAYS
1903 006254 016702 172656 MOV HOLD,R2 ;WAIT THIS AMT
1904 006260 66$: DEC R2 ;WAIT
1905 006260 005302 BNE 66$
1906 006262 001376 ;EXIT...
1907
1908 006264 042777 020000 004612 BIC #CLK,@TXCSR ;POKE CLK DOWN
1909 ;WAIT FOR CABLE & DRIVER DELAYS
1910 006272 016702 172640 MOV HOLD,R2 ;WAIT THIS AMT
1911 006276 67$: DEC R2 ;WAIT
1912 006276 005302 BNE 67$
1913 006300 001376

```

```

;EXIT...
DEC      SHIFT      ;# OF SHIFTS
CMP      #3,SHIFT   ;TIME TO LOAD NEXT CHAR ?
BNE      3$         ;NO ?
INC      R4         ;GENERATE NEXT CHAR
MOVB     R4,@TXDBUF ;LOAD NEXT CHARACTER
TST      SHIFT      ;IS IT 0 ?
BNE      2$         ;
TSTB     @RXCSR      ;RXDONE = 1 ?
BMI      5$         ;
HLT                      ;RXDONE SHOULD BE SET

MOV      @RXDBUF,R1  ;ACTUAL
CMP      R0,R1       ;COMPARE EXP VS ACT
BEQ      6$         ;
HLT      2           ;CHARACTERS SHOULD COMPARE

;CHECK OUT MODEM BYPASS JUMPER
TSTB     R4         ;LAST CHARACTER ?
BNE      1$         ;NO
SCOPE

```



```

1991 006642 016777 172262 172232      MOV      PASCNT,@LIGHTS      ;DISPLAY PASS COUNT
1992 006650 013701 000042              MOV      @#42,R1          ;CHECK FOR ACT-11 OR DDP
1993 006654 001405              BEQ      RESTRT          ;IF NOT, CONTINUE TESTING
1994 006656 000005              RESET
1995 006660 004711              LOGICAL: JSR      PC,(R1)
1996 006662 000240              NOP
1997 006664 000240              NOP
1998 006666 000240              NOP
1999 006670 012767 000340 171100 RESTRT: MOV      #340,PS          ;PREVENT INTERRUPTS (PRIO: 7)
2000 006676 104413              CKSWR          ;CHECK FOR ^G
2001 006700 012767 003446 172206      MOV      #TST1,RTRN
2002 006706 000167 174534      JMP      TST1
2003
2004              ;SCOPE LOOP AND ITERATION HANDLER
2005
2006 006712      .SCOPE:
2007      ;***** START OF CODE FOR THE X OR TESTER *****
2008 006712 000424      BR      4$
2009
2010 006714 013746 000004              MOV      @#4,-(SP)
2011 006720 012737 006740 000004      MOV      #1$,@#4
2012 006726 005737 177060              TST      @#177060
2013 006732 012637 000004              MOV      (SP)+,@#4
2014 006736 000404              BR      2$
2015 006740 022626      1$:      CMP      (SP)+,(SP)+
2016 006742 012637 000004              MOV      (SP)+,@#4
2017 006746 000403              BR      3$
2018 006750 016767 172142 172136      2$:      MOV      NEXT,RTRN
2019 006756 016716 172132      3$:      MOV      RTRN,(SP)
2020 006762 000002              RTI
2021 006764      4$:      ;***** END OF CODE FOR THE X OR TESTER *****
2022 006764 104413              CKSWR
2023 006766 032777 040000 172104      BIT      #SW14,@SWR
2024 006774 001407              TTST:  BEQ      1$
2025 006776 000432              BR      3$
2026 007000 105777 172100              TSTB     @TKCSR
2027 007004 100027              BPL      3$
2028 007006 017700 172074              MOV      @TKDBR,R0
2029 007012 000412              BR      2$
2030 007014 032777 004000 172056      1$:      BIT      #SW11,@SWR
2031 007022 001006              BNE      2$
2032 007024 005267 172074              INC      LPCNT
2033 007030 026767 172070 172064      CMP      LPCNT,ICOUNT
2034 007036 101412              BLOS     3$
2035 007040 105067 172202      2$:      CLRB     ERRFLG
2036 007044 005067 172054              CLR      LPCNT
2037 007050 012767 000005 172044      MOV      #5,ICOUNT
2038 007056 016767 172034 172030      MOV      NEXT,RTRN
2039 007064 016716 172024      3$:      MOV      RTRN,(SP)
2040 007070 000002              RTI
2041 007072 001407      BRW:      1407
2042 007074 000432      BRX:      432
2043
2044              ;CHECK FOR FREEZE ON CURRENT DATA
2045
2046 007076 104413      .SCOPE1: CKSWR          ;CHECK FOR ^G

```



```

2047 007100 032777 001000 171772      BIT      #SW09,@SWR
2048 007106 001402                BEQ      1$
2049 007110 016716 172004                MOV      LOCK,(SP)
2050 007114 000002                1$:      RTI
2051
2052                                ;TELETYPE OUTPUT ROUTINE
2053
2054 007116 010546                .TYPE:  MOV      R5,-(SP)
2055 007120 017605 000002                MOV      @2(SP),R5
2056 007124 062766 000002 000002                ADD      #2,2(SP)
2057 007132 105715                1$:      TSTB      (R5)                ;LOOK FOR '0'
2058 007134 001406                BEQ      3$
2059 007136 105777 171746                2$:      TSTB      @TPCSR                ;TEST DONE BIT
2060 007142 100375                BPL      2$
2061 007144 112577 171742                MOVB      (R5)+,@TPDBR                ;TYPE CHAR
2062 007150 000770                BR      1$                ;DO IT AGAIN UNTIL '0' IS SEEN
2063 007152 012605                3$:      MOV      (SP)+,R5
2064 007154 000002                RTI
2065
2066                                ;ASCII STRING INPUT ROUTINE
2067
2068 007156 010346                .INSTR: MOV      R3,-(SP)
2069 007160 010446                MOV      R4,-(SP)
2070 007162 017667 000004 000010                MOV      @4(SP),MSG
2071 007170 062766 000002 000004                ADD      #2,4(SP)
2072 007176 104402                .INST1: TYPE
2073 007200 000000                .MSG:  0
2074 007202 012704 012224                MOV      #INBUF,R4
2075 007206 012703 000007                MOV      #7,R3
2076 007212 105777 171666                1$:      TSTB      @TKCSR
2077 007216 100375                BPL      1$
2078 007220 117714 171662                MOVB      @TKDBR,(R4)
2079 007224 142714 000200                BICB      #200,(R4)
2080 007230 121427 000025                CMPB      (R4),#25                ;IS IT <^U>
2081 007234 001003                BNE      200$
2082 007236 104402 011434                TYPE,MCRLF
2083 007242 000755                BR      .INST1
2084 007244 122427 000015                200$:  CMPB      (R4)+,#15
2085 007250 001423                BEQ      INSTR2
2086 007252 117777 171630 171632                MOVB      @TKDBR,@TPDBR
2087 007260 105777 171624                2$:      TSTB      @TPCSR
2088 007264 100375                BPL      2$
2089 007266 005303                DEC      R3
2090 007270 001350                BNE      1$
2091 007272 000402                BR      .INSTG
2092 007274 010346                .INSTE: MOV      R3,-(SP)
2093 007276 010446                MOV      R4,-(SP)
2094 007300 104402                .INSTG: TYPE
2095 007302 011430                MQM
2096 007304 005737 010572                TST      @#RDSW
2097 007310 001402                BEQ      400$
2098 007312 104402 011434                TYPE,MCRLF
2099 007316 000727                400$:  BR      .INST1
2100 007320 012604                INSTR2: MOV      (SP)+,R4
2101 007322 012603                MOV      (SP)+,R3
2102 007324 000002                RTI

```

```

2103
2104
2105
2106 007326 010546
2107 007330 010446
2108 007332 016605 000004
2109 007336 012567 000170
2110 007342 012567 000166
2111 007346 012567 000164
2112 007352 112567 000162
2113 007356 112567 000157
2114 007362 010566 000004
2115 007366 005005
2116 007370 012704 012224
2117 007374 122714 000015
2118 007400 001420
2119 007402 121427 000060
2120 007406 002415
2121 007410 121427 000067
2122 007414 003012
2123 007416 142714 000060
2124 007422 152405
2125 007424 122714 000015
2126 007430 001414
2127 007432 006305
2128 007434 006305
2129 007436 006305
2130 007440 000760
2131 007442 122714 000015
2132 007446 001003
2133 007450 005737 010572
2134 007454 001023
2135 007456 104404
2136 007460 000742
2137
2138
2139
2140 007462 020567 000046
2141 007466 101365
2142 007470 020567 000036
2143 007474 103762
2144 007476 136705 000036
2145 007502 001357
2146
2147
2148
2149 007504 016704 000026
2150 007510 010524
2151 007512 062705 000002
2152 007516 105367 000017
2153 007522 001372
2154 007524 012604
2155 007526 012605
2156 007530 000002
2157 007532 000000
2158 007534 000000

;CONVERT ASCII STRING TO OCTAL

.PARAM: MOV R5, -(SP)
        MOV R4, -(SP)
        MOV 4(SP), R5
        MOV (R5)+, LOLIM
        MOV (R5)+, HILIM
        MOV (R5)+, DEVADR
        MOVB (R5)+, LOBITS
        MOVB (R5)+, ADRCNT
        MOV R5, 4(SP)
PARAM1: CLR R5
        MOV #INBUF, R4
        CMPB #15, (R4)
        BEQ PARERR
1$:      CMPB (R4), #60
        BLT PARERR
        CMPB (R4), #67
        BGT PARERR
        BICB #60, (R4)
        BISB (R4)+, R5
        CMPB #15, (R4)
        BEQ LIMITS
        ASL R5
        ASL R5
        ASL R5
        BR 1$
PARERR: CMPB #15, (R4)
        BNE 120$
        TST @#RDSW
        BNE PARTI
120$:    INSTER
        BR PARAM1

;IS FIRST CHARACTER A <CR>
;IS CKSWR ROUTINE BEING USED

;TEST TO SEE IF NUMBER IS WITHIN LIMITS
LIMITS: CMP R5, HILIM
        BHI PARERR
        CMP R5, LOLIM
        BLO PARERR
        BITB LOBITS, R5
        BNE PARERR

;STORE NUMBER AT SPECIFIED ADDRESS
1$:      MOV DEVADR, R4
        MOV R5, (R4)+
        ADD #2, R5
        DECB ADRCNT
        BNE 1$
PARTI:   MOV (SP)+, R4
        MOV (SP)+, R5
        RTI
LOLIM:   0
HILIM:   0

```



```

2159 007536 000000      DEVADR: 0
2160 007540 000000      LOBITS: 0
2161      007541      ADRCNT=LOBITS+1
2162
2163      ;SAVE PC OF TEST THAT FAILED AND R0-R5
2164
2165 007542 016667 000004 171424 .SAV05: MOV      4(SP),SAVPC
2166
2167      ;SAVE R0-R5
2168
2169 007550 010567 171414      SV05:  MOV      R5,SAVR5
2170 007554 010467 171406      MOV      R4,SAVR4
2171 007560 010367 171400      MOV      R3,SAVR3
2172 007564 010267 171372      MOV      R2,SAVR2
2173 007570 010167 171364      MOV      R1,SAVR1
2174 007574 010067 171356      MOV      R0,SAVR0
2175 007600 000002      RTI
2176
2177      ;RESTORE R0-R5
2178
2179 007602 016700 171350      .RES05: MOV      SAVR0,R0
2180 007606 016701 171346      MOV      SAVR1,R1
2181 007612 016702 171344      MOV      SAVR2,R2
2182 007616 016703 171342      MOV      SAVR3,R3
2183 007622 016704 171340      MOV      SAVR4,R4
2184 007626 016705 171336      MOV      SAVR5,R5
2185 007632 000002      RTI
2186
2187      ;CONVERT OCTAL NUMBER TO ASCII AND OUTPUT TO TELEPRINTER
2188
2189 007634 104402      .CONVR: TYPE
2190 007636 011434      MCRLF
2191 007640 010046      .CNVRT: MOV      R0,-(SP)
2192 007642 010146      MOV      R1,-(SP)
2193 007644 010346      MOV      R3,-(SP)
2194 007646 010446      MOV      R4,-(SP)
2195 007650 010546      MOV      R5,-(SP)
2196 007652 017601 000012      MOV      @12(SP),R1
2197 007656 016767 002402 171264      MOV      TEMP,TEMP3
2198 007664 062766 000002 000012      ADD      #2,12(SP)
2199 007672 012167 000154      MOV      (R1)+,WRDCNT
2200 007676 112167 000152      1$:  MOV      (R1)+,CHRCNT
2201 007702 112167 000147      MOV      (R1)+,SPACNT
2202 007706 013167 000144      MOV      @ (R1)+,BINWRD
2203 007712 016704 000140      2$:  MOV      BINWRD,R4
2204 007716 116705 000132      MOV      CHRCNT,R5
2205 007722 012700 012264      MOV      #TEMP,R0
2206 007726 010403      3$:  MOV      R4,R3
2207 007730 042703 177770      BIC      #177770,R3
2208 007734 062703 000060      ADD      #060,R3
2209 007740 110320      MOV      R3,(R0)+
2210 007742 006204      ASR      R4
2211 007744 042704 100000      BIC      #100000,R4
2212 007750 006204      ASR      R4
2213 007752 006204      ASR      R4
2214 007754 005305      DEC      R5

```

```

:SHIFT FOR NEXT #
:CLUGE TO STOP BIT 15 PROPAGATING.
:DITTO
:DITTO

```

2215	007756	001363			BNE	3\$	
2216	007760	012703	012324		MOV	#MDATA,R3	
2217	007764	114023		4\$:	MOVB	-(R0),(R3)+	
2218	007766	105367	000062		DECB	CHRCNT	
2219	007772	001374			BNE	4\$	
2220	007774	105767	000055		TSTB	SPACNT	
2221	010000	001405			BEQ	6\$	
2222	010002	112723	000040	5\$:	MOVB	#040,(R3)+	
2223	010006	105367	000043		DECB	SPACNT	
2224	010012	001373			BNE	5\$	
2225	010014	105013		6\$:	CLRB	(R3)	
2226	010016	104402			TYPE		
2227	010020	012324			MDATA		
2228	010022	005367	000024		DEC	WRDCNT	
2229	010026	001323			BNE	1\$	
2230	010030	016767	171114 002226		MOV	TEMP3,TEMP	
2231	010036	012605			MOV	(SP)+,R5	
2232	010040	012604			MOV	(SP)+,R4	
2233	010042	012603			MOV	(SP)+,R3	
2234	010044	012601			MOV	(SP)+,R1	
2235	010046	012600			MOV	(SP)+,R0	
2236	010050	000002			RTI		
2237	010052	000000			WRDCNT:	0	
2238	010054	000000			CHRCNT:	0	
2239		010055			SPACNT=CHRCNT+1		
2240	010056	000000			BINWRD:	0	
2241							
2242							
2243							
2244							
2245							
2246							
2247	010060	017605	000000		.SETFLG:MOV	@(SP),R5	
2248	010064	122767	000116 002132		CMPB	#'N',INBUF	:IS IT 'N'?
2249	010072	001002			BNE	1\$	
2250	010074	105015			CLRB	(R5)	:000
2251	010076	000406			BR	2\$	
2252	010100	122767	000131 002116	1\$:	CMPB	#'Y',INBUF	:IS IT 'Y'?
2253	010106	001005			BNE	3\$	
2254	010110	112715	177777		MOVB	#-1,(R5)	:377
2255	010114	062716	000002	2\$:	ADD	#2,(SP)	
2256	010120	000002			RTI		
2257	010122	104404		3\$:	INSTR		:RETRY
2258	010124	000755			BR	.SETFLG	
2259							
2260							
2261							
2262							
2263							
2264	010126	011646			.TRPSR:MOV	(SP),-(SP)	:GET PC OF RETURN
2265	010130	162716	000002		SUB	#2,(SP)	:PC OF TRAP
2266	010134	017616	000000		MOV	@(SP),(SP)	:GET TRP
2267	010140	006316			ASL	(SP)	:MULTIPLY TRAP ARG BY 2
2268	010142	042716	177001		BIC	#177001,(SP)	:CLEAR UNWANTED BITS
2269	010146	062716	001366		ADD	#.TRPTAB,(SP)	:POINTER TO SUBROUTINE ADDRESS
2270	010152	017616	000000		MOV	@(SP),(SP)	:SUBROUTINE ADDRESS


```

2271 010156 000136      JMP      @ (SP)+      ;GO TO SUBROUTINE
2272
2273                      ;ERROR HANDLER
2274
2275 010160 104413      .HLT:  CKSWR      ;CHECK FOR ^G
2276 010162 032777 020000 170710  BIT      #SW13,@SWR      ;INHIBIT ERROR TYPE OUT ?
2277 010170 001061      BNE      HALTS
2278 010172 021667 170736  CMP      (SP),LSTERR
2279 010176 001404      BEQ      1$
2280 010200 011667 170730  MOV      (SP),LSTERR
2281 010204 105067 171036  CLRB     ERRFLG
2282 010210 104406      1$:  SAVO5
2283 010212 011605      MOV      (SP),R5
2284 010214 162705 000002  SUB      #2,R5
2285 010220 011504      MOV      (R5),R4
2286 010222 006304      ASL      R4
2287 010224 061504      ADD      (R5),R4
2288 010226 006304      ASL      R4
2289 010230 042704 177001  BIC      #177001,R4
2290 010234 062704 013040  ADD      #.ERRTAB,R4
2291 010240 012467 000040  MOV      (R4)+,ERRMSG
2292 010244 012467 000046  MOV      (R4)+,DATAHD
2293 010250 011467 000054  MOV      (R4),DATABP
2294 010254 105767 170766  TSTB     ERRFLG
2295 010260 001403      BEQ      TYPMSG
2296 010262 005767 000042  TST      DATABP
2297 010266 001014      BNE      TYPDAT
2298 010270 104410      TYPMSG: CONVRT
2299 010272 010422      ERTAB0
2300 010274 112767 177777 170744  MOVB     #-1,ERRFLG
2301 010302 104402      TYPE
2302 010304 000000      ERRMSG: 0
2303 010306 005767 000004  TST      DATAHD
2304 010312 001402      BEQ      TYPDAT
2305 010314 104402      TYPE
2306 010316 000000      DATAHD: 0
2307 010320 005767 000004  TYPDAT: TST      DATABP
2308 010324 001402      BEQ      RESREG
2309 010326 104410      CONVRT
2310 010330 000000      DATABP: 0
2311 010332 104407      RESREG: RES05
2312 010334 005777 170540  HALTS:  TST      @SWR
2313 010340 100005      BPL      EXITER
2314 010342 010046      PUSHRO
2315 010344 016600 000002  MOV      2(SP),R0
2316 010350 000000      HALT
2317 010352 012600      POPRO
2318 010354 104413      EXITER: CKSWR
2319 010356 005267 170550      INC      ERRCNT
2320 010362 032777 000400 170510  BIT      #SW08,@SWR
2321 010370 001007      BNE      1$
2322 010372 032777 002000 170500  BIT      #SW10,@SWR
2323 010400 001407      BEQ      2$
2324 010402 016767 170510 170504  MOV      NEXT,RTRN
2325 010410 012706 001100      1$:  MOV      #STACK,SP
2326 010414 000177 170474      JMP      @RTRN

```

```

2327 010420 000002      2$: RTI
2328 010422 000001      ERTABO: 1
2329 010424 006        002      .BYTE 6,2
2330 010426 001174      SAVPC
2331      ;ENTER HERE ON POWER FAILURE
2332
2333
2334 010430 010046      .PFAIL: MOV R0,-(SP)      ;SAVE R0-R5 ON PROCESSOR STACK
2335 010432 010146      MOV R1,-(SP)
2336 010434 010246      MOV R2,-(SP)
2337 010436 010346      MOV R3,-(SP)
2338 010440 010446      MOV R4,-(SP)
2339 010442 010546      MOV R5,-(SP)
2340 010444 016746      MOV 24,-(SP)
2341 010450 010667      MOV SP,SAVSP      ;SAVE STACK POINTER
2342 010454 012767      MOV #RESTART,24      ;SET UP FOR POWER UP TRAP
2343 010462 000000      HALT      ;HALT ON POWER DOWN NORMAL
2344 010464 000777      1$: BR 1$
2345
2346      ;PROCESSOR WILL TRAP HERE WHEN POWER IS RESTORED
2347
2348 010466 016706      170500      RESTAR: MOV SAVSP,SP      ;RESTORE STACK POINTER
2349 010472 012605      MOV (SP)+,R5      ;RESTORE R0-R5
2350 010474 012604      MOV (SP)+,R4
2351 010476 012603      MOV (SP)+,R3
2352 010500 012602      MOV (SP)+,R2
2353 010502 012601      MOV (SP)+,R1
2354 010504 012600      MOV (SP)+,R0
2355 010506 012767      010430 167310      MOV #.PFAIL,24      ;SET UP FOR POWER FAILURE
2356 010514 012767      000340 167254      MOV #340,PS
2357 010522 012706      001100      MOV #STACK,SP
2358 010526 005067      001532      CLR TEMP
2359 010532 005267      001526      1$: INC TEMP
2360 010536 001375      BNE 1$
2361 010540 104410      CONVRT
2362 010542 010564      PFTAB
2363 010544 104402      TYPE
2364 010546 011437      MPFAIL
2365 010550 005067      170472      CLR ERRFLG
2366 010554 005067      170354      CLR LSTERR
2367 010560 000177      170330      JMP @RTRN
2368 010564 000001      PFTAB: 1
2369 010566 006        002      .BYTE 6,2
2370 010570 001114      RTRN
2371
2372
2373      ;CHECK SWITCH REGISTER ROUTINE. CHECKS FOR ^G TO ALLOW CHANGING
2374      ;OF LOC.176.
2375      ;LOCATIONS USED:
2376 010572 000000      RDSW: .WORD 0
2377
2378
2379 010574 005737      000042      .CKSWR: TST @#42
2380 010600 001042      BNE OUT
2381 010602 022767      000176 170270      CMP #CUREG,SWR
2382 010610 001036      BNE OUT      ;SOFTWARE SWITCH REGISTER PRESENT
      ;NO, GET OUT

```


2383	010612	105777	170266		TSTB	@TKCSR	:YES, WAIT FOR
2384	010616	100033			BPL	OUT	:READY, GET CHARACTER
2385	010620	017767	170262	176352	MOV	@TKDBR, .MSG	:AND STRIP OFF
2386	010626	042767	177600	176344	BIC	#177600, .MSG	:THE GARBAGE
2387	010634	122767	000007	176336	CMPB	#7, .MSG	:IS IT A <^G>
2388	010642	001021			BNE	OUT	
2389	010644	104402	010722		TYPE, \$CNTG		
2390	010650	005137	010572		.CNTLU: COM	@#RDSW	
2391	010654	104402	010727		TYPE, \$MSWR		
2392	010660	104411	010714		CNVRT, SWREGC		
2393	010664	104403	010737		INSTR, \$MNEW		
2394	010670	104405			PARAM		
2395	010672	000000			0		
2396	010674	177777			177777		
2397	010676	000176			SWREG		
2398	010700	000	001		.BYTE	0, 1	
2399	010702	104402	011434		TYPE, MCRI.F		
2400	010706	005037	010572		OUT: CLR	@#RDSW	
2401	010712	000002			RTI		
2402	010714	000001			SWREGC: 1		
2403	010716	006	002		.BYTE	6, 2	
2404	010720	000176			SWREG		
2405	010722	005015	043536	000	\$CNTG: .ASCIIZ	<15><12>/^G/	
2406	010727	015	051412	051127	\$MSWR: .ASCIIZ	<15><12>/SWR= /	
2407	010734	020075	000				
2408	010737	040	047040	053505	\$MNEW: .ASCIIZ	/ NEW= /	
2409	010744	020075	000				
2410		010750			.EVEN		
2411	010750	005015	042012	030525	MTITLE: .ASCIIZ	<15><12><12>/DU11 CZDUF-D TAPE F /<15><12>	
2412	010756	020061	055103	052504			
2413	010764	026506	020104	040524			
2414	010772	042520	043040	006440			
2415	011000	000012					
2416	011002	005015	042526	052103	MVECTO: .ASCIIZ	<15><12>/VECTOR ADDRESS-/	
2417	011010	051117	040440	042104			
2418	011016	042522	051523	000055			
2419	011024	005015	051461	020124	MREGAD: .ASCIIZ	<15><12>/1ST DEVICE: RECEIVER CONTROL REGISTER ADDRESS-/	
2420	011032	042504	044526	042503			
2421	011040	020072	042522	042503			
2422	011046	053111	051105	041440			
2423	011054	047117	051124	046117			
2424	011062	051040	043505	051511			
2425	011070	042524	020122	042101			
2426	011076	051104	051505	026523			
2427	011104	000					
2428	011105	015	040412	042522	MMULT: .ASCIIZ	<15><12>/ARE YOU RUNNING MULTIPLE DEVICES ? (Y OR N)-/	
2429	011112	054440	052517	051040			
2430	011120	047125	044516	043516			
2431	011126	046440	046125	044524			
2432	011134	046120	020105	042504			
2433	011142	044526	042503	020123			
2434	011150	020077	054450	047440			
2435	011156	020122	024516	000055			
2436	011164	005015	040514	052123	MLASTD: .ASCIIZ	<15><12>/LAST DEVICE: RECEIVER CONTROL REGISTER ADDRESS-/	
2437	011172	042040	053105	041511			
2438	011200	035105	042522	042503			

2439	011206	053111	051105	041440
2440	011214	047117	051124	046117
2441	011222	051040	043505	051511
2442	011230	042524	020122	042101
2443	011236	051104	051505	026523
2444	011244	000		
2445	011245	075	042504	044526
2446	011252	042503	020040	000
2447	011257	015	044012	053517
2448	011264	047040	053517	041040
2449	011272	047522	047127	041440
2450	011300	053517	020077	027056
2451	011306	051456	046105	041505
2452	011314	020124	047523	042515
2453	011322	044124	047111	020107
2454	011330	047524	051040	047125
2455	011336	040040	041501	051124
2456	011344	043505	000	
2457	011347	015	047412	052125
2458	011354	047440	020106	040522
2459	011362	043516	035105	042522
2460	011370	054524	042520	046040
2461	011376	051501	020124	042504
2462	011404	044526	042503	051040
2463	011412	041530	051123	040440
2464	011420	042104	042522	051523
2465	011426	000055		
2466	011430	020040	000077	
2467	011434	005015	000	
2468	011437	040	050040	053517
2469	011444	051105	043040	044501
2470	011452	052514	042522	020054
2471	011460	051120	043517	040522
2472	011466	020115	042522	052123
2473	011474	051101	020124	052101
2474	011502	052040	051505	020124
2475	011510	047111	050040	047522
2476	011516	051107	051505	000123
2477	011524	005015	047105	020104
2478	011532	043117	050040	051501
2479	011540	020123	040524	042520
2480	011546	043040	000	
2481	011551	015	051012	000
2482	011555	015	052012	051505
2483	011562	020124	041520	000055
2484	011570	005015	047514	045503
2485	011576	047440	020116	042523
2486	011604	042514	052103	042105
2487	011612	052040	051505	037524
2488	011620	024040	020131	051117
2489	011626	047040	026451	000
2490	011633	015	042012	020125
2491	011640	051120	047511	044522
2492	011646	054524	046040	053105
2493	011654	046105	000055	
2494	011660	005015	020043	043117

DEVICE: .ASCIIZ /=DEVICE /

MCOW: .ASCIIZ <15><12>/HOW NOW BROWN COW? ...SELECT SOMETHING TO RUN @ACTREG/

MRANGE: .ASCIIZ <15><12>/OUT OF RANGE:RETYPE LAST DEVICE RXCSR ADDRESS-/

MQM: .ASCIIZ / ?/

MCRLF: .ASCIIZ <15><12>

MPFAIL: .ASCIIZ / POWER FAILURE, PROGRAM RESTART AT TEST IN PROGRESS/

MEPASS: .ASCIIZ <15><12>/END OF PASS TAPE F/

MR: .ASCIIZ <15><12>/R/

MTSTPC: .ASCIIZ <15><12>/TEST PC-/

MLOCK: .ASCIIZ <15><12>/LOCK ON SELECTED TEST? (Y OR N)-/

MLEVEL: .ASCIIZ <15><12>/DU PRIORITY LEVEL-/

MSYNC: .ASCIIZ <15><12>/# OF SYNC CHARS SELECTED (1 OR 2)-/

2495 011666 051440 047131 020103
2496 011674 044103 051101 020123
2497 011702 042523 042514 052103
2498 011710 042105 024040 030440
2499 011716 047440 020122 024462

2500 011724 000055
2501 011726 005015 051511 051440 MWIRE6: .ASCIIZ <15><12>/IS SEC XMIT JUMPER #6 IN? (Y OR N)-/
2502 011734 041505 054040 044515
2503 011742 020124 052512 050115
2504 011750 051105 021440 020066
2505 011756 047111 020077 054450
2506 011764 047440 020122 024516
2507 011772 000055

2508 011774 005015 051511 051440 MWIRE5: .ASCIIZ <15><12>/IS SEC REC JUMPER #5 IN? (Y OR N)-/
2509 012002 041505 051040 041505
2510 012010 045040 046525 042520
2511 012016 020122 032443 044440
2512 012024 037516 024040 020131
2513 012032 051117 047040 026451

2514 012040 000
2515 012041 015 044412 020123 MWIRE4: .ASCIIZ <15><12>/IS OPT CLR ENABLE JUMPER #4 IN? (Y OR N)-/
2516 012046 050117 020124 046103
2517 012054 020122 047105 041101
2518 012062 042514 045040 046525
2519 012070 042520 020122 032043
2520 012076 044440 037516 024040
2521 012104 020131 051117 047040
2522 012112 026451 000

2523 012115 015 044412 020123 MEXTJ: .ASCIIZ <15><12>/IS THE TEST CONNECTOR INSTALLED ?(Y OR N)-/
2524 012122 044124 020105 042524
2525 012130 052123 041440 047117
2526 012136 042516 052103 051117
2527 012144 044440 051516 040524
2528 012152 046114 042105 037440
2529 012160 054450 047440 020122
2530 012166 024516 000055

2531 012172 006412 020040 020040 MSTATUS: .ASCIIZ <12> <15>/ STATUS MAP / <12> <15>
2532 012200 052123 052101 051525
2533 012206 020040 046440 050101
2534 012214 020040 020040 005040
2535 012222 000015

2536 .EVEN

2537
2538 ;BUFFERS FOR INPUT-OUTPUT

2539
2540 012224 000040 INBUF: .BLKB 4)
2541 012264 000040 TEMP: .BLKB 4)
2542 012324 000040 MDATA: .BLKB 4)

2543 ;*****

2544 ;UTILITIES

2545 ;*****

2546
2547 ;THIS UTILITY CALCULATES PRIORITY LEVEL

2548 012364 006367 000044 DULEV: ASL DUPRT ;SHIFT LEFT
2549 012370 006367 000040 ASL DUPRT ;
2550 012374 006367 000034 ASL DUPRT ;

```

2551 012400 006367 000030 ASL DUPRT ;
2552 012404 006367 000024 ASL DUPRT ;
2553 012410 016767 000020 000020 MOV DUPRT,LESS1 ;MOVE THIS TO LESS1
2554 012416 162767 000001 000012 SUB #1,LESS1 ;CREATE LESS1
2555 012424 042767 000037 000004 BIC #37,LESS1 ;CLEAR TNZVC
2556 012432 000207 RTS PC
2557 012434 000240 DUPRT: LEVEL5
2558 012436 000200 LESS1: LEVEL4 ;LEVEL TO ALLOW INTERRUPTS
2559
2560 ;NEW DU ADDRESSES
2561 012440 016767 000126 000422 DUADDR: MOV DUBASE,RXCSR ;XXX0
2562 012446 005267 000120 INC DUBASE
2563 012452 016767 000114 000412 MOV DUBASE,HRXCSR ;XXX1
2564 012460 005267 000106 INC DUBASE
2565 012464 016767 000102 000402 MOV DUBASE,RXDBUF ;XXX2
2566 012472 016767 000074 000400 MOV DUBASE,PARCSR ;XXX2
2567 012500 005267 000066 INC DUBASE
2568 012504 016767 000062 000364 MOV DUBASE,HRXDBUF ;XXX3
2569 012512 016767 000054 000362 MOV DUBASE,HPARCSR ;XXX3
2570 012520 005267 000046 INC DUBASE
2571 012524 016767 000042 000352 MOV DUBASE,TXCSR ;XXX4
2572 012532 005267 000034 INC DUBASE
2573 012536 016767 000030 000342 MOV DUBASE,HTXCSR ;XXX5
2574 012544 005267 000022 INC DUBASE
2575 012550 016767 000016 000332 MOV DUBASE,TXDBUF ;XXX6
2576 012556 005267 000010 INC DUBASE
2577 012562 016767 000004 000322 MOV DUBASE,HTXDBUF ;XXX7
2578 012570 000207 RTS PC
2579 012572 000000 DUBASE: 0
2580
2581 ;THIS UTILITY POKES THE MAINT DATA BASED UPON THE
2582 ;INFORMATION CONTAINED IN TEMP1 AND IT IS
2583 ;SHIFTED IN BY THE CONTENTS OF SHIFT
2584 012574 042777 040000 000302 RPOKE: BIC #MTDATA,@TXCSR
2585 012602 005067 166340 CLR TEMP2
2586 012606 006067 166332 ROR TEMP1 ;FORCE CARRY
2587 012612 006067 166330 ROR TEMP2 ;PICK UP CARRY IN BIT 15
2588 012616 006267 166324 ASR TEMP2 ;SHIFT INTO BIT 14
2589 012622 042767 100000 166316 BIC #BIT15,TEMP2 ;CLR BIT 15
2590 012630 056777 166312 000246 BIS TEMP2,@TXCSR ;POKE MAINT DATA
2591 012636 042777 020000 000240 BIC #CLK,@TXCSR ;POKE CLK
2592 012644 052777 020000 000232 BIS #CLK,@TXCSR ;
2593 012652 005367 166262 DEC SHIFT
2594 012656 001346 BNE RPOKE
2595 012660 000207 RTS PC
2596
2597 ;THIS ROUTINE CALCULATES ODD PARITY FOR AN 8 BIT CHAR
2598 012662 016767 166256 166256 ODD8: MOV TEMP1,TEMP2 ;SAVE TEMP1
2599 012670 005067 166254 CLR TEMP3
2600 012674 012727 000010 MOV #8,(PC)+
2601 012700 000000 1$: 0
2602 012702 006067 166240 2$: ROR TEMP2
2603 012706 005567 166236 ADC TEMP3
2604 012712 005367 177762 DEC 1$
2605 012716 001371 BNE 2$
2606 012720 006067 166224 ROR TEMP3

```



```

2607 012724 103404      BCS      3$
2608 012726 052767 000400 166210  BIS      #BIT8,TEMP1      ;SET ODD PARITY
2609 012734 000400      BR      3$
2610 012736 042767 000400 166200 3$:    BIC      #BIT8,TEMP1      ;CLR EVEN PARITY
2611                                ;TEMP1 NOW HAS ODD PARITY CHARACTER
2612 012744 000207      4$:    RTS      PC
2613
2614                                ;THIS ROUTINE CALCULATES EVEN PARITY FOR AN 8 BIT CHARACTER
2615 012746 016767 166172 166172  EVEN8:  MOV      TEMP1,TEMP2      ;SAVE TEMP1
2616 012754 005067 166170      CLR      TEMP3
2617 012760 012727 000010      MOV      #8.,(PC)+
2618 012764 000000      1$:    0
2619 012766 006067 166154      2$:    ROR      TEMP2
2620 012772 005567 166152      ADC      TEMP3
2621 012776 005367 177762      DEC      1$
2622 013002 001371      BNE      2$
2623 013004 006067 166140      ROR      TEMP3
2624 013010 103004      BCC      3$
2625 013012 052767 000400 166124  BIS      #BIT8,TEMP1      ;SET EVEN PARITY
2626 013020 000403      BR      4$
2627 013022 042767 000400 166114 3$:    BIC      #BIT8,TEMP1      ;CLR ODD PARITY
2628                                ;TEMP1 NOW HAS EVEN PARITY CHARACTER
2629 013030 000207      4$:    RTS      PC
2630 013032 062716 000002  TRPREG: ADD      #2,(SP) ;ALLOW IT TO 'CRUNCH' INTO HLT BACK
2631                                ;IN MAIN PART OF THE PROGRAM
2632 013036 000002      RTI
2633                                ;ERROR HLT TABLE
2634 013040 013124      .ERRTAB:  EMO      ;HLT 0 BIT ERROR (GENERAL)
2635 013042 000000      0
2636 013044 000000      0
2637 013046 013140      EM1      ;HLT 1 REGISTER ERROR
2638 013050 013311      DH1
2639 013052 013332      DT1
2640 013054 013202      EM2      ;HLT 2 RECEIVER ERROR
2641 013056 013311      DH1
2642 013060 013332      DT1
2643 013062 013244      EM3      ;HLT 3 TRANSMITTER ERROR
2644 013064 013311      DH1
2645 013066 013332      DT1
2646                                ;DEFAULT DU ADDRESSES
2647 013070 160040      RXCSR:  160040
2648 013072 160041      HRXCSR: 160041
2649 013074 160042      RXDBUF: 160042
2650 013076 160043      HRXDBUF: 160043
2651 013100 160042      PARCSR: 160042
2652 013102 160043      HPARCSR: 160043
2653 013104 160044      TXCSR:  160044
2654 013106 160045      HTXCSR: 160045
2655 013110 160046      TXDBUF: 160046
2656 013112 160047      HTXDBUF: 160047
2657                                ;DEFAULT DU VECTORS
2658 013114 000770      DURIV:  770      ;REC INTR VECTOR
2659 013116 000772      DURIS:  772      ;REC INTR STATUS
2660 013120 000774      DUTIV:  774      ;XMIT INTR VECTOR
2661 013122 000776      DUTIS:  776      ;XMIT INTR STATUS
2662                                ;ERROR MESSAGES

```

2663	013124	036440	042440	051122	EM0:	.ASCIIZ / = ERROR PC/
2664	013132	051117	050040	000103		
2665	013140	036440	051040	043505	EM1:	.ASCIIZ / = REGISTER ERROR PC/<15><12><1>/REGISTER /
2666	013146	051511	042524	020122		
2667	013154	051105	047522	020122		
2668	013162	041520	005015	051001		
2669	013170	043505	051511	042524		
2670	013176	020122	000040			
2671	013202	036440	051040	041505	EM2:	.ASCIIZ / = RECEIVER ERROR PC/<15><12><1>/REGISTER /
2672	013210	044505	042526	020122		
2673	013216	051105	047522	020122		
2674	013224	041520	005015	051001		
2675	013232	043505	051511	042524		
2676	013240	020122	000040			
2677	013244	036440	052040	040522	EM3:	.ASCIIZ / = TRANSMITTER ERROR PC/<15><12><1>/REGISTER /
2678	013252	051516	044515	052124		
2679	013260	051105	042440	051122		
2680	013266	051117	050040	006503		
2681	013274	000412	042522	044507		
2682	013302	052123	051105	020040		
2683	013310	000				
2684						:DATA HEADERS FOR ERROR MESSAGES
2685	013311	105	050130	041505	DH1:	.ASCIIZ /EXPECTED ACTUAL/
2686	013316	042524	020104	040440		
2687	013324	052103	040525	000114		
2688					.EVEN	
2689						:DATA TABLES FOR ERROR MESSAGES
2690	013332	000003			DT1:	3
2691	013334	006	004			.BYTE 6.4
2692	013336	001164				:REGISTER
2693	013340	006	004			.BYTE 6.4
2694	013342	001156				:EXPECTED DATA
2695	013344	006	002			.BYTE 6.2
2696	013346	001160				:ACTUAL DATA
2697		000001			.END	

AAA	002520	1178#																		
ACTREG	001216	898#	1062*	1126*	1140*	1141*	1148*	1230	1948	1951	1961									
ADDBAS	001306	938#	1058	1225*																
ADDKEE	001310	939#	1059	1226*																
ADDLAS	001312	940#	1060	1227*																
ADDROT	001322	944#	1063	1231*																
ADRCNT=	007541	2113*	2152*	2161#																
A10010=	***** GX	677																		
BASEAD	001204	893#	1058*	1065*	1108*	1145*	1146	1152*	1154*	1225	1955*	1967*	1971							
BASEDU	001364	961#	1072	1238*																
BASE IV	001212	896#	1064*	1118*	1229	1956*	1968*	1973	1974*	1975	1976*	1977	1978*	1979						
		1980*																		
BBB	002336	1125	1129#																	
BINWRD	010056	2202*	2203	2240#																
BITW =	002000	808#																		
BIT0 =	000001	756#	784	815																
BIT1 =	000002	755#	783																	
BIT10 =	002000	746#	774	808																
BIT11 =	004000	745#	773																	
BIT12 =	010000	744#	772	789																
BIT13 =	020000	743#	771	788	807															
BIT14 =	040000	742#	770	787	806															
BIT15 =	100000	741#	769	786	805	2589														
BIT2 =	000004	754#	782	1293																
BIT3 =	000010	753#	781	814																
BIT4 =	000020	752#	780	813																
BIT5 =	000040	751#	779	812																
BIT6 =	000100	750#	778	811																
BIT7 =	000200	749#	777	810																
BIT8 =	000400	748#	776	792	809	2608	2610	2625	2627											
BIT9 =	001000	747#	775	791																
BREAK =	000001	815#																		
BRW	007072	1290	1304	2041#																
BRX	007074	1291	1305	2042#																
BUFF1	000002R	677#	1267	1273																
BUFHRX	001346	954#	1076																	

HRXCSR	013072	1074*	1240	2563*	2648#														
HRXDBJ	013076	1076*	1242	2568*	2650#														
HTXCSR	013106	1080*	1246	2573*	2654#														
HTXDBJ	013112	1082*	1248	2577*	2656#														
ICOUNT	001122	858#	2033	2037*															
INBUF	012224	1181	1185	2074	2116	2248	2252	2540#											
INIFLG	001244	919#	1019	1022*															
INSTR=	104404	979#	1189	2135	2257														
INSTR =	104403	977#	1098	1109	1119	1130	1155	1165	1179	1192	1196	1200	1204	1295					
		1308	2393																
INSTR2	007320	2085	2100#																
ISYMOD=	000000	796#																	
IVBASE	001314	941#	1064	1229*															
IVKEEP	001316	942#	1061	1228*															
JMRBY	001203	889#	1057*	1207	1224	1790	1867												
KEEPAD	001206	894#	1059*	1065	1106*	1108	1152	1154	1226	1967									
KEEPIV	001214	897#	1061*	1117*	1228	1968													
LASTAD	001210	895#	1060*	1135	1146	1160	1227												
LESS1	012436	1070*	1237	2553*	2554*	2555*	2558#												
LEVEL0=	000000	766#																	
LEVEL1=	000040	765#																	
LEVEL2=	000100	764#																	
LEVEL3=	000140	763#																	
LEVEL4=	000200	762#	2558																
LEVEL5=	000240	761#	2557																
LEVEL6=	000300	760#																	
LEVEL7=	000340	759#																	
LIGHTS	001102	847#	1024*	1033*	1991*														
LIMITS	007462	2126	2140#																
LOBITS	007540	2112*	2144	2160#	2161														
LOCK	001120	857#	1336*	1426*	1516*	1606*	2049												
LOGICA	006660	1995#																	
LOKFLG	001247	922#	1298	1299															
LOLIM	007532	2109*	2142	2157#															
LPCNT	001124	859#	1010*	2032*	2033	2036*													
LSTERR	001134	863#	1015*	1988*	2278	2280*	2366*												
L1ESS	001336	950#	1070	1237*															
MAP	001634	1037	1039	1047#															
MCOW	011257	1950	2447#																
MCRLF	011434	1277	2082	2098	2190	2399	2467#												
MDATA	012324	2216	2227	2542#															
MEPASS	011524	1943	2477#																
MEXT =	010000	819#	1798	1875															
MEXTJ	012115	1205	2523#																
MINT =	004000	818#	1341	1431	1521	1611	1696	1746											
MITSEX	001301	930#	1053	1220*															
MLASTD	011164	1131	2436#																
MLEVEL	011633	1166	2490#																
MLOCK	011570	1296	2484#																
MMULT	011105	1120	2428#																
MPFAIL	011437	2364	2468#																
MQM	011430	2095	2466#																
MR	011551	1318	2481#																
MRANGE	011347	1156	2457#																
MREGAD	011024	1099	2419#																
MRESET=	000400	809#	1337	1402	1427	1492	1517	1582	1607	1672	1690	1692	1740	1742					

[illegible]

RTS	=	000004	2370														
RUNA	=	*****	782#														
RUNB	=	*****	1	53	70	148	664										
RUNC	=	*****	1	53	70	148	664										
RUND	=	*****	1	53	70	148	664										
RUNE	=	*****	1	53	70	148	664										
RUNF	=	000000	1	53	70	148	664										
RUNIT		006430	1949	1955#	1962												
RXCSR		013070	1073*	1239	1343*	1352	1376	1403	1433*	1442	1466	1493	1523*	1532	1556		
			1583	1613*	1622	1646	1673	1703*	1719	1753*	1769	1805*	1845	1882*	1922		
			1985	2561*	2647#												
RXDBUF		013074	1075*	1241	1338	1382	1428	1472	1518	1562	1608	1652	1700	1723	1750		
			1773	1802	1849	1879	1926	2565*	2649#								
RXDONE=		000200	777#														
RXERR	=	100000	786#														
SAVPC		001174	882#	2165*	2330												
SAVR0		001156	875#	2174*	2179	2694											
SAVR1		001160	876#	2173*	2180	2696											
SAVR2		001162	877#	2172*	2181												
SAVR3		001164	878#	2171*	2182	2692											
SAVR4		001166	879#	2170*	2183												
SAVR5		001170	880#	2169*	2184												
SAVSP		001172	881#	2341*	2348												
SAVO5	=	104406	983#	2282													
SCOPE	=	104400	971#	1410	1500	1590	1680	1730	1780	1857	1934						
SCOP1	=	104401	973#	1392	1482	1572	1662										
SEND	=	000020	813#	1341	1431	1521	1611	1696	1746	1798	1875						
SEREC		001200	886#	1054*	1199	1221											
SETFG		003144	1260	1262#													
SETFLG=		104412	991#	1121	1194	1198	1202	1206	1297								
SEVEN	=	004000	799#	1520													
SEXMIT		001177	885#	1053*	1195	1220											
SHIFT		001140	868#	1365*	1369*	1455*	1459*	1545*	1549*	1635*	1639*	1707*	1712*	1713	1717		
			1757*	1762*	1763	1767	1821*	1838*	1839	1843	1898*	1915*	1916	1920	2593*		
			798#	1430													
SIX	=	002000	2201*	2220	2223*	2239#											
SPACNT=		010055	774#														
SRD	=	002000	728#	1008	1284	2325	2357										
STACK	=	001100	929#	1268	1271												
STATUS		001300	781#														
STD	=	000010	920#	1011*													
STFLG		001245	776#														
STPSYN=		000400	2169#														
SV05		007550	846#	1023*	1028	1032*	1038	1047	1085	1217	1293	1306	2023	2030	2047		
SwR		001100	2276	2312	2320	2322	2381										
			837#	1032	1038	2381	2397	2404									
SwREG		000176	2392	2402#													
SwREGC		010714	708#	1085													
Sw00	=	000001	707#	1306													
Sw01	=	000002	706#														
Sw02	=	000004	705#														
Sw03	=	000010	704#														
Sw04	=	000020	703#														
Sw05	=	000040	702#														
Sw06	=	000100	701#	1047	1217												
Sw07	=	000200															

[illegible]

CZDUF-D MACY11 30A(1052) 21-NOV-78 15:52 PAGE 69
CZDUFD.P11 18-JUL-78 15:59 CROSS REFERENCE TABLE -- MACRO NAMES

M 5

SEQ 0064

\$WORDF 677#
\$WORDO 677#
\$WORDP 677#

. ABS. 013350 000

ERRORS DETECTED: 0

CZDUFD.BIN,CZDUFD.SEQ/CRF/SOL/NL:TOC=CZDU11.HLO/EQ:RUNF,CZDU11.PAR,CZDU11.KET,CZDUFD.P11
RUN-TIME: 6 9 .9 SECONDS
RUN-TIME RATIO: 103/16=6.1
CORE USED: 18K (35 PAGES)