

DL11

OVERLAY FOR ITEP
MD-11-DZDLO-C

EP-DZDLO-C-DL-A
COPYRIGHT © 1976
FICHE 1 OF 1

NOV 1976
digital
MADE IN U.S.A

IDENTIFICATION

PRODUCT CODE: MAINDEC-11-DZDLO-C-D
PRODUCT NAME: DL11 OVERLAY FOR INTERPROCESSOR TEST PROGRAM
PROGRAM DATE: OCTOBER 1976
MAINTAINER: DIAGNOSTICS
AUTHORS: R A JONES
JOHN EGOLF
REVISED BY: FAY BASHAW 1/21/75

THE INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION. DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT.

THE SOFTWARE DESCRIBED IN THIS DOCUMENT IS FURNISHED UNDER A LICENSE AND MAY ONLY BE USED OR COPIED IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE.

DIGITAL EQUIPMENT CORPORATION ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT THAT IS NOT SUPPLIED BY DIGITAL.

COPYRIGHT (C) 1973, 1976, BY DIGITAL EQUIPMENT CORPORATION

1.0 ABSTRACT.

THIS PROGRAM IS DESIGNED AS A MAINTENANCE AID FOR FIELD SERVICE PERSONEL. IT WILL VERIFY THE PROPER OPERATION OF A COMPLETE COMMUNICATION LINK FROM ONE PDP-11 SYSTEM TO ANOTHER OR TO A COMMUNICATION TEST CENTER.

THIS PROGRAM MUST BE USED IN CONJUNCTION WITH THE INTERPROCESSOR TEST PROGRAM(DZITP) ON A PDP-11 SYSTEM WITH A DL-11 INTERFACE.

2.0 REQUIREMENTS.

2.1 EQUIPMENT

- A. PDP-11 SYSTEM WITH 4K OF CORE.
- B. A DL11 COMMUNICATION INTERFACE.

2.2 STORAGE.

4K OF CORE

3.0 LOADING PROCEDURE

THIS PROGRAM IS IN ABSOLUTE FORMAT.
THE ABS LOADER MUST BE USED TO LOAD THE PROGRAM.

4.0 OPERATING PROCEDURES.

- A. TWO METHODS OF ENTERING PARAMETERS ARE PROVIDED
 - 1. LOAD ADDRESS 200 AND START TO ENTER PARAMS FROM CONSOLE TTY, PROCEED TO SECTION B.
 - 2. LOAD ADDRESS 200 AND SET SWITCH REGISTER BIT 15 BEFORE STARTING TO ENTER PARAMS FROM CONSOLE SWITCHES, PROCEED TO SECTION C.
- *THE PROGRAM MAY BE RESTARTED AT LOC 204 (ONCE PARAMETERS HAVE BEEN SELECTED)
- B. CONSOLE DIALOGUE PARAMETER INPUT (CURRENT VALUES FOR PARAMETERS ARE FOUND IN OVERLAY)

- 1. THE PROGRAM WILL TYPEOUT THE NAME OF THE VARIABLE OVERLAY.
 - A. IF YOU WISH TO SETUP JUST THE INDICATED OVERLAY, TYPE A CARAGE RETURN
 - B. IF YOU WISH TO SETUP A DN11, TYPE IN DN.
 - C. IF YOU WISH TO SETUP A DN11BB, TYPE IN DMB.

IF DN OR DMB WAS TYPED IN STEP 1 ABOVE THEN THE BUS ADDRESS, VECTOR ETC. REFERED TO IN STEPS 2 THRU 7, PERTAIN TO THE DN11 OR DN11BB.

- 2. THE PROGRAM WILL TYPE THE DEFAULT BUS ADDRESS OF THE INTERFACE UNDER TEST.
 - A. TYPE A CAR. RETURN TO USE DEFAULT BUS ADDRESS
 - B. TYPEIN ACTUAL BUS ADDRESS
- 3. THE PROGRAM WILL TYPE OUT THE DEFAULT VECTOR ADDRESS
 - A. TYPE A CAR. RETURN TO USE DEFAULT ADDRESS
 - B. TYPEIN ACTUAL VECTOR ADDRESS
- 4. THE PROGRAM WILL TYPE OUT THE DEFAULT INTERFACE PRIORITY
NOTE: 200=PRIO 4, 240=PRIO 5, 300=PRIO 6, ETC.

- A. TYPE A CAR. RETURN TO USE DEFAULT VALUE
 - B. TYPE IN ACTUAL VALUE
5. THE PROGRAM WILL TYPEOUT THE DEFAULT VALUE OF PARAM#1
IF REQUIRED BY THE ISR. (SEE SECT. 10.0 IN OVERLAY LISTING FOR PARAMETER DESCRIPTION)
- A. TYPE A CAR. RETURN TO USE DEFAULT VALUE
 - B. TYPE IN ACTUAL VALUE
6. THE PROGRAM WILL TYPEOUT THE DEFAULT VALUE OF PARAM#2
IF REQUIRED BY THE ISR.
- A. TYPE A CAR. RETURN TO USE DEFAULT VALUE
 - B. ENTER ACTUAL VALUE
7. THE PROGRAM WILL TYPEOUT THE DEFAULT VALUE OF PARAM#3
IF REQUIRED BY THE OVERLAY.
- A. TYPE A CAR. RETURN TO USE DEFAULT VALUE
THE DN-11 WILL USE PARAM #3 AS THE # TO DIAL.
IF USING A MODEM WITHOUT AUTOMATIC HANDSHAKING,
THE NUMBER MUST TERMINATE WITH A
"END-OF-NUMBER" CHARACTER (:).
 - B. ENTER ACTUAL VALUE.
8. THE PROGRAM WILL RETURN TO STEP B1 IF THIS SETUP
WAS FOR DN11 OR DN11EB.
9. THE PROGRAM WILL REQUEST THAT SWITCH REGISTER BE SET.
- A. SETUP SWITCH REGISTER AS SPECIFIED IN STEP D.
AND TYPE A CAR. RETURN.

NOTE: IF ANY OF THE ABOVE ITEMS 2 THRU 7 WERE CHANGED BY ENTERING
NEW VALUES, THE NEW VALUE BECOMES THE DEFAULT VALUE FOR SUBSEQUENT
RESTARTS OF THE PROGRAM.

- C. MANUAL PARAMETER INPUT FROM SWITCH REGISTER
1. THE PROGRAM HALTS FOR ISR (INTERFACE SERVICE ROUTINE) SPECIFICATION
 SWR14=SETUP DN-11B ISR
 SWR13=SETUP DN-11 ISR
 SWR=000000=SETUP VARIABLE ISR
 2. THE FOLLOWING HALTS ARE REPEATED FOR EACH ISR SPECIFIED.
 SETUP SEQUENCE IS: DN11, DN11-BB THEN VARIABLE OVERLAY. (EACH ENTRY SET SWITCHES THEN HIT CONTINUE.)
 - A. HALT FOR BUS ADDRESS OF INTERFACE
 - B. HALT FOR VECTOR ADDRESS OF INTERFACE
 - C. HALT FOR PRIORITY OF INTERFACE
 - D. HALT FOR INTERFACE PARAM #1 (SEE SECT. 10.0 IN OVERLAY LISTING FOR PARAMETER DESCRIPTION)
 - E. HALT FOR INTERFACE PARAM #2 (DN11 AND DNBB PARAMETERS ARE DISCUSSED IN SECT. 10.0 OF THE MONITOR.)
 - F. GO BACK TO STEP A IF THIS SETUP WAS FOR DN OR DNBB.
 3. HALT FOR OPERATIONAL SWITCH SETTINGS. (SEE STEP D.)
 - A. PRESS CONTINUE TO START TESTING

BEFORE ATTEMPTING TO RUN THIS PROGRAM, THE OPERATOR MUST ASCERTAIN THE COMPLETE COMMUNICATION LOOP AND PROCEDURES TO BE USED, INCLUDING THE TYPE OF MODEMS, THE TYPE OF INTERFACE BEING USED AT THE OTHER CPU AND THE MODES OF OPERATION, DATA AND PARAMETERS TO BE USED AT EACH CPU.

THIS WILL REQUIRED VOCAL COMMUNICATION WITH THE OPERATOR AT THE OTHER CPU UNLESS ITS CONFIGURATION AND OPERATION ARE FIXED AS A TEST CENTER.

AFTER DETERMINING THAT THE EQUIPMENTS ARE COMPATIBLE AND AGREEING ON THE MODE AND VARIABLE PARAMETERS TO BE USED, THE SYSTEM WHICH IS TO RECEIVE DATA FIRST SHOULD BE LOADED AND STARTED. IF THE MODEM BEING USED ON THIS SYSTEM HAS AN AUTOMATIC ANSWER FEATURE, IT SHOULD BE ENABLED.

THE SYSTEM WHICH IS TO TRANSMIT FIRST SHOULD THEN BE LOADED AND STARTED AND THE CONNECTION ESTABLISHED EITHER MANUALLY OR AUTOMATICALLY (VIA DN-11).

F01

D. OPERATIONAL SWITCH SETTINGS.

- SW15=1 HALT ON ERROR
- SW14=1 SINGLE PASS
 - SW14 HAS NO EFFECT IF SW04=0
- SW13=1 INHIBIT ERROR TIMEOUTS
- SW12=1 INHIBIT ALL TIMEOUTS EXCEPT ERRORS
 - IF SW12=0 AND SW04=1 END PASS IS TYPED
 - AND TRANSMITTED/RECEIVED DATA IS TYPED.
- SW11=1 USE PREVIOUSLY SPECIFIED DATA
- SW10=1 DATA SELECT (WITH SW09)
- SW09=1 DATA SELECT (WITH SW10)
 - 00=1 GET DATA FROM OPERATOR
 - 01=1 TEST MESSAGE #1 (\$A QUICK BROWN FOX)
 - 10=1 TEST MESSAGE #2 (\$B NUMERICS)
 - 11=1 TEST MESSAGE #3 (\$C CONTEST/QUICK BROWN FOX/NUMERICS)
- SW08=1 TRANSMIT RECEIVED DATA (INTERNAL LOOPBACK MODE)
- SW07=1 DO NOT TEST RECEIVED DATA
- SW06=1 MONITOR TRANSMITTED DATA ON CONSOLE TTY.*
- SW05=1 MONITOR RECEIVED DATA ON CONSOLE TTY.*
 - * IN MANY CASES, NOT ALL DATA WILL APPEAR ON THE CONSOLE TTY. THIS IS ESPECIALLY TRUE WHEN THE COMM INTERFACE IS RUNNING AT A FASTER BAUD THAN THE CONSOLE, BUT EVEN AT EQUAL OR SLOWER BAUDS, ALL CHARACTERS MAY NOT APPEAR ON THE CONSOLE.
- SW04=1 RETURN TO MONITOR FOR END PASS
 - WHEN SW04=0 PROGRAM LOOPS IN THE OVERLAY NEVER RETURNING TO THE MONITOR.
- SW03=1 INTERNAL LOOPBACK MODE
- SW02=1 EXTERNAL LOOPBACK MODE
- SW01=1 ONE-WAY-IN MODE
- SW00=1 ONE-WAY-OUT MODE

THIS PROGRAM HAS BEEN MODIFIED TO RUN ON A PROCESSOR WITH OR WITHOUT A HARDWARE SWITCH REGISTER. WHEN FIRST EXECUTED THE PROGRAM TESTS THE EXISTENCE OF A HARDWARE SWITCH REGISTER. IF NOT FOUND A SOFTWARE SWITCH REGISTER LOCATION (SWREG=LOC. 176) IS DEFAULTED TO. IF THIS IS THE CASE, UPON EXECUTION THE CONTENTS OF THE SWREG ARE DUMPED IN OCTAL ON THE CONSOLE TTY AND ANY CHANGES ARE REQUESTED

(IE) SWP:XXXXXX NEW=

POSSIBLE RESPONSES ARE:

1. <CR> IF NO CHANGES ARE TO BE MADE
2. 6 DIGITS 0-7 TO REPRESENT IN OCTAL THE NEW SWITCH REGISTER VALUE -LAST DIGIT FOLLOWED BY <CR>.
3. ↑U TO ALLOW REENTERING VALUE IF ERROR IS COMMITTED KEYING IN SWREG VALUE.

BUILT INTO THE PROGRAM IS THE ABILITY TO DYNAMICALLY CHANGE THE CONTENTS OF SWREG DURING PROGRAM EXECUTION. BY STRIKING ↑G (CNTRL G) ON CONSOLE TTY THE OPERATOR SETS A REQUEST FLAG TO CHANGE THE CONTENTS OF SWREG, WHICH IS PROCESSED IN KEY AREAS OF THE PROGRAM CODE (IE) ERROR ROUTINES, AFTER HALTS END OF PASS, AND OTHER APPLICABLE AREAS.

IF OPERATOR SPECIFIED DATA WAS INDICATED, THE PROGRAM WILL TYPE A REQUEST FOR THE DATA. DATA MAY BE ENTERED AS ASCII CHARACTERS OR OCTAL CODE. TYPE IN THE DATA TERMINATED WITH A CR. OCTAL CODE MAY BE ENTERED BY TYPING AN ↑(UP ARROW) FOLLOWED BY THE OCTAL CODE (IN THE RANGE 000 TO 377) SEPERATED BY SPACES AND TERMINATED BY ↑(UP ARROW).
I.E. ABCD↑ 000 123 377↑ EFG (CAR.RETURN)

A TYPICAL SWITCH SETTING FOR HALF-DUPLEX=003150 THIS SETTING USES INTERNAL LOOPBACK MODE, LOOPS IN OVERLAY, MONITORS TRANSMITTED AND RECEIVED DATA ON THE CONSOLE TTY, AND TESTS RECEIVED DATA USING TEST MESSAGE #3.

A TYPICAL SWITCH SETTING FOR FULL-DUPLEX=003144 THIS SETTING IS THE SAME AS ABOVE EXCEPT IT USES THE EXTERNAL LOOPBACK MODE.

ALL STANDARD MESSAGES (TEST MESSAGES 1-3) ARE PRECEDED BY 2 FILL CHARACTERS(177), AND ARE FOLLOWED BY A CR(015), LF(012) RECEIVE TERMINATING CHARACTER(001), 4 FILLS(177), AND A TRANSMIT TERMINATING CHARACTER(000). DURING TRANSMISSION, WHEN A 000 CHARACTER IS SEEN THE TRANSMISSION IS STOPPED. DURING RECEPTION, WHEN A 001 CHARACTER IS RECEIVED, THE RECEIVER IS SHUT OFF. IF THE MESSAGE WAS INPUTED BY THE OPERATER, THE TERMINATING CHARACTERS ARE ADDED.

TEST MODES

INTERNAL LOOPBACK MODE

1. THE OVERLAY WAITS TO RECEIVE A MESSAGE (TERMINATED BY (001))
2. VERIFIES THE DATA AGAINST THE DATA SELECTED BY SW09 AND SW10 (SW7=0)
3. TRANSMIT THE DATA SELECTED BY SW09 AND SW10 (SW9=0) OR TRANSMIT THE RECEIVED DATA (SW8=1)
4. RETURNS TO MONITOR FOR "END PASS" (SW4=1) OR GO TO STEP 1. (SW4=0)

EXTERNAL LOOPBACK MODE

1. THE OVERLAY SETS REQUEST TO SEND
2. WAIT FOR CLEAR TO SEND
3. TRANSMITS THE SELECTED DATA
4. RESETS REQUEST TO SEND
5. WAIT FOR MESSAGE TO BE RECEIVED
6. VERIFIES THE DATA (SW07=0)
7. RETURNS TO MONITOR FOR "END PASS". (SW04=1) OR GO TO STEP 1 (SW04=0)

ONE-WAY-IN MODE

1. THE OVERLAY WAITS FOR MESSAGE TO BE RECEIVED.
2. VERIFIES THE DATA (SW07=0)
3. RETURNS TO MONITOR FOR "END PASS" (SW04=1) OR GO TO STEP 1 (SW04=0)

ONE-WAY-OUT MODE

1. THE OVERLAY SETS REQUEST TO SEND
2. WAITS FOR CLEAR TO SEND
3. TRANSMITS SELECTED DATA
4. RETURNS TO MONITOR FOR "END PASS". (SW04=1) OR GO TO STEP 1 (SW04=0)

E. THE OVERLAY IS THEN ENTERED AND A CONNECTION ESTABLISHED EITHER MANUALLY OR AUTOMATICALLY.

IF ONE-WAY-IN OR INTERNAL LOOPBACK MODES ARE SELECTED.
THE OVERLAY WILL SET DATA TERMINAL READY AND WAIT FOR DATA.

IF ONE-WAY-OUT OR EXTERNAL LOOPBACK MODES WERE SELECTED.
THE OVERLAY WILL SET DATA TERMINAL READY AND REQUEST TO SEND.
THE OVERLAY WILL THEN WAIT FOR CLEAR TO SEND BEFORE ATTEMPTING TO TRANSMIT DATA.

THE PROGRAM WILL PRINTOUT A "WAITING FOR CLEAR TO SEND"
MESSAGE AND THE CONTENTS OF THE XMIT CSR EVERY 60 SECS.
UNTIL CLEAR TO SEND IS ASSERTED.

F. IF SW04=0 THE OVERLAY WILL CONTINUE TO TRANSMIT/RECEIVE DATA.

IF SW04=1 THE OVERLAY WILL RETURN TO THE MONITOR AND TYPE "END PASS".

IF BOTH SW04=1 AND SW14=1, THE PROGRAM WILL REQUEST NEW INTERFACE PARAMS AFTER ONE PASS OF THE SELECTED TEST MODE.

TEST EXECUTION MAY BE INTERRUPTED BY TYPING THE FOLLOWING CHARACTERS ON THE CONSOLE TTY.

LINE FEED = RESTART PROGRAM AT LOCATION 200.

QUESTION MARK = PRINTOUT FIRST 8 WORDS OF INPUT BUFFER.(ASCII)

THEN TYPE EITHER:

*WXXXXXX

TO PRINTOUT THE 8 WORDS AT LOC XXXXXX.

*BXXXXXX

TO PRINTOUT THE 16 BYTES AFTER LOC XXXXXX.

*C

TO CONTINUE

PROGRAM MUST BE RESTARTED AT 200 AFTER PRINTING.
CARRIAGE RETURN = RESTART AT REQUEST FOR NEW OPERATIONAL SWITCHES.

5.0 PROGRAM AND/OR OPERATOR ACTION

IF THE OPERATOR WISHES TO MANUALLY EXAMINE THE TRANSMIT OR RECEIVE BUFFERS, DO THE FOLLOWING: TO FIND THE STARTING ADDRESS OF THE RECEIVE BUFFER, LOAD ADDRESS 11020 AND EXAMINE. TO FIND THE STARTING ADDRESS OF THE TRANSMIT BUFFER, LOAD ADDRESS 11012 AND EXAMINE.

5.1 NORMAL HALTS SEE SECTION 4.

6.0 ERRORS

6.1 ERROR REPORTING

THE ONLY ERROR REPORT FROM THE CONTROL PROGRAM OCCURS IF THE INTERFACE SPECIFIED IS NOT LOADED.

IF DATA IS RECEIVED AND SWITCH 7 (NO DATA COMPARE) IS RESET, THE DATA WILL BE COMPARED AGAINST THE PRESELECTED DATA AFTER A LINE FEED CHARACTER IS RECEIVED. IF THERE IS A MISMATCH, THE FOLLOWING ERROR REPORT IS PRINTED:

RECEIVED DATA=RRRRRR
DATA SHOULD BE TTTTTT
DATA COMPARE ERROR; BAD DATA=BBB GOOD DATA=GGG

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 10
 DZDLOC.P11 29-OCT-76 10:28

WHERE RRRRRR IS THE RECEIVE BUFFER (UP TO 512 CHARACTERS)
 TTTTTT IS THE TRANSMIT BUFFER (UP TO 512 CHARACTERS)
 BBB IS THE BAD DATA CHARACTER
 GGG IS THE GOOD DATA CHARACTER

IF THE INTERFACE DETECTS A DATA ERROR, THE FOLLOWING
 WILL BE PRINTED BEFORE THE DATA IS COMPARED:

THERE WAS A RECEIVER ERROR. RECEIVER DATA REGISTER =XX<XXX

WHERE XXXXXX IS THE CONTENTS OF THE RECEIVER DATA REGISTER
 THE LOW BYTE IS THE DATA, AND THE HIGH BYTE IS THE ERROR BITS.

IF A RECEIVE TERMINATING CHARACTER<DD:> IS NOT DETECTED
 WITHIN 512 CHARACTERS A "BUFFER FULL" PRINTOUT WILL OCCUR.

7.0 RESTRICTIONS

THE OPERATION OF THIS PROGRAM REQUIRES COORDINATION BETWEEN
 THE OPERATOR AND THE OPERATOR OF ANOTHER PDP-11 SYSTEM
 UNLESS ONE OF THE SYSTEMS IS ALWAYS OPERATING IN A FIXED
 MODE. THE FOLLOWING TABLE LISTS THE VALID COMBINATIONS:

CPU #1	CPU #2
ONE-WAY-OUT	ONE-WAY-IN
ONE-WAY-IN	ONE-WAY-OUT
EXTERNAL-LOOPBACK	INTERNAL-LOOPBACK
INTERNAL-LOOPBACK	EXTERNAL-LOOPBACK
EXTERNAL-LOOPBACK	EXTERNAL-LOOPBACK (FULL DUPLEX)

WHEN THE COMMUNICATION LINK INVOLVES MODEMS THE FOLLOWING
 RESTRICTION APPLY:

IF RUNNING IN FULL DUPLEX MODE BOTH SYSTEMS
 MUST BE IN EXTERNAL LOOP BACK MODE.

BOTH SYSTEMS SHOULD BE RUNNING IDENTICAL ROUTINES.

EXAMPLE:
 SWITCHES 14,13,7,4 SHOULD BE THE SAME
 ON BOTH CPU'S

IF PROGRAM IS WAITING IN A SCAN ROUTINE AND TYPES OUT
 A "WAITING MESSAGE", IF AN INCOMING MESSAGE STARTS DURING
 THE TYPE OUT, IT WILL BE LOST BECAUSE THE TYPEOUT PRIORITY
 IS AT LEVEL 7. THIS WILL RESULT IN OVERRUN OR SILENCE OVER-
 RUN ERRORS, DEPENDING ON THE DEVICE. TO AVOID THIS SITUATION
 RUN WITH SWITCH 13 UP. IF OVERRUN DOES OCCURE DURING A
 TYPEOUT THE PROGRAM SHOULD BE RESTARTED.

IF USING AN ASYNCHRONOUS DEVICE, MODEMS AND THE
 MAYNARD TEST STATION AND INITIALIZE DOES NOT CLEAR THE
 CONNECTION (EXAMPLE THE DJ11) IF THE PROGRAM IS RESTARTED
 IN THE MIDDLE OF A MESSAGE AT LOC 204 OR BY HITTING CR
 AN IMMEDIATE ERROR MESSAGE FROM MAYNARD WILL BE RE-

CEIVED. THIS IS BECAUSE THE TEST STATION IS STILL LOOKING FOR THE REST OF THE INTERRUPTED MESSAGE. TO AVOID THIS ERROR, RESTART PROGRAM ONLY AT THE END OF THE MESSAGE CURRENTLY BEING TRANSMITTED.

8.0 MISCELLANEOUS

ITEP WAS CHECKED OUT USING THE FOLLOWING BELL TELEPHONE MODEMS.
201A (HALF-DUPLEX SYNC #RONOUS 2000 BAUD)
202C (HALF-DUPLEX ASYNCHRONOUS 1200 BAUD)
103A (FULL-DUPLEX ASYNCHRONOUS 110 BAUD)

9.0 PROGRAM DESCRIPTION

9.1 THE DL11 INTERFACE SERVICE PARAMS ARE SETUP, AS SPECIFIED BY THE OPERATOR, BY THE ITEP CONTROL PROGRAM.

TIME: PROVIDES A MEANS OF MEASURING ELAPSED TIME. IT IS INCREMENTED EVERY SECOND BY A CLOCK INTERRUPT ROUTINE IN ITEP.

9.2 WHEN THE OVERLAY IS FIRST ENTERED BY ITEP AT LOCATION START:, THE CONTENTS OF THE SWITCH REGISTER ARE STORED IN REGISTER 0. THE MODE AND DATA SELECTIONS ARE FIXED AT THIS TIME AND CANNOT BE ALTERED WITHOUT RETURNING TO THE CONTROL PROGRAM. THE INTERRUPT VECTORS AND VARIABLES ARE THEN SETUP. THE SELECTED ROUTINE DETERMINED BY THE MODE IS THEN ENTERED

9.3 THE OVERLAY THEN LOOPS IN ROUTINES: \$OWI, IF "ONE WAY IN" MODE WAS SELECTED. \$OWO, IF "ONE WAY OUT" MODE WAS SELECTED. \$ILB, IF "INTERNAL LOOP BACK" MODE WAS SELECTED. \$XLB, IF "EXTERNAL LOOP BACK" WAS SELECTED.

9.31 \$OWI: IN THIS ROUTINE THE RECEIVER IS INITIALIZED AND PROGRAM LOOPS WAITING FOR THE RECEIVER TO FINISH. IF NOTHING IS RECEIVED FOR 60 SECS A "WAITING" MESSAGE IS TYPED. WHEN THE RECEIVER IS DONE, THE PROGRAM CHECKS DATA IF SWITCHES PERMIT, AND TYPES END PASS DEPENDING ON SWITCH SETTINGS.

9.32 \$OWO: THE TRANSMITTER IS INITIALIZED AND PROGRAM LOOPS WAITING FOR TRANSMITTER TO FINISH. A "WAITING" MESSAGE IS TYPED EVERY 60 SECS IF THERE IS NO ACTION. WHEN THE TRANSMITTER IS DONE, THE PROGRAM EITHER LOOPS BACK TO \$OWO OR TYPES END PASS DEPENDING ON SWITCH SETTINGS.

9.33 \$ILB: THE RECEIVER IS INITIALIZED AND PROGRAM LOOPS WAITING FOR RECEIVER TO FINISH. A "WAITING" MESSAGE IS TYPED EVERY 60 SEC IF NO ACTION. WHEN RECEIVER IS DONE PROGRAM CHECKS DATA IF SWITCH SETTINGS PERMIT, AND END PASS IS TYPED IF SWITCH SETTINGS PERMIT. THEN THE TRANSMITTER IS INITIALIZED, A "WAITING" MESSAGE IS TYPED EVERY 60 SEC IF NO ACTION. WHEN TRANSMITTER IS DONE PROGRAM RETURNS TO START OF ROUTINE. (\$ILB)

9.34 \$XLB: IF IN HALF DUPLEX THE TRANSMITTER IS INITIALIZED, A "WAITING MESSAGE IS TYPED EVERY 60 SEC IF THERE IS NO ACTION

WHEN THE TRANSMITTER IS DONE THE RECEIVER IS INITIALIZED
A "WAITING" MESSAGE IS TYPED EVERY 60 SEC IF THERE IS NO ACTION.
WHEN THE RECEIVER IS DONE DATA IS CHECKED IF SWITCH SETTINGS
PERMIT AND END PASS IS TYPED IF SWITCHES ALLOW. THE PROGRAM NOW
REPEATS CYCLE STARTING AT \$XLB.
IF IN FULL DUPLEX THE RECEIVER AND TRANSMITTER ARE INITIALIZED
A "WAITING" MESSAGE IS TYPED EVERY 60 SEC IF THERE IS NO
ACTION. WHEN BOTH THE RECEIVER AND TRANSMITTER ARE DONE DATA IS
CHECKED. END PASS IS TYPED AND PROGRAM LOOPS TO \$XLB DEPENDING
ON THE SWITCH SETTINGS.

- 9.4 THE RETURN TO MONITOR ROUTINE FOR END PASS AT EOP:
LOCK; OUT INTERRUPTS AND SAVES THE TRANSMITTER INTERRUPT ENABLE
BIT AND ALL GENERAL REGISTERS. IT THEN RETURNS TO THE MONITOR
TO TYPE "END PASS". THE MONITOR CHECKS SW14 IF UP IT RETURNS
TO ENTER; OTHERWISE IT RESTARTS THE PROGRAM.
- 9.5 ENTER: IS ENTERED FROM THE MONITOR AFTER TYPEING "END PASS",
IT RESTORES THE GENERAL REGISTERS AND THE TRANSMITTER CSR
R1, SAVED IN EOP. THE DELAY FLAG IS SET AND PROGRAM RETURNS TO
THE SCAN ROUTINE (OWO, OWI, ILB, XLB) WHERE IT CAME FROM.
- 9.6 THE INITIALIZE TRANSMIT SUBROUTINE AT STARTX:
SETS UP THE INTERFACE AND POINTERS NECESSARY TO
INITIATE A TRANSMIT OPERATION.
AFTER SETTING "DATA TERMINAL READY" AND "REQUEST TO SEND" A CHECK
IS MADE ON PARAM2 TO DETERMINE IF HALF DUPLEX OPERATION
WAS SELECTED BY THE OPERATOR. IF IT WAS, THE
SUBROUTINE WAITS FOR CLEAR TO SEND.
A 'WAITING FOR CLEAR TO SEND' PRINTOUT OCCURS
EVERY 30 SECONDS UNTIL CLEAR TO SEND IS ASSERTED.
- 9.7 THE INITIALIZE RECEIVED SUBROUTINE AT STARTR:
SETS UP THE INTERFACE AND POINTERS NECESSARY TO
RECEIVE A MESSAGE.
- 9.8 THE TRANSMIT INTERRUPT SERVICE ROUTINE.
AT XISR: IS ENTERED VIA TRANSMIT INTERRUPTS
FROM THE INTERFACE.
A TEST IS MADE TO SEE IF THE LAST CHARACTER
TRANSMITTED WAS A NULL (ALL ZEROS) CHARACTER.
IF IT WAS; THE TRANSMIT LOGIC IN THE INTERFACE
IS RESET AND THE TRANSMIT COMPLETE FLAG IS SET.
AT XISR1: THE NEXT CHARACTER IS TRANSMITTED
AND PRINTED ON THE TTY IF THE MONITOR TRANSMIT
SWITCH IS SET.
- 9.9 THE RECEIVE INTERRUPT SERVICE ROUTINE
AT RISR: IS ENTERED VIA RECEIVER INTERRUPTS
FROM THE INTERFACE.
THE RECEIVED CHARACTER IS STORED IN
THE INPUT BUFFER AND PRINTED ON THE TTY IF
THE MONITOR RECEIVER SWITCH IS SET.
IF THE INPUT BUFFER IS FULL, A 'BUFFER FULL'
PRINTOUT WILL OCCUR. THIS INDICATES THAT A
LINE FEED CHARACTER WAS NOT RECOGNIZED

IN THE RECEIVED DATA (WITHIN 1000 CHARACTERS).
IF THE RECEIVED CHARACTER IS A LINE FEED,
THE RECEIVED LOGIC IS RESET AND THE
RECEIVE COMPLETE FLAG IS SET.
IF A 'RECEIVE ERROR' IS DETECTED AT RISR:, THE
CSR AND DBR WILL BE SAVED AND PRINTED OUT
AFTER THE COMPLETE MESSAGE HAS BEEN RECEIVED.

- 9.10 THE DATA TEST SUBROUTINE AT TESTD: IS
ENTERED AFTER A COMPLETE MESSAGE HAS BEEN
RECEIVED.
IF A 'RECEIVE ERROR' HAD BEEN DETECTED,
THE CONTENTS OF THE 'RECEIVE BUFFER' AT THE
TIME THE ERROR OCCURRED WILL BE PRINTED.
THE DATA IS COMPARED UNTIL A 'ALL ZEROS'
CHARACTER IS RECOGNIZED. 'FILL' (ALL ONES)
CHARACTERS ARE IGNORED. IF A MISMATCH
IS DETECTED, THE COMPLETE CONTENTS OF THE
INPUT BUFFER AND GOOD DATA IS PRINTED.

10.0 PARAMETERS FOR THE DL11

PARAM#1 MUST BE ALL ZEROS.

PARAM#2 BIT 0 OF THIS PARAMETER IS CHECKED BY THE SOFTWARE TO RUN
EITHER FULL-DUPLEX OR HALF-DUPLEX. BIT0=1 SELECTS FULL-DUPLEX,
BIT0=0 SELECTS HALF-DUPLEX. DEFAULT IS HALF-DUPLEX, ALL OTHER BITS MUST BE ZEROS.

PARAM#3 IS NOT USED(177777).

NO1

DL11 ITEP OVERLAY MACV11 27(1006) 29-OCT-76 14:36 PAGE 14
 0ZDLOC.P11 29-OCT-76 10:29

575					
576				*****	
577				DL11 INTERFACE SERVICE PARAMS	
578				*****	
579		011000		.=11000	
580	011000	046104	000040	DL11: .ASCIZ /DL /	;ISR NAME
581	011004	175610		BA: 175610	;BUS ADDRESS
582	011006	000300		RIV: 300	;VECTOR ADDRESS
583	011010	000200		PRIOR: 200	;PRIORITY
584	011012	000000		PARAM1: 000000	;PARAM #1
585	011014	000000		PARAM2: 000000	;PARAM #2
586	011016	177777		PARAM3: 177777	;PARAM #3
587	011020	000000		IRDA: .WORD 0	;INITIAL READ DATA ADDRESS
588	011022	000000		IXDA: .WORD 0	;INITIAL XMIT DATA ADDRESS
589	011024	000000		SETTLE: .WORD 0	;LINE SETTLE DELAY FLAG
590	011026	000000		.WORD 0	
591	011030	000000		B2016: .WORD 0	;ADDR OF BIN TO OCT TYPE ROUTINE
592	011032	000000		TIME: .WORD 0	;TIMER
593	011034	000000		.WORD 0	
594	011036	011102		.WORD START	;ADDR OF START OF PROGRAM
595	011040			TX.TERM:	
596	011040	000		.BYTE 000	;TRANSMITTER TERMINATING CHAR.
597	011041			RX.TERM:	
598	011041	001		.BYTE 001	;RECEIVER TERMINATING CHAR.
599	011042	000000		FLAG: .WORD 0	
600	011044	177570		SWR: 177570	
601	011046	177570		DISPLAY: 177570	
602					
603				*****	
604				CONSTANTS + WORKING STORAGE	
605				*****	
606		000000		STAT=R0	
607		100000		XFLG=100000	;XMIT COMPLETE FLAG
608		040000		RFLG=40000	;RCV COMPLETE FLAG
609		020000		DSFLG=20000	;DATA SET STATUS CHANGE FLAG
610		020000		BIT13=20000	;INHIBIT PRINTOUTS
611					
612	011050	000000		SXCSR: 0	;SAVED XMIT CSR
613	011052	000000		SRCR: 0	;SAVED RCV CSR
614	011054	000000		ERCSR: 0	;RCV CSR SAVED ON ERROR
615	011056	000000		ERDBR: 0	;RCV DATA REG SAVED ON ERROR
616	011060	000000		DSSTAT: 0	;RCV CSR SAVED ON DS CHANGE
617					
618	011062	000000		XCC: 0	;XMIT CHAR COUNT
619	011064	000000		RCC: 0	;RCV CHAR COUNT
620	011066	000000		RDA: 0	;RCV DATA ADDR.
621	011070	000000		XDA: 0	;XMIT DATA ADDR.
622					
623	011072	177560		TKS: 177560	
624	011074	177562		TKB: 177562	
625	011076	177564		TPS: 177564	
626	011100	177566		TPB: 177566	
627					
628		000001		FULL.DUPLEX=000001	

```

625
630
631
632 011102 000240
633 011104 017700 177734
634 011110 042700 177400
635 011114 013702 011006
636 011120 012722 013654
637 011124 013722 011010
638 011130 012722 013536
639 011134 013722 011010
640 011140 013704 011004
641 011144 013714 011012
642 011150 013702 011014
643 011154 042702 000001
644 011160 010264 000004
645
646
647
648
649
650
651
652 011164 005037 011032
653 011170 005037 013054
654 011174 005037 013060
655 011200 032700 000001
656 011204 001402
657 011206 000137 011362
658 011212 032700 000002
659 011216 001402
660 011220 000137 011254
661 011224 032700 000010
662 011230 001402
663 011232 000137 011460
664 011236 032700 000004
665 011242 001402
666 011244 000137 011710
667 011250 000000
668 011252 000776
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683 011254 104416
684 011256 004737 013374

```

```

*****
DL11-X INTERFACE SERVICE ROUTINE
*****
START:  NOP
        MOV     @SWR, R0      ; SETUP MODE IN R0
        BIC     #177400, R0   ; STRIP JUNK
        MOV     RIV, R2      ; SETUP
        MOV     @RISR, (R2)+  ; INTERRUPT
        MOV     @PRIOR, (R2)+ ; VECTORS
        MOV     @XISR, (R2)+
        MOV     @PRIOR, (R2)+
        MOV     BA, R4        ; SETUP BUS ADDR INDEX
        MOV     @PARAM1, @RCSR ; SETUP VARIABLES
        MOV     @PARAM2, R2
        BIC     #0001, R2
        MOV     R2, @XCSR(R4); IN CSR'S

```

```

*****
ROUTINE USED TO GOTO
SUBROUTINE DEPENDENT
ON MODE SELECTED.
*****

```

```

GO:      CLR     TIME
        CLR     DELAY
        CLR     STOP
        BIT     @OWO, MODE
        BEQ     1$
        JMP     $OWO
1$:      BIT     @OWI, MODE
        BEQ     2$
        JMP     $OWI
2$:      BIT     @ILB, MODE
        BEQ     3$
        JMP     $ILB
3$:      BIT     @XLB, MODE
        BEQ     4$
        JMP     $XLB
4$:      HALT
        BR      .-2

```

```

*****
ROUTINE USED IF "ONE WAY IN" MODE WAS SELECTED.
NOTE THAT WHEN IN THIS MODE HALF DUPLEX IS THE
ONLY MODE AVAILABLE.
"ONE WAY IN" MEANS THAT ONLY THE RECEIVER IS
ENABLED. THE TRANSMITTER IS NEVER "TURNED ON".
*****

```

```

$OWI:    KBDIN
        JSR     PC, STARTP

```

DL11 ITP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 16
 DZDLOC.P11 29-OCT-76 10:28

685	011262	032700	040000	15:	BIT	#RFLG, STAT
686	011256	001013			BNE	2\$
687	011270	023727	011032 000100		CMP	TIME, #100
688	011276	103771			BLO	1\$
689	011300	011402			MOV	2RCSR, R2
690	011302	016403	000004		MOV	XCSR(R4), R3
691	011306	104001			HLT	1
692	011310	005037	011032		CLR	TIME
693	011314	000762			BR	1\$
694						
695	011316	032777	000200 177520	2\$:	BIT	#MODAT, 2SWR
696	011324	001002			BNE	3\$
697	011326	004737	012300		JSR	PC, TESTD
698	011332	042700	040000	3\$:	BIC	#RFLG, STAT
699	011336	032777	000020 177500		BIT	#LOOP, 2SWR
700	011344	001405			BEQ	4\$
701	011346	012737	011360 013056		MOV	#4\$, BACK
702	011354	000137	012140		JMP	EOP
703	011360	000735		4\$:	BR	\$OWI

 ROUTINE USED IF "ONE WAY OUT" WAS SELECTED.
 NOTE THAT WHEN IN THIS MODE HALF DUPLEX IS THE ONLY
 MODE AVAILABLE.
 "ONE WAY OUT" MEANS THAT ONLY THE TRANSMITTER IS
 ENABLED. THE RECEIVER IS NEVER "TURNED ON."

714	011362	104416		\$OWO:	KBOIN	
715	011364	004737	013062		JSR	PC, STARTX
716	011370	005037	011032		CLR	TIME
717	011374	032700	100000	1\$:	BIT	#XFLG, STAT
718	011400	001013			BNE	2\$
719	011402	023727	011032 000100		CMP	TIME, #100
720	011410	103771			BLO	1\$
721	011412	011402			MOV	2RCSR, R2
722	011414	016403	000004		MOV	XCSR(R4), R3
723	011420	104001			HLT	1
724	011422	005037	011032		CLR	TIME
725	011425	000762			BR	1\$
726	011430	042700	100000	2\$:	BIC	#XFLG, STAT
727	011434	032777	000020 177402		BIT	#LOOP, 2SWR
728	011442	001405			BEQ	3\$
729	011444	012737	011456 013056		MOV	#3\$, BACK
730	011452	000137	012140		JMP	EOP
731	011456	000741		3\$:	BR	\$OWO
732						
733						
734						

735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789011460 104416
011462 004737 013374
011466 005037 011032
011472 032700 040000
011476 001013
011500 023727 011032 000100
011506 103771
011510 011402
011512 016403 000004
011516 104001
011520 005037 011032
011524 000762
011526 032777 000200 177310
011534 001002
011536 004737 012300
011542 042700 040000
011546 032777 000020 177270
011554 001405
011556 012737 011570 013056
011564 000137 012140
011570 032777 000400 177246
011576 001416
011600 013702 011020
011604 013703 011022
011610 010337 011070
011614 112223
011616 001376
011620 112743 000177
011624 005203
011626 112723 000177
011632 105023
011634 005037 011032
011640 004737 013062
011644 032700 100000
011650 001013
011652 023727 011032 000100
011660 103771
011662 011402
011664 016403 000004
011670 104001
011672 005037 011032
011676 000762
011700 042700 100000
011704 000137 011460

```

*****
ROUTINE USED IF INTERNAL LOOP BACK" WAS SELECTED.
NOTE THAT WHEN IN THIS MODE; HALF DUPLEX IS THE
ONLY MODE AVAILABLE.
"INTERNAL LOOP BACK" MEANS THAT THE RECEIVER IS "TURNED ON"
AND A COMPLETE MESSAGE IS RECEIVED. IF DATA IS TO BE CHECKED
IT IS; IF "END PASS" IS DESIRED; IT IS GIVEN.
THEN THE TRANSMITTER IS ENABLED. AFTER THE WHOLE MESSAGE
IS TRANSMITTED; THE CYCLE IS REPETED AS ABOVE.
*****

```

```

$ILB: KBOIN
JSR PC,STARTR
CLR TIME
1$: BIT #RFLG,STAT
BNE 2$
CMP TIME,#100
BLC 1$
MOV @RCSR,R2
MOV XCSR(R4),R3
HLT 1
CLR TIME
BR 1$
7$: BIT #NODAT,@SWR
BNE 3$
JSR PC,TESTD
BIC #RFLG,STAT
3$: BIT #LOOP,@SWR
BEQ 4$
MOV #4$,BACK
JMP EOP
4$: BIT #400,@SWR
BEQ 7$
MOV IRDA,R2
MOV IXDA,R3
MOV R3,XDA
MOVB (R2)+,(R3)+
BNE -2
MOVB #177,R3
INC R3
MOVB #177,(R3)+
CLRB (R3)+
7$: CLR TIME
JSR PC,STARTR
5$: BIT #XFLG,STAT
BNE 6$
CMP TIME,#100
BLO 5$
MOV @RCSR,R2
MOV XCSR(R4),R3
HLT 1
CLR TIME
BR 5$
6$: BIC #XFLG,STAT
JMP $ILB

```

```

;USE EXTERNAL DATA?
;BR IF NO
;SET POINTER
;SET POINTER
;SETUP XMIT DATA ADDR
;MOVE INPUT TO OUTPUT
;LOOP IF NOT ZERO CHAR
;INSERT A FILL CHAR
;BUMP ADDRESS
;INSERT ANOTHER FILL
;INSERT ZERO CHAR

```

```

790
791
792
793
794
795
796
797
798
799
800
801
802
803 011710 104416
804 011712 032737 000001 011014
805 011720 001402
806 011722 004737 013374
807 011726 004737 013062
808 011732 005037 011032
809 011736 032700 100000
810 011742 001016
811 011744 032700 040000
812 011750 001024
813 011752 023727 011032 000100
814 011760 103766
815 011762 011402
816 011764 016403 000004
817 011770 104001
818 011772 005037 011032
819 011776 000757
820 012000 032737 000001 011014
821 012006 001356
822 012010 042700 100000
823 012014 004737 013374
824 012020 000746
825 012022 032737 000001 011014
826 012030 001420
827 012032 032700 100000
828 012036 001013
829 012040 023727 011032 000100
830 012046 103765
831 012050 011402
832 012052 016403 000004
833 012056 104001
834 012060 005037 011032
835 012064 000756
836 012066 042700 100000
837 012072 042700 040000
838 012076 005037 011032
839 012102 032777 000200 176734
840 012110 001002
841 012112 004737 012300
842 012116 032777 000020 176720
843 012124 001671
844 012126 012737 011710 013056
845 012134 000137 012140

```

ROUTINE USED IF "EXTERNAL LOOP BACK" WAS SELECTED.
EITHER HALF OR FULL DUPLEX MAY BE SELECTED IN THIS MODE.
"EXTERNAL LOOP BACK" MEANS THAT THE TRANSMITTER IS FIRST
TURNED ON (IF HALF DUPLEX) AND THE WHOLE MESSAGE IS TRANSMITTED;
THEN THE RECEIVER IS ENABLED. AFTER THE WHOLE MESSAGE IS RECEIVED
DATA WILL THEN BE CHECKED IF DESIRED AND END PASS WILL
BE GIVEN IF DESIRED. THEN THE CYCLE IS REPEATED
AS ABOVE. IF RUNNING IN FULL DUPLEX THE PROGRAM
WAITS FOR BOTH THE RECEIVER AND TRANSMITTER TO
FINISH THEN RESTARTS THE RECEIVER AND TRANSMITTER.

```

$XLB: KBDIN
      BIT      #FULL.DUPLEX,PARAM2
      BEQ      1$
      JSR      PC,STARTR
      JSR      PC,STARTX
      CLR      TIME
      1$:      BIT      #XFLG,STAT
      BNE      3$
      2$:      BIT      #RFLG,STAT
      BNE      4$
      CMP      TIME,#100
      BLO      2$
      MOV      @RCSR,R2
      MOV      XCSR(R4),R3
      HLT      1
      CLR      TIME
      BR       2$
      3$:      BIT      #FULL.DUPLEX,PARAM2
      BNE      7$
      BIC      #XFLG,STAT
      JSR      PC,STARTR
      BR       2$
      4$:      BIT      #FULL.DUPLEX,PARAM2
      BEQ      8$
      BIT      #XFLG,STAT
      BNE      6$
      CMP      TIME,#100
      BLO      4$
      MOV      @RCSR,R2
      MOV      XCSR(R4),R3
      HLT      1
      CLR      TIME
      BR       4$
      5$:      BIC      #XFLG,STAT
      6$:      BIC      #RFLG,STAT
      CLR      TIME
      BIT      #MODAT,@SWR
      BNE      5$
      JSR      PC,TESTD
      5$:      BIT      #LOOP,@SWR
      BEQ      $XLE
      MOV      $XLB,BACK
      JMP      EOP

```

```

846
847
848
849
850
851
852
853 012140 104414 000340
854 012144 016437 000004 012276
855 012152 042737 177677 012276
856 012160 042764 000100 000004
857 012166 012766 012226 000002
858 012174 010037 013040
859 012200 010137 013042
860 012204 010237 013044
861 012210 010337 013046
862 012214 010437 013050
863 012220 010537 013052
864 012224 000207
865
866 012226
867 012226 013700 013040
868 012232 013701 013042
869 012236 013702 013044
870 012242 013703 013046
871 012246 013704 013050
872 012252 013705 013052
873 012256 012737 177777 013054
874 012264 053764 012276 000004
875 012272 000177 000560
876 012276 000000
877
878
879
880
881
882
883
884 012300 013746 011056
885 012304 001413
886 012306 032777 020000 176530
887 012314 001007
888 012316 104400 012500
889 012322 004077 176502
890 012326 005746
891 012330 104400 012561
892 012334 013701 011022
893 012340 013702 011020
894 012344 122122
895 012346 001776
896 012350 123741 011040
897 012354 001447
898 012356 122742 000002
899 012362 001005
900 012364 010237 012372
901 012370 104400

```

```

*****
ROUTINE TO RETURN
TO MONITOR FOR
END PASS.
*****

EOF:
      STPS,PRTY7
      MOV     XCSR(R4),QTPIE
      BIC     #1<TIE>,QTPIE
      BIC     #TIE,XCSR(R4)
      MOV     #ENTER,2(SP)
      MOV     R0,SAVR0
      MOV     R1,SAVR1
      MOV     R2,SAVR2
      MOV     R3,SAVR3
      MOV     R4,SAVR4
      MOV     R5,SAVR5
      RTS     PC

      ;SET PS PRIORITY TO 7
      ;SA-E TX CSR
      ;CLEAR ALL BUT TX IE.
      ;CLEAR TX IE (EVEN IF IT WASN'T SET)
      ;SET FOR RETURN IF SW 14=1
      ;SAVE REGISTER 0
      ;SAVE REGISTER 1
      ;SAVE REGISTER 2
      ;SAVE REGISTER 3
      ;SAVE REGISTER 4
      ;SAVE REGISTER 5
      ;RETURN TO CONTROL PROGRAM

ENTER:
      MOV     SAVR0,R0
      MOV     SAVR1,R1
      MOV     SAVR2,R2
      MOV     SAVR3,R3
      MOV     SAVR4,R4
      MOV     SAVR5,R5
      MOV     #-1,DELAY
      BIS     QTPIE,XCSR(R4)
      JMP     @BACK

      ;RESTORE R0
      ;RESTORE R1
      ;RESTORE R2
      ;RESTORE R3
      ;RESTORE R4
      ;RESTORE R5
      ;IF ORGINALLY SET; SET TX IE

QTPIE: 000000

*****
SUBROUTINE TO CHECK
RECEIVER DATA.
*****
TESTD: MOV     ERDR, -(SP)
      BEQ     TSTDAT
      BIT     #BIT13,@SWR
      BNE     TSTDAT
      TYPE     MSG0
      JSR     R0,@B2016
      TST     -(SP)
      TYPE     MSG1
      TSTDAT: MOV     IXDA, R1
      MOV     IRDA, R2
      SCAN4: CMPB    (R1)+, (R2)+
      BEQ     SCAN4
      CMPB    TX.TERM,-(R1)
      BEQ     TESTDX
      CMPB    #002,-(R2)
      BNE     Z$
      MOV     R2,1$
      TYPE

```

```

;WAS THERE A RECEIVE ERROR?
;BR IF NO
;INHIBIT PRINTOUTS?
;BR IF YES
;(15)(12)THERE WAS A RECEIVE ERROR. RBUF=
;PRINT CONTENTS OF RBUF
;(15)(12)
;SETUP XMIT DATA ADDR
;SETUP RCV DATA ADDR
;DATA OK ?
;BR IF OK
;IS IT END OF DATA
;BR IF YES

```

Address	Word	TestDX	Label	Comment
902	012372	000000	15:	WORD
903	012374	000437	BR	TESTDX
904	012376		25:	
905	012376	105712	TSTB	(R2)
906	012400	001435	BEQ	TESTDX
907	012402	122721	000177	CMPB #177, (R1)+
908	012406	001756	BEQ	SCAN4
909	012410	005301	DEC	R1
910	012412	122722	000177	CMPB #177, (R2)+
911	012416	001752	BEQ	SCAN4
912	012420	000240	SCAN4:	NOP
913	012422	032777	020000	176414
914	012430	001016	BIT	#BIT13, 2SWR
915	012432	104400	012564	DERR
916	012436	013737	011020	012446
917	012444	104400	RDAX:	0
918	012446	000000	RDAX:	0
919	012450	104400	012611	012464
920	012454	013737	011022	012464
921	012462	104400		
922	012464	011022		
923	012466	111103	DERR:	MOV B (R1), R3 ; SETUP XMIT DATA
924	012470	114202		MOV B -(R2), R2 ; SETUP RCV DATA
925	012472	104007		HLT+7 ; DATA ERROR HALT
926	012474	005726	TESTDX:	TST (SP)+
927	012476	000207		RTS PC ; RETURN FROM SUB/ROUT
928				
929	012500	005015	044124	051105
(1)	012561	015	000012	
(1)	012561	005015	042522	042503
(1)	012611	015	042012	052101
(1)	012634	005015	046120	040505
(1)	012703	015	053412	042510
(1)	012766	005015	046120	040505
(1)				
(1)	013040	000000	SAVR0:	0
930	013042	000000	SAVR1:	0
931	013044	000000	SAVR2:	0
932	013046	000000	SAVR3:	0
933	013050	000000	SAVR4:	0
934	013052	000000	SAVR5:	0
935	013054	000000	DELAY:	0
936	013056	000000	BACK:	0
937	013060	000000	STOP:	0
938				

H02

DL11 ITP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 21
DZDLOC.P11 29-OCT-76 10:28

```

939 ;*****
940 ;      INITIALIZE TRANSMIT SUBROUTINE
941 ;*****
942
943 STARTX:
944 013062 005737 013054 TST DELAY ;IF SW04=1 & SW14=0 WAIT BEFORE TURNING ON TX
945 013066 001416 BEQ 15 ;NO GO AHEAD AND TURN ON TX
946 013070 005037 013526 CLR TEMP1 ;PREPARE FOR DELAY
947 013074 012737 000007 013530 MOV #7,TEMP2
948 013102 062737 000001 013526 ADD #1,TEMP1 ;INCREMENT DELAY.....
949 013110 001374 BNE -6
950 013112 005337 013530 DEC TEMP2
951 013116 001371 BNE -14
952 013120 005037 013054 CLR DELAY ;ZERO POINTER.
953 013124 013737 011022 011070 15: MOV IXDA, XDA ;SETUP XMIT DATA ADDR.
954 013132 052714 000002 BIS #DTR, DRCR ;SET REQUEST TO SEND
955 013136 005737 013060 TST STOP
956 013142 001005 BNE 25
957 013144 104400 012634 TYPE ,MSG4
958 013150 000000 HALT
959 013152 005137 013060 COM STOP
960 013156 032737 000001 011014 25: BIT #FULL.DUPLEX,PARAM2;FULL DUPLEX?
961 013164 001003 BNE 35 ;BR IF YES
962 013166 032714 010000 BIT #10000,DRCR ;CARRIER UP?
963 013172 001375 BNE -4 ;BR IF YES
964 013174 052714 000004 35: BIS #RQTS,DRCR
965 013200 032714 000002 BIT #DTR, DRCR ;IS THIS A DL11-E?
966 013204 001425 BEQ CTSOK ;BR IF NO
967
968 013206 032714 020000 CTSW: BIT #CTS, DRCR ;IS CLEAR TO SEND SET?
969 013212 001017 BNE 25 ;BR IF YES
970 013214 023727 011032 000036 CMP TIME, #36 ;30 SECS ELAPSED?
971 013222 103771 BLO CTSW ;BR IF NO
972 013224 011402 MOV DRCR, R2 ;SETUP RCV CSR
973 013226 016403 000004 MOV XCSR(R4),R3 ;SETUP XMIT CSR
974 013232 032777 010000 175604 BIT #SW12, DSWR ;INHIBIT PRINTOUTS?
975 013240 001001 BNE 15 ;BR IF YES
976 013242 104002 HLT+2 ;PRINTOUT 'WAITING TO XMIT'
977 013244 005037 011032 15: CLR TIME ;RESET TIMER
978 013250 000756 BR CTSW ;WAIT SOME MORE
979 013252 032714 010000 25: BIT #10000,DRCR ;IS CARRIER UP?
980 013256 001775 BEQ 25 ;BR IF NO
981
982 013260 005737 011024 CTSOK: TST SETTLE ;CONNECTION JUST MADE?
983 013264 001416 BEQ 25 ;BR IF NO
984 013266 005037 013526 CLR TEMP1 ;YES PREPARE FOR DELAY
985 013272 012737 000030 013530 MOV #14*2,TEMP2
986 013300 062737 000001 013526 ADD #1,TEMP1 ;INCREMENT DELAY
987 013306 001374 BNE -6
988 013310 005337 013530 DEC TEMP2
989 013314 001371 BNE -14
990 013316 005037 011024 CLR SETTLE ;CLEAR DELAY FLAG
991 013322 032737 000001 011014 25: BIT #FULL.DUPLEX,PARAM2;FULL DUPLEX?
992 013330 001415 BEQ 15 ;BR IF NO
993 013332 032700 000004 BIT #XLB,MODE ;XLB MODE?
994 013336 001412 BEQ 15 ;BR IF NO

```

DL11 ITP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 22
 DZDLOC.P11 29-OCT-76 10:28

```

995 013340 012737 177777 013534      MOV      #-1,TRNFLG      ;SET FLAG
996 013346 052764 000100 000004      BIS      #TIE,XCSR(R4) ;SET INTERRUPT ENABLE
997 013354 000001                WAIT
998 013356 005737 013532      TST      SNCFLC      ;FIRST CHAR RECEIVED YET?
999 013362 001375                BNE      #-4          ;BR IF NO
1000 013364 052764 000100 000004 1$:  BIS      #TIE, XCSR(R4);SET XMIT INTERRUPT ENABLE
1001 013372 000207                RTS      PC          ;EXIT FROM SUBROUTINE
1002
1003 ;*****
1004 ;      INITIALIZE RECEIVER SUBROUTINE
1005 ;*****
1006 013374 005737 013060      STARTR: TST      STOP          ;FIRST TIME HERE?
1007 013400 001012                BNE      1$          ;BR IF NO
1008 013402 052714 000002      BIS      #DTR,DRCSR      ;SET DTR
1009 013406 104400 012766      TYPE      MSGS          ;MAKE CONNECTION
1010 013412 012737 177777 011024 2$:  MOV      #-1,SETTLE      ;YES SET DELAY FLAG
1011 013420 012737 177777 013060      MOV      #-1,STOP
1012 013426 032737 000001 011014 1$:  BIT      #FULL.DUPLEX,PARAM2;FULL DUPLEX?
1013 013434 001410                BEQ      3$          ;BR IF NO
1014 013436 032700 000004      BIT      #XLB,MODE      ;XLB MODE?
1015 013442 001405                BEQ      3$          ;BR IF NO
1016 013444 005037 013526      CLR      TEMP1          ;START DELAY
1017 013450 005237 013526      INC      TEMP1
1018 013454 001375                BNE      #-4
1019 013456 012737 177777 013532 3$:  MOV      #-1,SNCFLG      ;SET FLAG
1020 013464 013737 011020 011066      MOV      IRDA, RDA      ;SETUP RCV DATA ADDR
1021 013472 012737 001000 011064      MOV      #1000, RCC      ;SETUP RCV CHAR COUNT
1022 013500 042700 040000      BIC      #RFLG,STAT      ;CLEAR RFLG
1023 013504 005037 011054      CLR      ERCSR          ;RESET ERROR RECORDS
1024 013510 005037 011056      CLR      ERDBR
1025 013514 005764 000002      TST      R2,JF(R4)
1026 013520 052714 000143      BIS      #RIE+DTR+DIE+RE,DRCSR;SET INTERRUPT ENABLES
1027 013524 000207                RTS      PC          ;EXIT FROM SUBROUTINE
1028
1029 013526 000000      TEMP1:  0
1030 013530 000000      TEMP2:  0
1031 013532 000000      SNCFLG: 0
1032 013534 000000      TRNFLG: 0

```

```

1033      ;*****
1034      ; TRANSMIT INTERRUPT SERVICE ROUTINE
1035      ;*****
1036      XISR:  NOP
1037      CMPB   @XDA, TX.TERM      ; FINISHED XMITTING?
1038      BNE    XISR1              ; BR IF NO
1039      BIS     @XFLG, STAT        ; SET XMIT COMPLETE FLAG
1040      BIC     @RQTS, @RCSR       ; RESET REQUEST TO SEND
1041      BIC     @TIE, XCSR(R4)     ; RESET XMIT INTERRUPT ENABLE
1042      BR     XISR2
1043
1044      XISR1: MOVB   @XDA, XBUF(R4) ; XMIT NEXT CHAR.
1045      BIT     #100, @SWR         ; MONITOR OUTPUT?
1046      BEQ     NOXMON            ; BR IF NO
1047      TSTB   @TPS              ; IS TTY AVAILABLE
1048      BPL     NOXMON            ; BR IF NO
1049      MOVB   @XDA, @TPB        ; TYPE THE CHAR
1050      NOXMON:
1051      INC     XDA               ; INCREMENT ADDRESS
1052      XISR2: TST     TRNFLG       ; FIRST CHAR?
1053      BEQ     IS               ; BR IF NO
1054      BIC     @TIE, XCSR(R4)     ; CLEAR INTERRUPT ENABLE
1055      IS:    CLR     TIME         ; RESET TIMER
1056      CLR     TRNFLG           ; CLEAR FLAG
1057      RTI                      ; RETURN FROM INTERRUPT
1058      ;*****
1059      ; RECEIVE INTERRUPT SERVICE ROUTINE
1060      ;*****
1061      RISR:  NOP
1062      TSTB   @RCSR              ; IS RECEIVER DONE BIT SET
1063      BPL     RISR2             ; BR IF NO
1064      MOVB   @RBUF(R4), R1      ; STORE CHAR.
1065      BICB   #200, R1          ; STRIP A BIT
1066      MOVB   R1, @RDA          ; MOVE CHAR TO INBUF
1067      BIT     #40, @SWR        ; MONITOR INPUT?
1068      BEQ     NORMON           ; BR IF NO
1069      TSTB   @TPS              ; IS TTY AVAILABLE?
1070      BPL     NORMON           ; BR IF NO
1071      MOVB   R1, @TPB          ; TYPE THE CHAR
1072      NORMON:
1073      INC     RDA               ; BUMP POINTER
1074      CLRB   @RDA              ; CLEAR NEXT CHAR POSITION
1075      DEC     RCC              ; DECREMENT CHAR. COUNTER
1076      BNE    IS               ; BR IF BUFFER NOT FULL
1077      BIC     @RIE, @RCSR       ; RESET INTERRUPT ENAB
1078      MOV     @RCSR, R2         ; SETUP RCV CSR
1079      MOV     XCSR(R4), R3      ; SETUP XMIT CSR
1080      HLT+6   ; RECEIVER BUFFER FULL
1081      JSR     PC, STARTR        ; INITIALIZE RECEIVER
1082
1083      IS:    CMPB   RX.TERM, R1  ; IS IT LINE FEED?
1084      BNE    RISR1             ; BR IF NO
1085      BIC     @RIE+DIE, @RCSR   ; DISABLE INTERRUPTS
1086      BIS     @RFLG, STAT       ; SET RCVR COMPLETE FLAG
1087      RISR1: TST     @RBUF(R4)   ; IS THERE A DATA ERROR
1088      BPL     RISR2            ; BR IF NO

```

K02

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 24
 DZOLOC.P11 29-OCT-76 10:28

1089	014002	011437	011054		MOV	2RCSR	ERCSR	:SAVE RCSR
1090	014006	016437	000002	011056	MOV	RBUF(R4),ERDBR		:SAVE RDBR
1091	014014	005714			RISR2:	TST	2RCSR	:IS THERE A DATA SET STATUS CHANGE
1092	014016	100004				BPL	RISR3	:BR IF NO
1093	014020	011437	011060		MOV	2RCSR	DSSTAT	:SAVE STATUS
1094	014024	052700	020000		BIS	#DSFLG,	STAT	:SET FLAG
1095	014030	005037	013532		RISR3:	CLR	SNCFLG	:CLEAR FLAG
1096	014034	005037	011032		CLR	TIME		:RESET TIMER
1097	014040	000002			RTI			:RETURN FROM INTERRUPT
1098								
1099		000001			END			

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 26
 DZDLOC.P11 29-OCT-76 10:29 CROSS REFERENCE TABLE -- USER SYMBOLS

BA	011004	581#	640					
BACK	013056	701#	729*	764*	844*	875	935#	
B1T0	= 000001	575#						
B1T1	= 000002	575#						
B1T10	= 002000	575#						
B1T11	= 004000	575#						
B1T12	= 010000	575#						
B1T13	= 020000	575#	610#	886	913			
B1T14	= 040000	575#						
B1T15	= 100000	575#						
B1T2	= 000004	575#						
B1T3	= 000010	575#						
B1T4	= 000020	575#						
B1T5	= 000040	575#						
B1T6	= 000100	575#						
B1T7	= 000200	575#						
B1T8	= 000400	575#						
B1T9	= 001000	575#						
B2016	011030	591#	889					
CD	= 010000	575#						
CTS	= 020000	575#	968					
CTSOK	013260	966	982#					
CTSW	013206	968#	971	978				
DELAY	013054	653*	873*	935#	944	952*		
DERR	012466	914	923#					
DIE	= 000040	575#	1026	1085				
DISPLA	011046	601#						
DL11	011000	580#						
DSC	= 100000	575#						
DSFLG	= 020000	575#	609#	1094				
DSSTAT	011060	616#	1093*					
DTR	= 000002	575#	954	965	1008	1026		
ENTER	012226	857	866#					
EOP	012140	702	730	765	845	852#		
ER	= 100000	575#						
ERCSR	011054	614#	1023*	1089*				
EROSR	011056	615#	884	1024*	1090*			
FE	= 020000	575#						
FLAG	011042	599#						
FULL.D	= 000001	628#	804	820	825	960	991	1012
GO	011164	652#						
ILB	= 000010	575#	661					
IRDA	011020	587#	768	893	916	1020		
IXDA	011022	588#	769	892	920	922	953	
KBDIN	= 104416	575#	683	714	746	803		
LOOP	= 000020	575#	699	727	762	842		
MSG0	012500	888	929#					
MSG1	012561	891	929#					
MSG2	012564	915	929#					
MSG3	012611	919	929#					
MSG4	012634	929#	957					
MSG5	012766	929#	1009					
NOOAT	= 000200	575#	695	758	839			
NORMON	013720	1068	1070	1072#				
NOXMON	013622	1046	1048	1050#				
OR	= 040000	575#						

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 27
DZDLOC.P11 29-OCT-76 10:28 CROSS REFERENCE TABLE -- USER SYMBOLS

[illegible]

N02

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:35 PAGE 28
 DZDLOC.P11 29-OCT-76 10:28 CROSS REFERENCE TABLE -- USER SYMBOLS

TEMP1	013526	946*	948*	984*	986*	1016*	1017*	1029*										
TEMP2	013530	947*	950*	985*	988*	1030*												
TESTD	012300	697	760	841	884*													
TESTDX	012474	897	903	906	926*													
TIE	= 000100	575*	855	856	996	1000	1041	1054										
TIME	011032	592*	652*	687	692*	716*	719	724*	748*	751	756*	777*	781	786*				
		808*	613	818*	829	934*	838*	970	977*	1055*	1096*							
TKB	011074	624*																
TKS	011072	623*																
TPB	011100	626*	1049*	1071*														
TPS	011076	625*	1047	1069														
TR	= 000200	575*																
TRMFLG	013534	995*	1032*	1052	1056*													
TSTDAY	012334	885	887	892*														
TX. TER	011040	595*	896	1037														
TYPE	= 104400	575*	888	891	901	915	917	919	921	957	1009							
XBUF	= 000006	575*	1044*															
XCC	011062	618*																
XCSR	= 000004	575*	644*	690	722	754	784	816	832	854	856*	874*	973	996*				
		1000*	1041*	1054*	1079													
XDA	011070	621*	770*	953*	1037	1044	1049	1051*										
XFLG	= 100000	607*	717	726	779	788	809	822	827	836	1039							
XISR	013536	638	1036*															
XISR1	013570	1038	1044*															
XISR2	013626	1042	1052*															
XLB	= 000004	575*	664	993	1014													
XWAIT	= 104412	575*																
\$ILB	011460	663	746*	789														
\$OWI	011254	660	683*	703														
\$OWO	011362	657	714*	731														
\$XLB	011710	666	803*	843	844													
.	= 014042	579*	668	772	920*	949	951	963	987	989	999	1018						

DL11 ITEP OVERLAY MACY11 27(1006) 29-OCT-76 14:36 PAGE 30
 DZDLOC.P11 29-OCT-76 10:29 CROSS REFERENCE TABLE -- MACRO NAMES

BOX	18	575	603	629	939	1003	1033	1058
DCPARM	18							
DHDOC1	18							
DHPARM	18							
DJPARM	18							
DLPARM	18	561						
DPPARM	18							
DQDOC1	18							
DQPARM	18							
DUPARM	18							
DUPPAR	18							
DVDOC1	18							
DVPARM	18							
DZPARM	18							
HELLO	18							
HLT	575	691	723	755	785	817	833	925
SEQUAT	18	575						976
SINTF	18	575						1080
SITEP	18	645						
SSERV	18	618						

. ABS. 014042 000

ERRORS DETECTED: 0
 DEFAULT GLOBALS GENERATED: 0

. DZDLOC.SEG/SOL/CRF/NL:TOC=ITEP1.MAC,DZDLOC.P11
 RUN-TIME: 10 13 .8 SECONDS
 RUN-TIME RATIO: 75/26=2.8
 CORE USED: 16K (31 PAGES)

[illegible]